

[Telcordia GR-1060 - Document Information](#)

Contents

Preface	xiii
1. Introduction	1-1
1.1 Service Overview	1-1
1.2 Purpose and Scope	1-3
1.3 Changes From Issue 1 of TR-TSV-001060	1-3
1.4 Key Bellcore Documents	1-4
1.5 Requirement Terminology	1-6
1.6 Outline	1-7
2. Overview	2-1
2.1 Introduction	2-1
2.2 Services	2-1
2.3 XA-SMDS Feature Overview	2-3
2.4 BCC-ILEC Serving Arrangements	2-4
2.5 Network Architectures for BCC-ILEC Serving Arrangements	2-5
2.5.1 Introduction	2-5
2.5.2 Remote SNI Architecture.....	2-5
2.5.3 Integrated Networks Architecture	2-6
2.5.4 Separate Networks Architecture	2-7
2.5.5 Generic Requirements for BCC-ILEC Serving Arrangements ..	2-8
2.6 Example Network Interconnections.....	2-9
2.7 Network Model	2-10
2.7.1 Customer Premises Equipment.....	2-10
2.7.2 LEC Network	2-12
2.7.3 Interconnecting TLEC and BCC Networks	2-12
2.7.4 IC Networks	2-12
2.7.5 Operations.....	2-13
2.7.6 XA-OM and ECOM.....	2-13
2.8 ICIP Overview	2-13
3. Exchange Access SMDS Service Definition	3-1
3.1 Introduction	3-1
3.2 Service Overview	3-1

3.2.1	Originating XA-SMDS	3-2	
3.2.2	Terminating XA-SMDS	3-3	
3.3	Individually Addressed Data Unit Transport	3-3	
3.4	Addresses	3-4	
3.4.1	Individual Addresses	3-5	
3.4.2	Group Addresses	3-6	
3.5	Carrier Selection	3-7	
3.6	Source Address Validation	3-11	
3.7	Group-Addressed Data Unit Transport	3-11	
3.7.1	Introduction	3-11	
3.7.2	Definitions	3-12	
3.7.3	Examples	3-14	
3.7.4	Overview of Features	3-20	
3.7.5	Feature Descriptions	3-22	
3.7.6	Group Address Composition	3-25	
3.8	End-User Blocking	3-27	
3.9	Routing to Interexchange Carrier Networks	3-28	
3.9.1	Placement and Number of ICI Transmission Paths	3-28	
3.9.2	Routing on an Originating Basis	3-28	
3.9.3	Routing on a Terminating Basis	3-29	
3.9.4	ICI Failure Monitoring	3-29	
3.10	Other Features at the Subscriber-Network Interface	3-31	
3.10.1	Access Classes	3-31	
3.10.2	Address Screening	3-31	
3.10.3	Multiple Data Units in Transit Across the SNI	3-31	
4.	BCC-ILEC Serving Arrangements –Feature Support	4-1	
4.1	Introduction	4-1	
4.2	Carrier Selection	4-1	
4.3	Individually Addressed Data Unit Transport for Exchange SMDS	4-2	–
4.4	Individually Addressed Data Unit Transport for XA-SMDS	4-2	–
4.5	Routing to Interexchange Carrier Networks	4-3	
4.6	Group-Addressed Data Unit Transport for Exchange and Exchange Access SMDS	4-4	
4.6.1	Serving Arrangements –Introduction	4-4	
4.6.2	Serving Arrangements –Examples	4-5	
4.6.3	Serving Arrangements –Requirements	4-8	

5.	Inter-Carrier Interface Specification	5-1
5.1	Introduction	5-1
5.2	Overview	5-1
5.2.1	Definition of the ICI	5-1
5.2.2	ICIP Functions and Organization	5-3
5.3	ICIP Services	5-3
5.3.1	Introduction.....	5-3
5.3.2	Service-Specific Functions	5-4
5.3.3	Variable Length Data Transfer Layer Functions	5-6
5.3.4	Physical Layer Functions	5-7
5.4	Organization of the ICI Protocol	5-7
5.4.1	Overview	5-7
5.4.2	Conventions	5-10
5.4.3	Scope of Requirements	5-11
5.5	IEEE 802.6/DS3 ICIP Specification.....	5-11
5.5.1	IEEE 802.6/DS3 ICIP Level 3 Protocol Specification.....	5-11
5.5.2	IEEE 802.6/DS3 ICIP Level 2 Protocol Specification	5-24
5.5.3	IEEE 802.6/DS3 ICIP Level 1 Protocol Specification	5-34
5.5.4	IEEE 802.6/DS3 ICIP Format Summary	5-34
5.6	ATM/SONET ICIP Specification.....	5-38
6.	Performance and Quality of Service Objectives.....	6-1
6.1	Introduction	6-1
6.2	Availability Objectives.....	6-2
6.2.1	Scheduled Service Time	6-2
6.2.2	Service Availability	6-3
6.2.3	Mean Time Between Service Outages	6-3
6.2.4	Mean Time To Restore	6-3
6.3	Accuracy Objectives	6-3
6.3.1	Errored ICIP/SIP L3-PDU Ratio	6-4
6.3.2	Misdelivered ICIP/SIP L3-PDU Ratio	6-4
6.3.3	ICIP/SIP L3-PDU Not Delivered Ratio	6-5
6.3.4	Duplicated ICIP/SIP L3_PDU Ratio	6-6
6.3.5	Mis-sequenced ICIP/SIP L3-PDU Ratio	6-6
6.4	ICIP/SIP L3-PDU Delay Objectives	6-7
6.4.1	Delay for Individually Addressed ICIP/SIP L3_PDU's	6-8

6.4.2	Delay for Group Addressed ICIP/SIP L3_PDUs	6-9
7.	Usage Measurement Functionality to Support Billing	7-1
7.1	Introduction	7-1
7.1.1	XA-SMDS	7-1
7.1.2	BCC-ILEC Serving Arrangements Using the Separate Networks Architecture Model	7-3
7.1.3	BCC-ILEC Serving Arrangements Using the Remote SNI or Integrated Networks Architecture Model	7-4
7.1.4	Organization of Section 7	7-4
7.2	Service Characteristics Related to Usage Measurements	7-4
7.3	Inter-Network Usage Measurement Functionality	7-5
7.4	Data Generation for Individually Addressed Data Transport	7-6
7.4.1	Billing Treatment Determination	7-6
7.4.2	Generation Points	7-10
7.4.3	Type of Information Generated	7-12
7.4.4	Generation Flexibility	7-16
7.4.5	Example Generation Scenario: XA-SMDS	7-16
7.4.6	Generation Scenario: BCC-ILEC Serving Arrangements Using the Separate Networks Architecture Model	7-18
7.5	Data Generation for Group-Addressed Data Transport	7-19
7.5.1	Billing Treatment Determination	7-19
7.5.2	Generation Points	7-20
7.5.3	Type of Information Generated	7-22
7.5.4	Generation Flexibility	7-31
7.5.5	Example of Usage Information Generated for Group- Addressed Data Transport	7-31
7.6	Data Aggregation, Formatting, and Transmitting Functions	7-35
7.6.1	Data Aggregation	7-35
7.6.2	Data Formatting	7-39
7.6.3	Data Transmitting	7-43
7.7	Performance	7-43
7.8	Operations	7-55
8.	Miscellaneous Generic Requirements	8-1
8.1	Power Supply Requirements	8-1
8.2	Physical Requirements	8-1
8.3	Environmental Requirements	8-1

8.4	Electrical Safety Requirements	8-1
8.5	Quality and Reliability	8-1
8.6	System Administration	8-2
Appendix A: Pseudo Code and Flow Diagram for SMDS Exchange Access and Intercompany Serving ArrangementsAppendix A-1
Glossary		Glossary-1
Acronyms and Abbreviations		Glossary-1
Terms		Glossary-4
References		References-1

List of Tables and Figures

Figure 2-1. Services	2-2
Figure 2-2. Serving Arrangements Model	2-5
Figure 2-3. Remote SNI Architecture Model	2-6
Figure 2-4. Integrated Networks Architecture Model	2-7
Figure 2-5. Separate Networks Architecture Model	2-8
Figure 2-6. Example Network Interconnections	2-9
Figure 2-7. Network Model	2-11
Figure 3-1. Originating XA-SMDS - Overview	3-2
Figure 3-2. Terminating XA-SMDS - Overview	3-3
Figure 3-3. Carrier Selection.....	3-10
Figure 3-4. Summary of Relationships	3-14
Figure 3-5. Source LEC is Group Address Agent - Individual Addresses	3-15
Figure 3-6. Distant LEC is Group Address Agent - Individual Addresses	3-16
Figure 3-7. Source LEC is Group Address Agent - Nested Group Addresses	3-18
Figure 4-1. Re-routing in Case of Failures	4-3
Figure 4-2. Source LEC Network is GA Agent	4-6
Figure 4-3. LEC with serving arrangements is GA Agent	4-7
Figure 5-1. Example Physical Arrangements	5-2
Figure 5-2. Terms	5-3
Figure 5-3. Service Primitives	5-4
Figure 5-4. ATM/SONET ICIP and IEEE 802.6/DS3 ICIP Architectures	5-7
Figure 5-5. IEEE 802.6/DS3 ICIP Encapsulation	5-9
Figure 5-6. ATM/SONET ICIP Encapsulation	5-10
Figure 5-7. Format of the ICIP L3_PDU	5-12

Figure 5-8. Address Field	5-13
Table 5-1 . ICIP Users	5-15
Figure 5-9. Service-Specific Information _Format	5-17
Figure 5-10. ICIP Level 2 PDU Format	5-24
Figure 5-11. Access Control Field Format	5-24
Table 5-2 . Segment Type Values	5-25
Figure 5-12. ICIP Level 2 Sending Procedure State Diagram	5-28
Figure 5-13. Level 2 Receiver State Machine for MID X	5-32
Figure 5-14 (A). Overview of the IEEE 802.6/DS3 ICIP	5-35
Figure 5-14 (B). Overview of the ICIP _Continued	5-36
Figure 5-14 (C). Overview of the ICIP _Continued	5-37
Figure 6-1. Performance Model of XA-SMDS	6-1
Table 6-1. Delay (in msec) for Individually Addressed 512, 1600, 4096 Octet L3_PDU's	6-9
Table 6-2. Delay (in msec) for Group-Addressed 512, 1600, 4096 Octet L3_PDU's	6-10
Figure 7-1 . XA-SMDS Framework	7-2
Figure 7-2. Separate Networks Architecture Model	7-3
Figure 7-3. Overall Diagram of Usage Measurement Processing to Support Billing	7-5
Figure 7-4. SS Responsible for Generating Usage Information in an Originating BCC Network (SS#3)	7-10
Figure 7-5. SS Responsible for Generating Usage Information in a Terminating BCC Network (SS#1)	7-11
Figure 7-6. Example BCC and IC Network Configuration for Interexchange SMDS ..	7-17
Figure 7-7. Example BCC and ILEC Network Configuration for Jointly Offered Exchange SMDS	7-18
Figure 7-8. Example of Generation Points for Group-Addressed Data Transport	7-21
Figure 7-9. Example of Terminating XA-SMDS	7-23
Figure 7-10. Example of Source Network Functions for Exchange SMDS	7-25

Figure 7-11. Example of Destination Network Functions for Exchange SMDS	7-27
Figure 7-12. Example of Source Network Functions for Terminating XA-SMDS	7-28
Table 7-1. Summary of Usage Information Generated for Group-Addressed Data Transport	7-30
Figure 7-13. Example LEC Network Configurations	7-31
Figure 7-14. The Aggregation Process	7-36