
Generic Requirements for Multi-Fiber Single-Mode Optical Splices and Splicing Systems

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 Changes from GR-1095-CORE, Issue 1	1-1
1.3 Target Audience	1-9
1.4 Structure and Use of This Document	1-9
1.5 Requirements Terminology	1-9
1.6 Requirement Labeling Conventions	1-10
1.6.1 Numbering of Requirement and Related Objects	1-10
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification	1-11
2. General Information	2-1
2.1 Types of Multi-Fiber Splices and Splicing Systems	2-1
2.1.1 Multi-Fiber Fusion Splicers	2-1
2.1.2 Multi-Fiber Mechanical Splice Assemblies	2-3
2.2 Applicable Work Conditions	2-4
2.3 Manufacturer's Data	2-4
2.4 Product Analysis	2-5
3. General Requirements and Objectives	3-1
3.1 Documentation	3-1
3.1.1 Practices	3-1
3.1.2 Workcenter Information Package	3-2
3.1.3 Safety	3-2
3.1.4 Compatibility With Other Systems	3-2
3.1.5 Fiber Preparation/Storage	3-3
3.1.6 Adhesives	3-3
3.2 General Splice Criteria	3-3
3.2.1 Fiber Number and Size	3-3
3.2.2 Environmental Sealing	3-4
3.2.3 Strain Relief	3-5
3.2.4 Grip-Type Mechanical Splice	3-5
3.2.5 Universal Installation	3-6
3.3 Marking, Packaging, and Shipping	3-7
3.3.1 Marking	3-7
3.3.2 Package Label	3-7

3.3.3	Packaging and Shipping.....	3-8
4.	Features, Functions, Performance Criteria.....	4-1
4.1	Equipment: General Requirements and Objectives	4-1
4.1.1	Portability	4-1
4.1.2	Carrying Case.....	4-2
4.1.3	Surface Finish And Markings	4-2
4.1.4	Display and Controls.....	4-3
4.1.4.1	General Display Criteria	4-3
4.1.4.2	State of Charge Indicator	4-5
4.1.4.3	General Controls Criteria.....	4-5
4.1.5	Fiber Contacting Devices.....	4-6
4.1.6	Features	4-6
4.1.6.1	Support Equipment	4-7
4.1.6.2	Proof-testing (Tensile Testing) Capability	4-8
4.1.6.3	Heat Shrink Oven Adjustment.....	4-10
4.1.6.4	Fiber Alignment.....	4-10
4.1.6.5	Settings and Adjustments.....	4-11
4.1.6.6	Splice Loss Estimation System.....	4-13
4.1.6.7	Detection of Fiber Misalignment, Dust, Excessive Cleave Angle.....	4-15
4.1.6.8	Electrode Life	4-17
4.1.6.9	Maximizing Yield by Preventative Maintenance	4-18
4.1.6.10	Safe Splicing in Manholes, Basements, Vaults	4-21
4.1.7	Product Information	4-22
4.2	Fiber Ribbonizing.....	4-22
4.2.1Ribbonizing Tool, General Requirements	4-22
4.2.2	Ribbon Geometry	4-24
4.3	Splice Optical Criteria.....	4-25
4.3.1	Mean Splice Loss	4-26
4.3.1.1	Passive Alignment Splices and Splicing Equipment	4-26
4.3.1.2	Active Alignment Splices and Splicing Equipment	4-27
4.3.2	Splice Yield.....	4-27
4.3.2.1	Passive Alignment Splices and Splicing Equipment	4-27
4.3.2.2	Active Alignment Splices and Splicing Equipment	4-28
4.3.3	Criteria for Loss Within a Splice Module	4-28
4.3.4	Splice Reflectance Criteria.....	4-29
4.3.5	Sensitivity to Fiber Geometry	4-30
4.3.5.1	Diameter Mismatch.....	4-30
4.3.5.2	Core/Cladding Concentricity Error.....	4-30
4.4	Fusion Splice Strength Criteria	4-31
4.5	Equipment: Mechanical and Storage Environments Criteria.....	4-32
4.5.1	Initial Operation	4-32
4.5.2	Cleave Angle Tolerance.....	4-33
4.5.3	Shock.....	4-34

4.5.4	Vibration, Transportation	4-35
4.5.5	Storage Environment.....	4-35
4.6	Equipment: Electrical Requirements.....	4-36
4.6.1	AC-Powered Equipment	4-36
4.6.2	Battery Unit.....	4-36
4.6.3	Battery Operation	4-38
4.6.3.1	Battery Life (Splice Modules Made with One Charge)...	4-38
4.6.3.2	Time-out and Interlock	4-40
4.6.3.3	State of Battery Charge.....	4-40
4.6.4	Electromagnetic Compatibility	4-42
4.7	Materials and Consumables Criteria	4-43
4.7.1	Coefficient of Thermal Expansion (CTE) Mismatch.....	4-43
4.7.2	Toxicity	4-43
4.7.3	Fungus Resistance	4-44
4.7.4	Shelf Life.....	4-44
4.7.5	Index Matching Material.....	4-44
4.8	Fiber Splicing - Installation Conditions	4-47
4.8.1	Low Temperature Installation Criteria.....	4-47
4.8.2	High Temperature and High Humidity Installation Criteria	4-47
4.8.3	High Temperature, Low Humidity Installation Criteria	4-48
4.8.4	High Altitude.....	4-48
4.8.5	Electrode Wear.....	4-49
4.8.6	Vibration During Operation	4-50
4.9	Mechanical Splice Environmental Life Test Criteria.....	4-50
4.9.1	Splice Strength	4-50
4.9.2	Temperature Cycling.....	4-51
4.9.3	Humidity/Condensation Cycling.....	4-52
4.9.4	Effect of Immersion on Splice Performance.....	4-52
4.9.5	Vibration Splice Loss.....	4-53
4.9.6	Strength After Environmental Degradation	4-54
5.	Performance Verification And Test Procedures	5-1
5.1	General Information	5-1
5.1.1	Selection of Optical Fiber	5-1
5.1.1.1	Fiber Type.....	5-1
5.1.1.2	Fiber Coating, Buffer, Ribbon	5-2
5.1.1.3	Fiber Geometry	5-2
5.1.2	Selecting the Test Product.....	5-3
5.1.3	Instructions and Training	5-3
5.1.4	Test Methods.....	5-3
5.1.4.1	Transmission Measurement Facility	5-4
5.1.4.1.1	Description of Test Facility	5-4
5.1.4.1.2	Splice Loss.....	5-5
5.1.4.1.3	Reflectance.....	5-5
5.1.4.1.4	Facility Requirements	5-6

5.1.4.2	Backscatter Measurement Facility.....	5-6
5.1.4.2.1	Description of Test Facility	5-6
5.1.4.2.2	Splice Loss.....	5-8
5.1.4.2.3	Splice Reflectance Measurements	5-9
5.1.5	Measurement Error.....	5-10
5.1.6	Mechanical Splice and Consumables Conditioning.....	5-10
5.2	Product Analysis Procedures.....	5-10
5.2.1	Splicing Test Series A: As-Received, Storage, Handling	5-11
5.2.1.1	Initial Operation, Series A.1	5-12
5.2.1.2	Sensitivity to Fiber Geometry, Series A.2	5-13
5.2.1.3	Cleave Angle Tolerance Series, A.3	5-13
5.2.1.4	Shock Series, A.4.....	5-14
5.2.1.5	Vibration, Transportation Series, A.5.....	5-14
5.2.1.6	Storage Environments Series, A.6.....	5-15
5.2.2	Splicing Test Series B - Installation and Assembly Conditions	5-15
5.2.2.1	Low Temperature, Series B.1	5-17
5.2.2.2	High Temperature and High Humidity, Series B.2	5-17
5.2.2.3	Condensing, Series B.3.....	5-17
5.2.2.4	High Temperature and Low Humidity, Series B.4	5-17
5.2.2.5	High Altitude, Series B.5.....	5-18
5.2.2.6	Electrode Wear, Erosion, and Deposits, Series B.6.....	5-18
5.2.2.7	Operational Vibration Test, Series B.7	5-20
5.2.3	Splicing Test Series C, Environmental Life Testing.....	5-21
5.2.3.1	Initial Assembly and Splice Strength, Series C.1	5-24
5.2.3.2	Temperature Cycling, Series C.2.....	5-25
5.2.3.3	Humidity/Condensation Cycling, Series C.3.....	5-26
5.2.3.4	Fluid Immersion, C.4.....	5-28
5.2.3.4.1	Bulk Material	5-28
5.2.3.4.2	Completed Splices	5-29
5.2.3.5	Splice Vibration Test, Series C.5.....	5-30
5.2.3.6	Temperature Cycling, Series C.6.....	5-30
5.2.3.7	Environmental Degradation, Series C.7	5-31
5.2.3.8	Environmental Degradation, Series C.8	5-31
5.3	Splicing Equipment - Battery Tests	5-31
5.3.1	Battery Life (Without Heat-Shrink)	5-31
5.3.2	Battery Life (With Heat-Shrink)	5-31
5.4	Fiber Splice Performance Parameters	5-32
5.4.1	Mean Splice Loss	5-32
5.4.2	Splice Yield.....	5-33
5.4.3	Reflectance	5-33
5.4.4	Splice Strength	5-34
	Requirement-Object List	ROL-1
	References	References-1

ReferencesBellcore Documents	References-1
ReferencesExternal Sources.....	References-3
Glossary	Glossary-1
Requirement-Object Index	ROI-1

List of Figures

Figure 2-1. Schematic of Fusion Splicing Process	2-2
Figure 2-2. Placement of Multiple Fibers within a Fusion Arc.....	2-2
Figure 2-3. Schematic of Mechanical Splices	2-3
Figure 3-1. Fiber Clamp and Guard Arrangements for Taut Sheath Environment vs. Optimum Visibility.....	3-6
Figure 4-1. Schematic of Arc Test (Meltback Test).....	4-17
Figure 4-2. Fiber Ribbon Dimensions (mm)	4-24
Figure 4-3. Effect of Cleave Angle and Arc Duration on Fusion Splice Loss	4-34
Figure 5-1. Transmission Measurement Test Facility	5-4
Figure 5-2. Description of OTDR Measurement Test Facility	5-7
Figure 5-3. Automated OTDR Measurement Test Facility	5-8
Figure 5-4. Key OTDR Reflectance Parameters	5-9
Figure 5-5. Temperature Cycling Profiles.....	5-26
Figure 5-6. Temperature/Humidity Profile for Humidity/Condensation Test.....	5-27

List of Tables

Table 1-1.Changes from GR-1095-CORE Issue 1 to Issue 2.....	1-2
Table 4-1. Splice Loss Estimator Accuracy Criteria.....	4-14
Table 4-2. Fiber Ribbon Dimensions.....	4-24
Table 5-1. Conditioning of Consumable Materials.....	5-10
Table 5-2.Splicing Test Series A.....	5-11
Table 5-3.Splicing Test Series B Assembly Conditions.....	5-16
Table 5-4. Electrode Wear Procedure.....	5-19
Table 5-5.Splicing Test Series C, Environmental Life Test.....	5-21
Table 5-6.Optical Measurement Sequence for Environmental Life Test.....	5-23
Table 5-7.Optical Criteria Applied During Environmental Life Test.....	5-24
Table 5-8.Full Temperature Cycling Profile: Taking Measurements.....	5-25
Table 5-9.Temperature Cycling Profile: Accelerated Mode.....	5-26
Table 5-10.Temperature/Humidity Profile for Humidity/Condensation Test.....	5-27
Table 5-11.Organism Exposure for Bulk Mineral Oil-based Material.....	5-29
Table 5-12.Organism Exposure for Completed Splices.....	5-29
Table 5-13.Calculation Points for Mean Splice Loss.....	5-32
Table 5-14.Calculation Points for Splice Yield.....	5-33