

Contents

[Telcordia GR-1295 - Documentation Information](#)

Preface	Preface-1
1. Introduction	1-1
1.1 Document Description	1-1
1.2 Summary of Significant Changes to GR-1295-CORE, Issue 1	1-2
1.3 Organization	1-3
1.4 Requirements Terminology	1-3
1.5 Requirement Labeling Conventions	1-4
1.5.1 Numbering of Requirement and Related Objects	1-4
1.5.2 Requirement, Conditional Requirement, and Objective Object Identification	1-5
1.6 Technical Feature/Function Analysis/Audit	1-5
1.7 Additional RFTS Documentation	1-5
2. General Information	2-1
2.1 Product Definition	2-1
2.2 Principles of RFTS Operation	2-3
2.3 OS/RFTS Interaction	2-7
2.4 Operating Environment	2-8
2.5 Fiber Optic System Considerations	2-9
3. RFTS Test Overview	3-1
3.1 Optical Fiber Deployment	3-1
3.2 OTDR Testing Techniques	3-2
3.2.1 Intrusive Testing	3-2
3.2.2 Non-Intrusive Testing	3-2
3.3 Point-to-Point versus Point-to-Multipoint Networks	3-3
3.4 Trouble Detection and Isolation	3-4
3.5 Manual Fault Locating	3-4
3.5.1 Manual Test Procedures	3-5
3.5.2 Optical Traces	3-5
3.6 Remote (Automatic) Fault Locating	3-5
3.7 Non-Intrusive Testing	3-6
3.7.1 Specific Non-Intrusive Testing Techniques	3-7
3.7.2 Optical Bridging Test Access Unit: Switch/Coupler/WDM Hardware	3-9
4. Fiber Distributing Frame Architecture for Test Systems	4-1
4.1 Integrated Frame and Bay Layout	4-1
4.2 Integrated Fiber Test System /FDF: General Issues	4-1
4.2.1 Physical Frame Location	4-2
4.2.2 Optical Testing Components/Placement	4-2
4.3 Non-Intrusive Testing of the Fiber Optic Network	4-3
4.3.1 Branching Component Terminations on the FDF to Support Non- Intrusive Testing	4-4
4.4 Fiber Management Issues On the Integrated Testing/FDF	4-5

4.4.1	Overview	4-5
4.4.2	Service Provisioning	4-6
5.	General Requirements	5-1
5.1	Operational Features:	5-1
5.2	Compatibility Features:	5-2
5.3	Input/Output Features:	5-2
5.4	Network Equipment-Building System (NEBS) Features:	5-3
5.5	Display and Control Features:	5-3
5.5.1	OS/TSC	5-3
5.5.2	OS/TSC/RTU	5-4
5.5.3	OS/TSC/OTAU	5-6
5.6	Unit Powering Features:	5-6
5.7	Optical Input/Output Port Features:	5-7
5.8	Calibration and Maintenance Features:	5-7
5.9	Product Information:	5-7
5.9.1	Documentation	5-7
5.9.2	Performance Specification Sheet	5-8
5.10	Product Marking and Packaging:	5-9
5.10.1	Product Markings	5-9
5.10.2	Packaging Markings	5-9
5.11	Safety Features:	5-10
6.	Specific Requirements	6-1
6.1	Operational Criteria	6-1
6.1.1	Spectral Characteristics	6-1
6.1.2	Measurement Range	6-1
6.1.3	Resolution	6-2
6.1.4	Accuracy	6-3
6.1.4.1	Distance Accuracy	6-3
6.1.4.2	Loss/Reflectance Accuracy	6-3
6.1.5	Measurement Time	6-4
6.1.6	Optical Bandpass of the OTAU	6-4
6.1.7	Insertion Loss of the OTAU	6-4
6.1.8	Uniformity of the OTAU	6-4
6.1.9	Crosstalk of the OTAU	6-5
6.1.10	Directivity of the OTAU	6-5
6.1.11	Reflectance of the OTAU	6-5
6.1.12	Switching Time of the OTAU	6-5
6.1.13	Switch Durability	6-6
6.2	Mechanical Design Criteria	6-6
6.2.1	Shock Tests	6-6
6.2.2	Earthquake Criteria	6-7
6.2.3	Vibration Criteria	6-7
6.3	Environmental Criteria	6-7
6.3.1	Non-Operating Environment	6-7
6.3.2	Operating Environment	6-7
6.3.3	Altitude	6-8

6.4	Electromagnetic Interference	6-8
6.5	Safety Criteria	6-8
7.	Performance Verification Test Procedures	7-1
7.1	Operational Criteria	7-1
7.1.1	Spectral Characteristics	7-1
7.1.2	Measurement Range	7-1
7.1.3	Resolution	7-1
7.1.4	Accuracy	7-1
7.1.5	Measurement Time	7-2
7.1.6	Optical Bandpass of the OTAU	7-2
7.1.7	Insertion Loss of the OTAU	7-2
7.1.8	Uniformity of the OTAU	7-2
7.1.9	Crosstalk of the OTAU	7-2
7.1.10	Directivity of the OTAU	7-2
7.1.11	Reflectance of the OTAU	7-2
7.1.12	Switching Time of the OTAU	7-2
7.1.13	Switch Durability	7-3
7.2	Mechanical Design Criteria	7-3
7.2.1	Shock Tests	7-3
7.2.2	Earthquake Tests	7-3
7.2.3	Vibration Test	7-3
7.3	Environmental Criteria	7-3
7.3.1	Non-Operating Environment	7-4
7.3.2	Operating Environment	7-4
7.4	Electromagnetic Interference and Electrostatic Discharge	7-4
7.4.1	Electromagnetic Interference	7-4
7.5	Safety Criteria	7-4
	References	References-1

List of Figures

Figure 2-1.	Telcordia Generic Test Architecture	2-2
Figure 2-2.	RFTS (shaded) Overlaid on the Schematic View of the Fiber Plant	2-4
Figure 2-3.	Schematic View of RFTS with Proprietary Interface to Optical Test Access	2-6
Figure 2-4.	Schematic View of RFTS with Generic Interfaces to the Optical Test Access Unit, the OS, and the Network	2-7
Figure 3-1.	Designated Test Fibers	3-2
Figure 3-2.	Simplified Non-Intrusive Test Architecture	3-3
Figure 3-3.	General Schematic: Non-Intrusive Testing of Optical Network .	3-7
Figure 3-4.	WDM/Filter Architecture: Non-Intrusive Testing of Optical Network	3-8
Figure 3-5.	Coupler/Filter Architecture: Non-Intrusive Testing of Optical Network	3-8
Figure 3-6.	WDM Architecture: Optical Bridging Test Access Unit (OBTAU)	3-10
Figure 3-7.	Coupler/Filter Architecture: Optical Bridging Test Access Unit (OBTAU)	3-11
Figure 3-8.	System Upgrade: Nx2N New Bridging Unit Added to Existing 1xN OTAU to Produce OBTAU	3-12
Figure 4-1.	Integrated Testing/FDF	4-1
Figure 4-2.	Possible Locations for Non-Intrusive Testing Splitters	4-5
Figure 4-3.	Generic Frame Mountable Branching Component	4-5

List of Tables

Table 1-1.	Summary of Feature/Function Testing	1-5
Table 2-1.	Near Worst-Case Measurement Ranges for Various Types of Fiber Systems Operating in the 1310 nm and 1550 nm Windows . . .	2-9
Table 2-2.	Requirement Parameters for Long Reach (LR) and Very Long Reach (VR) SONET Systems	2-11
Table 5-1.	Performance Specification Sheet: RFTS	5-8
Table 6-1.	RTU Centroidal Wavelength Requirements and Objectives . . .	6-1
Table 6-2.	Measurement Range Requirement Criteria for RFTS	6-2
Table 6-3.	Measurement Range Objectives Criteria for RFTS	6-2
Table 6-4.	Resolution Requirements for RFTS	6-2
Table 6-5.	Resolution Objectives for RFTS	6-3
Table 6-6.	Distance Accuracy Requirements	6-3
Table 6-7.	RFTS Loss/Reflectance Accuracy Requirements	6-3
Table 6-8.	RFTS Loss/Reflectance Accuracy Requirements	6-3