

# Contents

## [Telcordia GR-1398 - Documentation Information](#)

1. Introduction . . . . .	1-1
1.1 Purpose and Scope . . . . .	1-1
1.2 Organization . . . . .	1-1
2. General Information . . . . .	2-1
2.1 Description of Product . . . . .	2-1
2.2 Ordering Options . . . . .	2-2
2.2.1 User Considerations . . . . .	2-2
2.3 Requirements Terminology . . . . .	2-3
2.4 Reference Documents . . . . .	2-3
2.5 Safety Considerations . . . . .	2-3
2.6 Units and Tolerances . . . . .	2-4
2.7 Quality Assurance Programs . . . . .	2-4
3. General Requirements . . . . .	3-1
3.1 Packaging Requirements . . . . .	3-1
3.2 End Sealing . . . . .	3-1
3.3 Marking . . . . .	3-1
3.3.1 Package, Coil, and Reel Marking . . . . .	3-1
3.3.2 Jacket Marking . . . . .	3-1
3.3.3 Length Marking . . . . .	3-2
3.3.4 Jacket Marking Durability . . . . .	3-2
3.4 Compatibility with Hardware . . . . .	3-2
4. Mechanical Design and Test Requirements . . . . .	4-1
4.1 Center Conductor . . . . .	4-1
4.1.1 Copper-Clad Steel Wire . . . . .	4-1
4.1.2 Tensile Strength of Composite Conductor . . . . .	4-2
4.1.3 Elongation of Composite Conductor . . . . .	4-2
4.1.4 Adhesion of Copper . . . . .	4-2
4.1.5 Copper Ductility . . . . .	4-2
4.1.6 Joints . . . . .	4-2
4.2 Dielectric . . . . .	4-3
4.2.1 Material . . . . .	4-3
4.2.2 Shrinkback . . . . .	4-3
4.2.3 Thermal Oxidative Stability - OIT Test . . . . .	4-4
4.2.3.1 OIT Test Method - Initial (Before Aging) . . . . .	4-4
4.2.3.2 OIT Test Method - After Aging . . . . .	4-4
4.2.3.3 OIT Requirements . . . . .	4-5
4.2.4 Adhesion . . . . .	4-5
4.2.4.1 Adhesion - Shear . . . . .	4-5
4.2.4.2 Adhesion - Tensile . . . . .	4-5
4.2.5 Patching . . . . .	4-6
4.2.6 Insulation Imperfections . . . . .	4-6
4.3 Overall Shield . . . . .	4-6
4.3.1 Laminated Shielding Tape . . . . .	4-6

4.3.1.1 Bonding Shielding Tape . . . . .	4-6
4.3.1.2 Non-bonding Shielding Tape . . . . .	4-7
4.3.1.3 Shielding Tape Material . . . . .	4-7
4.3.1.4 Average Core Diameter . . . . .	4-7
4.3.1.5 Core Ovality . . . . .	4-7
4.3.2 Braid Wire . . . . .	4-8
4.3.2.1 Material . . . . .	4-8
4.3.2.2 Braid Coverage . . . . .	4-8
4.4 Flooding Compound Under Jacket . . . . .	4-9
4.4.1 Compound Flow . . . . .	4-9
4.4.2 Corrosion Resistance . . . . .	4-10
4.5 Cable Jacket . . . . .	4-10
4.5.1 Jacket Tensile Strength and Elongation . . . . .	4-11
4.5.1.1 PVC Jacket - Initial (Before Aging) . . . . .	4-11
4.5.1.2 PVC Jacket - Resistance to Aging . . . . .	4-11
4.5.1.3 PE Jacket - Initial (Before Aging) . . . . .	4-11
4.5.1.4 PE Jacket - Resistance to Aging . . . . .	4-11
4.5.2 Thermal Oxidative Stability - OIT Test (PE Only) . . . . .	4-12
4.5.3 Ultraviolet Light Stability . . . . .	4-12
4.5.3.1 PVC Jacket . . . . .	4-12
4.5.3.2 PE Jacket . . . . .	4-12
4.5.4 Jacket Porosity (PVC Only) . . . . .	4-12
4.5.5 Plasticizer Compatibility (PVC Only) . . . . .	4-12
4.5.6 Jacket Thickness . . . . .	4-12
4.5.7 Jacket Eccentricity . . . . .	4-13
4.5.8 Diameter Over Jacket . . . . .	4-14
4.6 Integral Messenger (IM) . . . . .	4-15
4.6.1 Joints . . . . .	4-15
4.6.2 Messenger Wire Separation . . . . .	4-15
4.7 Gopher Protected (GP) Armor . . . . .	4-15
4.7.1 Armor Construction . . . . .	4-15
4.7.2 Armor . . . . .	4-16
4.7.3 Gopher Resistance Test . . . . .	4-16
4.8 Outer Jacket . . . . .	4-17
5. Completed Cable Physical Tests . . . . .	5-1
5.1 Cold Bend . . . . .	5-1
5.2 Cable Impact Test . . . . .	5-1
5.3 Jacket Longitudinal Shrinkage . . . . .	5-1
5.4 Adhesion of Dielectric to Shield . . . . .	5-1
5.5 Flammability . . . . .	5-1
5.6 Abrasion Resistance . . . . .	5-2
5.7 Compression Resistance . . . . .	5-2
5.8 Water Penetration (Buried Cables Only) . . . . .	5-3
5.9 National Electrical Code Listing . . . . .	5-3
6. Completed Cable Electrical Requirements . . . . .	6-1
6.1 Continuity and Shorts . . . . .	6-1

6.2	Conductor Resistance . . . . .	6-1
6.3	Impedance . . . . .	6-1
6.4	Structural Return Loss (SRL) . . . . .	6-2
6.5	Shielding Effectiveness . . . . .	6-2
6.6	Attenuation . . . . .	6-4
6.7	Dielectric Strength Between Conductors . . . . .	6-5
6.8	Jacket Leakage Test . . . . .	6-5
6.9	Insulation Resistance . . . . .	6-5
	Appendix A: Durability of Printing and Marking Test . . . . .	A-1
	Appendix B: References . . . . .	B-1



## List of Figures

Figure 4-1	Illustration of Wire Braid . . . . .	4-9
Figure 4-2	Cross-Section of Jacket . . . . .	4-13



## List of Tables

Table 4-1	Center Conductor Diameter and Material Properties . . . . .	4-1
Table 4-2	Properties of Polyethylene . . . . .	4-3
Table 4-3	Drop Cable Adhesion to Center Conductor . . . . .	4-5
Table 4-4	Average Core Diameter Over Tape . . . . .	4-7
Table 4-5	Core Ovality, Maximum . . . . .	4-8
Table 4-6	Drop Cable Jacket Material Requirements . . . . .	4-10
Table 4-7	Diameter Over Jacket . . . . .	4-14
Table 6-1	DC Loop Resistance at 20°C (68°F), Maximum . . . . .	6-1
Table 6-2	Attenuation at 20°C (68°F), Maximum dB/100 ft. (dB/100m) . . . .	6-4