

Common Channel Signaling Network Interface Specification (CCSNIS) Supporting Broadband Services

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 General	1-1
1.2 Use and Background of this Document	1-1
1.3 Foundation Documents	1-3
1.4 Definitions	1-4
1.5 Requirements Terminology	1-7
1.6 Organization of Document	1-7
1.7 Summary of Changes for Issue 5 of GR-1431-CORE	1-8
2. SS7 Interconnection Architecture for ATM/Broadband Networking	2-1
3. MTP-3 and Lower Layer Protocols for B-ICI Signaling	3-1
3.1 Alternatives	3-1
3.2 Associated Mode Interconnection	3-1
3.2.1 Physical Layer	3-1
3.2.2 ATM Layer	3-2
3.2.3 SAAL at the NNI	3-2
3.2.3.1 Overview	3-2
3.2.3.2 AAL Common Part Protocol	3-4
3.2.3.3 SSCOP Protocol	3-4
3.2.3.4 SSCF	3-5
3.2.3.5 Layer Management-Related Specifications	3-6
3.2.4 Message Transfer Part - Level 3 (MTP-3)	3-8
3.2.4.1 Message Discrimination and Distribution	3-9
3.2.4.2 Message Routing	3-9
3.2.4.3 Signaling Link Activation/Restoration	3-9
3.2.4.4 Changeover	3-10
3.2.4.5 Changeback	3-10
3.2.4.6 Management Inhibiting	3-10
3.2.4.7 Message Priorities and Congestion Control	3-10
3.2.4.8 Signaling Link Test	3-11
3.2.4.9 MTP User Flow Control	3-11
3.2.4.10 MTP Restart	3-11
4. Internetwork Call Control Procedures	4-1
4.1 Call Control Capabilities	4-1
4.2 Internetwork Call Control Messages and Flows	4-1
4.2.1 Brief Description of Call Associated Messages	4-2
4.2.2 Brief Description of Point-to-Multipoint Call	4-5
4.2.3 Call Flow Variations	4-8

	4.2.3.1	Timer T_{303} Expires for the Second Time	4-8
	4.2.3.2	RELEASE COMPLETE Received in Response to SETUP Message	4-10
	4.2.3.3	IAR Received in Response to IAM	4-10
	4.2.3.4	Premature Release	4-10
4.3		Common Procedures	4-13
	4.3.1	Assignment Procedure for VPCI/VCI and Bandwidth	4-13
	4.3.1.1	Procedures for Management of VPCI/VCI Value and Bandwidth for Each VPC	4-14
	4.3.1.2	Assignment Procedure for VPCI and Bandwidth	4-14
	4.3.2	Signaling Identifiers (SIDs)	4-15
	4.3.3	Assignment of Connection Identifiers	4-17
	4.3.4	Simple Message Segmentation	4-17
	4.3.5	Message and Parameter Compatibility Functions	4-20
	4.3.5.1	Definitions	4-20
	4.3.5.2	Unrecognized Messages	4-21
	4.3.5.3	Unrecognized Parameters	4-21
	4.3.5.4	Response of a Client Company BSS When an Indication of Unrecognized Information is Received from an Interconnecting Network BSS	4-30
	4.3.5.5	Response of Interconnecting Network BSS to Unrecognized Information	4-31
	4.3.6	Propagation Delay Determination	4-31
	4.3.7	Completion of the Transmission Path	4-31
4.4		Originating Call Control Access	4-33
	4.4.1	Addressing Plan	4-33
	4.4.1.1	Carrier Presubscription and Routing	4-34
	4.4.1.2	Default Address	4-34
	4.4.2	Direct Access	4-37
	4.4.3	Access via Intermediate BSS	4-37
	4.4.4	Originating Point-to-Multipoint Procedures	4-42
	4.4.4.1	Case 1 - No Existing Connection Link	4-42
	4.4.4.2	Case 2 - Existing Connection Link	4-42
	4.4.5	Originating Access Parameters	4-42
	4.4.5.1	AAL-Parameters Parameter	4-43
	4.4.5.2	<i>ATM End System Address (AESA) for Called Party Parameter</i>	4-43
	4.4.5.2A	AESA for Additional Calling Party Parameter	4-44
	4.4.5.3	AESA for Calling Party Parameter	4-44
	4.4.5.4	Additional ATM Cell Rate Parameter	4-44
	4.4.5.5	ATM Cell Rate Parameter	4-44
	4.4.5.6	Broadband Bearer Capability (BBC) Parameter	4-44
	4.4.5.7	Broadband High Layer Information Parameter	4-45
	4.4.5.8	Broadband Low Layer Information Parameter	4-45
	4.4.5.9	Called Party Number Parameter	4-45
	4.4.5.10	Called Party Subaddress Parameter	4-45
	4.4.5.11	Calling Party Number (CPN) Parameter	4-45

4.4.5.12	Calling Party Subaddress Parameter	4-46
4.4.5.13	Calling Party's Category Parameter	4-46
4.4.5.14	Carrier Identification Parameter (CIP)	4-46
4.4.5.15	Carrier Selection Parameter	4-46
4.4.5.16	Charge Number Parameter	4-46
4.4.5.17	Connection Element Identifier (CEI) Parameter	4-47
4.4.5.18	Destination Connection Link Identifier (DCLI) Parameter	4-47
4.4.5.18A	Generic Address Parameter (GAP)	4-47
4.4.5.19	Leaf Party Type Parameter	4-47
4.4.5.19A	Link Layer Core Parameters Parameter	4-48
4.4.5.19B	Link Layer Protocol Parameters Parameter	4-48
4.4.5.19C	National/International Call Indicator Parameter	4-48
4.4.5.20	Network Call Correlation Identifier	4-48
4.4.5.20A	Number Portability Forward Information Parameter	4-48
4.4.5.21	Origination Connection Link Identifier (OCLI) Parameter	4-49
4.4.5.22	Originating Line Information (OLI) Parameter	4-49
4.4.5.23	Origination Signaling Identifier (OSID) Parameter	4-49
4.4.5.24	Quality of Service Parameter	4-49
4.4.5.25	Segmentation Indicator Parameter	4-50
4.4.5.26	Transit Network Selection (TNS) Parameter	4-50
4.4.5.27	Echo Control Information Parameter	4-50
4.4.5.28	Narrowband Bearer Capability Parameter	4-50
4.4.5.29	Narrowband High Layer Compatibility Parameter	4-50
4.4.5.30	Narrowband Low Layer Compatibility Parameter	4-50
4.4.5.31	Progress Indicator Parameter	4-51
4.4.5.32	Backward Narrowband Interworking Indicator Parameter	4-51
4.4.5.33	Forward Narrowband Interworking Indicator Parameter	4-51
4.4.5.34	In-Band Information Indicator	4-51
4.4.5.35	Suspend/Resume Indicators Parameter	4-51
4.5	Terminating Call Control Access	4-51
4.5.1	Parameters Received by Terminating Entry BSS	4-57
4.5.2	Terminating Call Screening	4-57
4.6	Independent Local Exchange Carrier (ILEC) Interconnection	4-58
4.6.1	InterLATA or International Calls	4-58
4.6.1.1	Calls Originating in ILEC Network	4-58
4.6.1.2	Calls Terminating in ILEC Network	4-58
4.6.2	IntraLATA Calls	4-59
5.	Internetwork Call Control Messages	5-1
5.1	Address Complete Message (ACM)	5-1
5.1.1	Origination	5-1
5.1.2	Subsequent Signaling	5-3

5.2	Answer Message (ANM)	5-3
5.2.1	Origination	5-3
5.2.2	Subsequent Signaling	5-4
5.3	Call Progress Message (CPG)	5-5
5.3.1	Origination	5-5
5.3.2	Subsequent Signaling	5-6
5.4	Exit Message (EXM)	5-6
5.5	Initial Address Message (IAM)	5-7
5.5.1	Interface Between Client Company Network and IXC or INC for InterLATA Traffic	5-7
5.5.1.1	Call Originating in Client Company Network	5-7
5.5.1.2	Call Originating in ILEC's Network	5-33
5.5.1.3	Call from Interconnecting Network to Client Company Network (Network of Origination Unknown)	5-33
5.5.2	Interface Between Client Company Network and ILEC's Network	5-34
5.5.2.1	IntraLATA Calls	5-34
5.5.2.2	InterLATA Calls	5-36
5.5.3	Subsequent Signaling	5-37
5.6	IAM Acknowledgment (IAA) Message	5-37
5.6.1	Origination	5-37
5.6.2	Subsequent Signaling	5-38
5.7	IAM Reject (IAR) Message	5-38
5.7.1	Origination	5-38
5.7.2	Subsequent Signaling	5-39
5.8	Release Message (REL)	5-39
5.8.1	Origination	5-39
5.8.2	Subsequent Signaling	5-41
5.9	Release Complete Message (RLC)	5-41
5.9.1	Origination	5-41
5.9.2	Subsequent Signaling	5-41
5.10	Segmentation Message (SGM)	5-41
5.10.1	Origination	5-41
5.10.2	Subsequent Signaling	5-42
5.11	Suspend Message (SUS)	5-42
5.11.1	Origination	5-42
5.11.2	Subsequent Signaling	5-42
5.12	Resume Message (RES)	5-43
6.	Interconnection with Private Networks	6-1
7.	Maintenance Control Procedures and Messages	7-1
7.1	Blocking and Unblocking of Virtual Paths	7-1
7.2	Blocking Procedures	7-1
7.2.1	Client Company Procedures at Sending BSS	7-1
7.2.2	Client Company Procedures at Receiving BSS	7-2
7.2.3	Interconnecting Network Procedures at Receiving BSS	7-2
7.3	Unblocking Procedures	7-2

7.3.1	Client Company Procedures at Sending BSS	7-3
7.3.2	Client Company Procedures at Receiving BSS	7-3
7.3.3	Interconnecting Network Procedures at Receiving BSS	7-3
7.4	Reset Procedure	7-3
7.4.1	Client Company Procedures at Sending BSS - Reset Procedures for Point-to-Multipoint Calls	7-5
7.4.2	Client Company Procedures at Sending BSS	7-6
7.4.2.1	Reset Procedures for Point-to-Multipoint Connections - Client Company Procedures at Sending BSS	7-6
7.4.3	Client Company Procedures at Receiving BSS	7-7
7.4.3.1	Reset Procedures for Point-to-Multipoint Connections - Client Company Procedures at Receiving BSS	7-8
7.4.4	Interconnecting Network Procedures at Receiving BSS	7-8
7.5	User Part Availability Procedure	7-8
7.5.1	Client Company Procedures at Sending BSS	7-8
7.5.2	Client Company Procedures at Receiving BSS	7-9
7.5.2.1	Unavailability Cause: "Inaccessible Remote User"	7-9
7.5.2.2	Unavailability Cause: "Unequipped Remote User"	7-10
7.5.3	Interconnecting Network Procedures at Receiving BSS	7-10
7.6	Automatic Congestion Control	7-10
7.6.1	Client Company Procedures at Sending BSS	7-11
7.6.2	Client Company Procedures at Receiving BSS	7-11
7.6.3	Interconnecting Network Procedures at Receiving BSS	7-11
7.7	BISUP Signaling Congestion Control	7-11
7.8	VPCI Consistency Check Procedures	7-12
7.8.1	Initiating the VPCI Consistency Check - Client Company Procedures at Sending BSS	7-13
7.8.2	Initiating the VPCI Consistency Check - Client Company Procedures at Receiving BSS	7-13
7.8.3	Initiating the VPCI Consistency Check - Interconnecting Network Procedures at the Receiving BSS	7-14
7.8.4	Ending the VPCI Consistency Check - Client Company Procedures at Sending BSS	7-14
7.8.5	Ending the VPCI Consistency Check - Client Company Procedures at Receiving BSS	7-14
7.8.6	Ending the VPCI Consistency Check - Interconnecting Network Procedures at Receiving BSS	7-14
8.	Performance	8-1
9.	Interface Provisioning, Operations, and Maintenance	9-1
	Appendix A: BISUP Messages	A-1
	Appendix B: BISUP Parameters	B-1
B.1	Parameter Name Codes	B-1
B.2	AAL Parameters	B-3
B.3	AESA for Called Party	B-3
B.4	AESA for Calling Party	B-4

B.5	Additional ATM Cell Rate	B-4
B.6	ATM Cell Rate	B-6
B.7	Automatic Congestion Level	B-6
B.8	Broadband Bearer Capability	B-7
B.9	Broadband High Layer Information	B-8
B.10	Broadband Low Layer Information	B-8
B.11	Called Party Number	B-9
B.12	Called Party Subaddress	B-11
B.13	Called Party's Indicators	B-11
B.14	Calling Party Number	B-12
B.15	Calling Party Subaddress	B-14
B.16	Calling Party's Category	B-14
B.17	Carrier Identification Code	B-15
B.18	Carrier Selection Information	B-17
B.19	Cause Indicators	B-17
B.20	Charge Number	B-18
B.21	Connection Element Identifier	B-19
B.22	Consistency Check Result Information	B-20
B.23	Destination Connection Link Identifier	B-21
B.24	Destination Signaling Identifier	B-21
B.25	Generic Address	B-21
B.26	Leaf Party Type	B-22
B.27	Network Call Correlation Identifier	B-22
B.28	Origination Connection Link Identifier	B-23
B.29	Originating Line Information	B-23
B.30	Origination Signaling Identifier	B-24
B.31	Outgoing Facility Identifier	B-25
B.32	Quality of Service	B-25
B.33	Resource Identifier	B-26
B.34	Segmentation Indicator	B-27
B.35	Transit Network Selection	B-27
B.36	Echo Control Information	B-29
B.37	Narrowband Bearer Capability	B-30
B.38	Narrowband High Layer Compatibility	B-31
B.39	Narrowband Low Layer Compatibility	B-32
B.40	Progress Indicator	B-33
B.41	Backward Narrowband Interworking Indicator	B-34
B.42	Forward Narrowband Interworking Indicator	B-35
B.43	In-Band Information Indicators	B-35
B.44	Suspend/Resume Indicators	B-36
B.45	Link Layer Core Parameters	B-36
B.46	Link Layer Protocol Parameters	B-37
B.47	Number Portability Forward Information	B-37
B.48	AESA for Additional Calling Party	B-38
B.49	National/International Call Indicator	B-39
	Appendix C: BISUP Timers	C-1

Appendix D: BISUP Message Priorities D-1

Appendix E: Coding of the Message and Parameter Compatibility Information

 Subfields E-1

 E.1 Coding of the Message Compatibility Information Subfields E-1

 E.2 Coding of the Parameter Compatibility Information Subfields E-2

References References-1

Glossary Acronyms-1

List of Figures

Figure 1-1.	Relationship of Virtual Path/Connection Terms to ATM Network Elements	1-6
Figure 2-1.	Network Signaling Protocol Stacks for BISUP	2-1
Figure 2-2.	BISUP Over ATM in the CCS Associated Mode Signaling Network Interconnection Architecture	2-2
Figure 2-3.	Client Company STPs to ICN STPs Quasi-Associated Signaling Network Interconnection Architecture	2-3
Figure 2-4.	Client Company STPs to ICN BSS Quasi-Associated Signaling Network Interconnection Architecture	2-4
Figure 3-1.	SAAL for NNI Signaling	3-3
Figure 4-1.	Typical BISUP Call Setup and Release Message Flow (Assumes Calling Party Disconnect)	4-4
Figure 4-2.	Set-Up of a Unidirectional Point-to-Multipoint Call	4-6
Figure 4-3.	Set-Up of a Unidirectional Point-to-Multipoint Call (Concluded)	4-7
Figure 4-4.	Drop of a Leaf Party (Party B) by the Root and the Leaf Parties (Parties C and D) by Themselves	4-7
Figure 4-5.	En Bloc Release of the Call by the Root	4-8
Figure 4-6.	Call Clearing Because of Expiration of Timer T_{303} for the Second Time	4-9
Figure 4-7.	Call Cleared by Called User	4-11
Figure 4-8.	Call Released by Terminating BSS Using IAR Message	4-12
Figure 4-9.	Premature Release	4-13
Figure 4-10.	Assigning and Releasing Signaling Associations	4-16
Figure 4-11.	Use of SGM to Transmit IAM Parameters (Call Rejected by Terminating User)	4-19
Figure 4-12.	Interpretation of Message Compatibility Information Field for Type A or Type B BSS	4-23
Figure 4-12A.	Interpretation of Message Compatibility Information Field for Type A or Type B BSS (Continued from Figure 4-12)	4-24
Figure 4-13.	Interpretation of Parameter Compatibility Information Sub-Field for Type A or Type B BSS	4-27
Figure 4-14.	Interpretation of Parameter Compatibility Information Sub-Field for Type A or Type B BSS (Continued from Figure 4-13)	4-28
Figure 4-14A.	Interpretation of Parameter Compatibility Information Field for Type A or Type B BSS (Continued from Figure 4-13)	4-29
Figure 4-15.	Routing at Originating BSS	4-35
Figure 4-16.	Routing at Originating BSS (Continued from Figure 4-15)	4-36
Figure 4-17.	Originating Call Control Access: Direct	4-38
Figure 4-18.	Originating Call Control Access: Via Intermediate BSS	4-39
Figure 4-18A.	Originating Call Control Access: Via Intermediate IW BSS	4-40
Figure 4-18B.	Originating Call Control Access: Via Intermediate IW BSS	4-41

Figure 4-19. Terminating Call Control Access: Direct 4-52
Figure 4-20. Terminating Call Control Access: Via Intermediate BSS 4-53
Figure 4-20A. Terminating Call Control Access: Via Intermediate IW BSS . . 4-55
Figure 4-20B. Terminating Call Control Access: Via Intermediate IW BSS . . 4-56
Figure 4-21. IntraLATA ILEC Interconnection - Direct 4-59
Figure 4-22. IntraLATA ILEC Interconnection - Via Intermediate BSS 4-60
Figure 4-22A. IntraLATA ILEC Interconnection - Via Intermediate IW BSS . . 4-61
Figure 4-22B. IntraLATA ILEC Interconnection - Via Intermediate IW BSS . . 4-62
Figure 6-1. Public and Private Network Interworking Configuration 6-1

List of Tables

Table 3-1.	SSCOP Timers and Parameter Values	3-4
Table 3-2.	SSCF Timers and Parameter Values	3-6
Table 3-3.	Layer Management Parameters and Timers	3-7
Table 4-1.	Message Compatibility Information Field	4-22
Table 4-2.	Parameter Compatibility Information Subfield	4-25
Table 5-1.	Coding Rules for the Called Party Number Parameter	5-13
Table 5-2.	Coding of Nature of Address Indicator	5-18
Table A-1.	B-ISDN User Part Message Format	A-2
Table A-2.	B-ISDN User Part Parameter Format	A-2
Table A-3.	Message Type Code	A-3
Table A-4.	Address Complete Message	A-4
Table A-5.	Answer Message	A-4
Table A-6.	Call Progress Message	A-4
Table A-7.	Confusion Message	A-5
Table A-8.	Consistency Check Request Message	A-5
Table A-9.	Consistency Check Request Acknowledgment Message	A-5
Table A-10.	Consistency Check End Message	A-5
Table A-11.	Consistency Check End Acknowledgment Message	A-5
Table A-12.	Exit Message	A-5
Table A-13.	Initial Address Message	A-6
Table A-14.	IAM Acknowledgment Message	A-7
Table A-15.	IAM Reject Message	A-7
Table A-16.	Release Message	A-8
Table A-17.	Release Complete Message	A-8
Table A-18.	Blocking, Reset, Unblocking Messages	A-8
Table A-19.	Blocking Acknowledgment, Reset Acknowledgment, Unblocking Acknowledgment Messages	A-8
Table A-20.	User Part Available Message	A-9
Table A-21.	User Part Test Message	A-9
Table A-22.	Segmentation Message	A-9
Table A-23.	Suspend, Resume	A-9
Table B-1.	Parameter Names and Codes	B-1
Table B-2.	AAL-Parameters Parameter	B-3
Table B-3.	AESA for Called Party Parameter Field	B-3
Table B-4.	AESA for Calling Party Parameter Field	B-4
Table B-5.	Additional ATM Cell Rate Parameter Field	B-4
Table B-6.	ATM Cell Rate Parameter	B-6
Table B-7.	Automatic Congestion Level Parameter	B-7
Table B-8.	Broadband Bearer Capability Parameter	B-7
Table B-9.	Broadband High Layer Information Parameter	B-8
Table B-10.	Broadband Low Layer Information Parameter	B-8
Table B-11.	Called Party Number Parameter	B-9

Table B-12.	Called Party Subaddress Parameter	B-11
Table B-13.	Called Party's Indicators Parameter	B-11
Table B-14.	Calling Party Number Parameter	B-12
Table B-15.	Calling party's Category Parameter	B-14
Table B-16.	Carrier Identification Parameter with 3-Digit Carrier Identification Parameter Field	B-15
Table B-17.	Carrier Identification Parameter with 4-Digit Carrier Identification Parameter Field	B-15
Table B-18.	Codes Used in Fields of Carrier Identification Parameter	B-16
Table B-19.	Carrier Selection Parameter	B-17
Table B-20.	Cause Indicators Parameter	B-17
Table B-21.	Charge Number Parameter	B-18
Table B-22.	Connection Element Identifier Parameter	B-19
Table B-23.	Consistency Check Result Information Parameter	B-20
Table B-24.	Destination Connection Link Identifier Parameter	B-21
Table B-25.	Destination Signaling Identifier Parameter	B-21
Table B-26.	Leaf Party Type Parameter	B-22
Table B-27.	Network Call Correlation Identifier	B-22
Table B-28.	Origination Connection Link Identifier Parameter	B-23
Table B-29.	Originating Line Information Parameter	B-23
Table B-30.	Outgoing Facility Identifier Parameter	B-25
Table B-31.	QoS Parameter Field	B-25
Table B-32.	Resource Identifier Parameter	B-26
Table B-33.	Segmentation Indicator Parameter	B-27
Table B-34.	Transit Network Selection Parameter with 3-Digit Carrier Identification Code	B-27
Table B-35.	Transit Network Selection Parameter Field with 4-digit Carrier Identification Code	B-27
Table B-36.	Codes for Circuit Code Subfield	B-29
Table B-37.	Echo Control Information Parameter Field	B-29
Table B-38.	Narrowband Bearer Capability Parameter Field	B-30
Table B-39.	Narrowband High Layer Compatibility Parameter Field	B-31
Table B-40.	Narrowband Low Layer Compatibility Parameter Field	B-32
Table B-41.	Progress Indicator Parameter Field	B-33
Table B-42.	Backward Narrowband Interworking Indicator Parameter Field	B-34
Table B-43.	Forward Narrowband Interworking Indicator Parameter Field	B-35
Table B-44.	In-band Information Indicators Parameter Field	B-36
Table B-45.	Suspend/Resume Indicators Parameter Field	B-36
Table B-46.	Link Layer Core Parameters Parameter Field	B-37
Table B-47.	Link Layer Protocol Parameters Parameter Field	B-37
Table B-48.	Number Portability Forward Information Parameter Field	B-37
Table B-49.	AESA for Additional Calling Party Parameter Field	B-38
Table B-50.	National/International Call Indicator Parameter Field	B-39
Table D-1.	BISUP Message Priorities	D-1
Table E-1.	Coding of the Message Instruction Indicators	E-1

Table E-2. Coding of the Parameter Instruction Indicators E-4