
CCS Network Interface Specification (CCSNIS) Supporting Wireless Services Providers

Contents

Preface	Preface-1
1. Introduction.....	1-1
1.1 Purpose.....	1-3
1.2 Relationship With GR-145-CORE.....	1-4
1.3 Relationship With GR-1411-CORE.....	1-4
1.4 Changes from Previous Issues of GR-1434	1-5
1.4.1 Changes to GR-1434-CORE, Issue 1.....	1-5
1.4.2 Changes to GR-1434 Issue 2.....	1-5
1.5 Wireless Number Portability (WNP)	1-6
1.6 Wireless Intelligent Network (WIN).....	1-6
1.7 Enhanced Wireless Emergency Services (E9-1-1) Phase 2	1-8
2. CCS Network Interconnection Architecture.....	2-1
2.1 CCS Network Interconnection for Circuit-Related Applications	2-1
2.1.1 Basic Call Control.....	2-1
2.1.2 Toll-Free Service.....	2-2
2.1.3 Support for the Passing of Calling Party Number During Call Setup.....	2-2
2.1.4 Support for the Passing of Calling Party Number Anonymity Status During Call Setup.....	2-4
2.1.5 Support for the Passing of Call Forwarding Information During Call Setup.....	2-5
2.1.6 Support for the Passing of Jurisdiction Information To/From a WSP During Call Setup.....	2-5
2.1.7 Support for the Passing of Charge Number and Originating Line Information from a WSP to an IXC During Call Setup.....	2-6
2.1.8 Support for the Passing of Carrier Selection Method from a WSP to an IXC During Call Setup.....	2-6
2.1.9 Support for the Passing of Carrier Identification Information from a WSP to an IXC During Call Setup	2-6
2.1.10 Support for the delivery of Generic Name Parameter for WIN Phase 1 CNAP.....	2-7
2.1.11 Support for the Passing of Calling Party Name Anonymity Status During Call Setup.....	2-7
2.1.12 PCS 1900 (North American GSM) Services.....	2-8
2.1.13 Support for the Delivery of Enhanced Emergency Services (E9-1-1) Calls from WSP Customers.....	2-9

2.1.14	Support for Wireless Number Portability	2-9
2.2	CCS Network Interconnection for Pure SS7 Message Transport	2-9
2.2.1	ISDNUP Message Transport for Non-Bcc-Switched Trunk Circuit Connections.....	2-11
2.2.2	IS-41 Revision A TCAP Message Transport.....	2-11
2.2.3	IS-41 Revision B TCAP Message Transport	2-11
2.2.4	ANSI-41 TCAP Message Transport	2-12
2.2.5	ANSI-41 TCAP Message Transport using the International Mobile Station Identity (IMSI).....	2-13
2.2.6	TCAP Message Transport for PCS 1900 (North American GSM) Services	2-13
2.2.7	TCAP Message Transport for Over-the-Air Service Provisioning (OTASP)	2-14
2.2.8	TCAP Message Transport for HLR-based Calling Name Services	2-15
2.2.9	TCAP Message Transport for WIN Phase 1	2-15
2.2.10	TCAP Message Transport for WNP	2-16
2.2.11	TCAP Message Transport for Wireless Services Impacted by WNP.....	2-16
2.3	CCS Network Interconnection for TCAP-based Applications	2-16
2.3.1	Toll-Free Database Access.....	2-17
2.3.2	Calling Name Delivery	2-18
2.4	Disclosure of Routing and Addressing Information	2-18
2.4.1	Address Disclosure for Circuit-Related Applications.....	2-19
2.4.2	Address Disclosure for Pure SS7 Message Transport	2-19
2.4.3	Address Disclosure for TCAP-based Applications.....	2-21
3.	Interface Protocol.....	3-1
3.1	Message Transfer Part (MTP).....	3-1
3.2	ISDN User Part (ISDNUP)	3-1
3.3	Signaling Connection Control Part (SCCP).....	3-1
3.4	Transaction Capabilities Application Part (TCAP).....	3-1
4.	ISDN User Part Message Flow Scenarios.....	4-1
4.1	Example End-to-End Message Flows	4-1
4.2	WSC Originations on a Type 2A with SS7 Interface	4-1
4.3	WSC Terminations on a Type 2A with SS7 Interface	4-2
4.4	Interworking With MF Signaling on a Type 2A Interface.....	4-3
4.5	WSC Originations and Terminations on a Type 2B with SS7 Interface.....	4-3
4.6	Interworking a Type 1 Interface with an SS7 Trunk.....	4-4
4.7	WSC Originations and Terminations on a Type 1 with ISDN Interface	4-4
4.8	WSC Originated Emergency Services (E9-1-1) Phase 1 and Phase 2 Calls on a Type 2C Interface with SS7	4-5
4.9	Wireless Number Portability (WNP) Call Flows.....	4-5
5.	Capability Related Protocol	5-1

5.1	ISDN User Part Internetwork Call Control Protocol	5-1
5.1.1	Address Complete Message	5-2
5.1.2	Answer Message	5-2
5.1.3	Circuit Reservation Message	5-2
5.1.4	Circuit Reservation Acknowledgment Message	5-2
5.1.5	Continuity Message.....	5-2
5.1.6	Exit Message	5-2
5.1.7	Initial Address Message	5-3
5.1.7.1	Interface Between Bcc Network and IXC or INC for InterLATA Traffic	5-3
5.1.7.2	Interface Between Bcc Network and ILEC's Network	5-3
5.1.7.3	Interface Between Bcc Network and WSP Network	5-3
5.1.7.3.1	Calls Without IXC/INC Involvement	5-4
5.1.7.3.2	Calls With IXC/INC Involvement	5-7
5.1.8	Release Message	5-10
5.1.9	Release Complete Message.....	5-10
5.1.10	Resume Message.....	5-10
5.1.11	Suspend Message	5-10
5.1.12	Call Progress Message	5-10
5.1.13	Confusion Message	5-11
5.2	ISDN User Part Toll-Free Service Protocol.....	5-11
5.3	Line Information Database (LIDB) Access Protocol.....	5-11
5.4	ISDN User Part Protocol to Support ISDN Access	5-11
5.5	ISDN User Part Protocol to Support Calling Name Delivery Blocking Applications	5-12
5.6	ISDN User Part Protocol to Support Wireless Enhanced Emergency Services (E9-1-1)	5-12
5.7	ISDN USER PART to Wireless Enhanced Emergency Services (E9-1-1) Phase II	5-13
6.	Signaling Connection Control Part (SCCP).....	6-1
6.1	SCCP Information for Toll-Free Service	6-1
6.2	SCCP Information for IS-41 Rev. A TCAP Message Transport	6-1
6.3	SCCP Information for IS-41 Rev. B TCAP Message Transport	6-2
6.3.1	Messages Sent from the WSP to the Bcc	6-3
6.3.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-3
6.3.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-4
6.3.2	Messages Sent from the Bcc to the WSP	6-5
6.3.2.1	Message Requires WSP to Perform Global Title Translation.....	6-5
6.3.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-6
6.4	SCCP Information for Calling Name Delivery (CNAM)	6-7

6.5	SCCP Information for ANSI-41 TCAP Message Transport.....	6-7
6.5.1	Messages Sent from the WSP to the Bcc	6-7
6.5.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-7
6.5.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-8
6.5.2	Messages Sent from the Bcc to the WSP	6-8
6.5.2.1	Message Requires WSP to Perform Global Title Translation.....	6-9
6.5.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-9
6.6	SCCP Information for IS-725 (OTASP) TCAP Message Transport	6-10
6.6.1	Messages Sent from the WSP to the Bcc	6-10
6.6.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-10
6.6.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-10
6.6.2	Messages Sent from the Bcc to the WSP	6-10
6.6.2.1	Message Requires WSP to Perform Global Title Translation.....	6-11
6.6.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-11
6.7	SCCP Information for PCS 1900 TCAP Message Transport	6-11
6.7.1	Messages Sent from the WSP to the Bcc	6-12
6.7.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-12
6.7.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-12
6.7.2	Messages Sent from the Bcc to the WSP	6-12
6.7.2.1	Message Requires WSP to Perform Global Title Translation.....	6-12
6.7.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-13
6.8	SCCP Information for IS-751 (ANSI-41 Support for IMSI) TCAP Message Transport	6-13
6.8.1	Messages Sent from the WSP to the Bcc	6-13
6.8.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-13
6.8.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-13
6.8.2	Messages Sent from the Bcc to the WSP	6-13
6.8.2.1	Message Requires WSP to Perform Global Title Translation.....	6-14

6.8.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-14
6.9	SCCP Information for IS-764 (HLR-based Calling Name Services) TCAP Message Transport	6-14
6.10	SCCP Information for TCAP Message Transport for Wireless Number Portability (WNP)	6-14
6.10.1	Messages Sent from the WSP to the Bcc	6-15
6.10.1.1	Message Requires Bcc to Perform Global Title Translation (For Further Study)	6-15
6.10.1.2	Message Does not Require Bcc to Perform Global Title Translation.....	6-15
6.10.2	Messages Sent from the Bcc to the WSP	6-15
6.10.2.1	Message Requires WSP to Perform Global Title Translation.....	6-16
6.10.2.2	Messages Does Not Require WSP to Perform Global Title Translation.....	6-17
6.11	SCCP Information for TCAP Message Transport for Wireless Intelligent Network (WIN) Phase-1 Services (ANSI-41)	6-17
6.11.1	Messages Sent from the WSP to the Bcc	6-18
6.11.1.1	Message Requires Bcc to Perform Global Title Translation.....	6-18
6.11.1.2	Message Does Not Require Bcc to Perform Global Title Translation.....	6-19
6.11.2	Messages Sent from the Bcc to the WSP	6-19
6.11.2.1	Message Requires WSP to Perform Global Title Translation.....	6-19
6.11.2.2	Message Does Not Require WSP to Perform Global Title Translation.....	6-20
7.	Transaction Capabilities Application Part (TCAP)	7-1
7.1	Toll-Free Service.....	7-1
7.2	LIDB Access	7-1
7.3	PCS Home Database Service	7-1
7.4	Calling Name Delivery (CNAM).....	7-1
	Appendix A: ISDN User Part Message Flow Diagrams	A-1
	References	References-1
	Glossary	Glossary-1

List of Figures

Figure 2-1.	Bcc Provides Pure SS7 Message Transport and Routing Functions	2-10
Figure 2-2.	Bcc Provides Non-Circuit Related (TCAP-based) Applications.....	2-17
Figure A-1.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release Involving Bccs and an IXC	A-2
Figure A-2.	Typical Message Flow for Type 2A with SS7 Land-to-Mobile Call Setup and Release Involving Bccs and an IXC	A-3
Figure A-3.	Typical Message Flow for Type 2A with SS7 Mobile-to-Mobile Call Setup and Release Involving Bccs and an IXC	A-4
Figure A-4.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release	A-5
Figure A-5.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release With SS7-MF Interworking.....	A-6
Figure A-6.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release to FGD IXC Via Bcc Tandem	A-7
Figure A-7.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release to FGD IXC Via Bcc Tandem With SS7-MF Interworking	A-8
Figure A-8.	Typical Message Flow for Type 2A with SS7 Mobile-to-Land Call Setup and Release to FGD INC Via Bcc Tandem With SS7-MF Interworking	A-9
Figure A-9.	Typical Message Flow for Type 2A with SS7 Land-to-Mobile Call Setup and Release	A-10
Figure A-10.	Typical Message Flow for Type 2A with SS7 Land-to-Mobile Call Setup and Release from FGD IXC Via Bcc Tandem	A-11
Figure A-11.	Typical Message Flow for Type 2A with SS7 Land-to-Mobile Call Setup and Release With MF-SS7 Interworking.....	A-12
Figure A-12.	Typical Message Flow for Type 2A Land-to-Mobile Call Setup and Release With SS7-MF Interworking.....	A-13
Figure A-13.	Typical Message Flow for Type 2A Mobile-to-Land Call Setup and Release With MF-SS7 Interworking	A-14
Figure A-14.	Typical Message Flow for Type 2A Mobile-to-Land Call Setup and Release to FGD IXC Via Bcc Tandem With MF-SS7 Interworking	A-15
Figure A-15.	Typical Message Flow for Type 2A Mobile-to-Land Call Setup and Release to FGD INC Via Bcc Tandem With MF-SS7 Interworking	A-16
Figure A-16.	Typical Message Flow for Type 2B with SS7 Mobile-to-Land Call Setup and Release	A-17
Figure A-17.	Typical Message Flow for Type 2B with SS7 Land-to-Mobile Call Setup and Release	A-18
Figure A-18.	Typical Message Flow for Type 1 Land-to-Mobile Call Setup and Release	A-19

Figure A-19. Typical Message Flow for Type 1 Mobile-to-Land Call Setup and Release	A-20
Figure A-20. Typical Message Flow for Type 1 Mobile-to-Land Call Setup and Release to FGD IXC Via Bcc End Office	A-21
Figure A-21. Typical Message Flow for Type 1 Mobile-to-Land Call Setup and Release to FGD IXC Via Bcc End Office and Bcc Tandem	A-22
Figure A-22. Typical Message Flow for Type 1 Mobile-to-Land Call Setup and Release to FGD INC Via Bcc End Office	A-23
Figure A-23. Typical Message Flow for Type 1 with ISDN Mobile-to-Land Call Setup and Release to Bcc or ILEC End Office, or FGD IXC or INC, Via Bcc End Office.....	A-24
Figure A-24. Typical Message Flow for Type 1 with ISDN Land-to-Mobile Call Setup and Release	A-25
Figure A-25. Typical Message Flow for Type 2C with SS7 Mobile to Land Emergency Services (E9-1-1) Phase 1 and Phase 2 Call Setup and Release	A-26
Figure A-26. Call to Ported Wireline Customer - WSC Support for LNP.....	A-27
Figure A-27. Call in Area of Portability But Number Not Ported	A-28
Figure A-28. Call to Ported Wireline Customer - PSTN Support for LNP	A-29
Figure A-29. Call to Ported Wireline Customer - IXC Support for LNP	A-30