
Generic Requirements for Call-by-Call Service Selection Access to Interexchange Carrier (IXC) Services Via Signaling System No. 7 (SS7)

Contents

Preface	Preface-1
Introduction to Revision 1	Revision-1
1. Introduction	1-1
1.1 Definition	1-1
1.2 Background	1-2
1.3 Nomenclature	1-3
1.4 Document Organization	1-4
1.5 Requirements Terminology	1-5
1.6 Requirement Labeling Conventions.....	1-6
1.6.1 Numbering of Requirement and Related Objects	1-6
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification	1-6
2. Feature Description and Assumptions	2-1
2.1 High-Level Feature Description.....	2-1
2.1.1 PRI Access for CPE Connecting to a LEC	2-1
2.1.2 Business Group Members Access to IXC Services	2-2
2.1.3 Extensions to the SS7 ISDNUP Protocol.....	2-2
2.2 User Perspective.....	2-3
2.2.1 User of Class II Equipment.....	2-3
2.2.1.1 Origination.....	2-3
2.2.1.2 Termination.....	2-3
2.2.2 Business Group Entities Served by the SPCS.....	2-3
2.2.2.1 Origination.....	2-3
2.2.2.2 Termination.....	2-5
2.3 Assumptions	2-5
3. Feature Requirements	3-1
3.1 Main Feature Operations.....	3-1
3.1.1 Access Call Processing	3-1
3.1.1.1 Origination Treatment	3-1
3.1.1.2 Termination Treatment	3-5
3.1.2 Interoffice Call Processing.....	3-6
3.1.2.1 Originating Treatment	3-6
3.1.2.2 Call Processing at Intermediate Switches.....	3-10
3.1.2.3 Terminating Treatment	3-10

3.1.3	Release Treatment	3-11
3.1.4	Error Treatment and Abnormal Events	3-11
3.2	Other Feature Operations	3-12
3.2.1	Simulated Facility Groups for Class II Equipment	3-12
3.2.2	Simulated Facility Groups for Business Group Entities	3-13
3.3	Internal Call Processing	3-15
3.3.1	Screening	3-15
3.3.1.1	Originating	3-15
3.3.1.2	Terminating	3-17
3.4	Signaling	3-17
3.4.1	Customer Signaling	3-17
3.4.1.1	Class II Equipment Served by the SPCS	3-17
3.4.1.2	Business Group Entities Served by the SPCS	3-18
3.4.2	SS7 Interface Signaling	3-18
3.4.2.1	Interworking With Other Signaling Systems	3-19
3.4.2.2	Interface Specifications	3-19
4.	Operations and Administration	4-1
4.1	Memory Administration	4-1
4.1.1	PRI Access to SPCS	4-1
4.1.2	BGE Access to SPCS	4-2
4.2	Network Maintenance	4-3
4.2.1	Surveillance	4-3
4.3	Network Data Collection (NDC)	4-3
4.4	Network Traffic Management (NTM)	4-5
4.5	Charge Treatment Determination and Automatic Message Accounting	4-5
4.5.1	Special Treatment for Calls Involving CBCSS Access to IXC Services	4-6
4.5.2	Feature Interactions	4-7
Appendix A:	Data Dictionary for CBCSS Access to IXC Services	A-1
A.1	Scope and Definition	A-1
A.2	Allowed Data Values	A-2
A.3	Data Dictionary	A-3
A.4	Data Example	A-6
A.4.1	Overview of AFR	A-6
A.4.2	Customer Patterns	A-7
A.4.3	Customer Pattern Groups	A-7
A.4.4	Customer Schedule	A-8
Appendix B:	DSS1 NSF Information Element	B-1
B.1	Scope and Definition	B-1
B.2	Coding of Network-Specific Facilities Information Element	B-1
Appendix C:	SS7 NSF Parameter	C-1
C.1	Scope and Definition	C-1

C.2 Coding of ISDNUP Network-Specific Facilities Parameter.....	C-1
Appendix D: Message Sequence Diagrams.....	D-1
D.1 Introduction.....	D-1
D.2 Message Sequences.....	D-1
References	References-1
Acronyms.....	Acronyms-1

List of Figures

Figure 1-1.	CBCSS Architecture Configuration	1-1
Figure B-1.	Network-Specific Facilities Information Element.....	B-1
Figure C-1.	Network-Specific Facilities Parameter	C-1
Figure D-1.	Origination from Class II Equipment	D-2
Figure D-2.	Originating ISDN BGE	D-3
Figure D-3.	Originating Class II Equipment, AT is Utilized in the Routing	D-4
Figure D-4.	Termination to Class II Equipment	D-5

List of Tables

Table 3-1.	Mapping from ISDN Access to SS7.....	3-9
Table B-1.	Type of Network Identification	B-2
Table B-2.	Network Identification Plan.....	B-2
Table B-3.	Network Identification Coding.....	B-2
Table B-4.	Expansion	B-3
Table B-5.	Service/Feature	B-3
Table B-6.	Facility Coding Values	B-4
Table B-7.	Service Parameters	B-4
Table C-1.	Type of Network Identification	C-2
Table C-2.	Network Identification Plan.....	C-2
Table C-3.	Expansion	C-3
Table C-4.	Service/Feature	C-3
Table C-5.	Service Parameters	C-4