
ISDN Basic Rate Interface Call Control Switching and Signaling Generic Requirements

Contents

Preface	Preface-1
1. Introduction.....	1-1
1.1 Purpose.....	1-1
1.1.1 The ISDN Concept.....	1-1
1.1.2 Scope	1-2
1.1.3 Relation To The LSSGR	1-2
1.1.4 Relation To The PPSNGR (GR-301-CORE).....	1-2
1.1.5 Relation To National And International Standards.....	1-3
1.1.6 Relation To Previous Bellcore Documentation	1-4
1.2 General Description of ISDN Basic Rate Interface	1-4
1.3 Equipment Classes	1-5
1.4 Document Organization	1-6
1.5 Requirements Terminology.....	1-7
1.6 Requirement Labeling Conventions.....	1-8
1.6.1 Numbering of Requirement and Related Objects	1-8
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. Assumptions and Restrictions.....	2-1
2.1 Bearer Capabilities Supported.....	2-1
2.1.1 Circuit-Mode, 64-kbps Unrestricted Digital Transmission, 8-kHz Structured, Demand, Point-To-Point and Bidirectional Symmetric ..	2-2
2.1.2 Circuit-Mode, 64-kbps Unrestricted Digital Transmission-Rate Adapted From 56-kbps, 8-kHz Structured, Demand Point-to-Point and Bidirectional-Symmetric	2-2
2.1.3 Circuit-Mode, 64-kbps, 8-kHz Structured, Usable For Speech, Demand, Point-To-Point, and Bidirectional Symmetric	2-2
2.1.4 Circuit-Mode, 64-kbps, 8-kHz Structured, Usable For 3.1-kHz Audio Information Transfer, Demand, Point-To-Point, and Bidirectional Symmetric	2-2
2.1.5 Packet-Mode, Unrestricted, Virtual Call and Permanent Virtual Circuit Service, Point-To-Point, and Bidirectional Symmetric	2-3
2.2 Assumptions	2-3
2.3 Issues	2-6
2.3.1 Functional and Stimulus Signaling	2-6
2.3.2 Call Progress Indication To The Calling Party	2-6
2.3.3 Point-To-Point, Point-To-Multipoint, and Passive Bus	2-7

2.3.4	Treatment Of Calling Party When Called ISDN Equipment Is Delaying Call Establishment	2-8
2.3.5	Calls Coming Into An ISDN Exchange From The PSTN	2-8
2.3.6	Use Of STATus/STATus ENquiry	2-9
3.	Background	3-1
3.1	General	3-1
3.2	ISDN Protocol Layers	3-1
3.3	ISDN Signaling	3-2
4.	Overview	4-1
4.1	Introduction	4-1
4.2	Message Sequence Summary	4-1
4.2.1	Originating Treatment	4-1
4.2.2	Terminating Message Sequences For Successful Call Establishment	4-2
4.2.3	Call Clearing Message Sequences	4-3
4.2.3.1	User-Initiated Call Clearing	4-4
4.2.3.2	Network-Initiated Call Clearing	4-4
4.3	Example Use Of Message Sequences And Requirements	4-5
5.	Call Processing	5-1
5.1	General Rules For Message Processing	5-2
5.2	Origination Treatment	5-3
5.2.1	Origination From An ISDN Basic Rate Interface (BRI)	5-3
5.2.1.1	Overlap Sending	5-10
5.2.1.2	Enbloc Sending	5-12
5.2.1.3	Call Proceeding Indication Sent To Calling User Equipment	5-13
5.2.1.4	Misdialing Treatments	5-14
5.2.2	B-Channel Connection Procedures - X.25 Call Originations	5-17
5.2.3	D-Channel X.25 Call Origination	5-18
5.3	Termination Treatment	5-18
5.3.1	Termination To An ISDN Basic Rate Interface	5-19
5.3.1.1	Subscription Parameters	5-19
5.3.1.2	Interface Busy/Idle Status	5-20
5.3.1.3	Call Delivery	5-21
5.3.1.4	Expiration of Timer T303	5-29
5.3.1.5	Call Rejected by the Called Party	5-32
5.3.1.6	Channel Negotiation Procedures	5-37
5.3.1.7	Call Proceeding Indication	5-41
5.3.1.8	Called Party Alerting	5-43
5.3.1.9	Additional Procedures Related to Contention for Incoming Calls	5-48
5.3.1.10	Called Party Answer	5-51
5.3.1.11	Delivery of an Incoming X.25 Call	5-52
5.3.2	Termination To Non-ISDN Line	5-54

5.3.2.1	5.3.2.1	5-55
5.3.2.2	5.3.2.2	5-55
5.3.3	5.3.3	5-56
5.3.3.1	5.3.3.1	5-56
5.3.3.2	5.3.3.2	5-57
5.3.4	5.3.4	5-57
5.3.4.1	5.3.4.1	5-57
5.3.4.2	5.3.4.2	5-60
5.3.4.3	5.3.4.3	5-61
5.3.4.4	5.3.4.4	5-64
5.4	5.4	5-66
5.4.1	5.4.1	5-67
5.4.1.1	5.4.1.1	5-67
5.4.1.2	5.4.1.2	5-69
5.4.1.3	5.4.1.3	5-70
5.4.2	5.4.2	5-72
5.4.2.1	5.4.2.1	5-73
5.4.2.2	5.4.2.2	5-77
5.4.2.3	5.4.2.3	5-79
5.4.3	5.4.3	5-79
5.4.3.1	5.4.3.1	5-80
5.4.3.2	5.4.3.2	5-82
5.4.3.3	5.4.3.3	5-82
5.4.3.4	5.4.3.4	5-82
5.4.3.5	5.4.3.5	5-83
5.5	5.5	5-84
5.5.1	5.5.1	5-84
5.5.1.1	5.5.1.1	5-84
5.5.1.2	5.5.1.2	5-87
5.5.1.3	5.5.1.3	5-91
5.5.1.4	5.5.1.4	5-92
5.5.1.5	5.5.1.5	5-95
5.5.1.6	5.5.1.6	5-96
5.5.2	5.5.2	5-97
5.5.2.1	5.5.2.1	5-98
5.5.2.2	5.5.2.2	5-101
6.	6.	6-1
6.1	6.1	6-1
6.2	6.2	6-2
6.2.1	6.2.1	6-2
6.2.2	6.2.2	6-4

6.2.2.1	General Subscription Parameters Per Basic Rate Interface	6-4
6.2.2.2	Packet-Mode Data Service Parameters	6-8
6.2.3	Subscription Parameters Per Interface (OE/DN)	6-9
6.2.3.1	General Parameters Per DN	6-10
6.2.3.2	Circuit-Mode Parameters Per DN and Call Type	6-12
6.2.3.3	Packet-Mode Parameters Per DN	6-19
6.3	Configurations	6-22
6.3.1	B-Channel Access	6-23
6.3.2	Associated Group	6-23
6.3.3	Discussion Of Example Configurations	6-24
6.4	Call Reference Administration	6-26
6.4.1	Allocation And Release Of Call References	6-26
6.4.2	Call References Used In Messages Sent By The SPCS	6-27
6.4.3	Call References In Messages Received By The SPCS	6-27
6.5	SPCS Channel Assignment	6-28
6.5.1	Originating B-Channel Selection	6-29
6.5.2	D/B-channel Selection For Terminating Calls	6-30
6.5.2.1	Bearer Capability Indicates Channel Type	6-31
6.5.2.2	Throughput Class Indication of D-channel Subscription Parameter	6-32
6.5.2.3	Selection of a B-channel when the D-channel is Not Applicable	6-33
6.5.2.4	Selection of a B-channel When the D-channel May be Applicable	6-34
6.5.2.5	Selection of the D-channel	6-35
6.6	ISDN Code Interpretation	6-36
6.6.1	General	6-37
6.6.2	Address Transport Using The Keypad Information Element	6-38
6.6.2.1	General Use	6-38
6.6.2.2	ISDN Dialing Plan	6-38
6.6.3	Enbloc Signaling Method (Nonkeypad)	6-40
6.6.3.1	General Use	6-40
6.6.3.2	Called Party Number Information Element Interpretation	6-40
6.6.3.3	Transit Network Selection Information Element Interpretation	6-43
6.6.3.4	Operator System Access Information Element Interpretation	6-44
6.6.4	ISDN-To-ISDN Packet Connections	6-45
6.6.5	Interworking With Packet-Switched Public Data Networks	6-46
6.6.6	Subaddressing	6-47
6.7	ISDN Routing	6-47
6.7.1	Circuit-Mode Bearer Capabilities	6-47

6.7.1.1	General Procedures for Call Originations.....	6-47
6.7.1.2	Called Party Number	6-48
6.7.1.3	Transit Network Selection	6-49
6.7.1.4	Operator System Service Request	6-49
6.7.1.5	Combination Routing Information	6-50
6.7.2	Packet-Mode Call Types	6-51
6.7.2.1	Routing Packet-Mode Connection Requests	6-51
6.7.2.2	PHF Routing	6-51
6.7.2.3	RPOA Indicated.....	6-51
6.7.2.4	Called Address Only.....	6-52
6.7.3	Special Conditions (Network Management).....	6-53
6.7.4	N11 Routing.....	6-53
6.7.5	Terminating Calls.....	6-54
6.7.5.1	Intersystem Incoming Call Destination Codes	6-54
6.7.5.2	Intercept Treatment.....	6-54
6.8	Network Determination Of Interface Busy	6-54
6.8.1	Busy For Circuit-Switched Calls	6-54
6.8.1.1	Busy Limit for Originating Circuit-Switched Calls.....	6-55
6.8.1.2	Busy Limit for Terminating Circuit-Switched Calls	6-55
6.8.2	Busy for Packet Connections	6-56
6.8.2.1	General Criteria for Determining Packet Connection Busy 6-57	
6.8.2.2	Originating Busy Limit for X.25 Packet-Mode Access...	6-58
6.8.2.3	Terminating Busy Limit for X.25 Packet-Mode Access .	6-58
6.9	Timers	6-59
6.10	Tones And Announcements	6-63
6.10.1	Assumption For This Document	6-67
6.10.2	Timing of Inband Tones and Announcements Returned on an ISDN Call	6-67
6.10.3	Tones Associated With Call Origination	6-69
6.10.4	Tones Associated with the Attempted Completion of a Call.....	6-70
6.10.5	Tone Associated With The Termination Of Completed Calls.....	6-70
6.10.6	Tones And Announcements Associated With The Termination Of Calls That Cannot Be Completed.....	6-71
7.	Layer 3 Messages and Information Elements	7-1
7.1	Message Functional Definitions.....	7-1
7.1.1	Overview	7-1
7.1.2	Messages	7-2
7.1.2.1	ALERTing	7-3
7.1.2.2	CALL PROCeeding.....	7-5
7.1.2.3	CONNect	7-7
7.1.2.4	CONNect ACKnowledge	7-8
7.1.2.5	DISConnect.....	7-9
7.1.2.6	INFOrmation.....	7-11

7.1.2.7	PROGress	7-13
7.1.2.8	RELease	7-15
7.1.2.9	RELease COMplete	7-17
7.1.2.10	SETUP	7-18
7.1.2.11	SETUP ACKnowledge	7-24
7.1.2.12	STATus	7-25
7.1.2.13	STATus ENQuiry	7-27
7.2	Message Structure	7-28
7.2.1	General Coding Rules	7-28
7.2.2	Protocol Discriminator	7-29
7.2.3	Call Reference	7-29
7.2.4	Message Type	7-31
7.2.5	Other Information Elements	7-33
7.2.5.1	Shift Information Element	7-36
7.2.5.2	Bearer Capability	7-37
7.2.5.3	Call State	7-41
7.2.5.4	Called Party Number	7-44
7.2.5.5	Called Party Subaddress	7-46
7.2.5.6	Calling Party Number	7-47
7.2.5.7	Calling Party Subaddress	7-52
7.2.5.8	Cause	7-53
7.2.5.9	Channel Identification	7-72
7.2.5.10	Closed User Group	7-74
7.2.5.11	Endpoint Identifier	7-76
7.2.5.12	End-to-End Transit Delay	7-79
7.2.5.13	Feature Activation	7-81
7.2.5.14	Feature Indication	7-81
7.2.5.15	High Layer Compatibility	7-82
7.2.5.16	Information Rate	7-84
7.2.5.17	Information Request	7-86
7.2.5.18	Keypad	7-87
7.2.5.19	Low Layer Compatibility	7-88
7.2.5.20	Notification Indicator	7-89
7.2.5.21	Packet Layer Binary Parameters	7-91
7.2.5.22	Packet Layer Window Size	7-93
7.2.5.23	Packet Size	7-94
7.2.5.24	Progress Indicator	7-95
7.2.5.25	Redirecting Number	7-97
7.2.5.26	Redirecting Subaddress	7-103
7.2.5.27	Redirection Number	7-104
7.2.5.28	Reverse Charging Indication	7-106
7.2.5.29	Service Profile Identification	7-107
7.2.5.30	Signal	7-108
7.2.5.31	Transit Delay Selection and Indication	7-110

7.2.5.32	Transit Network Selection	7-111
7.2.6	National-Specific Information Elements (Codeset 5).....	7-112
7.2.6.1	Display Text.....	7-112
7.2.6.2	Operator System Access	7-118
Appendix A:	User-Network Message Sequences for Call Control	A-1
A.1	Introduction	A-1
A.2	Circuit-Switched Intraoffice Call Between Two ISDN Lines	A-1
A.2.1	ISDN Call Origination	A-2
A.2.1.1	Enbloc Origination.....	A-2
A.2.1.2	Overlap Origination	A-2
A.2.2	Successful Call Establishment	A-2
A.2.3	Call Clearing Message Sequences	A-4
A.2.3.1	ISDN User-Initiated Release Message Sequences	A-5
A.2.3.2	Network-Initiated Release Message Sequences - No Inband Tones.....	A-7
A.2.3.3	Network-Initiated Release Message Sequences With Inband Treatment.....	A-9
A.2.4	Message Sequences Resulting From Protocol Errors	A-10
A.3	Packet Call Establishment For ISDN Lines	A-12
A.3.1	User-Initiated B-Channel Connection To A PHF	A-13
A.3.2	Network-Initiated Connection To PHF And Notification Of Packet Calls	A-13
A.3.2.1	Packet Call on Idle Channel	A-14
A.3.2.2	Packet Call on Active Channel	A-14
A.3.3	Call Clearing Message Sequences	A-15
A.3.3.1	User-Initiated Call Clearing Message Sequences.....	A-15
A.3.3.2	Network-Initiated Call Clearing Message Sequences	A-16
A.3.4	Message Sequences Resulting From Protocol Errors	A-17
A.4	Intraoffice ISDN-To-ISDN, Circuit-Switched Calls Using Inband Tones And Announcements.....	A-17
A.4.1	ISDN Call Origination	A-17
A.4.2	Successful Call Establishment	A-18
A.4.3	Call Clearing Message Sequences	A-18
A.4.3.1	ISDN User-Initiated Call Clearing Message Sequences	A-18
A.4.3.2	Network-Initiated Call Clearing Message Sequences	A-18
A.4.4	Message Sequences Resulting From Protocol Errors	A-19
A.5	Interworking: Non-ISDN-To-ISDN Voice Call.....	A-19
A.5.1	Call Origination.....	A-20
A.5.2	Call Completion	A-20
A.5.3	Call Clearing Message Sequences	A-20
A.5.4	Message Sequences Resulting From Protocol Errors	A-21
A.6	Interworking ISDN-To-Non-ISDN Calls.....	A-21
A.6.1	ISDN Call Origination	A-21
A.6.2	Successful Call Establishment	A-22

A.6.3	Call Clearing Message Sequences	A-22
A.6.4	Message Sequences Resulting From Protocol Errors	A-23
A.7	Example Message Sequences For Specific Call Types.....	A-24
A.7.1	Network Release During Origination	A-25
A.7.1.1	Rejected Call with Enbloc Sending	A-25
A.7.1.2	Rejected Call with Overlap Sending.....	A-26
A.7.1.3	Partial Dial Treatment with Overlap Sending	A-26
A.7.2	ISDN-To-ISDN-Intrastwitch-Call Establishment.....	A-27
A.7.2.1	Double SETUP	A-27
A.7.2.2	Immediate Rejection.....	A-27
A.7.2.3	Delayed Rejection.....	A-28
A.7.2.4	No Answer.....	A-28
A.7.2.5	Immediate Connection.....	A-29
A.7.2.6	Delayed Immediate Connection	A-29
A.7.2.7	Normal Answer.....	A-30
A.7.2.8	Delayed Normal Answer	A-31
A.7.2.9	Point-To-Multipoint Answered Call - Contention Allowed....	A-31
A.7.3	Non-ISDN-To-ISDN Intrastwitch Call Establishment	A-32
A.7.3.1	Double SETUP	A-32
A.7.3.2	Immediate Rejection.....	A-32
A.7.3.3	Delayed Rejection by Called User.....	A-32
A.7.3.4	No Answer by Called User	A-33
A.7.3.5	Immediate Connection.....	A-33
A.7.3.6	Delayed Immediate Connection	A-33
A.7.3.7	Normal Answer.....	A-33
A.7.3.8	Delayed Normal Answer	A-34
A.7.4	Interswitch Call Over Non-ISDN Incoming Facility	A-34
A.7.4.1	Double SETUP	A-34
A.7.4.2	Immediate Rejection.....	A-34
A.7.4.3	Delayed Rejection.....	A-35
A.7.4.4	No Answer.....	A-35
A.7.4.5	Immediate Connection.....	A-35
A.7.4.6	Delayed Immediate Connection	A-35
A.7.4.7	Normal Answer.....	A-36
A.7.4.8	Delayed Normal Answer	A-36
A.7.5	ISDN-To-Non-ISDN Intrastwitch Call Establishment	A-36
A.7.5.1	Double SETUP	A-36
A.7.5.2	Immediate Rejection.....	A-36
A.7.5.3	Delayed Rejection.....	A-36
A.7.5.4	No Answer.....	A-37
A.7.5.5	Immediate Connection.....	A-37
A.7.5.6	Delayed Immediate Connection	A-37
A.7.5.7	Normal Answer.....	A-37

A.7.5.8	Delayed Normal Answer	A-37
A.7.5.9	ISDN-To-Non-ISDN-Intrastitch-Call Teardown by Non- ISDN Called User	A-38
A.7.6	Interswitch Call Over Non-ISDN Outgoing Facility	A-38
A.7.7	Packet Calls	A-39
A.7.7.1	Double SETUP	A-39
A.7.7.2	Immediate Rejection	A-39
A.7.7.3	Delayed Immediate Rejection	A-39
A.7.7.4	No Answer	A-39
A.7.7.5	Immediate Connection	A-39
A.7.7.6	Delayed Immediate Connection	A-40
A.7.7.7	Normal Answer	A-40
A.7.7.8	Delayed Normal Answer	A-41
References	References-1
Glossary	Glossary-1

List of Figures

Figure 4-1.	Valid Message Sequences	4-8
Figure 4-2.	Message Sequence for User-Initiated Call Clearing.....	4-9
Figure 4-3.	ISDN-BRI-to-ISDN-BRI Intraswitch Call Establishment/Call Answered/ Connection After Alerting Example.....	4-10
Figure 4-4.	Originating SETUP Message Coding Example.....	4-11
Figure 4-5.	CALL PROCEEDing Message Coding Example to Originating Party....	4-12
Figure 4-6.	Terminating SETUP Message Coding Example	4-13
Figure 4-7.	ALERTing Message Coding Example from Terminating Party	4-14
Figure 4-8.	ALERTing Message Coding Example to Originating Party	4-14
Figure 4-9.	CONNect Message Coding Example from Terminating Party	4-15
Figure 4-10.	CONNect ACKnowledge Message Coding Example to Terminating Party .. 4-15	
Figure 4-11.	CONN Message Coding Example to Originating Party.....	4-16
Figure 4-12.	CONN ACKnowledge Message Coding Example from Originating Party4- 16	
Figure 4-13.	DISconnect Message Coding Example from Originating Party.....	4-17
Figure 4-14.	DISconnect Message Coding Example to Terminating Party	4-17
Figure 4-15.	RELEase Message Coding Example to Originating Party	4-18
Figure 4-16.	RELEase COMplete Message Coding Example from Originating Party4-18	
Figure 4-17.	RELEase Message Coding Example from Terminating Party.....	4-19
Figure 4-18.	RELEase COMplete Message Coding Example to Terminating Party...4-19	
Figure 7-1.	General Message Organization Example.....	7-28
Figure 7-2.	Protocol Discriminator Information Element	7-29
Figure 7-3.	Call Reference Information Element	7-30
Figure 7-4.	Null Call Reference	7-31
Figure 7-5.	Message Type	7-31
Figure 7-6.	Network-Specific Message Type.....	7-31
Figure 7-7.	Formats of Information Elements	7-33
Figure 7-8.	Locking Shift Information Element.....	7-36
Figure 7-9.	Nonlocking Shift Information Element	7-37
Figure 7-10.	Bearer Capability Information Element.....	7-38
Figure 7-11.	Call State Information Element	7-41
Figure 7-12.	Called Party Number Information Element.....	7-44
Figure 7-13.	Called Party Subaddress Information Element.....	7-46
Figure 7-14.	Calling Party Number Information Element.....	7-48
Figure 7-15.	Calling Party Subaddress Information Element.....	7-52
Figure 7-16.	Cause Information Element	7-54
Figure 7-17.	Channel Identification Information Element	7-72
Figure 7-18.	Closed User Group Information Element.....	7-75

Figure 7-19.Endpoint Identifier information element	7-77
Figure 7-20.End-to-End Transit Delay Information Element	7-79
Figure 7-21.Feature Activation Information Element	7-81
Figure 7-22.Feature Indication Information Element.....	7-82
Figure 7-23.High Layer Compatibility Information Element	7-83
Figure 7-24.Information Rate Information Element.....	7-84
Figure 7-25.Information Request Information Element	7-86
Figure 7-26.Keypad Information Element.....	7-87
Figure 7-27.Low Layer Compatibility Information Element	7-88
Figure 7-28.Notification Indicator Information Element	7-89
Figure 7-29.Packet Layer Binary Parameters Information Element	7-91
Figure 7-30.Packet Layer Window Size Information Element	7-93
Figure 7-31.Packet Size Information Element	7-94
Figure 7-32.Progress Indicator Information Element.....	7-95
Figure 7-33.Redirecting Number Information Element	7-97
Figure 7-34.Redirecting Subaddress Information Element	7-103
Figure 7-35.Redirection Number Information Element	7-105
Figure 7-36.Reverse Charging Indication Information Element	7-106
Figure 7-37.Service Profile Identification Information Element.....	7-107
Figure 7-38.Signal Information Element.....	7-108
Figure 7-39.Transit Delay Selection and Indication Information Element	7-110
Figure 7-40.Transit Network Selection Information Element.....	7-111
Figure 7-41.Structure of Display Text Information Element	7-113
Figure 7-42.General Coding of Optional Control Tags.....	7-116
Figure 7-43.3-Octet Optional Control Tag	7-116
Figure 7-44.Operator System Access Information Element.....	7-118
Figure A-1.Message Sequences for Intraoffice ISDN-to-ISDN, Circuit-Switched Call..	A-42
Figure A-2.Call Clearing Message Sequences ISDN User-to-Network, Type A	A-43
Figure A-3.Call Clearing Message Sequences Network-to-ISDN, No Inband Treatment, Type B	A-45
Figure A-4.Call Clearing Message Sequences Network-to-ISDN, Inband Treatment, Type C.....	A-47
Figure A-5.Message Sequences Resulting from Network-Detected Protocol Errors ..	A-50
Figure A-6.Message Sequences for B-Channel Connection to Packet Handler, User Originated	A-51
Figure A-7.Message Sequences for Connection of an Idle B-channel to Packet Handler	A-51
Figure A-8.Message Sequences for Termination to Packet Handler Over an Active Channel (B or D).....	A-52
Figure A-9.Message Sequences for Intraoffice ISDN-to-ISDN Call with Inband Tones	A-53
Figure A-10.Message Sequences for Interworking Non-ISDN Voice Call to ISDN Line....	A-54

Figure A-11.Message Sequences for Interworking Intraoffice ISDN-to-Non-ISDN Voice Call.....	A-55
Figure A-12.Message Sequences for Interworking ISDN-to-Intraoffice Conventional Trunk	A-56
Figure A-13.Rejected Call with Enbloc Sending, No Inband Tones.....	A-57
Figure A-14.Rejected Call with Enbloc Sending, Inband Tones	A-58
Figure A-15.Rejected Call with Overlap Sending, No Inband Tones	A-59
Figure A-16.Rejected Call with Overlap Sending, Inband Tones	A-60
Figure A-17.Partial Dial Treatment with Overlap Sending, No Inband Tones.....	A-61
Figure A-18.Partial Dial Treatment with Overlap Sending, Inband Tones.....	A-62
Figure A-19.ISDN-to-ISDN, Double SETUP, No Inband Tones	A-63
Figure A-20.ISDN-to-ISDN, Double SETUP, Inband Tones	A-64
Figure A-21.ISDN-to-ISDN, Immediate Rejection, No Inband Tones.....	A-65
Figure A-22.ISDN-to-ISDN, Immediate Rejection, Inband Tones.....	A-66
Figure A-23.ISDN-to-ISDN, Delayed Rejection, No Inband Tones.....	A-67
Figure A-24.ISDN-to-ISDN, Delayed Rejection, Inband Tones.....	A-68
Figure A-25.ISDN-to-ISDN, No Answer, No Inband Tones	A-69
Figure A-26.ISDN-to-ISDN, No Answer, Inband Tones.....	A-70
Figure A-27.ISDN-to-ISDN, Immediate Communication	A-71
Figure A-28.ISDN-to-ISDN, Delayed Immediate Communication, No Inband Tones.....	A-72
Figure A-29.ISDN-to-ISDN, Delayed Immediate Communication, Inband Tones	A-73
Figure A-30.ISDN-to-ISDN, Normal Answer, No Inband Tones.....	A-74
Figure A-31.ISDN-to-ISDN, Normal Answer, Inband Tones.....	A-75
Figure A-32.ISDN-to-ISDN, Delayed Normal Answer, No Inband Tones	A-76
Figure A-33.ISDN-to-ISDN, Delayed Normal Answer, Inband Tones	A-77
Figure A-34.ISDN-to-ISDN, Point-to-Multipoint Answered Call, Contention Allowed	A-78
Figure A-35.Non-ISDN-to-ISDN, Double SETUP.....	A-79
Figure A-36.Non-ISDN-to-ISDN, Immediate Rejection	A-80
Figure A-37.Non-ISDN-to-ISDN, Delayed Rejection by Called User	A-81
Figure A-38.Non-ISDN-to-ISDN, No Answer by Called User.....	A-82
Figure A-39.Non-ISDN-to-ISDN, Immediate Connection	A-83
Figure A-40.Non-ISDN-to-ISDN, Delayed Immediate Connection	A-84
Figure A-41.Non-ISDN-to-ISDN, Normal Answer	A-85
Figure A-42.Non-ISDN-to-ISDN, Delayed Normal Answer	A-86
Figure A-43.Non-ISDN Incoming, Double SETUP.....	A-87
Figure A-44.Non-ISDN Incoming, Immediate Rejection	A-88
Figure A-45.Non-ISDN Incoming, Delayed Rejection	A-89
Figure A-46.Non-ISDN Incoming, No Answer	A-90
Figure A-47.Non-ISDN Incoming, Immediate Connection	A-91
Figure A-48.Non-ISDN Incoming, Delayed Immediate Connection.....	A-92
Figure A-49.Non-ISDN Incoming, Normal Answer	A-93
Figure A-50.Non-ISDN Incoming, Delayed Normal Answer.....	A-94
Figure A-51.ISDN-to-Non-ISDN, No Answer.....	A-95

Figure A-52.ISDN-to-Non-ISDN, Normal Answer A-96
Figure A-53.ISDN-to-Non-ISDN, Call Teardown by Non-ISDN Called User A-97
Figure A-54.Successful Interswitch Call Over Non-ISDN Outgoing Facility A-98
Figure A-55.Packet Call, Double SETUP A-99
Figure A-56.Packet Call, Immediate Rejection..... A-100
Figure A-57.Packet Call, Delayed Immediate Rejection A-101
Figure A-58.Packet Call, No Answer A-102
Figure A-59.Packet Call, Immediate Connection, Termination on Idle Channel A-103
Figure A-60.Packet Call, Immediate Connection, Termination on Active Channel.. A-104
Figure A-61.Packet Call, Delayed Immediate Connection, Termination on Idle Channel ...
A-105
Figure A-62.Packet Call, Delayed Immediate Connection, Termination on Active
Channel A-106
Figure A-63.Packet Call, Normal Answer, Termination on Idle Channel A-107
Figure A-64.Packet Call, Normal Answer, Termination on Active Channel..... A-108
Figure A-65.Packet Call, Delayed Normal Answer, Termination on Idle Channel... A-109
Figure A-66.Packet Call, Delayed Normal Answer, Termination on Active Channel A-

List of Tables

Table 5-1.	Cause Code Mapping From Q.931 to X.25 Because of General Call Clearing Conditions.....	5-80
Table 5-2.	Cause Code Mapping From Q.931 to X.25 Because of Premature Disconnection of a B-channel.....	5-82
Table 5-3.	Cause Code Mapping From Q.931 to X.25 Because of Virtual Call Rejection by Q.931 Procedures.....	5-82
Table 5-4.	Cause Code Mapping From X.25 to Q.931	5-83
Table 5-5.	Call States, Originating Interface, Before Address Sending Complete..	5-88
Table 5-6.	Call States, Originating Interface, After Address Sending Complete	5-89
Table 5-7.	Call States, Terminating Interface	5-91
Table 5-8.	Call States Resulting From Call Clearing Events.....	5-94
Table 5-9.	Call Processing If User Equipment Is In A Clearing Call State	5-101
Table 6-1.	Office Parameters	6-4
Table 6-2.	Subscription Parameters Per Interface.....	6-8
Table 6-3.	Packet-Mode Subscription Parameters Per Interface	6-9
Table 6-4.	Subscription Parameters Per Directory Number (DN)	6-12
Table 6-5.	Parameters Per Directory Number and Circuit-Mode Call Type	6-18
Table 6-6.	Packet-Mode Parameters Per Directory Number	6-22
Table 6-7.	Example Configurations	6-24
Table 6-8.	Correlation Between Signaling Methods.....	6-43
Table 6-9.	Operator System Request Interpretation.....	6-45
Table 6-10.	Combination of Routing Information	6-50
Table 6-11.	Timers At The SPCS	6-60
Table 6-12.	Inband Tones and the Corresponding Signal Information.....	6-65
Table 6-13.	Tones and Announcements Associated with Specific Cause Values	6-72
Table 6-14.	Recommended Announcements Associated with ISDN Specific Cause Values	6-74
Table 7-1.	User-to-Network ALERTing Message Content.....	7-3
Table 7-2.	Network-to-User ALERTing Message Content.....	7-3
Table 7-3.	User-to-Network CALL PROCeeding Message Content	7-5
Table 7-4.	Network-to-User CALL PROCeeding Message Content	7-5
Table 7-5.	User-to-Network CONNect Message Content.....	7-7
Table 7-6.	Network-to-User CONNect Message Content.....	7-7
Table 7-7.	User-to-Network CONNect ACKnowledge Message Content.....	7-8
Table 7-8.	Network-to-User CONNect ACKnowledge Message Content.....	7-9
Table 7-9.	User-to-Network DISConnect Message Content	7-9
Table 7-10.	Network-to-User DISConnect Message Content	7-10
Table 7-11.	User-to-Network INFOrmation Message Content.....	7-11
Table 7-12.	Network-to-User INFOrmation Message Content	7-12

Table 7-13. Network-to-User PROGRESS Message Content	7-14
Table 7-14. User-to-Network RELEase Message Content	7-15
Table 7-15. Network-to-User RELEase Message Content	7-15
Table 7-16. User-to-Network RELEase COMplete Message Content	7-17
Table 7-17. Network-to-User RELEase COMplete Message Content.....	7-17
Table 7-18. User-to-Network SETUP Message Content.....	7-18
Table 7-19. Network-to-User SETUP Message Content.....	7-21
Table 7-20. Network-to-User SETUP ACKnowledge Message Content.....	7-24
Table 7-21. User-to-Network STATus Message Content	7-25
Table 7-22. Network-to-User STATus Message Content	7-25
Table 7-23. Network-to-User STATus ENQuiry Message Content.....	7-27
Table 7-24. Message Types	7-32
Table 7-25. ITU-T Recommendation Q.931- and Q.932-defined Information Element Identifier Coding (Codeset 0)	7-35
Table 7-26. Call State Values	7-41
Table 7-27. ITU-T Standardized Cause Values.....	7-57
Table 7-28. National Standardized Cause Values	7-59
Table 7-29. Network Specific Cause Values	7-60
Table 7-30. Use of ITU-T Standardized Cause Values	7-69
Table 7-31. Use of National Standardized Cause Values.....	7-71
Table 7-32. Use of Network Specific Cause Values	7-72
Table 7-33. ASN.1 Encoded Data Structure Content	7-91
Table 7-34. Display Information (Relative Order of Octets 4, etc.).....	7-113
Table 7-35. Coding of ASCII Characters	7-117
