
ATM Service Access Multiplexer (SAM) Generic Requirements

Contents

| | |
|--|-----------|
| Preface | Preface-1 |
| 1. Introduction..... | 1-1 |
| 1.1 Scope of Document | 1-1 |
| 1.2 Document Organization | 1-3 |
| 1.3 Major Changes from Issue 1 | 1-3 |
| 1.4 Related Bellcore Documents | 1-5 |
| 1.5 Requirements Terminology | 1-6 |
| 1.6 Requirement Labeling Conventions..... | 1-6 |
| 1.6.1 Numbering of Requirement and Related Objects | 1-6 |
| 1.6.2 Requirement, Conditional Requirement, and Objective Object Identification | 1-7 |
| 2. Service Access Interfaces..... | 2-1 |
| 2.1 SMDS | 2-2 |
| 2.1.1 SMDS-Specific Interfaces..... | 2-3 |
| 2.1.2 SMDS Functions for Mapping SMDS Traffic to ATM | 2-3 |
| 2.1.2.1 SIP_CLS Layer | 2-4 |
| 2.1.2.2 AAL 3/4 Layer..... | 2-5 |
| 2.1.2.3 AAL 5 Layer..... | 2-5 |
| 2.1.2.4 ATM Layer | 2-6 |
| 2.1.2.5 Traffic and Congestion Control for SMDS..... | 2-6 |
| 2.2 Frame Relay Service | 2-7 |
| 2.2.1 Frame Relay UNI | 2-8 |
| 2.2.2 Mapping of Frame Relay Frames to ATM..... | 2-9 |
| 2.2.2.1 Frame Relay-ATM Network Interworking..... | 2-10 |
| 2.2.2.2 Frame Relay-ATM Service Interworking..... | 2-11 |
| 2.3 Cell Relay Service..... | 2-12 |
| 2.3.1 Cell Relay Service UNI..... | 2-12 |
| 2.3.1.1 ATM Layer | 2-13 |
| 2.3.1.2 Physical Layer..... | 2-13 |
| 2.3.1.3 FUNI to ATM Conversion..... | 2-13 |
| 2.3.2 Cell Relay Service Features | 2-14 |
| 2.3.3 Traffic and Congestion Control | 2-15 |
| 2.4 Native-mode LAN Interconnection Service..... | 2-16 |
| 2.4.1 Ethernet Interconnection | 2-16 |
| 2.4.1.1 Ethernet Interfaces | 2-16 |
| 2.4.1.2 Mapping Ethernet Frames to ATM..... | 2-17 |

| | | |
|---------|--|------|
| 2.4.1.3 | Bridging Ethernet Segments via ATM VCCs..... | 2-17 |
| 2.4.2 | Token Ring Interconnection..... | 2-18 |
| 2.4.2.1 | IEEE 802.5 Interface..... | 2-18 |
| 2.4.2.2 | Mapping of Token Ring Frames to ATM..... | 2-18 |
| 2.4.2.3 | Bridging Token Rings via ATM Virtual Connections..... | 2-18 |
| 2.4.3 | Fiber Distributed Data Interface (FDDI) Interconnection | 2-19 |
| 2.4.3.1 | FDDI Interfaces | 2-19 |
| 2.4.3.2 | Mapping of FDDI Frames to ATM..... | 2-19 |
| 2.4.3.3 | Bridging FDDI Rings via ATM Virtual Connections | 2-20 |
| 2.5 | Circuit Emulation Service | 2-20 |
| 2.5.1 | DS1 and DS3 Circuit Emulation | 2-20 |
| 2.5.1.1 | AAL1 | 2-21 |
| 2.5.1.2 | Physical Layer..... | 2-21 |
| 2.5.1.3 | DS1/DS3 Interworking Functions | 2-21 |
| 2.5.2 | Emulation of Other Data Streams | 2-22 |
| 2.5.2.1 | NxDS0 CES Modes | 2-22 |
| 2.5.2.2 | AAL1 | 2-23 |
| 2.5.2.3 | Physical Layer..... | 2-23 |
| 2.5.2.4 | NxDS0 Interworking Functions..... | 2-24 |
| 2.5.3 | Traffic and Congestion Control | 2-25 |
| 2.6 | Video Services..... | 2-25 |
| 2.6.1 | Support of Video Using Circuit Emulation..... | 2-26 |
| 2.6.2 | Support of Native Video Interfaces..... | 2-26 |
| 3. | SAMI Interface (SAMI) and Core Functions..... | 3-1 |
| 3.1 | SAMI and Related Access Network Standardization Efforts | 3-2 |
| 3.1.1 | ETSI and ITU-T | 3-2 |
| 3.1.1.1 | Background on the ETSI Approach: V5..... | 3-3 |
| 3.1.1.2 | VB5 network concept | 3-3 |
| 3.1.2 | The Broadband-Bearer Control Channel (B-BCC)..... | 3-4 |
| 3.1.3 | ATM Forum Residential Broadband (RBB) Group..... | 3-4 |
| 3.2 | SAMI Physical Layer | 3-4 |
| 3.3 | SAMI ATM Layer..... | 3-6 |
| 3.4 | Support for ATM Connections..... | 3-7 |
| 3.4.1 | Non-Switched ATM Connections (PVC) | 3-7 |
| 3.4.2 | Support for Switched ATM Connections (SVC) | 3-7 |
| 3.4.2.1 | Provisioning Signaling Channel Assignment | 3-9 |
| 3.4.2.2 | Relationship Between ATM Forum and SAM ATM Connection Requirements..... | 3-10 |
| 3.5 | Traffic and Congestion Control..... | 3-12 |
| 3.5.1 | Statistical Multiplexing and Concentration..... | 3-13 |
| 3.5.2 | Support for ABR | 3-13 |
| 3.5.3 | UPC/NPC at the SAMI | 3-13 |
| 3.6 | Survivability Options | 3-14 |
| 3.6.1 | SONET 1+1 Protection Switching | 3-14 |

| | | |
|---------|---|------|
| 3.6.2 | SONET Rings and ATM VP Rings | 3-14 |
| 3.6.3 | Advanced Survivability..... | 3-14 |
| 3.6.4 | ATM Cross-connect..... | 3-15 |
| 3.7 | Synchronization..... | 3-15 |
| 4. | Management Requirements..... | 4-1 |
| 4.1 | Network Element (NE)-to-Management System Communications..... | 4-1 |
| 4.1.1 | Operations Communications Protocol | 4-1 |
| 4.1.2 | Proprietary Interfaces for the SAM..... | 4-3 |
| 4.1.3 | Standard Open Interfaces for the SAM..... | 4-4 |
| 4.1.3.1 | CMIP-based Management Interface for the SAM..... | 4-6 |
| 4.1.3.2 | SNMP-based Management Interface for the SAM..... | 4-6 |
| 4.1.4 | Remote SAM Out-of-Band Operations Interface | 4-9 |
| 4.2 | Requirements for ATM-based Interfaces..... | 4-11 |
| 4.2.1 | SNMP MIB Support for the Physical and ATM Interface Layers...4-11 | |
| 4.2.1.1 | General ATM Interface Information..... | 4-11 |
| 4.2.1.2 | Physical Interface Layer Information | 4-13 |
| 4.2.1.3 | ATM Interface Layer Information..... | 4-15 |
| 4.2.2 | Interpretation of Tables that Reference GR-1248-CORE..... | 4-16 |
| 4.2.3 | Physical and ATM Layer Operations Flows..... | 4-17 |
| 4.2.3.1 | SAMI | 4-17 |
| 4.2.3.2 | SAM UNI..... | 4-17 |
| 4.2.3.3 | Applicable GR-1248 Operations Flow Requirements | 4-17 |
| 4.2.4 | Configuration Management | 4-18 |
| 4.2.4.1 | SAMI | 4-18 |
| 4.2.4.2 | SAM Core Functions | 4-19 |
| 4.2.4.3 | SAM UNI..... | 4-19 |
| 4.2.4.4 | Applicable GR-1248 Configuration Management Requirements | 4-20 |
| 4.2.5 | Fault Management..... | 4-22 |
| 4.2.5.1 | SAMI | 4-23 |
| 4.2.5.2 | SAM Core Functions | 4-23 |
| 4.2.5.3 | SAM UNI..... | 4-23 |
| 4.2.5.4 | Fault Management Requirements | 4-23 |
| 4.2.6 | Performance Management | 4-28 |
| 4.2.6.1 | SAMI | 4-28 |
| 4.2.6.2 | SAM Core Functions | 4-29 |
| 4.2.6.3 | SAM UNI..... | 4-29 |
| 4.2.6.4 | Applicable GR-1248 Performance Management Requirements | 4-30 |
| 4.2.7 | Activation/Deactivation Procedures..... | 4-33 |
| 4.2.7.1 | SAMI | 4-33 |
| 4.2.7.2 | SAM Core Functions | 4-34 |
| 4.2.7.3 | SAM UNI..... | 4-34 |
| 4.2.7.4 | Applicable GR-1248 Activation/Deactivation Criteria ... | 4-34 |

| | | |
|-------------|---|------|
| 4.2.8 | Network Data Collection (NDC) | 4-35 |
| 4.2.8.1 | SAMI | 4-35 |
| 4.2.8.2 | SAM Core Functions | 4-36 |
| 4.2.8.3 | SAM UNI..... | 4-36 |
| 4.2.9 | Applicable GR-1248 NDC Requirements..... | 4-36 |
| 4.2.10 | Common Monitoring Requirements | 4-38 |
| 4.2.10.1 | Applicable GR-1248 Requirements..... | 4-39 |
| 4.2.11 | Security Management..... | 4-40 |
| 4.2.12 | Accounting Management (Usage Information for Billing)..... | 4-42 |
| 4.2.13 | User-Network Management Requirements..... | 4-44 |
| 4.2.14 | Access Signaling Operations Requirements | 4-45 |
| 4.3 | Non-CRS Operations Requirements at the SAM..... | 4-45 |
| 4.3.1 | SMDS | 4-45 |
| 4.3.1.1 | SNMP MIB Support for the SMDS Interface..... | 4-45 |
| 4.3.2 | FRS..... | 4-48 |
| 4.3.2.1 | SNMP MIB Support for the Frame Relay Interface | 4-48 |
| 4.3.3 | NMLIS | 4-50 |
| 4.3.3.1 | LAN Extension Interface | 4-51 |
| 4.3.3.2 | SAM Configuration Management | 4-52 |
| 4.3.3.3 | SAM MAC-Layer Processing..... | 4-52 |
| 4.3.3.4 | SAMI VC Provisioning | 4-54 |
| 4.3.3.5 | Tunneling (Optional) | 4-54 |
| 4.3.3.6 | Multi-Protocol Interconnection Using VC Multiplexing..... | 4-55 |
| 4.3.3.7 | SNMP MIB Support for the LAN Interface | 4-55 |
| 4.3.4 | Circuit Emulation Service | 4-56 |
| 4.3.5 | Video | 4-57 |
| 5. | Other Common Requirements | 5-1 |
| 5.1 | Performance | 5-1 |
| 5.1.1 | ATM Transport Performance | 5-1 |
| 5.1.2 | Connection Setup Performance..... | 5-1 |
| 5.2 | Spatial and Environmental Criteria | 5-1 |
| 5.2.1 | Controlled Environment..... | 5-2 |
| 5.2.2 | Limited Environmental Control | 5-2 |
| 5.2.3 | Customer Premises..... | 5-2 |
| 5.3 | Equipment Design | 5-3 |
| 5.4 | Reliability | 5-3 |
| 5.5 | Product Support..... | 5-3 |
| Appendix A: | Simple Network Management Protocol..... | A-1 |
| A.1 | Introduction | A-1 |
| A.1.1 | Management Information Base (MIB)..... | A-2 |
| A.1.2 | SNMP Protocol Operations..... | A-3 |
| A.1.3 | SNMP Administrative Architecture..... | A-5 |
| A.2 | Current Status in Standards Bodies or Industry Groups | A-5 |

| | |
|--|--------------|
| A.3 Integration with the Telecommunications Management Network | A-7 |
| References | References-1 |
| Acronyms..... | Acronyms-1 |

List of Figures

| | | |
|-------------|--|------|
| Figure 1-1. | Basic SAM Configuration | 1-1 |
| Figure 2-1. | Service Access Multiplexer Model..... | 2-1 |
| Figure 2-2. | SMDS-ATM Mapping Function..... | 2-4 |
| Figure 2-3. | Protocol Architecture for FR-ATM Network Interworking | 2-10 |
| Figure 2-4. | Protocol Architecture for FR-ATM Service Interworking | 2-11 |
| Figure 2-5. | Support for Point-to-Multipoint Functions at the BSS | 2-14 |
| Figure 2-6. | Bridging Ethernet Segments via Point-to-Point ATM VCCs..... | 2-17 |
| Figure 2-7. | Bridging Token Rings via Point-to-Point ATM VCCs | 2-19 |
| Figure 2-8. | Bridging FDDI Rings via Point-to-Point ATM VCCs | 2-20 |
| Figure 2-9. | DS1 and DS3 Interworking Function | 2-22 |
| Figure 3-1. | SAMI Layering | 3-1 |
| Figure 3-2. | ETSI and ITU-T G.902 Reference Model | 3-2 |
| Figure 3-3. | Examples of Physical SAMI..... | 3-5 |
| Figure 3-4. | Example of SAM function implemented in STM Equipment | 3-5 |
| Figure 3-5. | Example of SAM function implemented in Hybrid Equipment..... | 3-5 |
| Figure 3-6. | Tunneling of Signaling from Multiple Subscribers | 3-9 |
| Figure 3-7. | An Example of Tunneling of Signaling Through a SAM..... | 3-10 |
| Figure 3-8. | An Example of SVC Support by Preestablished VPCs | 3-11 |
| Figure 4-1. | Operations Communication Case A: SAM at Remote Site | 4-2 |
| Figure 4-2. | Operations Communication Case B: SAM at CO | 4-3 |
| Figure 4-3. | Example Management System Architecture | 4-4 |
| Figure 4-4. | Leading Candidates for Management Interface Protocol Stacks..... | 4-5 |
| Figure 4-5. | Example of ifIndex Assignments to Interface Sublayers | 4-7 |
| Figure 4-6. | Out-of-Band Operations Channel Scenario | 4-9 |
| Figure 4-7. | SAM Architecture Assumed for NMLIS..... | 4-51 |
| Figure A-1. | Framework of Simple Network Management Protocol (SNMP) | A-1 |
| Figure A-2. | SNMP Message Structure..... | A-4 |

List of Tables

| | | |
|-------------|---|------|
| Table 3-1. | An Example of VPI Mapping at the SAMI | 3-12 |
| Table 4-1. | Example of the ifStackTable | 4-8 |
| Table 4-2. | Use of the ifGeneralGroup of objects for the ATM Interface | 4-12 |
| Table 4-3. | Applicable GR-1248 Operations Flow Requirements | 4-18 |
| Table 4-4. | Applicable GR-1248 Configuration Management Requirements | 4-20 |
| Table 4-5. | Applicable GR-1248 Fault Management Requirements..... | 4-24 |
| Table 4-6. | Applicable GR-1248 Performance Management Requirements | 4-30 |
| Table 4-7. | Applicable GR-1248 Activation/Deactivation Requirements | 4-34 |
| Table 4-8. | Applicable GR-1248 NDC Requirements | 4-37 |
| Table 4-9. | Applicable GR-1248 Common Monitoring Requirements..... | 4-39 |
| Table 4-10. | Applicable GR-1248 Security Management Requirements for SAM Interface to Management System | 4-41 |
| Table 4-11. | Applicable GR-1248 Accounting Management Requirements | 4-43 |
| Table 4-12. | Applicable GR-1248 CNM and ILMI Requirements | 4-44 |
| Table 4-13. | Use of ifGeneralGroup of Objects for the SIP Level 3 Sublayer | 4-46 |
| Table 4-14. | Use of ifGeneralGroup of Objects for the DS0 Sublayer | 4-47 |
| Table 4-15. | Use of ifGeneralGroup of Objects for the FR Sublayer | 4-49 |
| Table 4-16. | Use of ifGeneralGroup of Objects for the Ethernet Interface..... | 4-56 |
| Table A-1. | SNMPv1 and SNMPv2c Protocol Data Units (PDUs) | A-3 |
| Table A-2. | Core SNMPv1 Specifications | A-6 |
| Table A-3. | Core SNMPv2c Specifications | A-6 |