

Contents

Generic Requirements Notice Of Disclaimer	iii
Preface	xi
1 Introduction	
1.1 Purpose	1-1
1.2 Scope	1-2
1.3 Document Organization	1-2
1.4 Related Telcordia and Industry Documents and Standards	1-2
1.5 Requirements Terminology	1-3
1.6 Requirement Labeling Conventions	1-4
1.6.1 Numbering of Requirement and Related Objects	1-4
1.6.2 Requirement, Conditional Requirement, and Objective Identification	1-5
2 General Description	
3 UNI Physical Layer	
3.1 44.736 Mbit/s UNI	3-1
3.2 155.520 Mbit/s UNI	3-2
3.3 622.080 Mbit/s UNI	3-2
4 UNI ATM Layer	
4.1 ATM Sending Functions	4-1
4.1.1 ATM Cell Generation	4-1
4.1.2 Pre-assigned Traffic Type Indication	4-1
4.1.3 Payload Type Indication	4-2
4.2 ATM Receiving Functions	4-2
4.2.1 Cell Header Extraction and Validation	4-2
4.2.2 Pre-assigned Traffic Type Identification	4-3
4.2.3 VPI and VCI Allocation	4-3
4.3 Number of Active Connections	4-4
4.4 Subscription Parameters	4-4
5 Cell Relay Service	
5.1 Service Types	5-1
5.1.1 CRS Exchange Services	5-1
5.1.2 CRS Exchange Access Services	5-2
5.2 Summary of Core CRS Features	5-2
5.2.1 Connection Type	5-2
5.2.2 Communications Configurations	5-2
5.2.3 Cell Transfer Rates	5-3
5.2.4 Quality of Service Classes	5-3

5.2.5 SVC Addressing and Address Screening	5-3
5.3 Signaling for SVC CRS	5-3
6 SMDS	
6.1 Support for SMDS Features	6-1
6.2 Protocol Specification	6-2
6.2.1 SIP_CLS	6-2
6.2.2 CPCS	6-3
6.2.3 SAR	6-3
6.2.4 ATM	6-4
6.2.5 SMDS QOS Issues on a Multi-Service UNI	6-4
7 PVC Frame Relay Service	
7.1 Functional Architecture Assumptions	7-1
7.1.1 Scenario 1	7-1
7.1.2 Scenario 2	7-1
7.1.3 Scenario 3	7-2
7.2 Frame Relay Service Features	7-2
7.3 Protocol Specification	7-3
7.3.1 FR-SSCS	7-3
7.3.2 AAL5-CPCS and AAL5-SAR	7-4
7.3.3 ATM	7-4
8 Circuit Emulation Service	
8.1 Functional Architecture Assumptions	8-1
8.2 Circuit Emulation Features	8-2
8.3 Protocol Specification	8-2
9 Traffic and Performance	
9.1 Performance	9-1
9.1.1 Reference Traffic Loads	9-1
9.1.2 ATM Cell Transfer Performance	9-2
9.1.3 Connection Processing Performance	9-3
9.1.4 CRS Performance	9-3
9.1.5 SMDS Performance	9-3
9.1.6 FRS Performance	9-3
9.2 Traffic and Congestion Control	9-4
9.2.1 Traffic Parameters	9-4
9.2.1.1 CRS Traffic Characterization	9-4
9.2.1.2 SMDS Traffic Characterization	9-4
9.2.1.3 FRS Traffic Characterization	9-5
9.2.2 Traffic Control Functions	9-5
9.2.2.1 Connection Admission Control	9-5
9.2.2.2 Usage Parameter Control	9-6
9.2.2.2.1 Cell Delay Variation Tolerance	9-7

9.2.2.3 Priority Control	9-7
9.2.2.4 Explicit Forward Congestion indication	9-8
9.2.2.5 Flow Control	9-8
9.2.3 SMDS Traffic Control	9-8
9.2.4 FRS Traffic Control	9-8

10 Operations Criteria for a Multi-service UNI

10.1 Operations Support for PVC CRS	10-1
10.2 Operations Support for SMDS	10-1
10.2.1 Memory Administration	10-2
10.2.2 Maintenance	10-2
10.2.2.1 Alarm Monitoring	10-3
10.2.2.2 Performance Monitoring	10-3
10.2.2.2.1 Protocol Level Performance Monitoring	10-3
10.2.2.2.2 Physical Layer Performance Monitoring	10-4
10.2.2.3 Testing	10-5
10.2.3 Network Data Collection	10-5
10.3 Operations Support for PVC FRS	10-5
10.3.1 Potential Operations Architectures	10-5
10.3.2 Interworking In the ATM Network	10-6
10.3.3 Interworking in the Frame Relay Network	10-7
10.3.4 Interworking In a Standalone Device	10-7

11 Usage Information to Support Billing

11.1 Usage Measurement Framework	11-1
11.2 Service-Independent Usage Information	11-1
11.2.1 ATM Permanent Virtual Connections	11-1
11.2.2 ATM Switched Virtual Connections	11-3
11.3 Service-Specific Usage Information	11-3
11.3.1 CRS	11-3
11.3.2 SMDS	11-4
11.3.3 PVC FRS	11-5
11.3.4 CES	11-6

Appendix A: References

Appendix B: Acronyms

Requirement-Object Index

List of Figures

Figure 2-1	Multi-Service UNI Protocol Model	2-2
Figure 5-1	End User Connectivity via CRS	5-1
Figure 7-1	PVC FRS Functional Architecture (Scenario 2, Network I/W. Rec. I.555)	7-2
Figure 8-1	Circuit Emulation Functional Architecture Assumptions	8-2
Figure 9-1	Scope of UNI ATM Performance Objectives	9-2
Figure 11-1	Cell Relay Usage Information	11-3
Figure 11-2	SMDS Usage Information	11-4
Figure 11-3	Frame Relay Usage Information	11-5
Figure 11-4	Circuit Emulation Usage Information	11-6

List of Tables

Table 4-1	Pre-Assigned Header Values (Traffic Types) at the UNI	4-2
Table 9-1	Performance Objectives Across a BSS for ATM Connections Delivered to a DS3-based Multi-service UNI	9-3
Table 9-2	CDVT Values to be Supported by the UPC on a DS3-based Multi-service UNI	9-7