

Contents

Generic Requirements Notice of Disclaimer	iii
Contents	v
List of Figures	vii
List of Tables	ix
Preface	xi
About GR-2935-CORE	xii
To Submit Comments	xii
1. Introduction	1-1
1.1 Overview	1-1
1.2 Scope	1-2
1.2.1 Reasons for Revision 1	1-3
1.3 Organization	1-3
1.4 Terminology	1-3
1.5 Relation to Other Documents	1-6
1.6 Requirements Terminology	1-6
1.7 Requirement Labeling Conventions	1-7
1.7.1 Numbering of Requirement and Related Objects	1-7
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-8
2. Subscriber Interfaces	2-1
2.1 X.25 Direct Access	2-1
2.1.1 X.25 Address Block Format	2-1
2.1.2 X.25 TOA/NPI Address Subscription	2-8
2.2 Impacted X.25 Facilities and Features	2-9
2.2.1 Call Redirection and Call Deflection	2-10
2.2.1.1 Call Deflection Selection (CDS)	2-11
2.2.1.2 Call Redirection or Call Deflection Notification (CRCDN)	2-12
2.2.1.3 Call Redirection Memory Administration	2-15
2.2.2 Direct Call	2-16
2.2.2.1 Direct Call Memory Administration	2-17
2.2.3 Multiline Hunt Groups	2-19
2.2.4 Permanent Virtual Circuits	2-20
2.3 X.25 Dial-In and Dial-Out Access Interface - X.32	2-21
2.3.1 Standard X.32 Profile	2-21
2.3.2 Network User Identification (NUI) Override Subscription Facility	2-22
2.3.3 Customized Service	2-22
2.4 Asynchronous Access Interfaces	2-22
3. Interoffice Interfaces	3-1
3.1 X.75/X.75' Address Block Format	3-1
3.2 Address Format Configuration for X.75/X.75' Interfaces	3-5
3.3 Impacted X.75/X.75' Utilities - Call Redirection and Call Deflection	3-7
3.3.1 Call Redirection or Call Deflection Selection (CRCDS)	3-8

- 3.3.1.1 Receiving the CRCDS Utility 3-8
- 3.3.1.2 Transmitting the CRCDS Utility 3-9
- 3.3.2 Call Redirection or Call Deflection Notification (CRCDN) 3-12
 - 3.3.2.1 Receiving the CRCDN Utility 3-12
 - 3.3.2.2 Transmitting the CRCDN Utility 3-13
- 3.4 AC/PS X.25 Interface 3-15
- 4. Numbering 4-1
 - 4.1 Numbering Summary 4-1
 - 4.2 Address Handling 4-7
 - 4.2.1 DTE-DCE Interface: Call Request Packet 4-11
 - 4.2.2 DTE-DCE Interface: Incoming Call Packet 4-17
 - 4.2.3 DTE-DCE Interface: Call Accepted Packet 4-22
 - 4.2.4 DTE-DCE Interface: Call Connected Packet 4-24
 - 4.2.5 X.75/X.75': Call Request Packet 4-30
 - 4.2.5.1 Call Request Packet Received by Switch over an X.75/X.75'
Interface 4-30
 - 4.2.5.2 Call Request Packet Transmitted by Switch over an X.75/X.75'
Interface 4-34
- 5. Call Processing (Digit Analysis and Routing) 5-1
 - 5.1 PHF and PS Routing Tables 5-1
 - 5.2 Routing at Various ISDN and PPSN Interfaces 5-2
 - 5.2.1 Path Selection in PHFs 5-2
 - 5.2.1.1 Calls Originating With Packet Mode Bearer Capability 5-2
 - 5.2.1.2 Packet Mode Bearer Capability Tandem Routing 5-13
 - 5.2.2 Path Selection in PSs 5-17
 - 5.2.2.1 Calls Originating on a DTE/PS Interface 5-17
 - 5.2.2.2 Call Requests Received Over an X.75 or X.75' PS Interface 5-21
 - 5.2.2.3 PSN Routing 5-24
 - 5.2.3 Path Selection in ACs 5-26
- 6. Automatic Message Accounting (AMA) 6-1
 - 6.1 Address Length Issues 6-1
 - 6.2 Numbering Plan Identification Issues 6-1
- Appendix A: ISDN TL1 Memory Administration Parameters A-1
- Appendix B: Called and Calling Address Formats B-1
- Appendix C: ISDN Routing Flowcharts C-1
- References References-1
- Glossary Glossary-1

List of Figures

Figure 2-1	X.25 TOA/NPI Address Block Format (A bit set to 1)	2-3
Figure 2-2	X.25 Called and Calling DTE Address Fields for the TOA/NPI Format	2-3
Figure 3-1	X.75/X.75' TOA/NPI Address Block Format (A bit set to 1)	3-2
Figure 3-2	X.75/X.75' Called and Calling DTE Address Fields for the TOA/NPI Format	3-2
Figure 5-1	Calls Originating on a DTE/PS Interface - PSN Not Supported	5-27
Figure 5-2	Calls Received Over an X.75/X.75' Interface - PSN Not Supported	5-29
Figure 5-3	ISDN or PSTN Dial-Out Calls - PSN Not Supported	5-31
Figure 5-4	Calls Originating on a DTE/PS Interface - PSN Supported	5-32
Figure 5-5	Calls Received Over an X.75/X.75' Interface - PSN Supported	5-36
Figure 5-6	ISDN or PSTN Dial-Out Calls When ROA Is Not Signalled - PSN Supported	5-38
Figure 5-7	ISDN or PSTN Dial-Out Calls With ROA Signalled - PSN Supported	5-39
Figure B-1	ISDN - ISDN IntraNPA Calls (TOA/NPI - TOA/NPI Format)	B-3
Figure B-2	PPSN - PPSN Calls Within the Same DNIC (Non-TOA/NPI - TOA/NPI Format)	B-4
Figure B-3	ISDN - PPSN IntraLATA Calls Over a TOA/NPI Trunk (Non-TOA/NPI - Non-TOA/NPI Format)	B-5
Figure B-4	ISDN - ISDN InterLATA and InterNPA Calls (TOA/NPI - Non-TOA/NPI Format)	B-6
Figure B-5	PPSN - ISDN InterLATA Calls (TOA/NPI - TOA/NPI Format)	B-7
Figure B-6	PPSN - ISDN International Calls (Non-TOA/NPI Format; Foreign E.164 Address <= 13 Digits)	B-8
Figure B-7	PPSN - ISDN International Calls (Non-TOA/NPI Format; Foreign E.164 Address >= 14 Digits)	B-9
Figure B-8	ISDN - ISDN International Calls (Non-TOA/NPI Format; Foreign E.164 Address <= 12 Digits)	B-10
Figure B-9	ISDN - ISDN International Calls (Non-TOA/NPI Format; Foreign E.164 Address >= 13 Digits)	B-11
Figure B-10	ISDN - ISDN International Calls (TOA/NPI Format; Foreign E.164 Address <=14 Digits)	B-12
Figure B-11	ISDN - ISDN International Calls (TOA/NPI Format; Foreign E.164 Address = 15 Digits)	B-13
Figure C-1	Originating Packet Handler Function, Packet Mode Bearer Capability	C-2

List of Tables

Table 2-1	Coding of the Type of Address (TOA) Subfield for X.25	2-4
Table 2-2	Coding of the Numbering Plan Identification (NPI) Subfield for X.25	2-5
Table 2-3	Relevant Combinations of TOA and NPI for X.25	2-6
Table 3-1	Coding of the Type of Address (TOA) Subfield for X.75/X.75'	3-3
Table 3-2	Coding of the Numbering Plan Identification (NPI) Subfield for X.75/X.75'	3-3
Table 4-1	Conversion between Non-TOA/NPI Escape Code and TOA/NPI Formats	4-3
Table 4-2	TOA/NPI Address Digit Structure - Call Request Packet	4-3
Table 4-3	TOA/NPI Address Digit Structure - Incoming Call Packet	4-4
Table 4-4	Maximum Number of Called Address Digits in Main Address in Non-TOA/NPI Call Request Packet	4-5
Table 4-5	Maximum Number of Calling Address Digits in Main Address in Non-TOA/NPI Incoming Call Packet	4-6
Table 4-6	Maximum Number of Calling Address Digits in Main Address in Non-TOA/NPI Call Connected Packet	4-6
Table A-1	TOA/NPI Address Subscription Parameter	A-1
Table A-2	Call Redirection and Call Deflection Parameters	A-2
Table A-3	Direct Call Parameter	A-6
Table A-4	Permanent Virtual Circuit Parameter	A-7