
Generic Requirements for Portable Polarization Mode Dispersion (PMD) Test Sets

Contents [Telcordia GR-2947-Documentation Information](#)

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 Organization	1-1
1.3 Requirements Terminology	1-1
1.4 Requirement Labeling Conventions.....	1-2
1.4.1 Numbering of Requirement and Related Objects	1-2
1.4.2 Requirement, Conditional Requirement, and Objective Object Identification	1-3
2. GENERAL INFORMATION	2-1
2.1 Polarization Mode Dispersion.....	2-1
2.1.1 Causes of Birefringence and PMD.....	2-1
2.1.2 Birefringence Related to PMD	2-2
2.1.3 Mode Coupling	2-3
2.1.4 PMD and Pulse Broadening.....	2-5
2.1.5 Statistical Aspects	2-6
2.1.6 PMD Limitations in Digital Systems	2-9
2.2 Measurement of PMD	2-10
2.2.1 General	2-10
2.2.2 The Fixed Analyzer Method	2-11
2.2.3 The Jones Matrix Method	2-12
2.2.4 The Interferometric Method.....	2-13
2.3 Product Description	2-14
3. Design Criteria	3-1
3.1 Display and Control Features	3-1
3.2 Operation	3-3
3.3 Mechanical Design.....	3-4
3.4 Maintenance	3-5
3.5 Product Information	3-6
3.5.1 Documentation.....	3-6
3.5.2 Performance Specification Sheet	3-6
3.6 Product and Packaging Markings.....	3-7
3.6.1 Product Markings.....	3-7
3.6.2 Packaging Markings.....	3-8
3.7 Laser Protection	3-8

4.	Operational/Environmental Requirements.....	4-1
4.1	Operation.....	4-2
4.1.1	Measurement Accuracy.....	4-2
4.1.2	Measurement Repeatability.....	4-2
4.1.3	Measurement Range.....	4-2
4.1.4	Minimum Test Fiber Length.....	4-2
4.1.5	Measurement Time.....	4-2
4.2	Mechanical Design.....	4-3
4.2.1	Shock Tests.....	4-3
4.2.1.1	Shipment from Manufacturer.....	4-3
4.2.1.2	Local Transportation.....	4-3
4.2.1.3	During Use.....	4-3
4.2.2	Vibration Test.....	4-4
4.3	Power.....	4-4
4.4	Environment.....	4-4
4.5	Electromagnetic Interference and Electrostatic Discharge.....	4-4
4.5.1	Electromagnetic Interference.....	4-4
4.5.2	Electrostatic Discharge.....	4-5
4.6	Protection.....	4-5
4.6.1	Grounding.....	4-5
4.6.2	Leakage Current.....	4-5
4.6.3	Hot Surfaces.....	4-5
5.	Performance Test Procedures.....	5-1
5.1	Operation.....	5-1
5.1.1	Measurement Accuracy.....	5-1
5.1.2	Measurement Repeatability.....	5-2
5.1.3	Measurement Range.....	5-3
5.1.4	Minimum Fiber Length.....	5-3
5.1.5	Measurement Time.....	5-3
5.2	Mechanical Design.....	5-3
5.2.1	Shock Tests.....	5-3
5.2.1.1	Shipment from Manufacturer.....	5-3
5.2.1.2	Local Transportation.....	5-4
5.2.1.3	During Use.....	5-4
5.2.2	Vibration Test.....	5-5
5.3	Power.....	5-5
5.4	Environment.....	5-5
5.4.1	Non-Operating Environment.....	5-5
5.4.2	Operating Environment.....	5-6
5.5	Electromagnetic Interference and Electrostatic Discharge.....	5-6
5.5.1	Electromagnetic Interference.....	5-6
5.5.2	Electrostatic Discharge.....	5-6
5.6	Protection.....	5-6
5.6.1	Grounding.....	5-6

5.6.2	Leakage Current.....	5-7
5.6.3	Hot Surfaces.....	5-7
References	References-1
Glossary	Glossary-1

List of Figures

Figure 2-1.	Random Orientation of the Local Fast (F) and Slow (S) Polarization Axes Along a Fiber Length.....	2-1
Figure 2-2.	Causes of Birefringence in Optical Fiber	2-2
Figure 2-3.	PMD vs. Length for the Fibers of Table 2-1	2-4
Figure 2-4.	PMD Effects on a Narrow Impulse in two Source-Coherence Regions...	2-5
Figure 2-5.	Normalized Maxwellian Probability Distribution of the PMD	2-7
Figure 2-6.	Minutes Per Year that the Instantaneous PMD Exceeds a Particular Value	2-8
Figure 2-7.	PMD-Limited Lengths vs. PMD Coefficient for Two Values of Bit-Rate B and of Bit-Period Fraction f	2-10
Figure 2-8.	Schematic Wavelength Scans for Cable in Two Limits of Mode Coupling.....	2-12
Figure 2-9.	Instantaneous PMD vs. Wavelength.....	2-13
Figure 2-10.	Schematic Interferometric Scans for Cable in Two Limits of Mode Coupling.....	2-14
Figure 5-1.	Measurement Accuracy Test Setup	5-2

List of Tables

Table 2-1.	Effect of Mode Coupling Versus Length	2-3
Table 4-1.	Drop Test Heights.....	4-3
Table 4-2.	Environmental Extreme Requirements.....	4-4
Table 5-1.	Drop Test Heights.....	5-4
Table 5-2.	Vibration Test Parameters	5-5
Table 5-3.	Environmental Extreme Requirements.....	5-5