

Table of Contents

| | |
|--|------|
| Generic Requirements Notice of Disclaimer | iii |
| Preface | xiii |
| 1 Introduction | |
| 1.1 Purpose and Scope | 1-1 |
| 1.1.1 The Purpose of Bonding and Grounding | 1-1 |
| 1.1.2 Changes from TR-NWT-000295, Issue 2, to GR-295-CORE | 1-1 |
| 1.1.3 Equipment EMC Requirements | 1-1 |
| 1.2 Items Not Covered | 1-2 |
| 1.2.1 Choice of Bonding Topology | 1-2 |
| 1.3 Organization | 1-3 |
| 1.4 Schematic Identifiers | 1-4 |
| 1.5 Conventions for Generic Criteria | 1-4 |
| 1.5.1 Numbering of Requirement and Related Objects | 1-5 |
| 1.5.2 Requirement, Conditional Requirement, and Objective Object Identification | 1-5 |
| 2 Definitions | |
| 2.1 Abbreviations and Acronyms | 2-10 |
| 2.2 Equivalent Terms | 2-11 |
| 2.3 Grounding versus Bonding | 2-11 |
| 3 General Principles and Requirements for Bonding Networks | |
| 3.1 Reasons for Bonding and Grounding | 3-1 |
| 3.1.1 Personal Safety | 3-1 |
| 3.1.2 Equipment and Distribution Circuit Protection | 3-1 |
| 3.1.3 Equipment Operation | 3-2 |
| 3.1.4 Electromagnetic Interference Reduction | 3-2 |
| 3.1.5 Reference Buses | 3-2 |
| 3.1.6 Electrostatic Discharges (ESD) | 3-2 |
| 3.1.7 Reliability | 3-2 |
| 3.2 General Grounding Conductor and Connection Requirements | 3-2 |
| 3.2.1 Conductors Except for AC Equipment Grounding Conductor | 3-2 |
| 3.2.2 Requirements for ACEG Conductors | 3-3 |
| 3.2.3 Connections | 3-4 |
| 3.2.3.1 Terminals | 3-4 |
| 3.2.3.2 Splices | 3-5 |
| 3.2.4 Single Grounding Conductors | 3-5 |
| 3.2.4.1 Girdling | 3-5 |
| 3.2.4.2 Bending Radius | 3-6 |
| 3.3 Induction Effects | 3-6 |
| 3.3.1 Lightning and Fault Current Carrying Conductors | 3-6 |
| 3.4 Selection of the Bonding Topology | 3-6 |
| 3.4.1 Equipment Rearrangements | 3-7 |

4 Requirements for AC and DC Power Systems Associated with Equipment Bonding Networks

| | |
|--|-----|
| 4.1 AC Power Distribution and Supply | 4-1 |
| 4.1.1 Safety Requirements | 4-1 |
| 4.1.2 Raceways | 4-1 |
| 4.1.3 Use of ACEG Conductor | 4-1 |
| 4.1.4 External AC Power Supplies | 4-2 |
| 4.1.5 Internal AC Power Supplies | 4-2 |
| 4.1.5.1 Grounding Internal AC Power Supplies that Power Remote Loads | 4-2 |
| 4.1.6 Receptacles | 4-3 |
| 4.1.6.1 General-Purpose Receptacles | 4-3 |
| 4.1.6.2 Receptacles Powered from Internal AC Power Supplies | 4-3 |
| 4.1.6.3 Isolated Receptacles | 4-3 |
| 4.2 DC Power Distribution and Supply | 4-3 |
| 4.2.1 External Power Sources | 4-4 |
| 4.2.1.1 The BR Bus | 4-4 |
| 4.2.1.2 Grounding the Plant's Frame | 4-4 |
| 4.2.1.3 Location of the Power Plant | 4-4 |
| 4.2.1.4 Power Feeders | 4-4 |
| 4.2.2 Bonding of BR Terminals in Equipment | 4-5 |
| 4.2.2.1 Use of DC-I Power Distribution Systems | 4-6 |
| 4.2.2.2 Use of DC-C Power Distribution Systems | 4-6 |
| 4.2.3 Grounding Location | 4-6 |
| 4.2.3.1 BR Conductors | 4-7 |
| 4.2.3.2 Power Distribution Cabinets (PDCs) | 4-7 |
| 4.2.4 Internal Power Sources | 4-7 |
| 4.2.4.1 Frame Ground Reference Buses | 4-7 |
| 4.2.4.2 Exceptions | 4-7 |

5 IBN Principles and Requirements

| | |
|--|-----|
| 5.1 General Principles | 5-1 |
| 5.1.1 Establishing an IBN | 5-2 |
| 5.1.2 IBN Limits | 5-2 |
| 5.2 IBN Frames | 5-3 |
| 5.2.1 One Conductive Unit | 5-3 |
| 5.2.2 Insulation Resistance | 5-3 |
| 5.2.2.1 Anchor Bolts | 5-3 |
| 5.2.2.2 Bottom of Frames | 5-3 |
| 5.2.2.3 Superstructure Support | 5-4 |
| 5.2.2.4 Lighting Fixtures, etc. | 5-4 |
| 5.2.3 Frame-to-Frame Connections | 5-4 |
| 5.2.3.1 Peripheral Equipment Frame Grounding | 5-4 |
| 5.3 Establishing an SPCB and SPCW | 5-5 |
| 5.3.1 Establishing a Separate SPCW | 5-5 |
| 5.3.1.1 SPCW Dimensions | 5-5 |
| 5.3.1.2 SPCW Location | 5-6 |
| 5.3.1.3 SPCB Connections | 5-6 |
| 5.3.2 Using the BR Bus as an SPCB | 5-9 |
| 5.3.2.1 Requirements for Plants with an Insulated BR Bus | 5-9 |

| | | |
|-----------|--|------|
| 5.3.2.2 | Requirements for Plants with a Non-Insulated BR Bus | 5-10 |
| 5.4 | Nearby Common Bonding Network Members | 5-13 |
| 5.5 | Grounding Conductor Requirement | 5-13 |
| 5.5.1 | Clearing a Fault to the Frame of the Power Plant | 5-13 |
| 5.5.1.1 | Conductor B as Part of the Sole Fault-Clearing Path | 5-13 |
| 5.5.1.2 | Conductor A as Part of the Sole Fault-Clearing Path | 5-14 |
| 5.5.1.3 | Conductor A as a Redundant Fault-Clearing Conductor | 5-14 |
| 5.5.1.4 | Conductor A as a Coupled Bonding Conductor | 5-14 |
| 5.5.1.5 | Summary | 5-17 |
| 5.6 | IBN Topologies | 5-20 |
| 5.6.1 | Star-IBN and Chain-IBN Details | 5-20 |
| 5.6.2 | Mesh-IBN Detail | 5-25 |
| 5.6.2.1 | Preferred Arrangements for Mesh-IBN | 5-26 |
| 5.6.2.2 | Mesh-BN Intra-System Connections | 5-30 |
| 5.7 | Additional Requirements for Power Systems Serving an IBN | 5-31 |
| 5.7.1 | External Principal Power Plant Grounding Requirements | 5-31 |
| 5.7.1.1 | Grounding the BR Bus | 5-31 |
| 5.7.2 | CBN DC-C Loads | 5-31 |
| 5.7.2.1 | Loads Fed from the Principal DC Source | 5-31 |
| 5.7.2.2 | Loads Fed from Internal Power Sources | 5-32 |
| 5.7.3 | Grounding the External AC and DC Power Supplies Feeding IBN Loads (Other than Principal Power Source) | 5-32 |
| 5.7.3.1 | DC Power Supplies | 5-32 |
| 5.7.3.2 | AC Power Supplies | 5-32 |
| 5.7.3.2.1 | Treatment of the AC Conductors | 5-32 |
| 5.7.4 | AC Power Distribution to IBN Equipment | 5-33 |
| 5.7.5 | Specific Examples of AC and DC Grounding Principles for IBNs | 5-33 |
| 5.7.6 | Grounding the Common Power Plant and Powering the CBN and IBN Systems | 5-33 |

6 Mesh-BN Principles and Requirements

| | | |
|---------|--|-----|
| 6.1 | General Principles | 6-1 |
| 6.1.1 | Establishing a Mesh-BN | 6-2 |
| 6.2 | Mesh-BN Frames | 6-2 |
| 6.2.1 | One Conductive Unit | 6-2 |
| 6.2.1.1 | Anchor Bolts | 6-2 |
| 6.2.1.2 | Bottom of Frames | 6-3 |
| 6.2.1.3 | Superstructure Support | 6-3 |
| 6.2.1.4 | Frame-to-Frame Connections | 6-3 |
| 6.2.1.5 | Peripheral Equipment Frame Grounding | 6-3 |
| 6.3 | Specific Mesh-BN Principles and Requirements | 6-3 |
| 6.3.1 | Power System Requirements | 6-5 |
| 6.3.2 | Internal Power Supplies | 6-5 |
| 6.4 | Intrasystem Signal Cables | 6-6 |
| 6.5 | Signal Cable Interconnection Between Systems | 6-6 |
| 6.5.1 | Interconnection Between Two Mesh-BN Systems | 6-6 |
| 6.5.2 | Connection of Other CBN Members to Mesh-BN | 6-7 |

7 Performance Verification and Test Procedures

| | |
|---|-----|
| 7.1 General AC Power System Verification | 7-1 |
| 7.1.1 Listing Label and Wiring | 7-1 |
| 7.1.2 Continuity Tests | 7-1 |
| 7.2 IBN Verification | 7-1 |
| 7.2.1 Visual Tests | 7-1 |
| 7.2.1.1 Spotting IBN Violations | 7-1 |
| 7.2.2 Grounding of Power Supplies | 7-2 |
| 7.2.2.1 External Power Supplies | 7-2 |
| 7.2.3 SPCW Conductors | 7-2 |
| 7.2.3.1 Power Feeds | 7-2 |
| 7.2.4 Insulation Tests | 7-2 |
| 7.2.4.1 Low-Voltage Resistance Test | 7-3 |
| 7.2.4.2 High-Voltage Resistance Test | 7-3 |
| 7.2.5 Short-Circuit Tests | 7-3 |
| 7.3 Star/Chain-IBN Tests | 7-3 |
| 7.3.1 Star/Chain-IBN Noise Current Tests | 7-3 |
| 7.3.1.1 Abnormal Current Flow in Grounding Wires and Frames | 7-3 |
| 7.3.1.2 Correctly Wired Circuit Arrangements | 7-4 |
| 7.3.1.3 Correcting Incorrectly Wired Circuit Arrangements | 7-4 |
| 7.3.1.3.1 Multigrounded AC and DC Power Sources | 7-4 |
| 7.3.1.3.2 Overvoltage Protectors | 7-5 |
| 7.3.1.3.3 Improper Load Connections | 7-5 |
| 7.4 Mesh-IBN Verification | 7-5 |
| 7.4.1 Additional Criteria | 7-5 |
| 7.5 Mesh-BN Verification | 7-6 |
| 7.5.1 Additional Criteria | 7-6 |

Appendix A: Overview of Telecommunications Building Bonding and Grounding Methods

Appendix B: References

Requirement-Object Index

List of Figures

| | | |
|-------------|---|------|
| Figure 2-1 | Illustration of Certain Terms | 2-8 |
| Figure 2-2 | Illustration of a DC-I Power Distribution System | 2-9 |
| Figure 2-3 | Illustration of a DC-C Power Distribution System | 2-9 |
| Figure 5-1 | Simplified Isolated Bonding Network | 5-1 |
| Figure 5-2 | Typical Sequence of Connections to a Separate SPCW | 5-7 |
| Figure 5-3 | Using an Insulated BR Bus as the SPCW | 5-11 |
| Figure 5-4 | Using a Non-Insulated BR Bus as the SPCW | 5-12 |
| Figure 5-5 | Typical Grounding and Power Feed from a Dedicated DC Power Plant Powering IBN Loads in DC-I Configuration | 5-15 |
| Figure 5-6 | Typical AC Power Feed to an Isolated Bonding Network | 5-18 |
| Figure 5-7 | Typical Grounding for Common and Isolated Bonding Networks Powered from a Common Power Plant | 5-19 |
| Figure 5-8 | Simplified Star IBN Configuration | 5-21 |
| Figure 5-9 | Simplified Chain IBN Configuration | 5-22 |
| Figure 5-10 | Common Impedance Path in a Chain Bonding Configuration | 5-22 |
| Figure 5-11 | Avoidance of Common Impedance Path by using Star Bonding Configuration | 5-23 |
| Figure 5-12 | Example of a Loop Not Permitted on Star-/Chain-IBNs | 5-24 |
| Figure 5-13 | Example of a Loop Not Permitted on Chain-IBNs | 5-24 |
| Figure 5-14 | Example of Loops Not Permitted on Star-IBNs | 5-25 |
| Figure 5-15 | Illustration of a Mesh-IBN with a Single Frame Bonding Conductor Connecting to the SPCB | 5-27 |
| Figure 5-16 | Illustration of a Mesh-IBN with a Collection Bar | 5-28 |
| Figure 5-17 | Illustration of a Mesh-IBN with Frame Bonding Conductors Connected to SPCB Directly | 5-29 |
| Figure 5-18 | Illustration of a Mesh-IBN with Closely-Coupled Frame Bonding Conductors Connected to SPCB Directly | 5-30 |
| Figure 6-1 | A Simple Mesh-BN Configuration | 6-1 |
| Figure 6-2 | Illustration of Inter-frame Bonding for a Mesh-BN | 6-4 |
| Figure 6-3 | Illustration of Inter-frame Bonding for a Mesh-BN with a Ring Bonding Bus (shown under raised floor as an example) | 6-5 |
| Figure A-1 | Typical Power Service Entrance, Distribution, and Grounding | A-3 |

List of Tables

| | | |
|-----------|--|------|
| Table 2-1 | Cross-Reference for GR-295-CORE Terms | 2-11 |
| Table 5-1 | Tabulation of Typical SPCW Connections | 5-8 |
| Table 5-2 | Minimum Sizes (AWG/kcmil) for Conductor A When it is Part of the Sole Fault-Clearing Path | 5-16 |
| Table 5-3 | Minimum Sizes (AWG/kcmil) for Conductor A When it is Part of a Supplemental Fault-Clearing Path | 5-16 |