

---

# Switch Generic Requirements to Support an Internet Access Traffic Off-Load Architecture

## Contents

Preface .....	Preface-1
1. Introduction.....	1-1
1.1 Purpose.....	1-1
1.2 Background .....	1-1
1.3 Related Documents .....	1-2
1.4 Requirements Terminology.....	1-2
1.5 Requirement Labeling Conventions.....	1-3
1.5.1 Numbering of Requirements and Related Objects.....	1-3
1.5.2 Requirement, Conditional Requirement, and Objective Object Identification .....	1-4
2. General Information.....	2-1
2.1 Nature of Document.....	2-1
2.2 Present Mode of Operation .....	2-1
2.2.1 PMO Access Technologies for PSTN Ingress and Egress.....	2-3
2.2.1.1 POTS Lines.....	2-3
2.2.1.2 ISDN Lines (BRI and PRI).....	2-3
2.3 Off-Load Service Objectives.....	2-4
2.3.1 Service from an Internet User Perspective.....	2-5
2.3.2 Service from an Internet Service Provider Perspective .....	2-6
2.3.3 Service from an LEC Perspective .....	2-8
2.4 Network Architecture.....	2-9
2.4.1 Involved Network Elements.....	2-11
2.4.2 Options for Internet Call Routing .....	2-13
2.5 General Assumptions and Definitions .....	2-14
2.6 Internet Call Phases.....	2-17
2.6.1 Definitions.....	2-17
2.6.2 Discussion of Error Conditions.....	2-18
3. Off-Load via Switch-Based Translations.....	3-1
3.1 Overview .....	3-1
3.2 Serving Arrangement .....	3-2
3.2.1 Support for Overflow/Alternate Routing .....	3-3
3.3 Call Flows .....	3-8
3.3.1 ISP DN in Non-Portable NPA-NXX .....	3-9
3.3.2 ISP DN in Portable NPA-NXX, NP Query Performed by IS .....	3-10

---

---

3.3.3	ISP DN a Non-Ported DN in a Portable NPA-NXX, NP Query Performed by a Switch Outside the LEC Network .....	3-11
3.3.4	ISP DN Ported into IS, NP Query Performed by a Switch Outside the LEC Network .....	3-11
3.4	Requirements.....	3-12
3.4.1	Number Portability.....	3-12
3.4.2	Error Conditions.....	3-13
3.5	Single Number Service in an SBT Architecture .....	3-14
3.5.1	Single Number Service Call Flow .....	3-14
3.5.2	Single Number Service Requirements .....	3-15
4.	Off-Load via AIN Specific_Digit_String Trigger .....	4-1
4.1	Overview .....	4-1
4.2	Serving Arrangement .....	4-3
4.2.1	Support for Overflow/Alternate Routing .....	4-5
4.3	Call Flows .....	4-6
4.4	Requirements.....	4-9
4.4.1	Detection of Internet Call.....	4-9
4.4.1.1	Processing Database Query .....	4-10
4.4.2	Direction of Internet Call .....	4-18
4.4.2.1	Processing Database Response .....	4-18
4.5	Value-Added Services.....	4-22
4.5.1	Revenue Opportunities from Off-Load Architectures .....	4-22
4.5.2	Single Number Service .....	4-23
4.5.3	Alternate Route Selection .....	4-24
4.5.4	Reroute on Busy/No Answer .....	4-25
4.5.5	Expanded Calling Area .....	4-27
5.	Routing Using the Number Portability Trigger .....	5-1
5.1	Overview .....	5-1
5.1.1	Database Queries for NP.....	5-1
5.1.2	Applicability of NP to Internet Off-Load .....	5-1
5.1.3	NP Options .....	5-2
5.2	NP Option 1: Internetwork LRN.....	5-3
5.2.1	Serving Arrangement .....	5-4
5.2.2	Call Flows .....	5-4
5.2.3	Advantages, Disadvantages, and Issues .....	5-7
5.2.4	Ingress Switch Requirements.....	5-8
5.2.4.1	Detection of Internet Call .....	5-8
5.2.4.2	Processing the NP Database Query .....	5-12
5.2.4.3	Processing the NP Database Response with LRN.....	5-13
5.2.4.4	Routing of Internet Call Following NP Response with LRN .....	5-14
5.2.4.5	Default Routing (Query Not Completed or Successful)..	5-17
5.2.5	Egress Switch Requirements.....	5-17

---

---

5.3	NP Option 2: Intranetwork LRN.....	5-17
5.3.1	Serving Arrangement .....	5-18
5.3.2	Call Flows .....	5-18
5.3.2.1	Intranetwork Call.....	5-18
5.3.2.2	Internetwork Call.....	5-19
5.3.3	Advantages, Disadvantages, and Issues.....	5-20
5.3.4	Ingress Switch Requirements.....	5-21
5.3.5	Egress Switch Requirements.....	5-21
5.3.5.1	AIN Specific_Digit_String Trigger at the Egress Switch .....	5-22
5.3.5.2	Switch-Based Translations at the Egress Switch.....	5-22
5.3.5.3	PMO Routing at the Egress Switch .....	5-22
5.4	NP Option 3: Specialized NP Processing.....	5-23
5.4.1	Serving Arrangement .....	5-23
5.4.2	Call Flows .....	5-23
5.4.2.1	Intranetwork Call.....	5-23
5.4.2.2	Internetwork Call.....	5-25
5.4.3	Advantages, Disadvantages, and Issues.....	5-27
5.4.4	Ingress Switch Requirements.....	5-28
5.4.4.1	Detection of Internet Call .....	5-28
5.4.4.2	Processing the NP Query .....	5-28
5.4.4.3	Processing the NP Database Response with Trunk Group ID .....	5-28
5.4.4.4	Routing of Internet Call Following NP Response with Trunk Group ID .....	5-28
5.5	Advantages, Disadvantages, and Issues Associated with NP-Based Internet Off-Load.....	5-29
6.	Operations .....	6-1
6.1	Organization of Subsections .....	6-1
6.2	Assumptions and Background Requirements .....	6-3
6.3	Configuration Management and Memory Administration.....	6-3
6.3.1	Internet Off-Load via Switch-Based Translations .....	6-4
6.3.1.1	Call Identification and Direction Phase.....	6-4
6.3.1.2	Call Routing Phase .....	6-4
6.3.2	Internet Off-Load via the NP Trigger .....	6-5
6.3.2.1	Call Identification and Direction Phase.....	6-5
6.3.2.2	Call Routing Phase .....	6-6
6.3.3	Internet Off-Load via the AIN SDS Trigger .....	6-6
6.3.3.1	Call Identification and Direction Phase.....	6-6
6.3.3.2	Call Routing Phase .....	6-6
6.4	Fault Management.....	6-7
6.5	Performance Management .....	6-7
6.5.1	Different Kinds of Traffic .....	6-7
6.5.2	Need for Additional Measurements .....	6-8

---

---

6.5.3	Why Current Measurements are Insufficient .....	6-8
6.5.4	The ICR, a Supplemental Source for IS Trunk-Group Measurements .....	6-9
6.5.5	The New Measurements Collected at the ICR.....	6-9
6.6	Security Management.....	6-9
6.7	Accounting Management .....	6-9
6.7.1	Internet Off-Load via Switch-Based Translations .....	6-10
6.7.2	Internet Off-Load via the NP Trigger .....	6-10
6.7.3	Internet Off-Load via the AIN SDS Trigger .....	6-11
6.8	Feature Interaction Issues.....	6-11
6.8.1	Call Waiting .....	6-11
6.8.2	Data Off-Load in Call Terminations .....	6-11
	Requirement-Object List .....	ROL-1
	Requirement-Object Index .....	ROI-1
	References .....	References-1
	Bibliography .....	Bibliography-1
	Glossary .....	Glossary-1

---

## List of Figures

Figure 2-1.	Generic View of PSTN-Based Internet Access Architectures PMO.....	2-2
Figure 2-2.	Proposed Reference Architecture for Internet Off-Load.....	2-10
Figure 3-1.	Serving Arrangement for SBT-Based Off-Load .....	3-2
Figure 3-2.	Modem Distribution in Switch Translation Scenario .....	3-6
Figure 4-1.	Serving Arrangement for AIN-Based Off-Load.....	4-4
Figure 4-2.	Modem Distribution in AIN Scenario .....	4-6
Figure 4-3.	High-Level AIN Call Flow for Internet Off-Load.....	4-7
Figure 5-1.	NP Call Flow with Internetwork (Public) LRN.....	5-5
Figure 5-2.	NP Call Flow with Internetwork (Public) LRN.....	5-6
Figure 5-3.	NP Call Flow for Intranetwork LRN - Internetwork Call .....	5-19
Figure 5-4.	Call Flow with NP Specialized Processing - Intranetwork Call.....	5-24
Figure 5-5.	Call Flow for Specialized NP Routing - Internetwork Call.....	5-26