
Generic Requirements for Half-Ringer (HR) Units

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 Organization	1-1
1.3 Requirements Terminology	1-1
1.4 Requirement Labeling Conventions	1-2
1.4.1 Numbering of Requirement and Related Objects	1-2
1.4.2 Requirement, Conditional Requirement, and Objective Object Identification	1-3
1.5 Sample Size	1-3
2. General Information	2-1
2.1 General Product Description	2-1
2.1.1 Listing	2-1
3. Detailed Requirements	3-1
3.1 Materials	3-1
3.2 Mechanical Safety - Construction	3-1
3.3 Documentation	3-2
3.4 Marking, Packaging, and Shipping	3-2
3.4.1 Marking	3-2
3.4.2 Packing and Shipping	3-2
3.4.3 Lead Color	3-3
3.5 Quality Assurance	3-3
3.5.1 Quality Program Analysis	3-3
3.5.2 Product Quality Surveillance	3-3
3.6 Electrical	3-4
3.6.1 Electromagnetic Compatibility	3-4
3.6.1.1 Lightning Surge and AC Power Cross	3-4
3.6.2 Ringer Equivalence Number (REN)	3-5
3.6.3 Return Loss	3-5
3.6.4 Insertion Loss	3-5
3.6.5 Longitudinal Balance	3-7
3.6.6 Dial Pulse Distortion	3-9
3.6.7 Ring-Trip	3-12
3.6.8 Electrostatic Discharge (ESD)	3-13
3.7 Mechanical Requirement of Conductors	3-13

3.7.1	Conductor Pull-Out	3-13
3.7.2	Inside Wire Installation Spacings	3-13
3.7.3	Wiring	3-14
4.	Environmental Requirements.....	4-1
	References	References-1
	Glossary	Glossary-1

List of Figures

Figure 3-1.	Longitudinal-to-Metallic Balance (Performance)	3-8
Figure 3-2.	Dial Pulse Distortion	3-11
Figure 3-3.	Ring-Trip Test Circuit	3-12