

## Contents

Preface . . . . .	Preface-1
1. Introduction . . . . .	1-1
1.1 Purpose . . . . .	1-1
1.2 Use and Background of this Document . . . . .	1-1
1.3 Related Documents . . . . .	1-2
1.4 Organization of Document . . . . .	1-3
1.5 Requirements Terminology . . . . .	1-4
1.6 Changes from GR-3022-CORE, Issue 1 to Issue 2 . . . . .	1-5
2. Network Interconnection Architecture . . . . .	2-1
2.1 BICC Network Model . . . . .	2-1
2.1.1 Overview . . . . .	2-1
2.1.2 Definitions . . . . .	2-3
2.2 Network Interconnection Scenarios . . . . .	2-5
2.3 Protocol Model . . . . .	2-8
3. Lower Layer Transport Interface Protocol for Call Control . . . . .	3-1
3.1 BICC Transport Over MTP3 . . . . .	3-1
3.1.1 Signaling Transport Converter (STC) for MTP3 . . . . .	3-2
3.1.2 MTP3/MTP2/MTP1 . . . . .	3-3
3.1.3 MTP3/SAAL/ATM . . . . .	3-3
3.1.4 MTP3/M2PA/SCTP/IP . . . . .	3-3
4. Lower Layer Transport Interface Protocol for Bearer Connection Control . . . . .	4-1
5. Internetwork Call Flows and Capabilities Supported . . . . .	5-1
5.1 Call Control Capabilities . . . . .	5-1
5.2 Internetwork Call Control Messages and Flows . . . . .	5-1
5.3 Completion of Transmission Path . . . . .	5-8
6. Internetwork Call Control Protocol . . . . .	6-1
6.1 Address Complete Message . . . . .	6-3
6.2 Answer Message . . . . .	6-4
6.3 Application Transport Message . . . . .	6-4
6.4 CIC Reservation Message . . . . .	6-4
6.5 CIC Reservation Acknowledgment Message . . . . .	6-5
6.6 Continuity Message . . . . .	6-5
6.7 Exit Message . . . . .	6-6
6.8 Initial Address Message . . . . .	6-7
6.8.1 Call Origination . . . . .	6-7
6.8.1.1 Outgoing Bearer Set-Up Procedure - ATM Bearer Connection . . . . .	6-7
6.8.1.2 Outgoing Bearer Set-Up Procedure - IP Bearer Connection . . . . .	6-8
6.8.1.3 Parameters Sent in the IAM . . . . .	6-9

6.8.1.4	Incoming Bearer Set-Up Procedure - ATM Bearer Connection . . . . .	6-11
6.8.1.5	Incoming Bearer Set-Up Procedure - IP Bearer Connection . . . . .	6-11
6.8.2	Call Termination . . . . .	6-12
6.9	Release (REL) Message . . . . .	6-13
6.10	Release Complete (RLC) Message . . . . .	6-14
6.11	Resume (RES) Message . . . . .	6-14
6.12	Suspend (SUS) Message . . . . .	6-14
6.13	Call Progress (CPG) Message . . . . .	6-14
6.14	Confusion (CFN) Message . . . . .	6-15
7.	Internetwork Bearer Control Procedures . . . . .	7-1
7.1	General . . . . .	7-1
7.2	ATM Backbone Network . . . . .	7-1
7.2.1	ATM Bearer Control Procedures . . . . .	7-1
7.2.2	Interoperation Between Call Control and ATM Bearer Control Signaling . . . . .	7-2
7.3	IP Backbone Network . . . . .	7-2
7.3.1	IP Bearer Control Procedures . . . . .	7-2
7.3.2	Interoperation Between Call Control and IP Bearer Control Signaling . . . . .	7-2
8.	Maintenance Control Functions . . . . .	8-1
8.1	General . . . . .	8-1
8.2	Blocking Messages . . . . .	8-1
8.3	CIC Group Blocking Messages . . . . .	8-1
8.4	CIC Group Reset Messages . . . . .	8-2
8.5	CIC Group Unblocking Messages . . . . .	8-3
8.6	CIC Query Message . . . . .	8-3
8.7	Circuit Validation Test Message . . . . .	8-4
8.8	Continuity Check Request Message and Loop Back Acknowledgment Message . . . . .	8-4
8.9	Dual Seizure . . . . .	8-4
8.10	Reset CIC Message . . . . .	8-4
8.11	Test Calls . . . . .	8-5
8.12	Unblocking Message . . . . .	8-5
8.13	Unequipped CIC Message . . . . .	8-5
8.14	Automatic Repeat Attempt . . . . .	8-5
8.15	Receipt of Unreasonable and Unrecognized Signaling Information . . . . .	8-6
8.16	Signaling Network Congestion . . . . .	8-6
8.17	BICC Flow Control . . . . .	8-6
8.18	Automatic Congestion Control . . . . .	8-6
9.	Performance . . . . .	9-1
10.	Interface Provisioning, Operations, and Maintenance . . . . .	10-1
10.1	Configuration of Data . . . . .	10-1

11. BICC Evolution and Industry Status . . . . .	11-1
11.1 High-Level Description of ANSI and ITU-T BICC CS 1 . . . . .	11-1
11.2 High-Level Description of ANSI BICC CS 1+ (ITU-T BICC CS 2) . . . . .	11-2
11.3 High-Level Description of ITU-T BICC CS 3 . . . . .	11-5
Appendix A: BICC Message and Parameter Definitions . . . . .	A-1
A.1 Application Transport Message (APM) . . . . .	A-1
A.2 Application Transport Parameter (APP) . . . . .	A-1
A.3 Inter-Nodal Traffic Group Identifier . . . . .	A-2
A.4 Global Call Reference . . . . .	A-2
Appendix B: BICC Message Formats . . . . .	B-1
B.1 Message Format . . . . .	B-1
B.2 CIC Allocation . . . . .	B-1
B.3 Messages . . . . .	B-1
B.3.1 Message Exceptions . . . . .	B-1
B.3.2 Message Renaming . . . . .	B-2
B.4 Application Transport Message . . . . .	B-2
B.5 Initial Address Message . . . . .	B-3
Appendix C: BICC Parameter Formats . . . . .	C-1
C.1 Parameters . . . . .	C-1
C.1.1 Parameter Exceptions . . . . .	C-1
C.1.2 Parameter Renaming . . . . .	C-1
C.1.3 Parameter Coding . . . . .	C-1
C.2 Application Transport Parameter (APP) . . . . .	C-3
C.2.1 List of Identifiers . . . . .	C-9
C.2.2 Action Indicator . . . . .	C-10
C.2.3 Backbone Network Connection Identifier . . . . .	C-11
C.2.4 Interworking Function Address . . . . .	C-11
C.2.5 Codec List . . . . .	C-12
C.2.6 Single Codec . . . . .	C-12
C.2.7 BAT Compatibility Report . . . . .	C-12
C.2.8 Bearer Network Connection Characteristics . . . . .	C-13
C.2.9 Bearer Control Information . . . . .	C-14
C.2.10 Bearer Control Tunneling . . . . .	C-15
C.2.11 Bearer Control Unit Identifier . . . . .	C-15
C.2.12 Signal . . . . .	C-15
C.2.13 Bearer Redirection Capability . . . . .	C-15
C.2.14 Bearer Redirection Indicators . . . . .	C-15
C.2.15 Signal Type . . . . .	C-15
C.2.16 Duration . . . . .	C-16
C.3 Inter-Nodal Traffic Group Identifier . . . . .	C-16
C.4 Global Call Reference . . . . .	C-16
Appendix D: BICC Timers . . . . .	D-1
References . . . . .	References-1
Glossary . . . . .	Glossary-1



## List of Figures

Figure 2-1.	BICC Network Model . . . . .	2-1
Figure 2-2.	Network Configuration Scenarios - BICC at End Office Level . . . . .	2-6
Figure 2-3.	Network Configuration Scenarios - BICC at Tandem Level . . . . .	2-7
Figure 2-4.	Network Signaling Protocol Model for BICC . . . . .	2-8
Figure 3-1.	Network Signaling Protocol Stack for BICC Transport Over MTP3 . . . . .	3-2
Figure 4-1.	Network Signaling Protocol Stack for AINI . . . . .	4-1
Figure 5-1.	Backward ATM Bearer Connection Setup with COT and Gateway Serving Nodes (Type 3 Call) - BICC at Tandem Level . . . . .	5-4
Figure 5-2.	Backward ATM Bearer Connection Setup with COT and Gateway Serving Node (Type 4 Call) - BICC at Tandem Level . . . . .	5-5
Figure 5-3.	Backward IP Bearer Setup Using Bearer Control Tunneling with COT and Gateway Serving Node (Type 4 Call) - BICC at Tandem Level . . . . .	5-7
Figure B-1.	CIC Field . . . . .	B-1
Figure C-1.	Application Transport Parameter Field . . . . .	C-3
Figure C-2.	Content of the APM-User Information Field . . . . .	C-5
Figure C-3.	Content of the Originating Address (Destination Address) Field . . . . .	C-6
Figure C-4.	Encapsulated Application Information Field . . . . .	C-7
Figure C-5.	Length Indicator . . . . .	C-7
Figure C-6.	Compatibility Information . . . . .	C-8
Figure C-7.	Action Indicator . . . . .	C-10
Figure C-8.	Backbone Network Connection Identifier . . . . .	C-11
Figure C-9.	Interworking Function Address . . . . .	C-11
Figure C-10.	BAT Compatibility Report . . . . .	C-12
Figure C-11.	Diagnostics . . . . .	C-13
Figure C-12.	Bearer Network Connection Characteristics . . . . .	C-13
Figure C-13.	Bearer Control Information . . . . .	C-14
Figure C-14.	Bearer Control Tunneling . . . . .	C-15
Figure C-15.	Inter-nodal Traffic Group Identifier Parameter Field . . . . .	C-16
Figure C-16.	Global Call Reference Parameter Field . . . . .	C-16



## List of Tables

Table 11-1.	ITU-T and ANSI BICC Specifications - CS 1 . . . . .	11-2
Table 11-2.	ITU-T and ANSI BICC Specifications - CS 2/CS 1+ . . . . .	11-4
Table B-1.	Renamed Messages . . . . .	B-2
Table B-2.	Initial Address Message . . . . .	B-3
Table C-1.	Renamed Parameters . . . . .	C-1
Table C-2.	List of Identifiers . . . . .	C-9