

Contents

| | |
|---|-----------|
| Preface | Preface-1 |
| 1. Introduction | 1-1 |
| 1.1 Purpose and Scope | 1-1 |
| 1.2 Relationship to Other Next Generation Networks (NGN) Documents | 1-1 |
| 1.3 Target Audience | 1-2 |
| 1.4 Structure and Use of This Document | 1-2 |
| 1.5 Requirements Terminology | 1-2 |
| 1.6 Requirements Labeling Conventions | 1-3 |
| 1.6.1 Numbering of Requirement and Related Objects | 1-3 |
| 1.6.2 Requirement, Conditional Requirement, and Objective Object Identification | 1-4 |
| 2. VOP Architecture | 2-1 |
| 2.1 Overview | 2-1 |
| 2.2 Functional Elements | 2-1 |
| 2.3 Interfaces and Protocols | 2-4 |
| 2.4 Assumptions | 2-9 |
| 2.4.1 Connectivity | 2-9 |
| 2.4.2 Signaling | 2-9 |
| 2.4.3 Routing | 2-9 |
| 2.4.4 Core Network | 2-10 |
| 2.4.5 Call Types | 2-10 |
| 2.4.6 Resource Management | 2-12 |
| 2.4.7 Connection Control | 2-12 |
| 2.4.8 CN Bearer Connections | 2-12 |
| 2.4.9 Miscellaneous | 2-14 |
| 2.5 High-level Call Flows | 2-15 |
| 2.5.1 Successful Call Set Up | 2-15 |
| 2.5.1.1 TGW to TGW | 2-15 |
| 2.5.1.2 AGW to TGW | 2-17 |
| 2.5.1.3 TGW to AGW | 2-19 |
| 2.5.2 Successful Call Release Initiated by the Calling Party | 2-21 |
| 3. TGW Functional Architecture and High-Level Requirements | 3-1 |
| 3.1 TGW Functional Architecture | 3-1 |
| 3.2 Connection Control and Resource Management | 3-2 |
| 3.3 Routing Analysis | 3-3 |
| 3.4 Modularity, Scalability and Extensibility | 3-3 |
| 4. Interface Requirements | 4-1 |
| 4.1 Bearer Transport Interface | 4-1 |
| 4.1.1 IP Bearer Transport Interface | 4-1 |
| 4.1.2 ATM Bearer Transport Interface | 4-2 |
| 4.2 Gateway Connection Control Transport | 4-3 |
| 4.3 Gateway Control Interface | 4-3 |

| | | |
|-----------|--|------|
| 4.3.1 | Foundation Interface Compliance | 4-4 |
| 4.3.2 | Terminations, Contexts and Edge-to-Edge Connections . . . | 4-9 |
| 4.3.3 | Control Protocol Semantics and Syntax | 4-10 |
| 4.3.3.1 | Message Structure and Content | 4-10 |
| 4.3.3.2 | Commands and Command Contents | 4-12 |
| 4.3.3.3 | Syntax and Encoding | 4-13 |
| 4.3.4 | Properties, Events, Signals, Digit Map Specifications, and Packages | 4-13 |
| 4.3.5 | Call Statistics | 4-19 |
| 4.3.6 | Device Associations and Capabilities | 4-19 |
| 4.4 | Trunk Interface | 4-20 |
| 5. | Connection Control Procedures | 5-1 |
| 5.1 | Non-Call-Related Procedures | 5-1 |
| 5.1.1 | Startup/Registration | 5-1 |
| 5.2 | Normal Call-Related Procedures | 5-3 |
| 5.2.1 | Creating a Connection | 5-3 |
| 5.2.2 | Modifying a Connection | 5-5 |
| 5.2.3 | Deleting a Connection | 5-7 |
| 5.3 | Core Network Connection Procedures | 5-8 |
| 5.3.1 | Connection Establishment Procedures | 5-9 |
| 5.3.1.1 | SETUP | 5-9 |
| 5.3.1.2 | CALL PROCEEDING | 5-10 |
| 5.3.1.3 | CONNECT | 5-11 |
| 5.3.1.4 | CONNECT ACKNOWLEDGE | 5-11 |
| 5.3.2 | Connection Establishment States | 5-12 |
| 5.3.2.1 | Connection States at the User Side of the Interface | 5-12 |
| 5.3.2.1.1 | Null (U0) | 5-12 |
| 5.3.2.1.2 | Call Initiated (U1) | 5-13 |
| 5.3.2.1.3 | Outgoing Call Proceeding (U3) | 5-13 |
| 5.3.2.1.4 | Call Present (U6) | 5-13 |
| 5.3.2.1.5 | Connect Request (U8) | 5-13 |
| 5.3.2.1.6 | Incoming Call Proceeding (U9) | 5-13 |
| 5.3.2.1.7 | Active (U10) | 5-13 |
| 5.3.3 | Connection Tear Down Procedures | 5-14 |
| 5.3.3.1 | RELEASE | 5-14 |
| 5.3.3.2 | RELEASE COMPLETE | 5-14 |
| 5.3.4 | Connection Tear Down States | 5-15 |
| 5.3.4.1 | Release Request (U11) | 5-15 |
| 5.3.4.2 | Release Indication (U12) | 5-15 |
| 6. | Media Processing | 6-1 |
| 6.1 | Media Detection | 6-1 |
| 6.1.1 | Fax Calls | 6-1 |
| 6.1.2 | Data Modem Calls | 6-2 |
| 6.1.3 | Summary | 6-2 |
| 6.2 | Continuity Tone Detection, Generation, and Loop-back | 6-2 |
| 6.3 | Echo Cancellation | 6-3 |

| | | |
|-----------|--|--------------|
| 6.4 | Comfort Noise Insertion | 6-4 |
| 6.5 | Encoding and Transcoding Functions | 6-5 |
| 6.6 | Silence Detection/Suppression | 6-6 |
| 6.7 | Packetization Functions | 6-6 |
| 6.8 | Receive Path Delay | 6-6 |
| 7. | Management and Operations Requirements | 7-1 |
| 7.1 | Overview of NGN VOP Network Management Strategy | 7-1 |
| 7.1.1 | TMN Overview | 7-2 |
| 7.1.2 | Functional Management Strategy Overview | 7-3 |
| 7.1.3 | Description of Management Interfaces | 7-5 |
| 7.2 | Configuration Management Requirements | 7-6 |
| 7.2.1 | General Configuration Management | 7-6 |
| 7.2.2 | Capacity Installation | 7-6 |
| 7.2.3 | Service Provisioning | 7-8 |
| 7.2.4 | Status and Control | 7-10 |
| 7.3 | Fault Management Requirements | 7-12 |
| 7.3.1 | Alarm Surveillance | 7-13 |
| 7.3.2 | Fault Localization | 7-15 |
| 7.3.3 | Testing | 7-15 |
| 7.4 | Performance Management Requirements | 7-16 |
| 7.4.1 | General Monitoring Requirements | 7-16 |
| 7.4.1.1 | Counters and Monitoring Intervals | 7-16 |
| 7.4.1.2 | Generation of Threshold Crossing Alerts (TCAs) | 7-18 |
| 7.4.2 | TGW Performance Monitoring Requirements | 7-18 |
| 7.4.2.1 | Physical Layer Protocol Monitoring | 7-21 |
| 7.4.2.2 | ATM Layer Protocol and Traffic Monitoring | 7-21 |
| 7.4.2.2.1 | ATM Adaptation Layer | 7-23 |
| 7.4.2.2.2 | Signaling (for Bearer Connection Control Interface) | 7-24 |
| 7.4.2.3 | IP Layer Protocol and Traffic Monitoring | 7-24 |
| 7.4.2.4 | UDP Layer Protocol Monitoring | 7-26 |
| 7.4.2.5 | RTP Layer Protocol Monitoring | 7-26 |
| 7.4.2.6 | Megaco Protocol and Traffic Monitoring | 7-27 |
| 7.4.2.6.1 | TGW Modules or Components | 7-30 |
| | Requirement-Object Index | ROI-1 |
| | Acronyms | Acronyms-1 |
| | References | References-1 |

List of Figures

| | | |
|-------------|--|------|
| Figure 2-1. | High-Level VOP Network Architecture | 2-1 |
| Figure 2-2. | Overview of VOP Physical Interfaces | 2-4 |
| Figure 2-3. | Overview of Logical Interfaces and Protocols for the VOP Architecture | 2-5 |
| Figure 2-4. | Bearer and Signaling Transport Stack | 2-11 |
| Figure 2-5. | A Successful Call Set Up between Two TGWs using Two CCAs | 2-15 |
| Figure 2-6. | A Successful Call Set Up from an AGW to a TGW | 2-17 |
| Figure 2-7. | A Successful Call Set Up from a TGW to an AGW | 2-19 |
| Figure 2-8. | A Successful Call Release Initiated by the Calling Party | 2-21 |
| Figure 4-1. | Bearer and Signaling Transport Stacks | 4-1 |
| Figure 5-1. | Set Up and Call Proceeding messages | 5-11 |
| Figure 5-2. | Connect and Connect Ack Messages | 5-12 |
| Figure 5-3. | Release and Release Complete Messages | 5-14 |
| Figure 7-1. | TMN Logical Layers | 7-2 |
| Figure 7-2. | Functional Management Architecture Example | 7-4 |
| Figure 7-3. | Protocol Stack for Gateway Control Interface | 7-19 |
| Figure 7-4. | Protocol Stack for ATM Bearer Transport Interface | 7-20 |
| Figure 7-5. | Protocol Stack for IP Bearer Transport Interface | 7-20 |

List of Tables

| | | |
|------------|---|------|
| Table 2-1. | VOP Interface and Protocol Summary | 2-5 |
| Table 4-1. | Support Status for Elements of H.248' | 4-5 |
| Table 4-2. | Supplements to H.248' | 4-8 |
| Table 5-1. | SETUP message | 5-9 |
| Table 5-2. | ATM Adaptation Layer Information Element | 5-9 |
| Table 5-3. | ATM Traffic Descriptor Information Element | 5-10 |
| Table 5-4. | Broadband Bearer Capability Information Element | 5-10 |
| Table 5-5. | Generic Transport Identifier | 5-10 |
| Table 6-1. | Detection of Voice, Fax, and Data Modem Calls | 6-2 |