

Contents

1.	Introduction	1-1
1.1	Purpose and Scope	1-1
1.2	Background	1-1
1.3	Target Audience	1-3
1.4	Relationship to other Next Generation Network (NGN) Voice over Packet (VoP) GRs	1-4
1.5	Structure and Use of This Document	1-4
1.6	Requirements Terminology	1-5
1.7	Requirement Labeling Conventions	1-6
1.7.1	Numbering of Requirement and Related Objects	1-6
1.7.2	Requirement, Conditional Requirement, and Objective Object Identification	1-6
2.	VoP Performance Models	2-1
2.1	Measurement Points	2-1
2.1.1	Measurement Point (MP)	2-1
2.2	Performance Significant Reference Events	2-1
2.2.1	Exit Event	2-2
2.2.2	Entry Event	2-2
2.3	Signaling Reference Models	2-2
2.3.1	Signaling Reference Configurations	2-2
2.3.2	Performance Significant Reference Events	2-6
2.3.2.1	Scenario 1 - Example Call Flow	2-6
2.3.2.2	Scenario 2 - Example Call Flow	2-8
2.3.2.3	Scenario 3 - Example Call Flow	2-10
2.3.2.4	Scenario 4 - Example Call Flow	2-12
2.3.3	Hypothetical Reference Connection (HRX)	2-14
2.4	Transport Reference Models	2-15
2.4.1	Transport Reference Configurations	2-15
3.	Signaling Performance	3-1
3.1	Delay Concepts	3-1
3.1.1	Delay at a Single Boundary	3-1
3.1.2	Delay Between Two Boundaries	3-2
3.2	Classification of Call Attempts and Call Releases	3-3
3.2.1	Successful Call Set-up Message Flow	3-3
3.2.2	Failure Outside the Portion Under Test and User Blocking	3-4
3.2.3	Call Set Up Failure	3-4
3.2.4	Call Set Up Error	3-4
3.3	Access Function Performance Parameter Definitions	3-4
3.3.1	Call Set Up Delay	3-5
3.3.2	Call Answer Signal Delay (CASD)	3-6
3.3.3	Call Set Up Failure Probability	3-7
3.3.4	Call Set Up Error Probability	3-9
3.4	Access Function Objectives	3-10

3.4.1	Nature of Performance Objectives	3-10
3.4.2	Considerations for Specification of Objectives	3-10
3.4.3	Call Set-Up Delay Objectives	3-11
3.4.4	Call Answer Signal Delay Objectives	3-12
3.4.5	Call Set-Up Failure Probability Objectives	3-12
3.4.6	Call Set Up Error Probability Objectives	3-13
3.5	Access Function Allocation Rules	3-13
3.5.1	Distance Based Allocation of Delay	3-14
3.5.2	Call Set Up Delay Allocation	3-15
3.5.3	Call Answer Signal Delay Allocation	3-15
3.5.4	Call Set Up Failure Probability Allocation	3-15
3.5.5	Call Set Up Error Probability Allocation	3-16
3.6	Disengagement Function Performance Parameter Definitions	3-16
3.6.1	Successful Call Release	3-16
3.6.2	Call Release Delay	3-18
3.6.3	Call Release Failure Events	3-19
3.6.4	Call Release Failure Probability	3-22
3.6.5	Premature Disconnect Event	3-22
3.6.6	Premature Disconnect Probability	3-22
3.7	Disengagement Function Objectives	3-22
3.7.1	Call Release Delay Objectives	3-22
3.7.2	Call Release Failure Probability Objective	3-23
3.7.3	Premature Disconnect Probability Objectives	3-23
3.8	Disengagement Function Allocation Rules	3-23
3.8.1	Call Release Delay Allocation	3-23
3.8.2	Call Release Failure Probability Allocation	3-24
3.8.3	Premature Disconnect Probability Allocation	3-24
4.	Transport Performance Requirements	4-1
4.1	Performance Parameters	4-1
4.2	Reference Events for Transport Parameters	4-2
4.2.1	IP Core Network Reference Events	4-2
4.2.2	ATM Core Network Reference Events	4-2
4.3	Objectives and Allocation Rules	4-3
4.3.1	End-to-End Objectives	4-3
4.3.1.1	IP End-to-End Objectives	4-3
4.3.1.2	ATM End-to-End Objectives	4-4
4.3.2	Route Length Calculation	4-4
4.3.3	IP Packet Transfer Performance Parameter Allocations	4-5
4.3.3.1	Allocation of the IPTD Objective	4-5
4.3.3.2	Allocation of the IPLR Objective	4-5
4.3.3.3	Allocation of the IPDV Objective	4-5
4.3.4	ATM Cell Transfer Performance Parameter Allocations	4-6
4.3.4.1	Allocation of the CTD Objective	4-6
4.3.4.2	Allocation of the CLR Objective	4-6
4.3.4.3	Allocation of the ATM CDV Objective	4-6
4.4	QoS Mappings of ATM to IP (for IP over ATM)	4-7

4.4.1	Mapping of ATM CLR to IP IPLR	4-7
4.4.2	Mapping of ATM CTD to IP IPTD	4-7
4.4.3	Mapping of ATM CDV to IP IPDV	4-8
5.	Network Element Performance	5-1
5.1	Information Transfer Performance of Network Elements	5-1
5.2	Call Connection Agent	5-2
5.3	Access Gateway	5-2
5.4	Trunk Gateway	5-2
5.5	Signaling Gateway	5-3
5.6	Core Router	5-3
5.7	Signaling Performance of Network Elements	5-3
6.	Network Service Availability	6-1
6.1	Availability Parameters	6-1
6.1.1	Definition of Service Availability	6-1
6.1.2	Definition of Mean Time Between Service Outage	6-1
6.1.3	Related Parameters	6-1
6.2	Service Availability Definition	6-2
6.2.1	VoP Availability Function	6-2
	Appendix A: Definition of IP and ATM Transport Performance Parameters	A-1
A.1	IP Transport Performance Parameters from I.380	A-1
A.2	ATM Transport Performance Parameters from I.356	A-1
	Appendix B: Specialization of Performance Parameters to CCA	B-1
	References	References-1
	Acronyms and Abbreviations	Acronyms-1

List of Figures

Figure 1-1.	High Level VoP Network Architecture	1-2
Figure 2-1.	Scenario 1 Reference Configuration - PSTN to PSTN Call . . .	2-3
Figure 2-2.	Scenario 2 Reference Configuration - PSTN to VOP Subscriber (with POTS line) Call Scenario	2-4
Figure 2-3.	Scenario 3 Reference Configuration - VOP Subscriber to VOP Subscriber (both with POTS lines)	2-4
Figure 2-4.	Scenario 4 Reference Configuration - VOP Subscriber (with POTS line) to PSTN Subscriber	2-5
Figure 2-5.	Scenario 1 Call Flow	2-7
Figure 2-6.	Scenario 1 - Call Flow (Continued)	2-8
Figure 2-7.	Scenario 2 - Example Call Flow	2-8
Figure 2-8.	Scenario 2 - Example Call Flow (Continued)	2-9
Figure 2-9.	Scenario 3 - Example Call Flow	2-11
Figure 2-10.	Scenario 3 - Example Call Flow (Continued)	2-12
Figure 2-11.	Scenario 4 - Example Call Flow	2-13
Figure 2-12.	Scenario 4 - Example Call Flow (Continued)	2-14
Figure 2-13.	Scenario 1 Reference Configuration - PSTN to PSTN Call . .	2-16
Figure 2-14.	Scenario 2 Reference Configuration - PSTN to VOP Subscriber (with POTS line) Call Scenario	2-16
Figure 2-15.	Scenario 3 Reference Configuration - VOP Subscriber to VOP Subscriber (both with POTS lines)	2-17
Figure 3-1.	Delay at a Single Boundary	3-2
Figure 3-2.	Delay Between two Boundaries	3-2
Figure 3-3.	Successful Call Set-up	3-3

List of Tables

Table 3-1.	Consistent Boundary Names	3-5
Table 3-2.	Call Setup Delay: Starting and Ending Reference Events for Delay at a Single Boundary - Scenario 1	3-5
Table 3-3.	Call Setup Delay: Starting and Ending Reference Events for Delay at a Single Boundary - Scenario 2	3-5
Table 3-4.	Call Setup Delay: Starting and Ending Reference Events for Delay at a Single Boundary - Scenario 3	3-6
Table 3-5.	Call Setup Delay: Starting and Ending Reference Events For Delay at a Single Boundary - Scenario 4	3-6
Table 3-6.	Call Answer Signal Delay: Starting and Ending Reference Events for Delay - Scenario 1	3-7
Table 3-7.	Call Answer Signal Delay: Starting and Ending Reference Events for Delay - Scenario 2	3-7
Table 3-8.	Call Answer Signal Delay: Starting and Ending Reference Events for Delay - Scenario 3	3-7
Table 3-9.	Call Answer Signal Delay: Starting and Ending Reference Events For Delay - Scenario 4	3-7
Table 3-10.	REs at Initial (Bi) and Final (Bj) Boundaries Occurring During Successful Call Setup - Scenario 1	3-8
Table 3-11.	REs at Initial (Bi) and Final (Bj) Boundaries Occurring During Successful Call Setup - Scenario 2	3-8
Table 3-12.	REs at Initial (Bi) and Final (Bj) Boundaries Occurring During Successful Call Setup - Scenario 3	3-9
Table 3-13.	REs at Initial (Bi) and Final (Bj) Boundaries Occurring During Successful Call Setup - Scenario 4	3-9
Table 3-14.	Call Set-Up Delay Objectives	3-11
Table 3-15.	Call Answer Signal Delay Objectives	3-12
Table 3-16.	Call Set Up Failure Probability Objectives	3-13
Table 3-17.	Call Set Up Error Probability Objectives	3-13
Table 3-18.	Call Set-Up Delay Allocation	3-15
Table 3-19.	Call Answer Signal Delay Allocation	3-15
Table 3-20.	Call Set-Up Failure Probability Allocation	3-15
Table 3-22.	Events Defining Successful Call Release - Scenario 1	3-16
Table 3-21.	Call Set-Up Failure Probability Allocation	3-16
Table 3-23.	Events Defining Successful Call Release - Scenario 2	3-17
Table 3-24.	Events Defining Successful Call Release - Scenario 3	3-17
Table 3-25.	Events Defining Successful Call Release - Scenario 4	3-17
Table 3-26.	Call Release Delay Defining Reference Events for Scenario 1	3-18
Table 3-27.	Call Release Delay Defining Reference Events for Scenario 2	3-18
Table 3-28.	Call Release Delay Defining Reference Events for Scenario 3	3-18
Table 3-29.	Call Release Delay Defining Reference Events for Scenario 4	3-19
Table 3-31.	Call Release Failure Reference Events for Scenario 2	3-20
Table 3-30.	Call Release Failure Reference Events for Scenario 1	3-20
Table 3-32.	Call Release Failure Reference Events for Scenario 3	3-21

Table 3-33.	Call Release Failure Reference Events for Scenario 4	3-21
Table 3-34.	Call Release Delay Objectives	3-22
Table 3-35.	Call Release Delay Allocation	3-23
Table 3-36.	Premature Disconnect Probability Allocation	3-24
Table 4-1.	IP Reference Events Occurring During Successful IP Packet Transfer	4-2
Table 4-2.	ATM Reference Events Occurring During Successful ATM Cell Transfer	4-2
Table 4-3.	End-to-End IP Objectives	4-3
Table 4-4.	End-to-End ATM Objectives	4-4
Table 4-5.	IPLR Values in a Hybrid IP/ATM Network	4-7
Table 5-3.	Trunk Gateway Performance Allocations	5-2
Table 5-1.	CCA Performance Allocations	5-2
Table 5-2.	AG call Processing Performance Requirements	5-2
Table 5-4.	Signaling Gateway Performance Allocations	5-3
Table 6-1.	VoP Availability Function	6-2
Table B-1.	CCA Contribution to CSD: Associated REs for Scenario 1 . . .	B-1
Table B-2.	CCA Contribution to CASD: Associated REs for Scenario 1 . .	B-1
Table B-3.	CCA Contribution to CSD: Associated REs for Scenario 2 . . .	B-1
Table B-4.	CCA Contribution to CASD: Associated REs for Scenario 2 . .	B-2
Table B-5.	CCA Contribution to CSD: Associated REs for Scenario 3 . . .	B-2
Table B-6.	CCA Contribution to CSD: Associated REs for Scenario 4 . . .	B-2