

Table of Contents

[Telcordia GR-3125 - Documentation Information](#)

Generic Requirements Notice of Disclaimer	iii
List of Figures	ix
List of Tables	x
Preface	xi

1 Introduction

1.1 Purpose and Scope	1-1
1.2 Target Audience	1-1
1.3 Structure and Use of This Document	1-1
1.4 Outdoor FDH Information, Requirements, and Tests	1-2
1.5 Requirements Terminology	1-5
1.6 Requirement Labeling Conventions	1-6
1.6.1 Numbering of Requirement and Related Objects	1-6
1.6.2 Requirement, Conditional Requirement, and Objective Identification	1-7

2 General Information

2.1 Product Description	2-1
2.2 Deployment Environments	2-3
2.3 Installation and Operating Environment	2-4
2.3.1 Connector Performance in Harsh Environments	2-5
2.4 Related Telcordia Documents	2-5
2.5 FDH Component Devices	2-6

3 General Requirements

3.1 Documentation	3-1
3.1.1 Practices	3-1
3.2 Markings, Packaging, and Shipping	3-1
3.2.1 Identification	3-1
3.2.1.1 General	3-1
3.2.1.2 Listing	3-2
3.2.2 Shipping Container and Packaging Arrangement	3-2
3.2.3 Package Label	3-2
3.3 Labels	3-3
3.4 Consumable Materials	3-3
3.5 Product Changes	3-3
3.6 Safety and Reliability Considerations	3-3
3.7 Installation Size and Weight	3-4
3.8 Maintenance	3-4
3.9 Components	3-4
3.10 Tools	3-5
3.11 Quality	3-5
3.12 Security	3-5

4 Functional Design Criteria

- 4.1 Materials 4-1
 - 4.1.1 Metallic Materials 4-1
 - 4.1.2 Polymeric and Other Non-Metallic Materials 4-1
- 4.2 Cable Management Compartments 4-2
 - 4.2.1 Access Compartments 4-2
 - 4.2.2 Cable Entrance Capacity 4-2
 - 4.2.3 Cable Compatibility 4-2
 - 4.2.4 Cable Termination Hardware 4-3
 - 4.2.5 Bonding and Grounding Hardware 4-3
- 4.3 Service Provider Splice Compartment 4-4
 - 4.3.1 Splice Storage Capacity 4-4
 - 4.3.2 Fiber and Splice Protection 4-4
- 4.4 Connector Bulkhead 4-5
 - 4.4.1 Bulkhead Capacity 4-5
 - 4.4.2 Connector Sleeves 4-6
 - 4.4.3 Connector Requirements 4-6
 - 4.4.4 Pigtail Requirements 4-6
- 4.5 Fundamental FDH Requirements 4-6
 - 4.5.1 Deployment Configurations 4-6
 - 4.5.2 Optical Power Monitoring 4-7
 - 4.5.3 FDH Mounting Hardware 4-7
 - 4.5.4 Door Restainers 4-8
 - 4.5.5 Drainage for Condensate 4-8
 - 4.5.6 Insect Resistance 4-8
 - 4.5.7 Fire Safety 4-9
- 4.6 Finish 4-9
 - 4.6.1 Color 4-9
 - 4.6.2 Appearance 4-9
 - 4.6.3 Paint Adhesion 4-10
 - 4.6.4 Paint Adhesion After Exposure 4-10
 - 4.6.5 Flexibility 4-10
 - 4.6.6 Ultraviolet Resistance 4-10
- 4.7 Screens and Filters 4-11

5 Application-Specific Requirements

- 5.1 General 5-1
 - 5.1.1 Testing 5-1
- 5.2 Electrical Criteria 5-2
 - 5.2.1 Bond Clamp Retention 5-2
 - 5.2.2 AC Fault Test 5-2
- 5.3 Mechanical Criteria 5-2
 - 5.3.1 Cable Clamping 5-5
 - 5.3.2 Sheath Retention 5-6
 - 5.3.2.1 Sheath Retention Test Configuration 5-7
 - 5.3.3 Cable Flexing 5-7
 - 5.3.3.1 Cable Flexing Test Configuration 5-8
 - 5.3.4 Cable Torsion 5-9
 - 5.3.4.1 Cable Torsion Test Configuration 5-10



5.3.5	Vertical Drop	5-10
5.3.6	Impact Resistance	5-11
5.3.7	Central Member (CM) Protrusion	5-11
5.4	Environmental Criteria	5-12
5.4.1	Accelerated Thermal Aging	5-13
5.4.2	Assembly	5-13
5.4.3	Temperature and Humidity	5-13
5.4.4	Weather Tightness	5-14
5.4.5	Water Resistance	5-15
5.4.5.1	Wind-Driven Rain	5-16
5.4.5.2	Rain Intrusion	5-17
5.4.5.3	Flooded Conditions	5-18
5.4.6	Wind Resistance: Door Restrainers (Vertically Hinged Doors)	5-18
5.4.7	Wind Resistance: Horizontally Hinged Doors	5-21
5.4.8	Wind Resistance	5-22
5.4.9	Corrosion Resistance	5-25
5.4.10	Chemical Resistance	5-25
5.4.11	Ultraviolet Resistance	5-27
5.4.12	Fungus Resistance	5-28
5.4.13	Firearms Resistance	5-28
5.4.14	Steam Resistance	5-29
5.4.15	Cable Core Blocking Ability	5-29
5.4.16	Fire Resistance	5-30
5.4.17	Rodent Resistance	5-31
5.4.18	Pole-Mounted, Aerial FDH Criteria	5-31
5.4.19	Lifting Details	5-32
5.5	Earthquake, Environmental Vibration, and Transportation Vibration	5-32
5.5.1	Conformance Criteria	5-33
5.5.1.1	Earthquake - Physical Performance Criteria	5-34
5.5.1.2	Earthquake - Functional Performance Criteria	5-35
5.5.1.3	Earthquake - FDH and Anchor Criteria	5-35
5.5.1.4	Environmental Vibration Criteria	5-36
5.5.1.5	Earthquake Test Method Details	5-37
5.5.1.5.1	Environmental Vibration Test Procedure Details	5-40
5.5.1.6	Transportation Vibration—Packaged Equipment Test Plan Details	5-40
5.5.1.7	Static Test Procedure	5-40
5.6	Airborne Contaminants	5-42
5.6.1	Conformance Criteria - Airborne Contaminants	5-43
5.6.2	Optional Airborne Contaminants Test	5-44
5.6.2.1	Gaseous Contaminants Test Method	5-44
5.6.2.2	Two Cleaning Procedures for Copper Coupons	5-47
5.6.2.3	Test Procedure - Mixed Flowing Gas	5-50
5.6.2.4	Measuring Parameters	5-50
5.6.2.4.1	Safety Procedures for Testing Gaseous Contaminants	5-51
5.7	Craft Interaction	5-52
5.7.1	Front Plane Connector Disconnect and Reconnect Test	5-52
5.7.1.1	Conformance Criteria	5-52
5.7.1.2	Measurements	5-52
5.7.1.3	Disconnect and Reconnect Test Procedure	5-53
5.7.1.4	Product Testers	5-53

5.7.2 Rear-Plane Fiber Optic Terminal (FOT) Jumper Disconnect, Adapter Replacement and Reconnect Test	5-54
5.7.2.1 Conformance Criteria	5-55
5.7.2.2 Test Method	5-55
5.7.2.3 Product Testers	5-56

6 Components

Appendix A: Observational Standard

Appendix B: Wind-Driven Rain Test Set-Up Calibration Procedure

Appendix C: References

Appendix D: Glossary

Requirement-Object Index

List of Figures

Figure 2-1	Schematic of the Fiber Distribution Hub Role	2-2
Figure 2-2	Basic Fiber Distribution Hub	2-2
Figure 5-1	Schematic of Feeder-Cable, Monitored Network for Cable Mechanical Tests	5-4
Figure 5-2	Schematic of Distribution-Cable, Monitored Network for Cable Mechanical Tests	5-4
Figure 5-3	Sheath Retention Test Configuration	5-7
Figure 5-4	Cable Flexing Test Configuration	5-8
Figure 5-5	Cable Torsion Test Configuration	5-10
Figure 5-6	Central Member Protrusion Test Configuration	5-12
Figure 5-7	Temperature Humidity Profile	5-14
Figure 5-8	Dynamic Wind Test	5-20
Figure 5-9	Wind Resistance Test Configuration (Part A)	5-23
Figure 5-10	Wind Resistance Test Configuration (Part B)	5-24
Figure 5-11	Chemical Resistance Test Configuration	5-27
Figure 5-12	Test Bar Samples	5-28
Figure 5-13	Cable Core Blocking Test Configuration	5-30
Figure 5-14	Earthquake Zone Map	5-33
Figure 5-15	Earthquake Synthesized Waveform - VERTEQII	5-37
Figure 5-16	Required Response Spectra	5-38
Figure 5-17	Commercial Transportation Vibration Environment	5-41
Figure 5-18	Anthropometric Hand Dimensions to Support Table 5-7	5-54
Figure 5-19	Anthropometric Hand Dimensions to Support Table 5-8	5-57
Figure A-1	Observational Standard	A-1
Figure B-1	Wind Speed and Rainfall Verification Fixture	B-2
Figure B-2	Reduction of Water Collection Aperture with an Inclined Rain Gauge During Wind-Drive Rain Testing	B-3

List of Tables

Table 1-1	GR-3125 Outdoor FDH Summary of Information	1-2
Table 2-1	Deployment Environments for Fiber Distribution Hubs	2-3
Table 5-1	Pass/Fail Criteria for Cable/FDH Mechanical Tests	5-5
Table 5-2	Cable Pullout Criteria Levels	5-6
Table 5-3	Impact Criteria Levels	5-11
Table 5-4	Corrosion Resistance Criteria Levels	5-25
Table 5-5	Test Result Document References	5-28
Table 5-6	Outdoor Contaminant Levels	5-43
Table 5-7	Typical Coupon Weight Gains During MFG Exposures	5-49
Table 5-8	Target Air Composition and Duration of MFG Testing for Equipment Designated for Indoor or Outdoor Use	5-50
Table 5-9	Recommended Hand Size of Product Tester	5-54
Table 5-10	Recommended Hand Size of Product Tester	5-57