

Table of Contents

- Generic Requirements Notice of Disclaimer** iii
- Table of Contents** v
- List of Figures** ix
- List of Tables** x
- Preface** xi

1 General

- 1.1 Product Description 1-1
 - 1.1.1 Purpose and Scope 1-2
- 1.2 Reasons for GR-3164-CORE, Issue 1 1-2
- 1.3 Safety Considerations 1-2
- 1.4 Reference Documents 1-3
- 1.5 Units and Tolerances 1-3
- 1.6 Product Reliability and Quality Management Systems 1-4
 - 1.6.1 Product Changes 1-4
- 1.7 Requirements Terminology 1-4
- 1.8 Requirement Labeling Conventions 1-5
 - 1.8.1 Numbering of Requirement and Related Objects 1-5
 - 1.8.2 Requirement, Conditional Requirement, and Objective Identification . . . 1-5

2 Conductors

- 2.1 General 2-1
- 2.2 Conductor Sizes 2-1
- 2.3 Factory Joints or Splices 2-1
- 2.4 Conductor Elongation 2-1

3 Conductor Insulation

- 3.1 Insulation Material 3-1
- 3.2 Insulation Construction 3-1
 - 3.2.1 Dual Insulation 3-1
- 3.3 Splices 3-2
- 3.4 Insulation Tests 3-2
 - 3.4.1 Test Sample Requirements 3-2
 - 3.4.2 Insulation Imperfections 3-2
 - 3.4.3 Insulation Adhesion 3-2
 - 3.4.4 Tensile Strength and Elongation 3-3
 - 3.4.5 Resistance to Aging 3-3
 - 3.4.6 Compression Resistance 3-4
 - 3.4.7 Cold Bend 3-4
 - 3.4.8 Shrinkback 3-4
- 3.5 Twist Lengths and Color Coding 3-4
- 3.6 Core Assembly 3-6

4 Binders, Core Wraps, Screens, and Ripcords

4.1 Binders 4-1
4.2 Core Wraps 4-1
4.3 Foil Screens 4-1
4.4 Jacket Ripcords 4-2

5 Jacket

5.1 Test Sample Requirements 5-1
5.2 General Design and Materials 5-1
5.3 Jacket Thickness 5-1
5.4 Tensile Strength and Elongation 5-2
5.5 Resistance to Aging 5-2
5.6 Jacket Color 5-3
5.7 Repairs 5-3

6 Electrical Requirements

6.1 Introduction 6-1
6.2 DC Conductor Resistance 6-1
6.3 Conductor Resistance Unbalance 6-2
6.4 Capacitance Unbalance — Pair-to-Ground 6-2
6.5 Insertion Loss (Attenuation) 6-2
6.6 Insulation Resistance 6-3
6.7 Characteristic Impedance and Structural Return Loss 6-3
6.8 Return Loss 6-4
6.9 Crosstalk 6-4
6.9.1 Near-End Crosstalk (NEXT) 6-4
6.9.2 Power-Sum Near-End Crosstalk (PS NEXT) 6-5
6.9.3 Attenuation to Crosstalk Ratio, Far-End (ACRF) for Category 5e and 6 Products 6-6
6.9.4 Power-Sum Attenuation-to-Crosstalk Ratio, Far-End (PS ACRF) for Category 5e and 6 Products 6-7
6.10 Propagation Delay (PD) 6-7
6.10.1 Propagation Delay Skew (PD Skew) 6-8
6.11 Transverse Conversion Loss (TCL) and Transverse Conversion Transfer Loss (TCTL) 6-9
6.11.1 Transverse Conversion Loss (TCL) 6-9
6.11.2 Equal-Level Transverse Conversion Transfer Loss (ELTCTL) 6-9
6.12 Surface Transfer Impedance (Screened Wire Products Only) 6-10
6.13 DC Voltage Test 6-10
6.13.1 Conductor-to-Conductor 6-10
6.13.2 Conductor-to-Screen 6-10
6.14 Jacket Leakage Test 6-10
6.15 Continuity of Metallic Wire Elements 6-11

7 Completed Wire Tests — Mechanical and Environmental

7.1 Cold Wrap Test 7-1
7.2 Impact Test 7-1
7.2.1 Standard Application 7-1
7.2.2 Severe Cold Environment Application 7-2

7.3 Jacket Removal 7-2

7.4 Fire Resistance and Listing 7-3

7.5 Ultraviolet (UV) Resistance 7-4

7.6 Temperature Rating 7-4

8 Packaging and Marking Requirements

8.1 Wire Jacket Marking 8-1

 8.1.1 Length Marking 8-1

 8.1.2 Marking Height and Legibility 8-1

 8.1.3 Marking Durability 8-2

8.2 Packaging 8-2

 8.2.1 Marking 8-2

9 Product Classification and Premises Wire Types

9.1 Introduction 9-1

9.2 Inside Wire 9-1

 9.2.1 Mechanical Design Requirements 9-1

 9.2.1.1 Conductors 9-1

 9.2.1.2 Conductor Insulation 9-1

 9.2.1.3 Twist Lengths and Color Coding 9-1

 9.2.1.4 Core Assembly 9-1

 9.2.1.5 Binders 9-2

 9.2.1.6 Core Wrap 9-2

 9.2.1.7 Foil Screens (Optional) 9-2

 9.2.1.8 Ripcord (Optional) 9-2

 9.2.2 Jacket 9-2

 9.2.3 Electrical Requirements 9-2

 9.2.4 Completed Wire Mechanical and Environmental Tests 9-3

 9.2.5 Packaging and Marking Requirements 9-4

9.3 Indoor/Outdoor Wire 9-4

 9.3.1 Mechanical Design Requirements 9-4

 9.3.1.1 Conductors 9-4

 9.3.1.2 Conductor Insulation 9-4

 9.3.1.3 Twist Lengths and Color Coding 9-4

 9.3.1.4 Core Assembly 9-4

 9.3.1.5 Binders 9-5

 9.3.1.6 Core Wrap 9-5

 9.3.1.7 Ripcord (Optional) 9-5

 9.3.2 Jacket 9-5

 9.3.3 Electrical Requirements 9-5

 9.3.4 Completed Wire Mechanical and Environmental Tests 9-6

 9.3.5 Packaging and Marking Requirements 9-7

Appendix A: Test Procedures for Wicking and Hygroscopicity

A.1 Test Procedure for Wicking A-1

A.2 Test Procedure for Hygroscopicity A-1

Appendix B: Durability of Printing and Marking Test

B.1 Specimen Preparation B-1

B.2 Apparatus B-1
 B.3 Exposure B-1
 B.4 Procedure B-1

Appendix C: References

C.1 References C-1
 C.2 Telcordia Reference Notes C-4
 C.2.1 Contact Telcordia C-4
 C.2.2 Order Documents Online From the Telcordia Information SuperStore . C-4
 C.2.3 Telcordia Web Sites for Generic Requirements Information C-5
 C.2.4 Telcordia Licensing Agreements C-5

Appendix D: Acronyms

Requirement-Object Index

List of Figures

Figure 7-1	Impact Anvil for Cold Impact Test	7-2
Figure A-1	Wicking Test Configuration	A-2

List of Tables

Table 2-1	Conductor Diameter	2-1
Table 3-1	Standard Insulation Color Coding	3-5
Table 3-2	Binder Color Codes	3-6
Table 6-1	Insertion Loss	6-2
Table 6-2	Structural Return Loss (SRL)	6-3
Table 6-3	Return Loss	6-4
Table 6-4	Near-End Crosstalk (NEXT) Loss	6-5
Table 6-5	Power-Sum Near-End Crosstalk (PS NEXT) Loss	6-6
Table 6-6	Attenuation-to-Crosstalk Ratio, Far-End (ACRF)	6-7
Table 6-7	Power-Sum Attenuation-to-Crosstalk Ratio, Far-End (PS ACRF)	6-7
Table 6-8	Propagation Delay (ns at 100 m)	6-8
Table 6-9	Transverse Conversion Loss (TCL)	6-9
Table 6-10	Equal-Level Transverse Conversion Transfer Loss (ELTCTL)	6-10
Table 9-1	Electrical Testing for Inside Wire Products	9-3
Table 9-2	Electrical Testing for Indoor/Outdoor Wire Products	9-6