

Contents

List of Figures	vii
List of Tables	ix
1. Introduction	1-1
1.1 Document Overview	1-1
1.2 Purpose of the Document	1-1
1.3 Applicability of Technical Specifications	1-1
1.4 Alternative Arrangements	1-1
1.5 Organization	1-2
2. Service Summary	2-1
2.1 SAS/TS Overview	2-1
2.2 ONA Circuit Switched Trunk BSA - Option D with Tandem Signaling	2-3
2.3 Feature Group D with Tandem signaling	2-3
2.4 800 Access Service with Tandem Signaling	2-4
2.5 Interconnecting CCS Signaling Networks	2-4
2.6 Network Synchronization	2-5
3. Interface Descriptions	3-1
3.1 Interface Overview	3-1
3.2 NCI Code Components	3-1
3.3 Conventions and Explanations	3-4
3.3.1 Transmit and Receive Transmission Directions	3-4
3.3.2 Simplex Signaling Sense	3-5
3.4 Interface Code Availability by Interface Group	3-7
3.4.1 Interface Group 2	3-8
3.4.2 Interface Group 6	3-9
3.4.3 Interface Group 9	3-10
3.4.4 Interface Group 11	3-10
3.5 Interface Illustrations	3-12
3.5.1 Interface Protocol—High Capacity	3-12
3.5.1.1 Interface Codes 04DS ()-()	3-12
3.5.1.2 Interface Codes 02FCF()-()	3-13
3.5.2 Interface Protocol-Duplex	3-14
3.5.2.1 Interface Codes 04DX2	3-14
3.5.3 Interface Protocol—E&M	3-15
3.5.3.1 Interface Codes 06EA2-E and 06EA2-M	3-15
3.5.3.2 Interface Codes 08EB2-E and 08EB2-M	3-16
3.5.3.3 Interface Code 08EC2	3-17
3.5.4 Interface Protocol—Reverse-Battery	3-18
3.5.4.1 Interface Code 04RV2-O	3-18
3.5.4.2 Interface Code 04RV2-T	3-19
3.5.5 Interface Protocol—Transmission Only, No Signaling	3-20
3.5.5.1 Interface Code 04NO2	3-20
3.5.6 Interface Protocol—Single-Frequency	3-21
3.5.6.1 Interface Code 04SF2	3-21

- 4. Signaling Arrangements 4-1
 - 4.1 Supervisory Signaling 4-1
 - 4.1.1 General Description 4-1
 - 4.1.2 E&M Lead Signaling 4-1
 - 4.1.2.1 Type I E&M Lead Signaling (EA-E, EA-M) 4-1
 - 4.1.2.2 Type II E&M Lead Signaling (EB-E, EB-M) 4-1
 - 4.1.2.3 Type III E&M Lead Signaling (EC) 4-2
 - 4.1.3 Loop Reverse-Battery Signaling (RV-O, RV-T) 4-6
 - 4.1.4 Duplex Signaling (DX) 4-6
 - 4.1.5 Single-Frequency Signaling (SF) 4-10
 - 4.1.6 Digital Multiplexed Signaling (DS) 4-10
 - 4.1.6.1 SF Signaling for Digital Multiplexed Interface (DS-L) 4-11
 - 4.1.7 Common Channel Signaling (CCS) 4-11
 - 4.2 Interface Signaling Protocol 4-12
 - 4.2.1 General Description 4-12
 - 4.2.2 Multifrequency Signaling Protocol 4-13
 - 4.2.2.1 Exchange Access North American Signaling 4-13
 - 4.2.2.2 Exchange Access International Signaling 4-14
 - 4.2.3 CCS/SS7 Signaling 4-16
- 5. Technical Specifications 5-1
 - 5.1 Technical Specifications Overview 5-1
 - 5.1.1 Transmission Facilities 5-1
 - 5.1.2 Transmission Parameters 5-2
 - 5.1.3 Voice Band Data Transmission Parameters 5-2
 - 5.1.4 Digital Trunks Acceptance Tests 5-3
 - 5.1.5 Transmission Level Points (TLPs) 5-4
 - 5.1.6 CCS/SS7 Network Interconnection Specifications 5-5
 - 5.2 Loss Plans 5-6
 - 5.3 Voice Grade Transmission Parameter Limits 5-6
 - 5.4 Transmission and Interface Specifications 5-11
 - 5.4.1 Transmission Parameter Limits 5-11
 - 5.4.2 Interface Code Availability 5-13
 - 5.4.3 Transmission Level Points (TLPs) and Interface Codes 5-14
- Appendix A: References A-1
- Appendix B: Bibliography B-1
- Appendix C: Glossary C-1
- Appendix D: Acronyms D-1

List of Figures

Figure 2-1	SAS/TS Transport Configuration and Transmission Parameters . . .	2-1
Figure 2-2	SAS/TS with CCS/SS7 Capabilities	2-2
Figure 3-1	Transmission Conventions	3-4
Figure 3-2	Simplex Standard for 4-Wire DX at POT	3-5
Figure 3-3	Simplex Standard for 4-Wire Reverse-Battery (RV) at POT	3-6
Figure 4-1	Illustration of Type I E&M Lead Interface with Customer Originate on M Lead	4-3
Figure 4-2	Illustration of Type II E&M Lead Interface with Customer Originate on M Lead	4-4
Figure 4-3	Illustration of Type III E&M Lead Interface with Customer Originate on M Lead	4-5
Figure 4-4	Illustration of Loop Reverse-Battery Signaling—Customer Terminating	4-7
Figure 4-5	Illustration of Loop Reverse-Battery Signaling—Customer Originating	4-8
Figure 4-6	Illustration of DX Signaling Circuit	4-9
Figure 4-7	EANA Signaling Protocol	4-14
Figure 4-8	EAIN Signaling Protocol	4-16
Figure 4-9	Illustrative CCS/SS7 Signaling Protocol	4-18

List of Tables

Table 3-1	Conductor Codes Used for SAS/TS	3-2
Table 3-2	Glossary of Protocol and Protocol Option Codes	3-2
Table 3-3	Impedance Codes	3-3
Table 3-4	POT NCI Codes for SAS/TS	3-8
Table 3-5	Digital High-Capacity Interfaces	3-10
Table 3-6	Optical High-Capacity Interfaces	3-11
Table 5-1	Transmission Type A 1 Loss Deviation, Attenuation Distortion, and Echo Control Limits	5-7
Table 5-2	Transmission Type A 1 C-Message Noise Limits	5-8
Table 5-3	Transmission Type A 1 C-Notched Noise Limits	5-9
Table 5-4	Data Type DA 1 Transmission Limits	5-10
Table 5-5	Design Loss in dB Between EO Access Line (Loop) Interface (Analog) and Center of IC Switch	5-12
Table 5-6	SAS/TS Alternate Design Loss in dB Between EO Access Line (Loop) Interface (Analog) and Center of IC Switch for Tandem Access Using the Applicable Arrangements	5-13
Table 5-7	TSP POT Interface Code Combinations	5-14
Table 5-8	SAS/TS TLPs at the LEC Switch	5-14
Table 5-9	SAS/TS TLPs and Interface Codes at the POT	5-15
Table 5-10	SAS/TS Digital Signal and Interface Code at the POT	5-16