

Table of Contents

1 Introduction

- 1.1 Structure and Use of This Document 1-1
- 1.2 Definition 1-1
- 1.3 Background 1-2
- 1.4 High-Level Feature Description 1-5
- 1.5 Changes from TR-NWT-000394, Issue 4, to GR-394-CORE, Issue 1 1-6
- 1.6 Changes from GR-394-CORE, Issue 1 to Issue 1, Revision 1 1-7
- 1.7 Changes from GR-394-CORE, Issue 1, Revision 1 to Issue 1, Revision 2 1-7
- 1.8 Changes from GR-394-CORE, Issue 1, Revision 2 to Issue 1, Revision 3 1-7
- 1.9 Changes from GR-394-CORE Issue 1, Revision 3, to Issue 2 1-7
- 1.10 Changes from GR-394-CORE, Issue 2, to Issue 3 1-8
- 1.11 Changes from GR-394-CORE, Issue 3, to Issue 4 1-8
- 1.12 Changes from GR-394-CORE, Issue 4, to Issue 5 1-8
- 1.13 Changes from GR-394-CORE, Issue 5, to Issue 6 1-8
- 1.14 Changes from GR-394-CORE, Issue 6, to Issue 7 1-9
- 1.15 Changes from GR-394-CORE, Issue 7, to Issue 8 1-9
- 1.16 Requirements Terminology 1-9
- 1.17 Requirement Labeling Conventions 1-10
 - 1.17.1 Numbering of Requirement and Related Objects 1-10
 - 1.17.2 Requirement, Conditional Requirement, and Objective Identification 1-10

2 User Perspective

3 Feature Requirements

- 3.1 Feature Operations 3-1
 - 3.1.1 Main Feature Operations 3-2
 - 3.1.1.1 Originating Treatment; LEC to IXC (All-SS7 Connection) 3-3
 - 3.1.1.2 Terminating Treatment; IXC to LEC 3-12
 - 3.1.1.3 Receiving and Sending a CPG at an SS7 AT 3-13
 - 3.1.2 Other Feature Operations 3-13
 - 3.1.2.1 Test Calls From a LEC to an IXC 3-13
 - 3.1.3 Release Treatment 3-13
 - 3.1.4 Error Treatment and Abnormal Events 3-14
 - 3.1.4.1 Dual Seizure 3-14
 - 3.1.4.2 Expiration of Timers 3-14
 - 3.1.4.3 Receipt of Unexpected Messages 3-14
 - 3.1.4.4 Additional Procedures 3-15
 - 3.1.4.5 Receipt of Unrecognized Message Types 3-15
 - 3.1.4.6 Tones and Announcements 3-15
 - 3.1.4.7 ISDNUP Flow Control 3-15
 - 3.1.4.8 ISDNUP Reaction to TFC/Isolation 3-16
 - 3.1.4.9 Automatic Congestion Control (ACC) Procedures 3-16
- 3.2 Internal Call Processing Controls 3-16
 - 3.2.1 Screening 3-16
 - 3.2.1.1 Originating 3-16
 - 3.2.1.2 Terminating 3-16

3.2.2 Charge Treatment Determination and Automatic Message Accounting (AMA)	3-17
3.2.2.1 Originating LATA	3-17
3.2.2.2 Terminating LATA	3-20
3.3 Administration	3-21
3.4 Maintenance	3-22
3.4.1 Maintenance Measurements	3-23
3.4.2 Input/Output Messages	3-24
3.4.3 Circuit Maintenance	3-25
3.5 Interactions	3-26
3.5.1 Interworking With Exchange Access Inband Signaling	3-26
3.5.1.1 Originating Treatment: Exchange Access Inband Signaling to SS7 IXC Interface	3-26
3.5.1.2 Originating Treatment: SS7 to Exchange Access Inband Signaling IXC Interface	3-32
3.5.1.3 Terminating Treatment: Inband Signaling to SS7	3-35
3.5.1.4 Terminating Treatment: SS7 to Inband Signaling	3-35
3.5.2 Interworking With Feature Group B (FGB)	3-35
3.5.2.1 Originating Treatment: SS7 to AT, Inband Signaling to Feature Group B (FGB) Carrier	3-35
3.5.2.2 Originating Treatment: Inband Feature Group B (FGB) From Non-EAEO to SS7	3-36
3.5.3 Interworking With Traditional Inband Signaling	3-37
3.5.4 Feature Interactions	3-37
3.5.4.1 Calling Party Number (CPN)	3-37
3.5.4.2 Carrier Selection	3-39
3.5.4.3 Service Code	3-40
3.5.4.4 Carrier Identification Parameter (CIP)	3-41
3.5.4.5 Jurisdiction Information Parameter (JIP)	3-45
3.6 Timing and Tolerances	3-46
3.7 Performance	3-46

Appendix A: SS7 Messages

Appendix B: SS7 Parameters

B.1 Backward Call Indicators	B-1
B.2 User Service Information (Bearer Capability Parameter)	B-3
B.3 Called Party Number	B-4
B.4 Calling Party Number	B-6
B.5 Calling Party's Category	B-7
B.6 Cause Indicators	B-8
B.7 Charge Number	B-10
B.8 Continuity Indicators	B-12
B.9 Service Code	B-12
B.10 Forward Call Indicators	B-13
B.11 Message Type	B-14
B.12 Nature of Connection Indicators	B-15
B.13 Originating Line Information	B-16
B.14 Outgoing Trunk Group Number	B-17
B.15 Carrier Selection	B-17

B.16 Transit Network Selection B-18
B.17 Optional Backward Call Indicators B-20
B.18 Carrier Identification Parameter B-21
B.19 Hop Counter B-22
B.20 Automatic Congestion Level B-23
B.21 Jurisdiction Information B-23

Appendix C: Interoffice Signaling Figures

Appendix D: Bearer Independent Call Control (BICC)

D.1 Introduction D-1
D.2 Motivation D-1
D.3 BICC Architecture D-2
 D.3.1 BICC Network Architecture D-2
 D.3.2 BICC Protocol D-3
 D.3.3 BICC Messages and Parameters D-5
D.4 BICC Protocol Industry Status D-6
 D.4.1 ITU-T Study Group 11 D-6
 D.4.2 T1S1 D-7
D.5 Summary D-8

Appendix E: Session Initiation Protocol (SIP)

E.1 Introduction E-1
E.2 Motivation E-1
E.3 SIP Architecture E-2
 E.3.1 SIP Network Architecture E-2
 E.3.1.1 Clients E-3
 E.3.1.2 Servers E-4
 E.3.1.2.1 Proxy Servers E-4
 E.3.1.2.2 Redirect Servers E-4
 E.3.1.2.3 Location Servers E-5
 E.3.1.2.4 Registrar Server E-5
 E.3.2 SIP Protocol E-5
 E.3.3 SIP Messages and Parameters E-6
 E.3.3.1 SIP Request Messages E-6
 E.3.3.2 SIP Response Messages E-7
 E.3.3.3 SIP Message Headers E-8
 E.3.4 SIP Call Flows E-10
 E.3.4.1 ISUP to SIP Interworking E-10
 E.3.4.2 SIP to ISUP Interworking E-12
 E.3.4.3 SIP to ISUP Interworking with Preconditions E-14
 E.3.4.4 ISUP to SIP and ISUP Interworking (SIP Bridging) E-16
E.4 Summary E-19

Appendix F: IMS and SS7 Interconnection

F.1 Introduction F-1
 F.1.1 IMS Overview F-1
 F.1.2 IMS Functional Architecture F-2
F.2 IMS and SS7 Interconnection F-3

- F.2.1 IMS - PSTN Call Flow Overview F-4
 - F.2.1.1 IMS Origination to the PSTN F-4
 - F.2.1.2 PSTN Origination to IMS F-5
- F.2.2 Protocol Interworking F-5
 - F.2.2.1 Lower-Layer Interworking F-5
 - F.2.2.2 SIP - ISUP Interworking F-6
 - F.2.2.2.1 IMS Call Origination F-7
 - F.2.2.2.2 PSTN Call Origination F-8
 - F.2.2.2.3 Additional Interworking Considerations F-9

Appendix G: References

Appendix H: Acronyms

Requirement-Object Index

List of Figures

Figure 1-1	Telcordia GR Diagram	1-3
Figure B-1	Backward Call Indicators Parameter	B-1
Figure B-2	User Service Information Parameter	B-3
Figure B-3	Called Party Number Parameter	B-4
Figure B-4	Calling Party Number Parameter	B-6
Figure B-5	Calling Party's Category Parameter	B-7
Figure B-6	Cause Indicators Parameter	B-8
Figure B-7	Charge Number Parameter	B-10
Figure B-8	Continuity Indicators Parameter	B-12
Figure B-9	Service Code Parameter	B-12
Figure B-10	Forward Call Indicators Parameter	B-13
Figure B-11	Message Type Parameter	B-14
Figure B-12	Nature of Connection Indicators Parameter	B-15
Figure B-13	Originating Line Information Parameter	B-16
Figure B-14	Outgoing Trunk Group Number Parameter	B-17
Figure B-15	Carrier Selection Parameter	B-17
Figure B-16	Transit Network Selection Parameter with a 4-Digit Carrier Identification Code	B-18
Figure B-17	Optional Backward Call Indicators Parameter	B-20
Figure B-18	Carrier Identification Parameter with a 4-Digit Carrier Identification Code	B-21
Figure B-19	Hop Counter Parameter	B-22
Figure B-20	Automatic Congestion Level Parameter	B-23
Figure B-21	Jurisdiction Information Parameter	B-23
Figure C-1	Exchange Access Inband Signaling: Direct	C-1
Figure C-2	Exchange Access Inband Signaling: Tandem	C-2
Figure C-3	SS7 for Call Setup and Release: Not Involving an IXC	C-3
Figure C-4	SS7 for Call Setup and Release to IXC: Direct	C-4
Figure C-5	SS7 for Call Setup and Release to IXC: Tandem	C-5
Figure C-6	Exchange Access Inband Signaling to SS7	C-6
Figure C-7	International Exchange Access Inband to SS7	C-7
Figure C-8	SS7 to Exchange Access Inband Signaling	C-8
Figure C-9	SS7 to International Exchange Access Inband Signaling	C-9
Figure D-1	Initial BICC Architecture	D-2
Figure D-2	BICC Network Model	D-3
Figure D-3	Backward Bearer Connection Setup with COT	D-4
Figure E-1	Generic SIP-Based Network Architecture	E-3
Figure E-2	SIP Stack	E-6
Figure E-3	ISUP to SIP Interworking	E-11
Figure E-4	SIP and ISUP Interworking	E-13
Figure E-5	SIP ISUP Interworking with Preconditions	E-15
Figure E-6	SIP-ISUP-SIP Interworking	E-17
Figure F-1	IMS Architecture Framework	F-2
Figure F-2	Interconnection Architecture	F-4
Figure F-3	Protocol Interworking	F-6
Figure F-4	IMS Call Origination	F-7
Figure F-5	PSTN Call Origination	F-8

List of Tables

Table 3-1	Message Priorities	3-2
Table 3-2	Coding Rules for the Called Party Number Parameter	3-5
Table 3-3	I and II Digits and Originating Line Information	3-7
Table 3-4	Switch Processing Time Requirements	3-47
Table A-1	Address Complete Message	A-1
Table A-2	Answer Message	A-2
Table A-3	Continuity Message	A-2
Table A-4	Exit Message	A-2
Table A-5	Initial Address Message	A-3
Table A-6	Release Message	A-3
Table A-7	Release Complete Message - Circuit Reservation Acknowledgment Message	A-3
Table A-8	Circuit Reservation Message	A-4