

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Scope and Purpose	1-1
1.2 Changes From Previous Issues	1-1
1.2.1 TA-TSY-000418, Issue 2, September 1989	1-2
1.2.2 TA-NWT-000418, Issue 3, November 1991	1-2
1.2.3 TR-NWT-000418, Issue 2, December 1992	1-3
1.2.4 GR-418-CORE, Issue 1, December 1997	1-3
1.2.5 Future Additions	1-3
1.3 Related Telcordia Documents	1-4
1.4 Document Organization	1-4
1.5 Requirements Terminology	1-4
1.6 Requirement Labeling Conventions	1-5
1.6.1 Numbering of Requirement and Related Objects	1-5
1.6.2 Requirement, Conditional Requirement, and Objective Object Identification	1-6
2. System Reliability and Service Availability Criteria	2-1
2.1 Reliability Definitions	2-3
2.1.1 Traditional View	2-3
2.1.2 Emergent View	2-5
2.1.2.1 Customer Experienced Downtime	2-6
2.1.2.2 Outage Frequency and Duration	2-6
2.1.2.3 Service Restoration Time	2-6
2.1.2.4 International Standards Efforts	2-6
2.2 Interoffice Applications	2-7
2.2.1 Asynchronous Transmission Products	2-7
2.2.1.1 DS3 Channel Availability Requirement	2-10
2.2.1.2 Unavailability Due to Hardware Reliability	2-12
2.2.1.3 Systems That Directly Interface at DS1, DS1C or DS2 Levels	2-14
2.2.2 SONET End Terminals and Terminal Multiplexers	2-15
2.2.2.1 Allocations of Maximum Downtime for 250-Mile Route	2-16
2.2.2.2 Allocations of Maximum Downtime for 50-Mile Route	2-18
2.2.2.3 Discussion of Cable Failures	2-19
2.2.3 SONET Regenerators	2-21
2.2.4 Optical Amplifiers	2-21
2.2.5 SONET Rings and Add/Drop Multiplexers	2-23
2.2.5.1 Hardware/Media	2-25
2.2.5.2 Protection Switch	2-28
2.2.5.3 Software/Procedural	2-28
2.2.6 Digital Cross-Connect Systems With SONET Interfaces	2-29

2.3	Loop Applications	2-29
2.3.1	Feeder Segment	2-31
2.3.1.1	Asynchronous Transmission	2-31
2.3.1.2	SONET Transport	2-32
2.3.1.2.1	Terminal Multiplexers	2-32
2.3.1.2.2	Add/Drop Multiplexers	2-33
2.3.2	Distribution Segment	2-35
2.3.2.1	Common Criteria	2-36
2.3.2.2	Digital Cross-Connect System	2-37
2.3.2.3	Feeder Network	2-37
2.3.2.4	Host Digital Terminal	2-37
2.3.2.5	Optical Network Unit	2-38
2.3.2.6	Unassigned Allocation	2-39
2.3.2.7	Other Availability Considerations	2-39
2.3.2.8	Powering Availability	2-40
2.4	Operations System Reliability Criteria	2-40
2.4.1	OS Interface Module	2-41
2.4.2	OS Platform	2-42
2.4.3	OS Link	2-43
2.5	Additional System Reliability Criteria	2-43
2.5.1	System Outage Information	2-43
2.5.2	Failure Group Size Criteria	2-44
2.5.3	Silent Failure Criteria	2-45
2.5.4	Memory Backup and Restoration	2-45
2.6	Equipment Maintenance	2-46
2.6.1	Maintenance Criteria for Interoffice and Feeder Applications	2-46
2.6.2	Maintenance Criteria for FITL Systems	2-47
2.6.3	Required Information on Maintenance Activities	2-48
2.7	Infant Mortality Criteria	2-49
2.8	Procedures for Calculating Failure Rates of Circuit Packs and Modules	2-50
2.8.1	Device Quality Factors	2-51
2.8.2	Device Stress Factors	2-52
2.8.3	Ambient Temperature Factors	2-52
2.8.4	Alternative Calculation Techniques	2-52
2.9	Procedures for Calculating System Unavailability and Related Reliability Parameters	2-53
2.9.1	System Reliability Model	2-53
2.9.2	Repair Rate Assumptions	2-54
2.9.3	Link Loss Budget	2-55
2.9.4	Outage Graphs	2-56
2.9.5	Other System Documentation	2-56
2.9.6	Summary Table of Reliability Parameters	2-56
2.10	Reliability Considerations for DWDM Equipment	2-57
2.10.1	Critical Component Reliability	2-57
2.10.2	Redundancy	2-58

2.10.3	Single Point Failures	2-58
2.10.4	Failure Group Size	2-59
3.	Sub-Assembly and Environmental Criteria	3-1
3.1	Component Reliability Assurance	3-1
3.2	Physical Design Criteria	3-1
3.3	Environmental Criteria	3-2
3.4	Third-Party Equipment	3-3
3.5	Short-Life Products and Equipment	3-4
4.	Testing	4-1
4.1	Product Life Cycle	4-1
4.2	Initial System Qualification (IQ)	4-2
4.2.1	Product Specifications	4-3
4.2.2	Electrical and Optical Tests	4-4
4.2.3	Special Tests	4-6
4.2.3.1	Temperature Cycle Endurance	4-6
4.2.3.2	Other	4-7
4.2.4	Environmental Tests	4-7
4.2.5	Mechanical Tests	4-7
4.2.6	Reliability Model Verification	4-8
4.2.7	Maintenance Procedures	4-8
4.2.8	Qualification Report	4-9
4.3	Periodic System Requalification (RQ)	4-10
4.3.1	Electrical and Optical Tests	4-10
4.3.2	Special Tests	4-11
4.3.3	Environmental Tests	4-11
4.3.4	Mechanical Tests	4-12
4.3.5	Requalification Report	4-12
4.3.6	Reliability Model Verification	4-12
4.4	Reliability Testing	4-12
4.4.1	Test Purpose and Frequency	4-13
4.4.2	Test Conditions and Procedure	4-14
4.5	First Office Application (FOA) Qualification	4-16
4.6	Manufacturing Tests	4-17
4.6.1	Design for Testability	4-17
4.6.2	Routine Manufacturing Tests	4-18
4.6.3	Data Analysis and Reporting	4-19
4.7	Standardized Test Procedures	4-20
4.8	Temperature Cycle Endurance Test	4-21
4.8.1	Test Conditions	4-21
4.8.2	Temperature Extremes	4-21
4.8.2.1	Soak Time	4-22
4.8.2.2	Ramp Rate	4-22
4.8.2.3	Test Duration	4-23
4.8.2.4	Humidity	4-24
4.8.3	Test Configurations	4-24
4.8.4	Measurements	4-26

4.8.4.1	Measurement Parameters	4-26
4.8.4.2	Frequency of Measurements	4-28
4.8.5	Pass/Failure Criteria	4-28
4.8.6	Example Test Set-Up	4-30
5.	Manufacturing and Assembly Reliability	5-1
5.1	Incoming Lot Controls	5-1
5.2	Manufacturing and Assembly Practices	5-1
5.2.1	Manufacturing Process Qualification	5-2
5.2.2	Technologies	5-3
5.2.3	Manufacturing Controls	5-4
5.2.4	In-Process Tests and Inspections	5-5
5.2.5	Manufacturing Process Requalification	5-6
5.2.6	ESD Controls	5-6
5.3	Circuit Pack and System Functional Testing	5-7
5.4	Corrective Action Program	5-7
6.	Software Reliability and Quality (R&Q)	6-1
6.1	Definitions	6-2
6.2	Design for R&Q	6-3
6.2.1	Fault Detection, Containment, Recovery, and Reporting	6-3
6.2.2	Fault History	6-4
6.2.3	Trend Detection	6-4
6.2.4	Prevention of Interference	6-4
6.2.5	Concurrency	6-5
6.2.6	Modularity/Interdependency	6-5
6.2.7	High-Level Languages	6-6
6.2.8	Design and Architecture Documentation	6-6
6.2.9	Database	6-7
6.2.10	Data Integrity	6-7
6.2.11	Operations Systems (OS) Compatibility	6-7
6.2.12	NE Software Release Information	6-8
6.3	Firmware	6-8
6.3.1	Design Methodology	6-8
6.3.2	Firmware/Software Coupling	6-8
6.3.3	Stability	6-9
6.3.4	Mounting	6-9
6.3.5	Classification	6-9
6.3.6	Considerations for Update Procedures	6-10
6.3.7	Circuit Pack Level Testing	6-10
6.3.8	Pass/Fail Indication	6-10
6.3.9	Record Administration	6-11
6.3.10	Change History	6-11
6.3.11	Identification	6-11
6.3.12	Downward/Upward Compatibility	6-11
6.3.13	Traceability	6-12
6.3.14	Spare Circuit Pack Administration	6-12
6.3.15	Documentation	6-12

6.4	Patching	6-12
6.4.1	Patch Monitoring	6-13
6.4.2	Patch Assurance	6-13
6.4.2.1	Development	6-13
6.4.2.2	Pre-Release	6-14
6.4.2.3	Field Deployment	6-14
6.4.3	Patch Sequence Numbers and Identification	6-15
6.4.4	Patch Propagation to Other Releases	6-16
6.4.5	Patch Space	6-16
6.4.6	Defective Patches	6-16
6.4.7	Writable Firmware Devices	6-17
6.4.8	Feature Patching	6-17
6.4.9	Patch Information	6-18
6.4.9.1	Patch Information Available From the System	6-18
6.4.9.2	Patch Content Information	6-18
6.4.10	Patching Tools	6-20
6.4.11	Patch 5 Measurements	6-22
6.5	Testing	6-23
6.5.1	Criteria Common to Test Phases	6-23
6.5.1.1	Planning	6-24
6.5.1.2	Test Case Preparation and Reviews	6-25
6.5.1.3	Test Execution and Results	6-26
6.5.1.4	Regression Tests	6-27
6.5.1.5	Test Status Reports	6-27
6.5.1.6	Entry/Exit Criteria	6-27
6.5.1.7	Root Cause Analysis	6-28
6.5.1.8	Stability Measurements	6-28
6.5.2	Module Testing	6-29
6.5.2.1	Test Case Preparation and Reviews	6-29
6.5.2.2	Module Test Entry/Exit Criteria	6-29
6.5.3	Functional Unit Testing	6-29
6.5.3.1	Test Case Preparation and Reviews	6-30
6.5.3.2	Functional Unit Test Entry/Exit Criteria	6-30
6.5.4	Integration Test	6-31
6.5.4.1	Test Planning	6-31
6.5.4.2	Test Case Preparation and Reviews	6-31
6.5.4.3	Test Execution and Results	6-32
6.5.4.4	Integration Test Entry/Exit Criteria	6-32
6.5.5	System Test	6-33
6.5.5.1	Test Case Preparation and Reviews	6-33
6.5.5.2	Test Execution and Results	6-34
6.5.5.3	System Test Entry/Exit Criteria	6-34
6.5.6	FOA Testing	6-36
6.5.6.1	Planning for FOA	6-36
6.5.6.2	Test Activity	6-36
6.5.6.3	First Office Application Entry/Exit Criteria	6-37
6.5.7	Interoperability Testing	6-38

6.6	Feature/Release Delivery Information	6-38
6.6.1	Feature/Release Availability Information	6-38
6.6.2	Feature Request Dates	6-38
6.6.3	Release Support Period	6-39
6.6.4	Dropped or Delayed Features or Releases	6-39
6.7	Downtime and Service Impact	6-39
6.8	Referenced Software Criteria	6-39
6.8.1	Software Quality Program Generic Requirements	6-40
6.8.2	Software Reliability and Quality Acceptance Requirements	6-40
6.8.3	R&Q Measurements for Telecommunications Systems	6-41
7.	Field Performance and Customer Support	7-1
7.1	Field Performance	7-1
7.1.1	Collection and Analysis Program Capabilities	7-1
7.1.2	Hardware Performance Tracking	7-2
7.1.3	Software Performance Tracking	7-3
7.1.4	Product Repair	7-3
7.1.5	No Trouble Found (NTF) Circuit Packs	7-3
7.1.6	Dead On Arrival (DOA) Circuit Packs	7-4
7.1.7	Turnaround Time for Repairs	7-4
7.1.8	Engineering Complaints	7-4
7.1.9	Corrective Action	7-5
7.2	Customer Support	7-5
7.2.1	General Documentation and Reporting of Data	7-6
7.2.2	Engineering, Ordering, and Sparing	7-6
7.2.3	Training	7-7
7.2.4	Installation	7-7
7.2.4.1	Documentation	7-8
7.2.4.2	Installation Practices	7-8
7.2.4.3	Supplier's Acceptance Test Plan	7-9
7.2.4.4	Other Installation Issues	7-9
7.2.5	Customer Maintenance	7-9
7.2.5.1	Hardware	7-10
7.2.5.2	Software	7-10
7.2.5.3	Additional Maintenance Criteria	7-11
7.2.6	Product Updates	7-11
7.2.7	Technical Assistance	7-12
	Appendix A: Example Tables for Reliability Model Verification	A-1
	Appendix B: Overview of Telcordia Sampling Plans	B-1
	References	References-1
	Acronyms	Acronyms-1
	Index	Index-1

List of Figures

Figure 2-1.	Asynchronous Network Hypothetical Reference Circuit	2-9
Figure 2-2.	DS1 Availability Criteria - Asynchronous Transport	2-10
Figure 2-3.	DS3 Asynchronous Transport Criteria Prorated by Distance	2-12
Figure 2-4.	Hardware/Software Availability Criteria - Asynchronous Transport	2-14
Figure 2-5.	SONET HRC - Linear Network Architecture	2-16
Figure 2-6.	Downtime Allocations for 250-Mile SONET HRC	2-17
Figure 2-7.	SONET 50-Mile Reference Circuit	2-19
Figure 2-8.	Downtime Allocations for a 50-Mile Reference Circuit	2-20
Figure 2-9.	SONET HRC - With Transmitter Boosters and Receiver Preamps	2-22
Figure 2-10.	Downtime Allocations for 250-Mile SONET HRC With Boosters and Preamplifiers	2-22
Figure 2-11.	Introduction of Rings Into the SONET HRC	2-25
Figure 2-12.	End-to-End Ring Path	2-27
Figure 2-13.	Self-Healing Ring Downtime Allocation	2-28
Figure 2-14.	Subscriber Loop HRC	2-30
Figure 2-15.	Predicted Unavailability of a Unidirectional Ring	2-34
Figure 4-1.	Example Set-Up of Equipment for a Temperature Cycle Test	4-30
Figure 6-1.	Software Testing Life Cycle	6-24

List of Tables

Table 2-1.	DS3 Channel Availability Objective, DSX-3 to DSX-3	2-11
Table 2-2.	Loop Downtime Allocations - Asynchronous Feeder and DLC	2-32
Table 2-3.	Loop Downtime Allocations - SONET Feeder and DLC	2-34
Table 2-4.	Loop Downtime Allocations - FITL Systems	2-36
Table 2-5.	Classes of OS Reliability	2-41
Table 2-6.	Hardware Reliability Requirements for Classes of OS Reliability	2-42
Table 2-7.	Example Link Loss Budget Calculation	2-55
Table 2-8.	Supplier-Provided Reliability Parameters	2-57
Table 4-1.	Information for Using Tables 4-2 through 4-5	4-31
Table 4-2.	Required Optical Test Parameters - Digital Systems	4-32
Table 4-3.	Required Electrical Test Parameters - Digital Systems	4-33
Table 4-4.	Required Electrical Test Parameters - Analog Systems	4-34
Table 4-5.	Other Required Test Parameters	4-36
Table 4-6.	Summary of (Sub)Assembly and Environmental Tests	4-37
Table A-1.	Single Failure Simulation	A-1
Table A-2.	Second Failure and Restoration Simulation	A-2
Table B-1.	Sampling Plan Variables	B-2