

Table of Contents

1 General

1.1 Purpose	1-1
1.2 Scope and Product Descriptions	1-1
1.2.1 Wire Products for Rural and Suburban Applications	1-2
1.3 GR Hierarchy for Twisted-Pair Products	1-3
1.4 Safety Considerations	1-4
1.5 Reference Documents	1-5
1.6 Units and Tolerances	1-5
1.7 Product Reliability/Quality Assurance	1-5
1.7.1 Product Changes	1-6
1.8 Reasons for GR-492-CORE Reissues	1-6
1.8.1 Reasons for GR-492-CORE, Issue 2	1-6
1.8.2 Reasons for GR-492-CORE, Issue 1	1-7
1.9 Organization	1-7
1.10 Requirements Terminology	1-8
1.11 Requirement Labeling Conventions	1-9
1.11.1 Numbering of Requirement and Related Objects	1-9
1.11.2 Requirement, Conditional Requirement, and Objective Identification	1-10

2 Conductors

2.1 General Design Features	2-1
2.2 Copper Cladding Adherence and Ductility	2-2
2.3 Copper Hardness	2-2
2.4 Conductor Size	2-2
2.5 Factory Joints	2-3
2.6 Conductor Elongation and Breaking Strength	2-3
2.6.1 Conductor Elongation	2-3
2.6.2 Conductor Breaking Strength	2-4

3 Conductor Insulation

3.1 General Features	3-1
3.2 Polyolefin Insulations	3-2
3.2.1 Thermal Oxidative Stability - Insulation	3-2
3.3 Poly(VinylChloride) Insulation Requirements	3-3
3.4 Insulation Construction and Dimensions	3-3
3.5 Lead-Free and Low Lead/Cadmium Materials	3-4
3.6 Imperfections and Porosity	3-5
3.7 Splices	3-5
3.8 Insulation Adhesion to Conductor	3-5
3.8.1 Adhesion Test #1	3-6
3.8.2 Adhesion Test #2	3-6
3.9 Tensile Strength and Elongation	3-6
3.10 Resistance to Aging	3-6
3.11 Compression Resistance	3-7
3.12 Cold Bend	3-7
3.13 Shrinkback (Longitudinal)	3-8

3.14 Insulation Color Coding	3-8
3.15 Twist Lengths	3-9
3.15.1 Tight-Twist Pair Products	3-9
3.16 Conductor Identification - Mechanical Ridge	3-9
4 Core Construction	
4.1 Binders	4-1
4.2 Core Wrap	4-1
4.3 Jacket Ripcords	4-2
5 Shields and Foils	
6 Jacket Requirements	
6.1 Introduction	6-1
6.2 General Design and Materials Choices	6-1
6.3 Lead-Free and Low Lead/Cadmium Materials	6-2
6.4 Polyolefin Jackets	6-2
6.5 Patching and Repairs	6-3
6.6 Ultraviolet Resistance	6-4
6.7 Jacket Thickness	6-4
6.8 Tensile Strength and Elongation	6-5
6.9 Resistance to Aging	6-5
6.10 Thermal Oxidative Stability - Polyolefin Jackets	6-6
6.11 Environmental Stress Crack Resistance (Polyolefin Jackets)	6-6
6.12 Porosity and Imperfections	6-6
7 Electrical Requirements	
7.1 DC Conductor Resistance	7-1
7.2 DC Resistance Unbalance	7-1
7.3 Mutual Capacitance	7-1
7.4 Capacitance Unbalance	7-2
7.4.1 Pair-to-Pair	7-2
7.4.2 Pair-to-Ground	7-2
7.5 Insertion Loss (Attenuation)	7-2
7.6 Voltage Test	7-2
7.7 Insulation Resistance	7-3
7.7.1 Dry Test Condition	7-3
7.7.2 Wet (Immersed) Test Condition	7-4
7.8 Continuity and Shorts	7-5
8 Finished Product Tests	
8.1 Cold Bend or Wrap Tests	8-1
8.2 Spark Test	8-1
8.3 Cold Impact Test	8-1
8.4 Flammability and Listing	8-2
8.5 Jacket Removal	8-2
8.6 Abrasion	8-3
8.7 Hardware Compatibility	8-4
8.7.1 General	8-5

8.7.2 Pull Test	8-5
---------------------------	-----

9 Marking and Packaging Requirements

9.1 Wire Product Marking	9-1
9.1.1 Jacket or Outer Sheath Marking	9-1
9.1.2 Length Marking	9-1
9.1.3 Marking Height and Legibility	9-2
9.1.4 Marking Durability	9-2
9.2 Packaging	9-2
9.2.1 General Features	9-3
9.2.2 Marking	9-3
9.3 Low Temperature Impact Resistance for Spools	9-4

10 Product Classification

10.1 General Descriptions and Application Review	10-1
10.2 Single-Pair Aerial Service Wire – F-Drop	10-1
10.2.1 Conductors	10-2
10.2.2 Conductor Insulation - Adhesion	10-2
10.2.3 Ripcords	10-2
10.2.4 Jacket	10-2
10.2.5 Electrical Requirements	10-3
10.2.6 Finished Wire Mechanical and Environmental Tests	10-3
10.2.7 Packaging and Marking Requirements	10-4
10.3 Rural Wire	10-4
10.3.1 Conductors	10-4
10.3.2 Conductor Insulation	10-5
10.3.3 Jacket	10-5
10.3.4 Electrical Requirements	10-6
10.3.5 Finished Wire Mechanical and Environmental Tests	10-6
10.3.6 Packaging and Marking Requirements	10-6
10.4 Block Wire	10-7
10.4.1 Conductors	10-8
10.4.2 Conductor Insulation	10-8
10.4.2.1 Lead-Free and Low Lead/Cadmium Materials	10-9
10.4.3 Jacket	10-9
10.4.3.1 Lead-Free and Low Lead/Cadmium Materials	10-10
10.4.4 Electrical Requirements	10-10
10.4.5 Finished Wire Mechanical and Environmental Tests	10-10
10.4.6 Packaging and Marking Requirements	10-11

Appendix A: Historical Information

A.1 Superseded Documents	A-1
A.2 Cable Product Descriptions	A-1
A.3 Single-Pair Buried Service Drop Wire (TR-NWT-000123)	A-2
A.3.1 Insulation Resistance (Wet)	A-2
A.3.2 Impact Test	A-2
A.3.3 Finished Wire Breaking Strength	A-3
A.4 Bridle Wire (TA-TSY-000128)	A-3
A.4.1 Impact Test	A-3

A.5 Tree Wire (TA-TSY-000129)	A-3
A.6 Generic Conductor Properties	A-4
A.6.1 Conductor Sizes	A-4
A.6.2 Conductor Elongation	A-5
A.7 Insulation and Jacket Materials	A-5
A.7.1 Black Synthetic Rubber	A-5
A.7.2 Material Specifications for Polyethylenes	A-6
A.7.3 Poly(VinylChloride) Insulation Materials	A-7
A.8 Insulated Conductor Splices	A-7
A.9 Color Permanency and Durability of Ink Markings	A-8
A.10 Fusing Coordination	A-8

Appendix B: Test Procedures for Wicking and Hygroscopicity

B.1 Test Procedure for Wicking	B-1
B.2 Test Procedure for Hygroscopicity	B-1

Appendix C: Printing and Marking Durability Test

C.1 Specimen Preparation	C-1
C.2 Apparatus	C-1
C.3 Sample Conditioning	C-1
C.4 Procedure	C-1

Appendix D: References

D.1 To Obtain Additional Reference Material	D-4
D.2 Telcordia Document Sets—Family of Requirements (FR) and Family of Documents (FD)	D-5
D.3 Telcordia Reference Notes	D-6
D.3.1 Contact Telcordia Customer Service	D-6
D.3.2 Order Documents Online From the Telcordia Information SuperStore	D-6
D.3.3 Web Sites for Generic Requirements Information	D-7
D.3.4 Licensing Agreements for Telcordia Documents	D-7

Appendix E: Acronyms

Requirement-Object Index

List of Figures

Figure 8-1	Horizontal Scrape Abrasion Apparatus	8-4
Figure 9-1	Preferred Packaging	9-2
Figure A-1	Fusing Coordination Test Schematic	A-10
Figure B-1	Wicking Test	B-2

List of Tables

Table 2-1	Copper-Clad Steel Conductor Diameter	2-3
Table 2-2	Conductor Elongation	2-3
Table 2-3	Conductor Breaking Strength	2-4
Table 3-1	Polyethylene Material Requirements	3-2
Table 3-2	Poly(VinylChloride) Material Requirements	3-3
Table 3-3	Color Code	3-8
Table 7-1	DC Resistance	7-1
Table 7-2	Voltage Withstand Test Conditions	7-3
Table 7-3	Temperature Correction Coefficients	7-4
Table 10-1	Electrical Testing for Single-Pair Aerial Service Wire Products	10-3
Table 10-2	Electrical Testing for Rural Wire Products	10-6
Table 10-3	Block Wire Color Code	10-7
Table 10-4	Block Wire Color Specification	10-8
Table 10-5	Electrical Testing for Block Wire Products	10-10
Table A-1	Single-Pair Buried Service Wire - Conductors	A-2
Table A-2	Voltage Withstand - Test Voltage (kV)	A-2
Table A-3	Bridle Wire - Conductor Elongation	A-3
Table A-4	Tree Wire - Conductor Diameter	A-4
Table A-5	Tree Wire - Conductor Strength	A-4
Table A-6	Tree Wire - Insulation Compressive Strength	A-4
Table A-7	Tree Wire - Conductor Resistance	A-4
Table A-8	Copper Conductor Diameter	A-5
Table A-9	Copper Conductor Elongation	A-5
Table A-10	Polyethylene Cable Jacket Material Requirements	A-6
Table A-11	PVC Insulation Materials Properties, Requirements, and Procedures	A-7
Table A-12	Test Conditions - Currents and Duration	A-10