

Contents

Generic Requirements	
Notice Of Disclaimer	iii
Preface	xi
1. Introduction	1-1
1.1 General	1-1
1.2 Content	1-2
1.3 Reasons for Reissue	1-2
1.4 Requirement Terminology	1-2
2. Interface Specifications	2-1
2.1 General	2-1
2.2 Impedance Matching	2-1
2.3 Signal Specifications	2-1
2.3.1 Transmission Rate	2-1
2.3.2 Line Code	2-2
2.3.3 Test Termination and Frequency	2-2
2.3.4 Pulse Shape	2-2
2.3.5 Pulse Imbalance	2-2
2.3.6 60-Hz Variations In Pulse Amplitude	2-2
2.3.7 Power Level	2-2
2.3.8 Pulse Density	2-3
2.3.9 Quasi-Random Signal (QRS)	2-3
2.4 Network Signal at the NI	2-4
2.4.1 Network Pulse Characteristics	2-4
2.4.2 Network Signal Amplitude	2-4
2.5 Customer Installation (CI) Signal at the NI	2-4
2.5.1 CI Pulse Characteristics	2-4
2.5.2 CI Signal Amplitude	2-4
2.6 Electrical Protection	2-5
2.7 Synchronization	2-5
3. Clear Channel Capability (CCC)	3-1
3.1 Bipolar with 8-Zero Substitution (B8ZS)	3-1
3.2 Zero-Byte Time Slot Interchange (ZBTSI)	3-1
4. Jitter, Wander, and Phase Transients	4-1
4.1 General	4-1
4.1.1 Jitter	4-1
4.1.2 Wander	4-1
4.1.3 Phase Transients	4-1
4.2 Network Signal at the NI	4-1
4.2.1 Network Signal Jitter	4-1
4.2.2 Network Signal Wander	4-2
4.2.3 Network Signal Phase Transients	4-2
4.3 Customer Installation Signal at the NI	4-2

4.3.1	CI Signal Jitter	4-2
4.3.2	CI Signal Wander	4-3
4.3.3	CI Signal Phase Transients	4-3
5.	Powering Arrangements	5-1
5.1	T1 Facility	5-1
5.2	Sealing Current	5-1
6.	Framing Formats	6-1
6.1	General	6-1
6.2	Frame	6-1
6.3	Superframe (SF) Format	6-1
6.4	Extended Superframe (ESF) Format	6-1
6.4.1	Terminal Synchronization Channel	6-2
6.4.2	Cyclic Redundancy Check (CRC-6) Channel	6-2
6.4.3	ESF Data Link (DL)	6-3
6.5	Free (Unframed) Format	6-3
6.6	Framing Format Selection	6-3
7.	DS1 Applications	7-1
7.1	Unchannelized	7-1
7.2	Primary Rate ISDN	7-1
7.3	Asynchronous Transfer Mode (ATM)	7-2
7.4	24 Channels with Robbed-Bit Signaling	7-2
7.5	24 Channels at 64 kb/s	7-2
7.6	44/48 Channels Using 32-kb/s ADPCM	7-2
7.7	23 Channels at 64 kb/s with Overhead Channel	7-2
8.	Maintenance	8-1
8.1	Remote Alarm Indication (RAI)	8-1
8.2	Alarm Indication Signal (AIS)	8-1
8.3	Loopbacks	8-1
8.4	DS1 Idle Signal	8-2
9.	DS1 Performance	9-1
9.1	Accuracy Objective	9-1
9.2	Availability Objectives	9-1
9.3	DS1 Performance Tests	9-2
9.3.1	Short-Duration Test Limits	9-2
9.3.2	Long-Duration Test Limits	9-3
10.	POT Network Channel Interface Codes	10-1
10.1	General	10-1
10.2	Interface Code Components	10-1
10.3	Code Selection	10-1
10.4	NCI Code Combinations	10-3
10.5	Interface Illustration	10-4
11.	Connector Arrangements	11-1
12.	DS1 Interface Connector	12-1
12.1	General Information	12-1
12.2	Connector Functions	12-1

12.3 Loopback Activate/Deactivate Methods	12-2
13. Cable Characteristics	13-1
13.1 Customer Installation Cables	13-1
13.2 Carrier Cables	13-1
Appendix A: References	A-1
Appendix B: Glossary	B-1

List of Figures

Figure 2-1	Network Interface	2-7
Figure 2-2	Isolated Pulse Template and Corner Points	2-8
Figure 2-3	Pulse Amplitude Envelope with 60 Hz Longitudinal Currents	2-9
Figure 4-1	Frequency Weighting Functions for Jitter Specifications	4-3
Figure 6-1	Channelized DS1 Frame Bit Assignment	6-4
Figure 10-1	Interface Types 04DU9-XX Operability Requirements	10-4
Figure 11-1	Connector Pin Assignments (8-Position/RJ48C)	11-2
Figure 11-2	Connector Pin Assignments (8-Position/RJ48X with Shorting Bars)	11-3
Figure 11-3	Connector Pin Assignments (50-Position/RJ48M)	11-4
Figure 11-4	Connector Pin Assignments (50-Position/RJ48H)	11-5
Figure 12-1	Deployment of DS1 Interface Connector at the NI	12-4
Figure 13-1	Attenuation and Phase Shift of PIC Cable	13-2
Figure 13-2	Real and Reactive Components of Characteristic Impedance	13-3

List of Tables

Table 6-1	Superframe Format	6-5
Table 6-2	Extended Superframe Format	6-6
Table 10-1	Total Wires	10-2
Table 10-2	Glossary of Protocol Codes and Selected Options	10-2
Table 10-3	Impedance	10-3
Table 10-4	Compatible Interface Combinations	10-3