

Table of Contents

Preface	xxxiii
1 Introduction	
1.1 General	1-1
1.2 Purpose and Limitations of This Document	1-2
1.3 Organization of the Document	1-3
1.4 Changes to GR-905-CORE	1-5
1.4.1 New Information for GR-905-CORE, Issue 20	1-5
1.4.2 New Information for GR-905-CORE, Issue 19	1-6
1.4.3 New Information for GR-905-CORE, Issue 18	1-7
1.4.4 New Information in GR-905-CORE, Issue 17	1-7
1.4.5 New Information in GR-905-CORE, Issue 16	1-8
1.4.6 New Information in GR-905-CORE, Issue 15	1-9
1.4.7 New Information in GR-905-CORE, Issue 14	1-9
1.4.8 New Information in GR-905-CORE, Issue 13	1-10
1.4.9 New Information in GR-905-CORE, Issue 12	1-10
1.4.10 New Information in GR-905-CORE, Issue 11	1-11
1.4.11 New Information in GR-905-CORE, Issue 10	1-11
1.4.12 Changes to GR-905-CORE, Issue 9	1-12
1.4.13 Changes to GR-905-CORE, Issue 8	1-12
1.4.14 Changes to GR-905-CORE, Issue 7	1-12
1.4.15 Changes to GR-905-CORE, Issue 6	1-13
1.4.16 Changes to GR-905-CORE, Issue 5	1-13
1.4.17 Changes to GR-905-CORE, Issue 4	1-13
1.4.18 Changes to GR-905-CORE, Issue 3	1-14
1.4.19 Changes to GR-905-CORE, Issue 2, Revision 2	1-14
1.4.20 Changes to GR-905-CORE, Issue 2, Revision 1	1-15
1.5 Requirements Terminology	1-16
1.6 Requirement Labeling Conventions	1-16
1.6.1 Numbering of Requirement and Related Objects	1-16
1.6.2 Requirement, Conditional Requirement, and Objective Identification	1-17
1.6.3 Requirements in This GR	1-17
1.7 Related Documents	1-17
2 CCS Network Interconnection Architecture	
2.1 Network Architecture	2-2
2.1.1 Overview	2-2
2.1.2 CCS Network Interconnection Architectures	2-4
2.1.2.1 Interconnection Using STPs and D-Link Quads	2-5
2.1.2.2 Interconnection Using A-Links	2-5
2.1.2.3 Other Interconnections	2-5
2.1.3 CCS Network Provider Network Topology	2-10
2.1.4 CCS Network Provider Network Access	2-11
2.1.5 CCS Network Availability	2-11
2.1.6 CCS Network Engineering	2-11

2.1.6.1	Fundamental Guidelines for Signaling Link Diversity and Capacity Planning	2-12
2.1.6.1.1	A-Link Set Diversity and Capacity Planning	2-13
2.1.6.1.2	D-Link Set Diversity and Capacity Planning	2-14
2.1.6.1.3	Link Augmentation	2-15
2.2	Protocol Architecture	2-16
2.2.1	Overview	2-16
2.2.1.1	Message Transfer Part (MTP)	2-16
2.2.1.2	Signaling Connection Control Part (SCCP)	2-16
2.2.1.3	Integrated Services Digital Network User Part (ISDNUP)	2-16
2.2.1.4	Transaction Capabilities Application Part (TCAP)	2-17
2.2.1.5	Operations, Maintenance, and Administration Part (OMAP)	2-17
2.2.2	Addressing of Signaling Points	2-18
2.2.2.1	Assignment of Network Codes	2-19
2.2.2.2	Assignment of Cluster Codes	2-21
2.2.2.3	Assignment of Cluster Member Codes	2-22
2.2.2.4	Multiple Point Code Capability	2-22
2.2.3	Interconnecting STP Protocol Requirements	2-22
2.2.3.1	Protocol	2-22
2.2.3.2	Interconnecting STP Functions	2-24
2.2.3.2.1	Internetwork Routing	2-24
2.2.3.2.2	Message Screening	2-26
2.3	Interconnection to VOP Networks	2-28
2.3.1	VOP Network Architecture	2-28
2.3.1.1	Access Gateway (AG)	2-29
2.3.1.2	Trunk Gateway (TG)	2-30
2.3.1.3	Signaling Gateway (SG)	2-30
2.3.1.4	Call Connection Agent (CCA)	2-30
2.3.1.5	Service Agent (SA)	2-30
2.3.1.6	Routing and Translation Server (RTS)	2-31
2.3.1.7	Billing Agent (BA)	2-31
2.3.1.8	Feature Server (FS)	2-31
2.3.1.9	Core Network	2-31
2.3.2	VOP Network Interconnection	2-31
2.3.3	Interconnection to SIP Networks	2-34
2.4	Interconnection to BICC Networks and to Networks Using ATM HSLs and IPVHSLs	2-35
2.4.1	BICC Networks	2-35
2.4.2	ATM HSLs and IPVHSLs	2-36

3 Interface Protocols and Messages

3.1	Message Transfer Part	3-1
3.1.1	Signaling Link Functions	3-1
3.1.1.1	SS7 Signal Units	3-2
3.1.1.2	Functions and Codes of the Signal Unit Fields	3-3
3.1.1.3	Initial Alignment Procedure	3-4
3.1.1.4	Processor Outage	3-5
3.1.1.5	Level 2 Flow Control	3-5
3.1.2	Signaling Network Functions	3-6
3.1.2.1	MTP Message Handling	3-6

3.1.2.1.1	Message Labeling	3-6
3.1.2.2	Message Discrimination and Distribution	3-7
3.1.2.3	MTP Routing	3-7
3.1.2.3.1	Signaling Route Determination	3-7
3.1.2.3.2	Signaling Link Selection	3-8
3.1.2.4	Congestion Control and Message Priorities	3-8
3.1.2.5	MTP Network Management Functions	3-9
3.1.3	Signaling Traffic Management	3-9
3.1.3.1	Emergency Changeover	3-10
3.1.3.2	Signaling Link Changeback	3-12
3.1.3.3	Management Inhibiting	3-12
3.1.3.4	Forced Rerouting	3-13
3.1.3.5	Controlled Rerouting	3-13
3.1.3.6	MTP Restart Procedure	3-14
3.1.4	Signaling Link Management	3-16
3.1.4.1	Signaling Link Activation/Deactivation	3-16
3.1.4.2	Procedures to Minimize Link Oscillation	3-17
3.1.5	Signaling Route Management	3-17
3.1.5.1	Transfer Prohibited/Transfer Cluster Prohibited Message	3-17
3.1.5.2	Transfer Allowed/Transfer Cluster Allowed Message	3-19
3.1.5.3	Transfer Restricted/Transfer Cluster Restricted Message	3-19
3.1.5.4	Transfer Controlled Message	3-20
3.1.5.5	Signaling Route Set Test Message	3-21
3.1.5.6	Signaling Route Set Congestion Test Message	3-21
3.1.6	CCS Network Provider STPs to ICN CCSSO Interface Alternative	3-22
3.2	ISDNUP Non-Capability (Non-Call) Related Messages	3-23
3.2.1	Blocking Messages	3-23
3.2.1.1	CCS Network Provider Procedures at Sending Switch	3-23
3.2.1.2	CCS Network Provider Procedures at Receiving Switch	3-24
3.2.1.3	ICN Procedures at Receiving Switch	3-24
3.2.2	Circuit Group Blocking Messages	3-24
3.2.2.1	CCS Network Provider Procedures at Sending Switch	3-25
3.2.2.2	CCS Network Provider Procedures at Receiving Switch	3-26
3.2.2.3	ICN Procedures at Receiving Switch	3-27
3.2.3	Circuit Group Reset Messages	3-27
3.2.3.1	CCS Network Provider Procedures at Sending Switch	3-28
3.2.3.2	CCS Network Provider Procedures at Receiving Switch	3-28
3.2.3.3	ICN Procedures at Receiving Switch	3-29
3.2.4	Circuit Group Unblocking Messages	3-29
3.2.4.1	CCS Network Provider Procedures at Sending Switch	3-30
3.2.4.2	CCS Network Provider Procedures at Receiving Switch	3-30
3.2.4.3	ICN Procedures at Receiving Switch	3-30
3.2.5	Circuit Query Messages	3-30
3.2.5.1	CCS Network Provider Procedures at Sending Switch	3-31
3.2.5.2	Procedures at Receiving Switch	3-33
3.2.6	Circuit Validation Test Messages	3-34
3.2.6.1	CCS Network Provider Procedures at Sending Switch	3-34
3.2.6.2	Procedures at Receiving Switch	3-35
3.2.7	Continuity Check Request Message and Loop Back Acknowledgment Message	3-35

3.2.7.1	CCS Network Provider Procedures at Sending Switch	3-35
3.2.7.2	Procedures at Receiving Switch	3-36
3.2.8	Dual Seizure	3-36
3.2.9	Reset Circuit Message	3-36
3.2.9.1	CCS Network Provider Procedures at Sending Switch	3-36
3.2.9.2	CCS Network Provider Procedures at Receiving Switch	3-37
3.2.9.3	ICN Procedures at Receiving Switch	3-37
3.2.10	Test Calls	3-37
3.2.11	Unblocking Messages	3-39
3.2.11.1	CCS Network Provider Procedures at Sending Switch	3-39
3.2.11.2	CCS Network Provider Procedures at Receiving Switch	3-39
3.2.11.3	ICN Procedures at Receiving Switch	3-39
3.2.12	Unequipped Circuit Identification Code Message	3-39
3.2.12.1	CCS Network Provider Procedures at Sending Switch	3-40
3.2.12.2	CCS Network Provider Procedures at Receiving Switch	3-41
3.2.12.3	ICN Procedures at Receiving Switch	3-41
3.3	Testing and Maintenance Messages	3-42
3.3.1	Signaling Link Test Message	3-42
3.3.2	Messages in the MRVT and SRVT	3-42
3.3.2.1	Messages in the MRVT	3-43
3.3.2.1.1	CCS Network Provider Procedures at Sending Interconnecting STP	3-43
3.3.2.1.2	CCS Network Provider Procedures at Receiving Interconnecting STP	3-44
3.3.2.1.3	ICN Procedures at Receiving Node	3-44
3.3.2.2	Messages in the SRVT	3-44
3.3.2.2.1	CCS Network Provider Procedure at Sending Interconnecting STP	3-45
3.3.2.2.2	CCS Network Provider Procedure at Receiving Interconnecting STP	3-45
3.3.2.2.3	ICN Procedure at Receiving Node	3-46

4 Capabilities Supported

4.1	Internetwork Call Control (Non-ISDN)	4-1
4.1.1	Internetwork Call Control Messages and Flows	4-2
4.1.1.1	Call Flow Variations	4-5
4.1.2	Originating InterLATA Call Control Access	4-8
4.1.2.1	Dialing Plan	4-8
4.1.2.1.1	Presubscription	4-8
4.1.2.1.2	Called Party Address Parameter Based on Dialed Digits	4-9
4.1.2.2	Originating Call Screening	4-12
4.1.2.3	Originating Automatic Message Accounting (AMA) Recording	4-12
4.1.2.4	Direct Access to ICN	4-13
4.1.2.5	Access via Access Tandem	4-14
4.1.2.5.1	All-SS7 Originating Access	4-14
4.1.2.5.2	MF from EO to AT, SS7 from AT to ICN	4-14
4.1.2.5.3	SS7 from EO to AT, MF from AT to ICN	4-14
4.1.2.6	QoR Scenario	4-19
4.1.2.7	Originating Access Mandatory Parameters	4-19
4.1.2.8	Originating Access Additional Parameters	4-19

4.1.2.8.1	Calling Party Number (CPN)	4-19
4.1.2.8.2	Charge Number	4-19
4.1.2.8.3	Originating Line Information Parameter	4-20
4.1.2.8.4	Interaction of Charge Number, CPN, and OLIP	4-20
4.1.2.8.5	Carrier Selection Indicator	4-20
4.1.2.8.6	Transit Network Selection (TNS) Parameter	4-21
4.1.2.8.7	Service Code Parameter	4-21
4.1.2.8.8	Carrier Identification Parameter (CIP)	4-22
4.1.2.8.9	Parameters Associated with Call Forwarding	4-22
4.1.2.8.10	Generic Address Parameter (GAP)	4-23
4.1.2.8.11	Jurisdiction Information Parameter (JIP)	4-23
4.1.2.8.12	Hop Counter Parameter	4-23
4.1.2.8.13	Generic Name Parameter	4-23
4.1.2.8.14	Parameters Associated with E9-1-1 Calls	4-23
4.1.2.9	Call Utilizes LNP and Requires an Intermediate Carrier to Complete	4-24
4.1.3	Terminating Call Control Access	4-25
4.1.3.1	Parameters Received by the Terminating Entry Switch	4-25
4.1.3.2	QoR Scenario	4-29
4.1.3.3	Terminating Call Screening	4-29
4.1.3.4	Terminating AMA Recording	4-29
4.1.4	Tones and Announcements	4-30
4.1.4.1	Busy Conditions	4-30
4.1.4.2	Events Resulting in an Unsuccessful Call	4-31
4.1.5	Other LATA Carrier Interconnection	4-32
4.1.5.1	Calls Routed Based on Carrier Identification Code	4-33
4.1.5.2	Calls Routed Based on Dialed Number	4-35
4.1.6	Tandem Service Provider (TSP) Interconnection	4-39
4.1.6.1	TSP Interconnection for Originating Traffic	4-40
4.1.6.2	TSP Interconnection for Terminating Traffic	4-40
4.1.7	Trunk Type Based on Routing Decisions	4-43
4.1.8	Completion of Transmission Path	4-46
4.1.9	Procedures for Handling Unrecognized Messages/Parameters	4-46
4.1.9.1	Receipt of an Unrecognized Message Type	4-46
4.1.9.2	Receipt of an Unrecognized Parameter	4-46
4.1.9.3	Receipt of an Unrecognized Parameter Value	4-46
4.1.10	ISDNUP Reaction to TFC/Isolation	4-47
4.1.10.1	Congestion/Isolation at Call Origination	4-47
4.1.10.2	Congestion/Isolation During Call Setup	4-48
4.1.10.3	Congestion During Call Release	4-49
4.1.10.4	Resetting Circuits	4-49
4.1.10.5	Other Procedures	4-49
4.1.10.6	ICN ISDNUP Reaction to TFC/Isolation	4-50
4.1.11	Automatic Congestion Control	4-50
4.1.11.1	Detection of Congestion and Transmission of Automatic Congestion Level Parameter	4-51
4.1.11.2	Reception of and Response to ACL Parameter	4-51
4.1.11.3	ACC Procedures for ICNs	4-52
4.1.12	Hop Counter Procedures	4-53
4.2	Additional SS7 Capabilities Supporting ISDN	4-53

4.2.1	Internetwork Call Control Messages and Flows	4-54
4.2.1.1	ISDN Calling Party to ISDN Called Party	4-55
4.2.1.1.1	Call Flow Variations	4-57
4.2.1.1.2	SS7-to-MF Interworking	4-63
4.2.1.1.3	MF-to-SS7 Interworking	4-63
4.2.1.2	ISDN Calling Party to Non-ISDN Called Party	4-63
4.2.1.2.1	Call Flow Variations	4-67
4.2.1.3	Non-ISDN Calling Party to ISDN Called Party	4-67
4.2.1.3.1	Call Flow Variations	4-67
4.2.2	Originating Call Control Access	4-71
4.2.2.1	Dialing Plan	4-71
4.2.2.1.1	Subscription Parameters per DN	4-72
4.2.2.1.2	Presubscription	4-72
4.2.2.2	Originating Access Modified and New Mandatory Parameters	4-72
4.2.2.2.1	Forward Call Indicators Parameter	4-72
4.2.2.2.2	User Service Information Parameter	4-73
4.2.2.2.3	Cause Indicators Parameter	4-73
4.2.2.2.4	Event Information Parameter	4-73
4.2.2.2.5	Optional Backwards Call Indicators	4-73
4.2.2.2.6	Called Party Number Parameter	4-73
4.2.2.3	Originating Access Modified and Additional Parameters	4-73
4.2.2.3.1	Calling Party Number (CPN) Parameter	4-73
4.2.2.3.2	Generic Address Parameter (GAP)	4-74
4.2.2.3.3	Access Transport Parameter (ATP)	4-75
4.2.2.3.4	Jurisdiction Information Parameter (JIP)	4-75
4.2.2.3.5	Other Optional Parameters	4-75
4.2.2.3.6	QoR Scenario	4-76
4.2.2.4	Originating Automatic Message Accounting (AMA) Recording	4-76
4.2.3	Terminating Call Control Access	4-76
4.2.3.1	Parameters Received by the Terminating Entry Switch	4-76
4.2.3.2	Terminating Access AMA Recording	4-77
4.2.3.3	QoR Scenario	4-78
4.2.4	Completion of Transmission Path	4-78
4.2.4.1	CCS Network Provider Originating or Tandem CCSSO	4-78
4.2.4.2	CCS Network Provider Terminating CCSSO	4-78
4.2.4.3	ICN Tandem CCSSO	4-79
4.2.5	ISDN Call Forwarding	4-79
4.2.5.1	Terminating Traffic from an ICN - Calls to an ISDN Basic Rate Base DN Which Are ISDN Call Forwarded	4-79
4.2.5.2	Terminating Traffic to an ISDN Primary Rate Interface with Class II Equipment	4-80
4.2.5.3	Network Interface for Calls Which are ISDN Call Forwarded from an ISDN Interface	4-80
4.2.5.3.1	Original Called Number (OCN) Parameter	4-80
4.2.5.3.2	Redirecting Number (RN) Parameter	4-80
4.2.5.3.3	Redirection Information (RI) Parameter	4-81

5 Capability Related Protocol

5.1	ISDN Internetwork Call Control Protocol	5-1
5.1.1	Address Complete Message	5-2

5.1.1.1	Origination	5-2
5.1.1.2	Subsequent Signaling	5-2
5.1.2	Answer Message	5-3
5.1.2.1	Origination	5-3
5.1.2.2	Subsequent Signaling	5-4
5.1.3	Circuit Reservation Message	5-4
5.1.3.1	Mandatory Parameters	5-5
5.1.4	Circuit Reservation Acknowledgment	5-5
5.1.5	Continuity Check	5-5
5.1.5.1	Continuity Check for CCSSOs with the Multiple Point Code Capability	5-9
5.1.6	Exit Message	5-10
5.1.7	Initial Address Message	5-10
5.1.7.1	Traffic Routed Based on Carrier Identification Code	5-11
5.1.7.1.1	Call Originates in CCS Network Provider Network	5-12
5.1.7.1.2	Call Originates in OLC's Network	5-22
5.1.7.1.3	Call Terminates in CCS Network Provider Network	5-24
5.1.7.1.4	Call Terminates in OLC's Network	5-27
5.1.7.2	Traffic Routed Based on Dialed Digits	5-28
5.1.7.2.1	Call Originates in CCS Network Provider Network	5-29
5.1.7.2.2	Call Originates in OLC's Network	5-33
5.1.7.2.3	CCS Network Provider Network Receives a Terminating Call	5-34
5.1.7.2.4	Call Terminates in OLC's Network	5-36
5.1.8	Release Message	5-38
5.1.9	Release Complete Message	5-40
5.1.9.1	Origination	5-40
5.1.10	Resume Message	5-40
5.1.10.1	Origination	5-41
5.1.10.2	Subsequent Signaling	5-41
5.1.11	Suspend Message	5-41
5.1.11.1	Origination	5-41
5.1.11.2	Subsequent Signaling	5-41
5.1.12	Call Progress Message	5-41
5.1.13	Confusion Message	5-42
5.1.13.1	Origination	5-42
5.1.13.2	Subsequent Signaling	5-42
5.2	ISDNUP Protocol to Support ISDN Access	5-43
5.2.1	Address Complete Message (ACM) for ISDN Access	5-43
5.2.1.1	Origination	5-43
5.2.1.2	Subsequent Signaling	5-45
5.2.2	Answer Message for ISDN Access	5-46
5.2.2.1	Origination	5-46
5.2.2.2	Subsequent Signaling	5-46
5.2.3	Call Progress Message for ISDN Access	5-47
5.2.3.1	Origination	5-47
5.2.3.2	Subsequent Signaling	5-48
5.2.4	Initial Address Message for ISDN Access	5-48
5.2.4.1	Origination	5-48
5.2.4.2	Subsequent Signaling	5-51

5.2.5 Release Message for ISDN Access	5-51
6 Physical Level Specifications	
6.1 Bearer Facility Transmission Rate	6-1
6.2 Diverse Physical Level Facility Routing for Combined Link Sets	6-1
6.2.1 Diversity Provisioning and Maintenance Guidelines	6-2
6.3 Facility Transmission Signal Structure	6-2
6.3.1 DS1 Signal Structure	6-2
6.3.2 DS0 Signal Structure	6-2
6.4 Physical Level Link Interface	6-3
6.4.1 V.35 Interface	6-3
6.4.2 DS0 Interface	6-3
6.5 Synchronization	6-3
7 Performance	
7.1 Signaling Network Transport Time	7-1
7.1.1 Network Components	7-1
7.1.2 Reference Connections	7-3
7.1.3 Time Intervals	7-4
7.1.4 Network Performance Guidelines	7-9
7.1.4.1 Internetwork Call Control	7-9
7.1.4.2 Database Queries and Responses	7-13
7.1.5 Network Timing Requirements	7-13
7.2 Signaling Network Availability	7-16
7.2.1 Diversity	7-16
7.2.1.1 Diversity Analysis for the Network Access Segment	7-19
7.2.1.1.1 Reference Model and Terminology	7-20
7.2.1.1.2 A-Link Diversity Analysis	7-21
7.2.1.2 Diversity Analysis for the Backbone Network Segment	7-24
7.2.1.2.1 Reference Model and Terminology	7-24
7.2.1.2.2 D-Link Diversity Analysis	7-24
7.3 Lost Message Probability	7-27
7.4 Undetected Error Probability	7-27
7.5 Message-Out-Of-Sequence Probability	7-27
7.6 Signaling Link Error Performance	7-28
8 Interface Provisioning, Operations, and Maintenance	
8.1 Introduction	8-1
8.1.1 Operational Guidelines	8-1
8.1.2 Assumptions	8-1
8.2 Link Provisioning and Maintenance	8-1
8.2.1 General Link Provisioning	8-2
8.2.2 Timer Values	8-2
8.2.3 Procedural Information	8-2
8.2.4 Other Protocol Information	8-3
8.2.5 Link Measurement Data	8-4
8.2.6 Link Control Office Designation	8-4
8.2.6.1 General Responsibilities	8-5
8.2.6.2 General Link Responsibilities	8-5

8.2.6.3	Link Provisioning and Maintenance Coordination Responsibilities	8-7
8.2.6.4	Signaling Link Control Designation Responsibilities	8-7
8.2.7	Exchange Point of Contact Information	8-7
8.2.8	Route Diversity Management	8-7
8.3	SS7 Trunk Provisioning and Maintenance	8-7
8.3.1	Conversion from MF to SS7 Signaling	8-8
8.3.2	Management of Dual Seizures	8-8
8.3.2.1	Alarm Reporting Procedures	8-8
8.3.3	Continuity Check Procedure	8-8
8.3.3.1	Frequency of Continuity Tests	8-9
8.3.4	Assignment Criteria	8-9
8.3.4.1	Separation of Traffic by Trunk Groups	8-10
8.3.5	Exchange of Trunk Provisioning Information and Translations Questionnaire	8-10
8.3.6	Tones and Announcements	8-11
8.4	Link Testing (Level One)	8-12
8.5	Compatibility Testing	8-12
8.5.1	Background	8-12
8.5.2	Terminology	8-12
8.5.3	Objective	8-13
8.6	Internetwork Compatibility Tests for Levels 2 and 3	8-13
8.6.1	Intrusive Compatibility Tests	8-16
8.6.1.1	Level 2 Tests	8-16
8.6.1.2	Level 3 Tests	8-35
8.6.2	Non-Intrusive Compatibility Tests	8-36
8.6.2.1	Level 2 Tests	8-36
8.6.2.2	Level 3 Tests	8-38
8.7	Signaling Route Management Tests	8-45
8.8	ISDNUP Call Setup Tests	8-50
8.8.1	Trunk Maintenance Tests	8-51
8.8.2	Call Setup Tests	8-68
8.9	Non-ISDN Call Setup Call-Through Tests	8-77
8.9.1	Test Configurations	8-77
8.9.1.1	SS7 Trunk Interface Compatibility Testing Arrangement	8-77
8.9.1.2	SS7 Trunk Interface End-to-End Testing Arrangement	8-80
8.9.1.3	Test Equipment	8-84
8.9.1.4	Messages Sequences and Protocol Simulator	8-84
8.9.1.5	Trunk Test Set	8-85
8.9.1.6	Test Procedures	8-85
8.9.1.7	Protocol Analysis	8-85
8.10	Intrusive Tests	8-88
8.11	Introduction to Compatibility Tests for ISDN Access	8-104
8.11.1	Operational Guidelines	8-104
8.11.2	Prerequisites	8-104
8.11.3	Purpose	8-104
8.11.4	ISDN Impacts on ISDNUP Messages	8-105
8.11.5	Description of Tests	8-105
8.12	Call-Through Tests	8-105
8.12.1	Recommended Minimum Subset of Call-Through Tests	8-105
8.13	Test-Set Generated Tests	8-109

8.13.1	Basic Calls	8-109
8.13.2	IAM Followed By ANM	8-110
8.13.3	REL With Cause, Temporary Failure	8-111
8.13.4	Terminating REL With Cause, Bearer Capability Not Implemented, User	8-111
8.13.5	Terminating REL With Cause, Bearer Capability Not Implemented, Remote Local Network	8-112
8.13.6	Terminating REL With Cause, Normal Release (Data)	8-112
8.13.7	Originating REL After ACM (Data)	8-113
8.13.8	Originating REL With Cause, Normal Release (Data)	8-113
8.13.9	Terminating REL With Cause, User Busy	8-114
8.13.10	Terminating REL With Cause, Call Rejected, Location User	8-114
8.13.11	Upgrade Routing (Optional Test, Network Architecture Dependent)	8-115
8.13.12	Terminating REL With Cause, User Alerting, No Answer	8-115
8.13.13	Terminating REL With Cause, No User Responding (Data)	8-116
8.13.14	ACM With "Call Delay at the Terminating Interface"	8-116
8.13.15	ACM With "Call Delay at the Terminating Interface (Excessive Delay)," Followed by ANM	8-117
8.13.16	Intercept RELs	8-117
8.13.17	Intercept ACM, Provide Tone or Announcement	8-118
8.13.18	REL on Announcement Time-Out	8-119
8.13.19	Intercept ACM, Route to Tone or Announcement	8-119
8.13.20	CPG After ACM	8-120
8.13.21	T _t Expiration	8-121
8.13.22	CPG With ALERTing	8-121
8.13.23	CPG With ALERTing, ANM	8-122
8.13.24	ASC Route Does Not Support Requested Bearer	8-122
8.13.25	GAP Without CPN	8-123
8.13.26	GAP With CPN	8-123

Appendix A: Message and Parameter Formats and Codes

A.1	MTP Message Formats	A-1
A.1.1	General	A-1
A.1.2	Routing Label	A-2
A.1.3	Heading Code (H0)	A-2
A.1.4	Changeover Message	A-3
A.1.4.1	Format	A-3
A.1.4.2	Fields	A-3
A.1.4.3	Signal Codes	A-3
A.1.5	Changeback Message	A-4
A.1.5.1	Format	A-4
A.1.5.2	Fields	A-4
A.1.5.3	Signal Codes	A-4
A.1.5.4	Changeback Code	A-4
A.1.6	Emergency Changeover Message	A-5
A.1.6.1	Format	A-5
A.1.6.2	Fields	A-5
A.1.6.3	Signal Codes	A-5
A.1.7	Transfer-Prohibited Message	A-6

A.1.7.1	Format	A-6
A.1.7.2	Fields	A-6
A.1.7.3	Signal Codes	A-6
A.1.7.4	Signaling Point Identity	A-6
A.1.8	Transfer-Allowed Message	A-7
A.1.8.1	Format	A-7
A.1.8.2	Fields	A-7
A.1.8.3	Signal Codes	A-7
A.1.8.4	Signaling Point Identity	A-7
A.1.9	Transfer-Restricted Message	A-8
A.1.9.1	Format	A-8
A.1.9.2	Fields	A-8
A.1.9.3	Signal Codes	A-8
A.1.9.4	Signaling Point Identity	A-8
A.1.10	Signaling-Route-Set-Test Message	A-9
A.1.10.1	Format	A-9
A.1.10.2	Fields	A-9
A.1.10.3	Signal Codes	A-9
A.1.11	Management Inhibit Message	A-10
A.1.11.1	Format	A-10
A.1.11.2	Fields	A-10
A.1.11.3	Signal Codes	A-10
A.1.12	Transfer-Controlled Message	A-11
A.1.12.1	Format	A-11
A.1.12.2	Fields	A-11
A.1.12.3	Signal Codes	A-11
A.1.12.4	Signaling Point Identity	A-11
A.1.12.5	Status Field	A-11
A.1.13	Signaling-Route-Set-Congestion-Test Message	A-12
A.1.13.1	Format	A-12
A.1.13.2	Fields	A-12
A.1.13.3	Signal Codes	A-12
A.1.14	Traffic Restart Message	A-12
A.1.14.1	Format	A-12
A.1.14.2	Fields	A-13
A.1.14.3	Signal Codes	A-13
A.1.15	Abbreviations Used for MTP Message H1 Codes	A-13
A.2	ISDNUP Formats	A-15
A.2.1	ISDNUP Message Formats	A-15
A.2.2	ISDNUP Parameter Formats	A-25
A.2.2.1	Backward Call Indicators Parameter	A-25
A.2.2.2	User Service Information Parameter	A-27
A.2.2.3	Called Party Number Parameter	A-28
A.2.2.4	Calling Party Number Parameter	A-30
A.2.2.5	Calling Party's Category	A-31
A.2.2.6	Carrier Selection	A-32
A.2.2.7	Cause Indicators Parameter	A-33
A.2.2.8	Charge Number Parameter	A-36
A.2.2.9	Circuit Group Characteristics Indicator	A-38
A.2.2.10	Circuit Group Supervision Message Type Indicator	A-39

A.2.2.11	Circuit Identification Name Parameter	A-40
A.2.2.12	Circuit State Indicator Parameter	A-41
A.2.2.13	Circuit Validation Response Indicator Parameter	A-42
A.2.2.14	CLLI™ Code Parameter	A-42
A.2.2.15	Continuity Indicators Parameter	A-43
A.2.2.16	Forward Call Indicators	A-43
A.2.2.17	Message Type Parameter	A-45
A.2.2.18	Nature of Connection Indicators	A-46
A.2.2.19	Originating Line Information Parameter	A-47
A.2.2.20	Outgoing Trunk Group Number	A-48
A.2.2.21	Range and Status Parameter	A-48
A.2.2.22	Service Code Parameter	A-49
A.2.2.23	Suspend/Resume Indicators	A-50
A.2.2.24	Transit Network Selection Parameter	A-50
A.2.2.25	Carrier Identification Parameter	A-52
A.2.2.26	Event Information Indicators	A-54
A.2.2.27	Optional Backward Call Indicators	A-55
A.2.2.28	Original Called Number Parameter	A-56
A.2.2.29	Redirecting Number Parameter	A-58
A.2.2.30	Redirection Information Parameter	A-58
A.2.2.31	Automatic Congestion Level Parameter	A-59
A.2.2.32	Hop Counter Parameter	A-59
A.2.2.33	Jurisdiction Information Parameter	A-60
A.2.2.34	Generic Address Parameter	A-61
A.2.2.35	Redirect Capability Parameter	A-63
A.2.2.36	Redirect Counter Parameter	A-64
A.2.2.37	Redirection Number Parameter	A-64
A.2.2.38	Generic Digits Parameter	A-66
A.2.2.39	Calling Geodetic Location	A-67
A.2.3	Modified ISDNUP Messages to Support ISDN Access	A-77
A.2.4	Modified ISDNUP Parameters to Support ISDN Access	A-79
A.2.4.1	User Service Information - Modified for ISDN Access	A-79
A.2.4.2	Calling Party Number Parameter - Modified for ISDN Access	A-81
A.2.4.3	Cause Indicators Parameter - Modified for ISDN Access	A-83
A.2.4.4	Original Called Number Parameter - Modified for ISDN Access	A-87
A.2.4.5	Redirecting Number Parameter - Modified for ISDN Access	A-89
A.2.4.6	Redirection Information Parameter	A-90
A.2.5	Additional ISDNUP Parameters to Support ISDN Access	A-91
A.2.5.1	Access Transport Parameter	A-91
A.2.5.2	Notification Indicator Parameter	A-92
A.3	Testing and Maintenance Message Formats	A-93
A.3.1	General	A-93
A.3.2	Routing Label	A-93
A.3.3	Signaling Link Test Messages	A-93
A.3.3.1	Format	A-93
A.3.3.2	Fields	A-94
A.3.3.3	Signal Codes	A-94
A.3.4	Message Formats	A-95

Appendix B: Timer Values**Appendix C: Facility and Translation Requirements**

C.1 Call-Through Test Requirements	C-1
C.2 Test-Set Generated Test Requirements	C-1

Appendix D: Basic Network Test Configurations**Appendix E: Variables for Additional ISDN Call-Through Tests****Appendix F: Statement of Principles**

F.1 Introduction	F-1
F.2 Protection	F-1
F.3 Detection	F-2
F.4 Containment	F-2
F.5 Correction	F-3

Appendix G: Bearer Independent Call Control

G.1 Introduction	G-1
G.2 Motivation for BICC	G-1
G.3 BICC Architecture	G-2
G.3.1 BICC Network Architecture	G-2
G.3.2 BICC Protocol	G-3
G.3.3 BICC Messages and Parameters	G-3
G.3.3.1 BICC Messages and Parameters Different from ISUP Counterparts	G-4
G.3.3.1.1 Initial Address Message (IAM)	G-4
G.3.3.1.2 Continuity Message (COT)	G-5
G.3.3.1.3 Exit Message (EXM)	G-6
G.3.3.2 ISUP Messages Not Used in BICC Protocol	G-6
G.3.3.3 ISUP Parameters Not Used in BICC Protocol	G-7
G.4 BICC/ISUP Interconnection Issues	G-7
G.4.1 Parameters Modified for BICC from ISUP, and Defined for BICC but not for ISUP	G-8
G.4.1.1 CIC Parameter	G-8
G.4.1.2 APP	G-9
G.4.1.3 Global Call Reference Parameter	G-9
G.4.1.4 Inter-Nodal Traffic Group Identifier	G-10
G.4.2 Continuity Procedures	G-10
G.4.2.1 BICC Network Signaling to ISUP Network	G-10
G.4.2.2 ISUP Network Signaling to BICC Network	G-11
G.4.3 Parameters and Messages Defined for ISUP but not for BICC	G-12
G.4.4 Message Priority	G-12
G.4.5 Sample Call Flow	G-13

Appendix H: High Speed Links (HSLs)

H.1 Introduction	H-1
H.2 Asynchronous Transfer Mode High-Speed Links (ATM HSLs)	H-1
H.2.1 Motivation for ATM HSLs	H-1

H.2.2 ATM HSL Architecture	H-2
H.2.2.1 ATM HSL Network Architecture	H-2
H.2.2.1.1 Using ATM HSLs for Network Interconnection	H-4
H.2.2.1.2 ATM HSL Protocol	H-5
H.2.2.1.3 Physical Layer	H-5
H.2.2.1.4 ATM Layer	H-6
H.2.2.1.5 Signaling ATM Adaptation Layer (SAAL)	H-6
H.2.2.1.6 MTP Level 3	H-6
H.2.2.1.7 Differences between SS7/MTP2 and SS7/ATM	H-7
H.2.3 ATM HSL/MTP Interconnection Issues	H-9
H.2.3.1 ATM HSL Network Interconnection Architectures	H-10
H.2.3.2 Protocol Differences	H-11
H.2.3.2.1 STPs	H-11
H.2.3.2.2 Signaling Message Length	H-11
H.2.3.2.3 Signaling Link Selection (SLS)	H-12
H.2.3.2.4 Changeover Order Message Format	H-12
H.2.3.3 Differences in Engineering MTP Level 2 Links and ATM HSLs	H-12
H.2.3.4 Performance	H-13
H.2.3.4.1 Signaling Network Transport Time	H-13
H.2.3.4.2 Signaling Network Availability	H-13
H.2.3.4.3 Diversity	H-14
H.2.3.4.4 Messages	H-14
H.2.3.5 Interface Provisioning, Operations, and Maintenance	H-14
H.3 Internet Protocol Virtual High-Speed Links (IPVHSLs)	H-15
H.3.1 Motivation for IPVHSLs	H-15
H.3.2 IPVHSL Architecture	H-16
H.3.2.1 IPVHSL Network Architecture	H-16
H.3.2.2 IPVHSL Protocol	H-17
H.3.3 IPVHSL/MTP Interconnection Issues	H-19
H.3.3.1 Protocol Differences	H-21
H.3.3.1.1 Message Length	H-21
H.3.3.1.2 Signaling Link Selection	H-21
H.3.3.1.3 Differences in Engineering MTP Level 2 Links and IPVHSLs	H-22
H.3.3.2 Performance	H-23
H.3.3.2.1 Signaling Network Transport Time	H-23
H.3.3.2.2 Signaling Network Availability	H-24
H.3.3.2.3 Diversity	H-24
H.3.3.2.4 Messages	H-25
H.3.3.3 Interface Provisioning, Operations, and Maintenance	H-25

Appendix I: Session Initiation Protocol (SIP)

I.1 Introduction	I-1
I.2 Motivation	I-1
I.3 SIP Architecture	I-2
I.3.1 SIP Network Architecture	I-2
I.3.1.1 Clients	I-3
I.3.1.2 Servers	I-4
I.3.1.2.1 Proxy Servers	I-4
I.3.1.2.2 Redirect Servers	I-4

I.3.1.2.3 Location Servers	I-5
I.3.1.2.4 Registrar Server	I-5
I.3.2 SIP Protocol	I-5
I.3.3 SIP Messages and Parameters	I-6
I.3.3.1 SIP Request Messages	I-6
I.3.3.2 SIP Response Messages	I-7
I.3.3.3 SIP Message Headers	I-8
I.3.4 SIP Call Flows	I-9
I.3.4.1 ISUP to SIP Interworking	I-10
I.3.4.2 SIP to ISUP Interworking	I-11
I.3.4.3 ISUP to SIP to ISUP Interworking (SIP Bridging)	I-14
I.4 Summary	I-16

Appendix J: Probability Models for System Failures

J.1 Case 1: Series System	J-1
J.2 Case 2: Parallel System	J-2

Appendix K: IP Multimedia Subsystem (IMS) Overview

K.1 Introduction	K-1
K.2 3GPP IMS Architecture	K-1
K.3 3GPP IMS Session Flows	K-5
K.3.1 General End-to-End IMS Session Flow	K-5
K.3.2 Interworking with the PSTN	K-9
K.3.2.1 PSTN Origination	K-9
K.3.2.2 PSTN Termination	K-12
K.4 ATIS NGN Architecture	K-15
K.4.1 ATIS NGN Functional Architecture and Interfaces	K-15
K.5 Relationship Between 3GPP IMS and ATIS NGN Functional Architectures	K-18
K.6 3GPP IMS Architecture in Support of Emergency Calling	K-21
K.7 Enhancements to ATIS NGN Architecture to Support Emergency Services	K-23
K.7.1 Call Flow Example - Legacy Wireline Emergency Origination Delivered to an i3 PSAP	K-31
K.7.2 Call Flow Example - Legacy Wireline Emergency Origination Delivered to a Legacy PSAP	K-34
K.8 ATIS Activity Related to the Interconnection of IMS Origination Networks with Legacy and Next Generation Emergency Services Networks	K-38
K.8.1 Call Flow Example - Mobile Origination Routed to Legacy Selective Router using Cell-Based Location Information	K-42
K.8.2 IP to TDM Signaling Interworking to Support the Interconnection of IMS Origination Networks with Legacy Selective Routers	K-45

Appendix L: Network Interconnection to Support the Delivery of Legacy Emergency Call Originations to IP-Enabled PSAPs

L.1 Introduction	L-1
L.2 Overview of the NENA i3 Solution	L-1
L.2.1 Functional Elements of the i3 Solution	L-2
L.2.2 i3 Interfaces	L-5
L.2.3 Network Interconnection Architecture Overview	L-6

L.2.3.1	Interconnection of Legacy Wireline End Offices and Legacy Network Gateways	L-6
L.2.3.2	Interconnection of Legacy Wireless Mobile Switching Center and Legacy Network Gateway	L-8
L.2.3.3	Call Flow - Legacy Originating Network Directly Connected to Legacy Network Gateway	L-11
L.2.3.3.1	Call Flow in Support of Emergency Call Origination from Wireline Caller	L-12
L.2.3.3.2	Call Flow in Support of Emergency Call Origination from Wireless Caller - MPC/GMLC Location Used for Display; Mapped Location Used for Routing	L-13
L.2.3.4	Legacy Originating Network to i3 ESInet Interconnection Involving an SR	L-14
L.2.4	Signaling Protocol Interworking	L-15

Appendix M: Session Border Control (SBC) Overview

M.1	Introduction	M-1
M.2	Overview of SBC Functionality	M-1
M.2.1	Call Control Signaling Path (CCSP) Functionality	M-2
M.2.1.1	Access Control and Authentication, Authorization and Accounting (AAA)	M-2
M.2.1.2	Signaling Protocol Translation and Interworking	M-3
M.2.1.3	Call/Session-Based Routing	M-3
M.2.1.4	Data Services Platform (DSP) Service Control	M-3
M.2.1.5	Topology and End User Hiding	M-4
M.2.1.6	Security	M-4
M.2.2	Media Path (MP) Functionality	M-4
M.2.2.1	Access Control	M-4
M.2.2.2	Call/Session Managed Media Control	M-5
M.2.2.3	Topology Hiding	M-5
M.2.2.4	Security	M-5
M.2.3	Operations, Administration, Maintenance and Provisioning (OAMP) Functionality	M-5
M.3	Relationship with ATIS NGN Architecture	M-6
M.4	Relationship with ATIS Emergency Services Next Generation Network (ES-NGN) Architecture	M-7
M.5	Data Border Function	M-7

Appendix N: SS7-Based Interconnection Between Emergency Services IP Networks and Legacy Selective Routers to Support Emergency Call Delivery and Transfer

N.1	Introduction	N-1
N.2	Transition Scenarios Involving Legacy SR-to-Emergency Services IP Network (ESInet) Interconnection	N-3
N.2.1	Originating Network Served by Legacy SR; Target PSAP Served by ESInet	N-3
N.2.2	Originating Network Served by ESInet; Target PSAP Served by Legacy SR	N-10
N.2.2.1	Emergency Call Originates from a Legacy Originating Network	N-10

N.2.2.2 Emergency Call Originates from an i3-Compliant Originating Network	N-12
N.2.2.3 Call Flow Example - Originating Network Served by ESInet; Target PSAP Served by Legacy SR	N-13
N.2.3 Emergency Call Transferred from an i3 PSAP to PSAP Served by a Legacy SR	N-18
N.2.4 Emergency Call Transferred from a PSAP Served by a Legacy SR to an i3 PSAP	N-19

Appendix O: Support for Text to 9-1-1

O.1 Introduction	O-1
O.2 SMS to 9-1-1 Functional Architecture	O-2
O.3 Text Delivery to Legacy Selective Routers Via SS7-Supported Trunk Groups	O-5
O.4 Support for TCC-to-TCC Communication	O-6
O.5 Regulatory Considerations	O-7
O.6 Standards Support for MMS Text to 9-1-1	O-8
O.7 Support for Interworking with TTY	O-10

Appendix P: Improved Location Accuracy for Wireless Emergency Calling

P.1 Introduction	P-1
P.1.1 NEAD Privacy and Security Plan	P-4
P.2 High-Level Functional Architecture for Heightened Accuracy Location	P-6
P.2.1 Functional Elements	P-6
P.2.2 Functional Interfaces	P-9
P.2.2.1 NEAD Query Interface (Nq)	P-9
P.2.2.2 NEAM Provisioning Interface (Np)	P-12
P.2.2.3 Call Delivery Interface	P-16
P.2.2.4 NEAD-to-ELS Query Interface	P-17
P.2.2.5 ELS-NEAM Provisioning Interface	P-17
P.3 Considerations Related to Delivery of Heightened Accuracy Location to PSAPs	P-18

Appendix Q: References

Q.1 Telcordia Documents	Q-1
Q.2 Alliance for Telecommunications Industry Solutions (ATIS)	Q-3
Q.3 European Telecommunications Standards Institute (ETSI) Documents	Q-5
Q.4 Federal Communications Commission (FCC)	Q-5
Q.5 International Telecommunications Union - Telecommunications Standardization Sector Documents (ITU-T)	Q-5
Q.6 Internet Engineering Task Force (IETF) Documents	Q-5
Q.7 National Emergency Number Association (NENA) Documents	Q-6
Q.8 Network Interconnection/Interoperability Forum (NIIF) (formerly the Network Operations Forum [NOF]) Documents	Q-7
Q.9 3rd Generation Partnership Project (3GPP) Documents	Q-7
Q.10 Telecommunications Industry Association (TIA)	Q-8
Q.11 United States Telephone Association (USTA) Documents	Q-8
Q.12 Other Documents	Q-8
Q.13 Websites for Non-Telcordia Reference Material	Q-9

Q.14 Family of Requirements (FR) and Family of Documents (FD) Sets	Q-9
Q.15 Reference Notes	Q-9
Q.15.1 Contact Customer Service	Q-9
Q.15.2 Order Documents Online from our Information Store	Q-10
Q.15.3 Web Sites for Generic Requirements Information	Q-11
Q.15.4 Licensing Agreements for Telcordia Documents	Q-11

Appendix R: Glossary

R.1 Definitions of Terms	R-1
R.2 Acronyms and Abbreviations	R-4

List of Figures

Figure 1-1	GR-905-CORE and Other Document Relationships	1-1
Figure 2-1	Relationships Among Terms Defined in Text	2-4
Figure 2-2	STPs to ICN STPs Signaling Network Interconnection Architecture	2-7
Figure 2-3	STPs to ICN SEP Signaling Network Interconnection Architecture	2-8
Figure 2-4	STPs to ICN STP/Combined Node Signaling Network Interconnection Architecture	2-9
Figure 2-5	STPs to OLC A-Link Concentrator Signaling Network Interconnection Architecture	2-10
Figure 2-6	An Example of a CCS Network Architecture	2-12
Figure 2-7	A-Link Set Capacity Planning with 2-Way Diversity	2-13
Figure 2-8	D-Link Set Capacity Planning with 3-Way Diversity	2-15
Figure 2-9	SS7 Protocol Architecture	2-17
Figure 2-10	Routing Label Structure for North American Networks	2-18
Figure 2-11	Signaling Point Code (SPC) Structure	2-18
Figure 2-12	Conceptual View of Gateway Screening and Routing Functions	2-24
Figure 2-13	Key Elements in a VOP Network	2-29
Figure 2-14	Interconnection to PSTN	2-32
Figure 3-1	Format for MSU	3-3
Figure 3-2	Format for LSSU	3-3
Figure 3-3	Format for FISU	3-3
Figure 4-1	Typical Call Setup and Release (Assumes Calling Party Disconnect)	4-4
Figure 4-2	Call Flow Variations	4-7
Figure 4-3	Originating Call Control Access: Direct	4-10
Figure 4-4	Originating Call Control Access: Via Access Tandem - All SS7	4-11
Figure 4-5	Originating Access: Interworking Inband Exchange Access Signaling to SS7	4-15
Figure 4-6	Originating Access: Interworking Inband International Exchange Access Signaling to SS7	4-16
Figure 4-7	Originating Access: Interworking of SS7 to Inband Exchange Access Signaling	4-17
Figure 4-8	Originating Access: Interworking of SS7 to Inband International Exchange Access Signaling	4-18
Figure 4-9	Terminating Call Control Access: Direct	4-27
Figure 4-10	Terminating Call Control Access: Via Access Tandem	4-28
Figure 4-11	IntraLATA OLC Interconnection: Direct	4-36
Figure 4-12	IntraLATA OLC Interconnection: Via Tandem — All SS7	4-37
Figure 4-13	IntraLATA OLC Interconnection: Via Access Tandem — Interworking MF to SS7	4-38
Figure 4-14	IntraLATA OLC Interconnection: Via Access Tandem — Interworking SS7 to MF	4-39
Figure 4-15	Originating Call Control Access: CCS Network Provider EO with TSP Tandem CCSSO	4-41
Figure 4-16	Terminating Call Control Access: Via TSP Tandem	4-42
Figure 4-17	Illustration of Internetwork Trunk Groups	4-45

Figure 4-18	Typical Call Setup Between Two ISDN End Users	4-56
Figure 4-19	Call Setup Attempt from ISDN Calling Party to ISDN Called Party, with a Confusion Message	4-59
Figure 4-20	Call Setup Attempt — Timer T ₃₀₃ Expires for the First Time	4-60
Figure 4-21	Call Setup Attempt for Speech or 3.1-kHz Audio Call, RELease COMplete Message after Second SETUP Message at Called ISDN End User	4-61
Figure 4-22	Call Setup Attempt for Unrestricted Digital Information, RELease COMplete Message after Second SETUP Message at Called ISDN End User	4-62
Figure 4-23	Call Setup from ISDN Caller to Non-ISDN Called Party with SS7-to-MF Interworking	4-64
Figure 4-24	Call Setup Between Two ISDN End Users with MF-to-SS7 Interworking	4-65
Figure 4-25	Call Setup Attempt from ISDN Calling Party to Non-ISDN Called Party	4-66
Figure 4-26	Call Setup Attempt from ISDN Calling Party to Non-ISDN Called Party, Called Party Disconnect	4-68
Figure 4-27	Call Setup Attempt from Non-ISDN Calling Party to ISDN Called Party, Second SETUP Message and Call Proceeding at Called ISDN End User	4-69
Figure 4-28	Call Setup Attempt from Non-ISDN Calling Party to ISDN Called Party, RELease COMplete Message with “Call Rejected” after First SETUP Message	4-70
Figure 4-29	ISDN Call Forwarding — Base DN Has I-CFV or I-CFIB, and Call Is Forwarded	4-81
Figure 4-30	ISDN Call Forwarding — Base DN Has I-CFDA, and Call Is Forwarded Before ACM Is Sent to Originating CCSSO	4-82
Figure 4-31	ISDN Call Forwarding — Base DN Has I-CFDA, and Call Is Forwarded After ACM Is Sent to Originating CCSSO	4-83
Figure 5-1	CCS Network Provider Network Interfaces for Originating Traffic (Routed Based on Carrier Identification Code)	5-12
Figure 5-2	CCS Network Provider Network Interfaces for Terminating Traffic	5-25
Figure 5-3	CCS Network Provider Network Interfaces for Traffic Routed on Dialed Digits	5-29
Figure 6-1	DS1 Interface (V.35 Port on the Interconnecting SP)	6-4
Figure 6-2	DS1 Interface (DS0A Port on the Interconnecting SP)	6-5
Figure 6-3	DS0 Clock and Signal Formats	6-6
Figure 7-1	Signaling Message Transport - Examples	7-5
Figure 7-2	CCS Network Provider Signaling Message Transport - Examples	7-6
Figure 7-3	IXC Signaling Message Transport - Examples	7-7
Figure 7-4	IXC Signaling Message Transport - Examples	7-8
Figure 7-5	Example of IAM Transport	7-10
Figure 7-6	Example of REL Message Transport	7-14
Figure 7-7	CCS MTP Network Downtime Objective	7-17
Figure 7-8	STP-to-STP Interface Downtime Objective	7-18
Figure 7-9	STP-to-CCSSO Interface Downtime Objective	7-19
Figure 7-10	Generic Network Access Segment Model	7-20
Figure 7-11	Network Access Segment (CCSSO to Mated STPs)	7-23

Figure 7-12	D-Link(s) - No Diversity	7-24
Figure 7-13	2-Way D-Link Diversity	7-25
Figure 7-14	3-Way D-Link Diversity	7-26
Figure 8-1	Level 2 Tests	8-14
Figure 8-2	Level 3 Intrusive Tests	8-15
Figure 8-3	Level 3 Non-Intrusive Tests	8-16
Figure 8-4	Signaling Route Management Example	8-47
Figure 8-5	Hubbing Test Example	8-49
Figure 8-6	SS7 Trunk Interface Compatibility Testing Arrangement	8-78
Figure 8-7	SS7 Trunk Interface End-to-End Testing Arrangement (Two LEC Networks and One IXC Network)	8-82
Figure A-1	Routing Label	A-2
Figure A-2	Changeover Message	A-3
Figure A-3	Changeback Message	A-4
Figure A-4	Emergency Changeover Message	A-5
Figure A-5	Transfer-Prohibited Message	A-6
Figure A-6	Transfer-Allowed Message	A-7
Figure A-7	Transfer-Restricted Message	A-8
Figure A-8	Signaling-Route-Set-Test Message	A-9
Figure A-9	Management Inhibit Message	A-10
Figure A-10	Transfer-Controlled Message	A-11
Figure A-11	Signaling-Route-Set-Congestion-Test Message	A-12
Figure A-12	Traffic Restart Message	A-12
Figure A-13	Backward Call Indicators Parameter	A-25
Figure A-14	User Service Information Parameter	A-27
Figure A-15	Called Party Number Parameter	A-28
Figure A-16	Calling Party Number Parameter	A-30
Figure A-17	Calling Party's Category Parameter	A-31
Figure A-18	Carrier Selection Parameter	A-32
Figure A-19	Cause Indicators Parameter	A-33
Figure A-20	Charge Number Parameter	A-36
Figure A-21	Circuit Group Characteristics Indicator Parameter	A-38
Figure A-22	Circuit Group Supervision Message Type Indicator Parameter	A-39
Figure A-23	Circuit Identification Name Parameter	A-40
Figure A-24	Circuit State Indicator Parameter	A-41
Figure A-25	Circuit Validation Response Indicator Parameter	A-42
Figure A-26	CLLI™ Code Parameter	A-42
Figure A-27	Continuity Indicators Parameter	A-43
Figure A-28	Forward Call Indicators Parameter	A-43
Figure A-29	Message Type Parameter	A-45
Figure A-30	Nature of Connection Indicators Parameter	A-46
Figure A-31	Originating Line Information Parameter	A-47
Figure A-32	Outgoing Trunk Group Number Parameter	A-48
Figure A-33	Range and Status Parameter	A-48
Figure A-34	Service Code	A-49
Figure A-35	Suspend/Resume Indicators Parameter	A-50
Figure A-36	Transit Network Selection Parameter Field with 4-Digit Carrier Identification Code	A-50
Figure A-37	Codes for Circuit Code Subfield	A-52

Figure A-38	Carrier Identification Parameter with 4-Digit Carrier Identification Parameter Field	A-52
Figure A-39	Event Information Indicators Parameter Field	A-54
Figure A-40	Optional Backward Call Indicators Parameter Field	A-55
Figure A-41	Original Called Number Parameter	A-56
Figure A-42	Redirection Information Parameter	A-58
Figure A-43	Automatic Congestion Level Parameter	A-59
Figure A-44	Hop Counter Parameter	A-59
Figure A-45	Jurisdiction Information Parameter	A-60
Figure A-46	Generic Address Parameter	A-61
Figure A-47	Redirect Capability Parameter	A-63
Figure A-48	Redirect Counter Parameter	A-64
Figure A-49	Redirection Number Parameter	A-64
Figure A-50	Generic Digits Parameter Field	A-66
Figure A-51	Calling Geodetic Location Parameter Field	A-67
Figure A-52	Ellipsoid Point Shape Description	A-68
Figure A-53	Shape Description of an Ellipsoid Point with Uncertainty	A-70
Figure A-54	Shape Description of a Point with Altitude and Uncertainty	A-71
Figure A-55	Shape Description of an Ellipse on the Ellipsoid	A-73
Figure A-56	Shape Description of an Ellipsoid Circle Sector	A-74
Figure A-57	Shape Description of Polygon	A-76
Figure A-58	User Service Information Parameter - Modified for ISDN Access	A-79
Figure A-59	Calling Party Number Parameter - Modified for ISDN Access	A-81
Figure A-60	Cause Indicators Parameter - Modified for ISDN Access	A-83
Figure A-61	Original Called Number Parameter - Modified for ISDN Access	A-87
Figure A-62	Redirection Information Parameter - Modified for ISDN Access	A-90
Figure A-63	Access Transport Parameter - Added for ISDN Access	A-91
Figure A-64	Notification Indicator Parameter - Added for ISDN Access	A-92
Figure D-1	Configuration A (Call-Through Tests)	D-1
Figure D-2	Configuration B (Test-Set Generated Tests)	D-2
Figure G-1	Initial BICC Architecture	G-3
Figure G-2	Backward Bearer Connection Setup with COT	G-14
Figure H-1	Example of CCS Network Architecture with A-, C-link ATM HSLs	H-3
Figure H-2	Example of CCS Network Architecture with B-, C-, D-link ATM HSLs	H-4
Figure H-3	SS7 56-Kbps Links and ATM HSL Protocol Model	H-8
Figure H-4	Network Architecture for IPVHSLs	H-17
Figure H-5	IPVHSL Protocol Stack	H-19
Figure I-1	Generic SIP-based Network Architecture	I-3
Figure I-2	SIP Stack	I-6
Figure I-3	ISUP to SIP Interworking	I-10
Figure I-4	SIP and ISUP Interworking	I-12
Figure I-5	ISUP-SIP-ISUP Interworking	I-14
Figure J-1	Series System	J-1
Figure J-2	Parallel System	J-2
Figure K-1	3GPP Reference Architecture for the IP Multimedia Core Network Subsystem	K-2
Figure K-2	Simplified IMS Functional Architecture	K-3

Figure K-3	Procedures for the Establishment of Sessions (without Preconditions)	K-6
Figure K-4	PSTN Origination with IMS Termination Example	K-10
Figure K-5	IMS Origination with PSTN Termination Example	K-13
Figure K-6	ATIS NGN Functional Architecture as Described in ATIS-1000018	K-16
Figure K-7	Proposed Update to ATIS NGN Functional Architecture	K-20
Figure K-8	3GPP IMS Reference Architecture in Support of Emergency Services	K-21
Figure K-9	Adaptation of VoIP Interconnection Reference Model for ES-NGN	K-24
Figure K-10	ATIS ESIF-IMS911 IMS-based NG9-1-1 Service Architecture	K-26
Figure K-11	Preliminary View of NG9-1-1 Internetwork Architectural Configuration	K-30
Figure K-12	Delivery of a Legacy Wireline Emergency Origination to an i3 PSAP	K-32
Figure K-13	Delivery of a Legacy Wireline Emergency Origination to a Legacy PSAP	K-35
Figure K-14	IMS Origination Network-to-Emergency Services Network Interconnection Architecture as Specified in ATIS-0700015	K-38
Figure K-15	Routing of Mobile Origination to a Legacy Selective Router Based on Cell-Based Location	K-43
Figure L-1	i3 Functional Architecture in Support of 9-1-1 Call Routing	L-2
Figure L-2	Legacy Wireline Originating Network to i3 ESInet Interconnection	L-8
Figure L-3	Legacy Wireless Originating Network to i3 ESInet Interconnection	L-11
Figure L-4	Legacy Originating Network to i3 ESInet Interconnection Using Direct Connection to Legacy Network Gateway	L-12
Figure L-5	Emergency Call Setup: Origination in a Legacy Network and Termination to i3 PSAP	L-16
Figure M-1	ATIS-1000026.2008(R2013) Locations of SBC Functions	M-2
Figure M-2	ATIS NGN Functional Architecture Showing the Data Border Function within the EAG (from ATIS-1000046)	M-9
Figure N-1	Originating Network Served by Legacy SR; Target PSAP Served by i3 ESInet	N-3
Figure N-2	Initial Call, Originating Network on SR, i3 PSAP on ESInet with Location-by-Value	N-7
Figure N-3	Originating Network Served by ESInet; Target PSAP Served by Legacy SR	N-10
Figure N-4	Initial Call, Originating Network on ESInet, PSAP on SR with Location-by-Reference	N-14
Figure O-1	ATIS J-STD-110 (Version 1) SMS to 9-1-1 Architecture	O-3
Figure O-2	TCC-to-TCC Interconnection Architecture	O-7
Figure O-3	SMS/MMS Text to 9-1-1 High Level Functional Architecture as Specified in ATIS J-STD-110.v002	O-9
Figure P-1	High-Level Architecture for Heightened Accuracy Location (as specified in ATIS-0700028)	P-6
Figure R-1	Relationships Among Some Frequently Used Terms	R-3

List of Tables

Table 2-1	Assignment of Network Cluster Codes to States, Provinces, and Territories (as shown in Chapter T1.111.8 of ATIS-1000111.2005[R2015])	2-19
Table 3-1	Circuit Query Actions - Transient and Unequipped States	3-32
Table 3-2	Circuit Query Actions - Blocking States	3-32
Table 3-3	Circuit Query Actions - Busy/Idle States	3-33
Table 4-1	Originating Access Type by TGN on AMA Record	4-13
Table 4-2	Terminating Access Type by TGN on AMA Record	4-30
Table 4-3	Handling of Events Resulting in an Unsuccessful Call	4-32
Table 4-4	Example ACC Control Response Percentages	4-52
Table 4-5	Completion of Transmission Path at Originating or Tandem CCSSO	4-78
Table 5-1	Coding Rules for the Called Party Number Parameter	5-14
Table 5-2	Correspondence Between MF Sequence and Coding of Called Party Number	5-16
Table 5-3	Correspondence Between MF INC Sequence and Coding of Called Party Number	5-16
Table 7-1	Average One-Way Message Transport Times (ms) — IAM	7-11
Table 7-2	Average One-Way Message Transport Times (ms) — ACM, ANM, REL, RLC Messages	7-15
Table 7-3	Network Access Segment Component Downtime Allocations	7-21
Table 8-1	Signaling Route Management Routing List	8-47
Table 8-2	Recommended Minimal Subset of Call-Through Tests	8-107
Table A-1	Message Priorities	A-16
Table A-2	Address Complete Message	A-17
Table A-3	Answer Message	A-17
Table A-4	Blocking and Blocking Acknowledgment Messages	A-17
Table A-5	Circuit Group Blocking and Unblocking Messages	A-17
Table A-6	Circuit Group Reset and Circuit Group Reset Acknowledgment Messages	A-18
Table A-7	Circuit Query Message	A-18
Table A-8	Circuit Query Response Message	A-18
Table A-9	Circuit Reservation Message	A-19
Table A-10	Circuit Reservation Acknowledgment Message	A-19
Table A-11	Circuit Validation Test Message	A-19
Table A-12	Circuit Validation Response Message	A-19
Table A-13	Continuity Message	A-20
Table A-14	Continuity Check Request Message	A-20
Table A-15	Exit Message	A-20
Table A-16	Initial Address Message	A-21
Table A-17	Loop Back Acknowledgment Message	A-21
Table A-18	Release Message	A-22
Table A-19	Release Complete Message	A-22
Table A-20	Reset Circuit Message	A-22
Table A-21	Resume Message	A-22
Table A-22	Suspend Message	A-23
Table A-23	Unblocking Message	A-23

Table A-24	Unblocking Acknowledgment Message	A-23
Table A-25	Unequipped Circuit Identification Code Message	A-23
Table A-26	Call Progress Message	A-24
Table A-27	Confusion Message	A-24
Table A-28	Address Complete Message - Modified for ISDN Access	A-77
Table A-29	Answer Message - Modified for ISDN Access	A-77
Table A-30	Initial Address Message - Modified for ISDN Access	A-78
Table A-31	Call Progress Message - Modified for ISDN Access	A-78
Table A-32	Signaling Link Test Message	A-94
Table A-33	MRVT Message	A-95
Table A-34	MRVA (Success) Message	A-97
Table A-35	MRVA (Failure) Message	A-98
Table A-36	SRVT Message	A-99
Table A-37	SRVA (Success) Message	A-101
Table A-38	SRVA (Failure) Message	A-102
Table B-1	MTP Level 2 Timer Values	B-1
Table B-2	MTP Level 3 Timer Values	B-2
Table B-3	ISDNUP Timer Values	B-4
Table B-4	Testing and Maintenance Timer Values	B-6
Table B-5	Timer Values in the MRVT and SRVT	B-6
Table E-1	Values	E-2
Table K-1	Correspondence Between 3GPP Functional Entities and ATIS NGN Architecture Functional Entities	K-19
Table K-2	SIP to SS7 Interworking in Support of Delivery of Emergency Calls from IMS Origination Networks to Legacy Selective Routers	K-47
Table K-3	SIP to CAMEL/Feature Group D MF Interworking in Support of Delivery of Emergency Calls from IMS Origination Networks to Legacy Selective Routers	K-47
Table O-1	Character Mappings in Support of RTT/MSRP - TTY Interworking	O-11