

Generic Requirements for a -48 Volt Telecommunications Switchmode Rectifier/Power Supply

Contents

Preface	Preface-2
1. Introduction.....	1-1
1.1 Purpose and Scope	1-1
1.2 Structure and Use of This Document.....	1-1
1.3 Requirements Terminology.....	1-2
1.4 Requirement Labeling Conventions.....	1-3
1.4.1 Numbering of Requirement and Related Objects	1-3
1.4.2 Requirement, Conditional Requirement, and Objective Object Identification	1-3
2. General Information.....	2-1
2.1 General Design Requirements.....	2-1
2.1.1 Fail-Safe Design.....	2-1
2.1.2 Open Architecture and Backward Compatibility	2-1
2.2 Engineering, Installation, and Maintenance.....	2-1
2.2.1 Code Compliance	2-1
2.2.2 Fire Resistance	2-2
2.2.3 Environmental Requirements.....	2-3
2.2.4 Electromagnetic Interference (EMI)	2-3
2.2.5 Ground System.....	2-3
2.2.6 Electrostatic Discharge (ESD)	2-4
2.2.7 Electrical Isolation	2-4
2.2.8 Frame Current	2-5
2.2.9 Shipping Temperature and Humidity.....	2-5
2.2.10 Acoustical Noise	2-5
2.2.11 Safety and Hazards.....	2-5
2.2.12 Toxic Materials	2-6
2.2.13 Marking of Components	2-6
2.2.14 Sparing	2-6
2.2.15 Nameplate	2-7
3. Electrical Requirements	3-1
3.1 AC Input Source.....	3-1
3.2 AC Ground	3-2
3.3 Inrush Current	3-3
3.4 Power Factor	3-3
3.5 AC Input Protection	3-3

3.6	Low AC Voltage Protection.....	3-3
3.7	Hold-Up Time	3-3
3.8	Phase Failure	3-4
3.9	Power Interruption	3-4
3.10	Telephone Influence Factor (TIF).....	3-4
3.11	Voltage Output.....	3-4
3.12	Float Voltage Adjustment	3-5
3.13	Voltage Regulation.....	3-5
3.14	Voltage/Temperature Coefficient.....	3-5
3.15	Warm-Up Time	3-5
3.16	Voltage Drift	3-6
3.17	Load Sharing	3-6
3.18	Current Limit.....	3-6
3.19	Current Walk-In	3-7
3.20	Stability	3-7
3.21	Dynamic Response.....	3-7
3.22	Output Protection and Disconnect	3-8
3.23	Voice Frequency Output Noise.....	3-8
3.24	Wideband Output Noise.....	3-9
3.25	Electromagnetic Influence (EMI)	3-9
3.26	Efficiency	3-9
3.27	Soft Start.....	3-10
3.28	Discharge of Capacitors	3-10
3.29	Rectifier Reliability	3-10
3.30	Induced Frame Current	3-10
4.	Physical Design.....	4-1
4.1	Enclosure.....	4-1
4.2	Shock and Vibration.....	4-1
4.3	Earthquake.....	4-1
4.4	Paint.....	4-1
4.5	Cooling.....	4-2
4.6	Materials.....	4-2
4.7	Handling.....	4-3
5.	Rectifier Interfaces and Alarms	5-1
5.1	Interface Status and Signals	5-1
5.2	Rectifier Interface.....	5-1
5.2.1	Voltage and Current Levels	5-1
5.2.2	Interconnect Wires and Harness	5-1
5.2.3	Rectifier Interface	5-2
5.2.4	Rectifier-Rectifier Interconnection	5-5
5.2.5	Rectifier-Primary Distribution and Battery Interconnection	5-5
5.2.6	Rectifier-Digital Monitor/Control Interface.....	5-5
5.2.6.1	Rectifier ac Input Monitor	5-6

5.2.6.2	<i>Digital Control Remote Monitor Interconnect</i>	5-7
5.2.6.3	<i>Digital Control Adjunct Interconnect</i>	5-8
5.3	Internal High-Voltage Shutdown	5-8
5.4	Current Limit Adjustment	5-8
5.5	Rectifier Test	5-9
5.6	Output Current Meter	5-9
5.7	Internal Protection	5-9
5.8	Test Points	5-9
5.9	PWB Nesting	5-10
5.10	Jacks	5-10
6.	Components	6-1
6.1	Transformers and Magnetic Coils	6-1
6.2	Hook-Up Wire	6-1
6.3	Power Conductors	6-3
6.4	Electrical and Mechanical Hardware	6-3
6.5	Electrical Power Wire Terminations	6-4
6.6	Resistors	6-4
6.7	Electrolytic Capacitors	6-4
6.8	Capacitors (Except Electrolytic)	6-5
6.9	Semiconductors	6-5
6.10	Circuit Breakers	6-6
6.11	Fuses	6-6
6.12	Meters	6-6
6.13	Relays	6-7
6.14	Switches	6-7
6.15	Printed Wire Boards	6-8
7.	Quality Assurance, Documentation, and Training	7-1
7.1	Hardware Quality Assurance Plan	7-1
7.2	Documentation	7-1
7.3	Training Requirements	7-2
8.	Performance Verification and Test Procedures	8-1
8.1	General Tests and Inspections for Section 2	8-1
8.1.1	Fire Resistance (Sect 2.2.2)†	8-1
8.1.2	Operating Environment (Sect 2.2.3)†	8-1
8.1.3	Electrostatic Discharge (Sect 2.2.6)†	8-1
8.1.4	Electrical Isolation (Sect 2.2.7)†	8-2
8.1.5	Dielectric (Sect 2.2.7)	8-2
8.1.6	Shipping Temperature and Humidity (Sect 2.2.9)†	8-2
8.1.7	Acoustical Noise (Sect 2.2.10)†	8-2
8.1.8	Safety and Hazards (Sect 2.2.11)†	8-2
8.1.9	Toxic Materials (Sect 2.2.12)†	8-3
8.1.10	Marking of Components (Sect 2.2.13)†	8-3
8.1.11	Nameplate (Sect 2.2.15)†	8-3

8.2	Electrical Tests for Section 3	8-3
8.2.1	AC Input Source (Sect 3.1)	8-3
8.2.2	Withstand Surge Capability (Sect 3.1)	8-5
8.2.3	AC Ground (Sect 3.2)	8-5
8.2.4	Inrush Current (Sect 3.3)†	8-6
8.2.5	Power Factor (Sect 3.4)†	8-6
8.2.6	AC Input Protection (Sect 3.5)†	8-6
8.2.7	Low AC Voltage Protection (Sect 3.6)†	8-6
8.2.8	Phase Failure (Sect 3.8)†	8-7
8.2.9	Power Interruption (Sects 3.8 and 3.9)†	8-7
8.2.10	Telephone Influence Factor (TIF) (Sect 3.10)†	8-7
8.2.11	Voltage Output (Sect 3.11)†	8-8
8.2.12	Float Voltage Adjustment (Sect 3.12)†	8-8
8.2.13	Voltage Regulation (Sect 3.13)†	8-8
8.2.14	Voltage/Temperature Coefficient (Sect 3.14)†	8-9
8.2.15	Warm-Up Time (Sect 3.15)†	8-9
8.2.16	Voltage Drift (Sect 3.16)†	8-9
8.2.17	Current Limit (Sect 3.18)†	8-9
8.2.18	Current Walk-In (Sect 3.19)†	8-10
8.2.19	Stability (Sect 3.20)†	8-10
8.2.20	Dynamic Response (Sect 3.21)†	8-10
8.2.21	Output Protection and Disconnect (Sect 3.22)†	8-10
8.2.22	Voice Frequency Output Noise (Sect 3.23)†	8-11
8.2.23	Wideband Output Noise (Sect 3.24)†	8-11
8.2.24	Electromagnetic Influence (EMI) (Sect 3.25)†	8-11
8.2.25	Efficiency (Sect 3.26)†	8-11
8.2.26	Soft Start (Sect 3.27)†	8-11
8.2.27	Discharge of Output Capacitors (Sect 3.28)†	8-12
8.2.28	Life and Reliability (Sect 3.29)†	8-12
8.2.29	Induced Frame Current (Sect 3.30)†	8-12
8.3	Physical Design Tests and Inspections for Section 4	8-12
8.3.1	Enclosure (Sect 4.1)†	8-12
8.3.2	Shock and Vibration (Sect 4.2)†	8-12
8.3.3	Earthquake (Sect 4.3)†	8-12
8.3.4	Paint (Sect 4.4)†	8-12
8.3.5	Cooling (Sect 4.5)†	8-13
8.3.6	Materials (Sect 4.6)†	8-13
8.3.7	Handling (Sect 4.7)†	8-13
8.4	Electrical Tests for Section 5	8-13
8.4.1	Interface Status and Signals (Sect 5.1)†	8-13
8.4.2	Internal High-Voltage Shutdown (Sect 5.3)†	8-14
8.4.3	Current Limit Adjustment (Sect 5.4)†	8-14
8.4.4	Rectifier Test (Sect 5.5)†	8-14
8.4.5	Output Current Meter (Sect 5.6)†	8-14

8.4.6	Internal Protection (Sect 5.7)†	8-15
8.4.7	Test Points (Sect 5.8)†	8-15
8.4.8	PWB Nesting (Sect 5.9)†	8-15
8.4.9	Jacks (Sect 5.10)†	8-15
8.5	Component Tests and Inspections for Section 6	8-15
8.5.1	Transformers and Magnetic Coils (Sect 6.1)†	8-15
8.5.2	Power Conductors (Sect 6.3)†	8-16
8.5.3	Electrical and Mechanical Hardware (Sect 6.4)†	8-16
8.5.4	Electrical Power Wire Termination (Sect 6.5)†	8-16
8.5.5	Resistors (Sect 6.6)†	8-16
8.5.6	Electrolytic Capacitors (Sect 6.7)†	8-16
8.5.7	Capacitors (Except Electrolytic) (Sect 6.8)†	8-16
8.5.8	Semiconductors (Sect 6.9)†	8-16
8.5.9	Circuit Breakers (Sect 6.10)†	8-17
8.5.10	Fuses (Sect 6.11)†	8-17
8.5.11	Meters (Sect 6.12)†	8-17
8.5.12	Relays (Sect 6.13)†	8-17
8.5.13	Switches (Sect 6.14)†	8-17
8.5.14	Printed Wire Boards (Sect 6.15)†	8-17
8.6	Miscellaneous Tests and Inspections for Section 7	8-17
8.6.1	Documents (Sect 7.2)†	8-17
Glossary		Glossary-1
References		Reference-1

List of Tables

Table 2-1.	Test voltages for Electrical Isolation	2-4
Table 3-1.	Voltage Limits	3-1
Table 3-2.	Desired Rectifier Efficiency	3-9
Table 5-1.	Interface Connection Functions	5-2
Table 6-1.	Maximum Allowable Temperature	6-1
Table 6-2.	Maximum Permissible Current.....	6-2
Table 6-3.	Maximum Operating Voltage and Temperature.....	6-2
Table 6-4.	Suggested Torques, Clamping Load, and Electrical Current Rating.....	6-3
Table 6-5.	Semiconductor Torque Limits	6-5
Table 6-6.	Allowable Temperatures For Switches and Contacts	6-7
Table 8-1.	Test Equipment.....	8-3
Table 8-2.	1960 Single Frequency TIF Weighing Values	8-7

List of Figures

Figure 5-1.	Rectifier Interface	5-4
Figure 5-2.	D Connector Plugs and Sockets.....	5-6
Figure 8-1.	Test Connections	8-4