

# Contents

## Telcordia GR-955-Documentation Information

<b>Notice Of Disclaimer</b> . . . . .	iii
<b>List of Figures</b> . . . . .	vii
<b>1 Introduction</b>	
1.1 Purpose and Scope . . . . .	1-1
1.2 Summary of Changes . . . . .	1-1
1.3 Organization . . . . .	1-2
<b>2 General Information</b>	
2.1 Description . . . . .	2-1
2.2 Preparing Stripped Fibers . . . . .	2-1
2.3 Analysis Criteria . . . . .	2-1
<b>3 General Requirements</b>	
3.1 Documentation . . . . .	3-1
3.1.1 Practices . . . . .	3-1
3.1.2 Work Center Information Package . . . . .	3-1
3.1.3 Instructions . . . . .	3-1
3.2 Marking, Packaging, and Shipping . . . . .	3-2
3.2.1 Marking . . . . .	3-2
3.2.2 Packaging and Shipping . . . . .	3-2
3.3 Quality and Reliability . . . . .	3-2
3.3.1 Product Reliability Audit . . . . .	3-2
3.3.2 Product Quality Audit . . . . .	3-3
3.3.3 Initial Product Qualification and Periodic Requalification . . . . .	3-3
<b>4 Performance Requirements and Objectives</b>	
4.1 General Functional Requirements for Single and Multi-Fiber Strippers . . . . .	4-1
4.2 Coating Strippability . . . . .	4-1
4.2.1 Coating Strippability – Single Fiber – 250 µm Protective Coating . . . . .	4-1
4.2.2 Coating Strippability – Single Fiber – 900 µm Buffer Coating . . . . .	4-3
4.2.3 Coating Strippability – Ribbon and Ribbonized Fibers . . . . .	4-4
4.3 Fiber Tensile Strength . . . . .	4-5
4.3.1 Center Strip – Single Fiber – 250 µm Protective Coating . . . . .	4-5
4.3.2 End Strip, 250 µm Protective Coating, 900 µm Buffer Coating, and Fiber Ribbon. . . . .	4-5
4.4 Tool Life . . . . .	4-7
4.5 Environmental Exposure – Single and Multi-Fiber Strippers . . . . .	4-7
4.5.1 Storage Environment . . . . .	4-7
4.5.2 Drop Test . . . . .	4-7
4.5.3 Vibration and Dust Exposure . . . . .	4-8

4.5.4 Battery Life – Heat Stripper . . . . . 4–8

**5 Performance Verification/Test Procedure**

5.1 Test Program . . . . . 5–1

5.2 Coating Strippability . . . . . 5–1

5.2.1 Coating Strippability – 250 µm Protective Coating . . . . . 5–1

5.2.2 Coating Strippability – 900 µm Buffer Coating . . . . . 5–1

5.2.3 Coating Strippability – Ribbon and Ribbonized Fiber . . . . . 5–2

5.3 Fiber Tensile Strength Test . . . . . 5–3

5.3.1 Center Strip – 250 µm Protective Coating . . . . . 5–3

5.3.1.1 Pretest Baseline for 250 µm Protective Coating . . . . . 5–3

5.3.1.2 Tensile Test 250 µm Coated Fiber . . . . . 5–3

5.3.2 Fiber Tensile Strength Test – End Strip – 250 and 900 µm Fiber . . . . . 5–4

5.3.2.1 Pretest Baseline – End Strip – 250 µm and 900 µm Fiber . . . . . 5–6

5.3.2.2 Tensile Test – 250 µm and 900 µm Fiber . . . . . 5–6

5.3.2.3 Fiber Tensile Strength Test – End Strip – Fiber Ribbon . . . . . 5–6

5.4 Tool Life Test . . . . . 5–8

5.5 Environmental Exposure – Single and Multi-Fiber Strippers . . . . . 5–8

5.5.1 Storage Environment . . . . . 5–8

5.5.2 Drop Test . . . . . 5–9

5.5.3 Vibration and Dust Exposure . . . . . 5–9

5.5.4 Battery Life – Heat Stripper . . . . . 5–9

**Appendix A: References**

Related Documents . . . . . References–1

**Requirement-Object Index**

## List of Figures

Figure 4-1	Minimum Fiber Strip Length – 250 $\mu\text{m}$ Protective Coating . . . . .	4-2
Figure 4-2	Minimum Fiber Strip Length – 900 $\mu\text{m}$ Buffer Coating . . . . .	4-3
Figure 4-3	Stripped Ribbon or Ribbonized Fiber . . . . .	4-5
Figure 5-1	Tensile Testing – Center Strip 250 $\mu\text{m}$ Coated Fiber . . . . .	5-4
Figure 5-2	Test Fixture – End Strip – 250 and 900 m Coated Fiber . . . . .	5-5
Figure 5-3	Tensile Testing – End Strip – 250 $\mu\text{m}$ and 900 $\mu\text{m}$ Fiber . . . . .	5-5
Figure 5-4	Stripped Ribbon Fibers – Card Test Fixture . . . . .	5-7
Figure 5-5	Tensile Testing Stripped Ribbon Fibers . . . . .	5-8