
A View of System M-NTSC Video Jitter and Wander Specifications on Compressed Systems at 45 Mb/s

Contents [Telcordia SR-4274-Documentation Information](#)

Foreword.....	Foreword-1
1. Introduction.....	1-1
1.1 Purpose and Scope	1-1
1.2 Target Audience	1-1
1.3 Document Structure	1-1
2. Video Performance: Impairments and Causes	2-1
2.1 General	2-1
2.2 Additional Impairments and Related Causes of Analog Video (System M-NTSC) on Compressed Systems at 45 Mb/s	2-1
2.2.1 CODEC Functionality: Related Analog Distortions, Digital Artifacts, and Causes.....	2-1
2.2.2 Network Functionality: Related Distortions, Digital Artifacts, and Causes.....	2-3
2.3 Jitter and Wander and Applicability to End-to-End Video Signals	2-3
2.3.1 Video Source.....	2-4
2.3.2 Encoder	2-4
2.3.3 Telecommunications Network	2-5
2.3.4 Decoder	2-5
2.3.5 Video Destination	2-5
2.4 Telecommunications Network - Phase Noise Relationships	2-6
2.4.1 Significant Instants.....	2-6
2.4.2 Video Jitter Units	2-6
2.4.3 Network Jitter Specifications	2-7
2.4.4 Decoder Jitter/Wander Transfer.....	2-7
2.4.5 Decoder Jitter and Wander Tolerance.....	2-7
2.4.6 Encoder/Decoder Pair Jitter Generation	2-8
2.4.7 Encoder DS3 Jitter Generation	2-8
2.5 Phase Noise: Jitter, Wander, and Phase Transients.....	2-9
2.5.1 General	2-9
2.5.2 Jitter.....	2-10
2.5.2.1 Specifications.....	2-10
2.5.2.2 Measurements	2-11

2.5.2.3	ATIS Technical Report #8 on Jitter Measurement Methodology.....	2-12
2.5.3	Wander.....	2-12
2.5.3.1	Specifications.....	2-12
2.5.3.2	Measurements.....	2-14
2.5.4	Summary and Conclusion of Jitter and Wander Recommended Objectives for Analog Video (System M-NTSC).....	2-18
3.	Recommended Detailed Objectives for Testing Analog Video (System M-NTSC) Signals.....	3-1
3.1	Test Equipment.....	3-1
3.2	User Interface.....	3-1
3.2.1	Video Performance Specifications.....	3-1
3.2.1.1	Parameters for Testing.....	3-1
3.2.1.2	Testing Methodologies.....	3-1
3.2.1.3	Recommended Objectives.....	3-3
4.	Interfaces.....	4-1
Appendix A: Research Supporting the Detailed Recommended Objectives of Section 3..... A-1		
A.1	Introduction.....	A-1
A.2	Limit on DS3 Phase Variation.....	A-1
A.3	Limits on Video Signal Phase Variation.....	A-4
A.4	Video Decoder Phase Transfer Function.....	A-6
A.5	Transient Analysis.....	A-7
A.6	Another Video Decoder Phase Transfer Function.....	A-10
A.7	Conclusions.....	A-14
Appendix B: An Independent Case Study and Perspective in Real-Time on CODEC and Network Functionality..... B-1		
B.1	Introduction.....	B-1
B.2	A SONET Overview.....	B-2
B.3	Pointer Adjustments Influence on Video.....	B-3
B.4	Interaction with Studio Equipment.....	B-5
B.5	Test Results.....	B-8
B.6	Solutions.....	B-10
B.7	About the Tektronix VM 700 Frame Jitter Measurements.....	B-14
B.8	Conclusion.....	B-15
References	References-1
Glossary	Glossary-1
Index	Index-1

List of Figures

Figure 1-1.	Video Transmission Service Channel, Compressed at 45 Mb/s.....	1-1
Figure 2-1.	List of Timing and Jitter Related Specifications (End-to-End).....	2-4
Figure 2-2.	Decoder Jitter Transfer: Typical Areas Where Jitter Occurs	2-7
Figure 2-3.	Encoder/Decoder Jitter Generation	2-8
Figure 2-4.	Jitter Measurement from the Encoder	2-8
Figure 2-5.	Phase Noise.....	2-9
Figure 2-6.	Synchronized Clock Phase Noise Testing	2-10
Figure 2-7.	Asynchronous Transport Phase Noise Testing	2-10
Figure 2-8.	Jitter Measurement Model	2-12
Figure 2-9.	MTIE Definition	2-13
Figure 2-10.	Wander Measurement Model	2-14
Figure 3-1.	Jitter and Wander Accommodation Template	3-4
Figure 4-1.	Network Interface (NI) Example of System Included as Network Channel Terminating Equipment.....	4-1
Figure 4-2.	Network Interface (NI) Example of Video System Included as Customer Equipment.....	4-1
Figure 4-3.	Point of Termination (Carrier to Carrier) Between an LEC and IC	4-2
Figure B-1.	STS-1 Frame Structure	B-2
Figure B-2.	Simple OC-n Optical Transmission Network.....	B-3
Figure B-3.	Example of NTSC Color Subcarrier Phase Change after Pointer Adjustment.....	B-4
Figure B-4.	PAL Frame Jitter as a Result of Two Single Pointer Adjustments	B-6
Figure B-5.	Test Setup	B-6
Figure B-6.	Example of Tracking Error between two PLLs.....	B-8
Figure B-7.	Video Output Without Pointer Adjustments	B-9
Figure B-8.	Video Output With a Single Pointer Adjustment	B-10
Figure B-9.	Video Output With a Double Pointer Adjustment.....	B-11
Figure B-10.	Single Pointer Adjustment every 10 sec., Alternating Polarity.....	B-12
Figure B-11.	Single Pointer Adjustment every 1 sec., Alternating Polarity.....	B-13
Figure B-12.	Single Pointer Adjustment every 10 sec., Same Polarity	B-13
Figure B-13.	Single Pointer Adjustment every 1 sec., Same Polarity	B-14
Figure B-14.	Frame Jitter with Pointer Adjustment Buffer Option	B-15

List of Tables

Table 2-1.	SONET Hierarchy and Summary of Specifications of Jitter at Network Interface	2-11
Table B-1.	Overview of Video Artifacts	B-4
Table B-2.	Contents of Betacam Tape.....	B-8
Table B-3.	Proposed Limits for Frame Jitter and Phase Change.....	B-12