

---

# Service Provider Identification Architectural Analysis

## Contents

## [Telcordia SR-4783-Documentation Information](#)

Preface .....	Preface-1
Executive Summary .....	ES-1
1. Introduction .....	1-1
1.1 Background .....	1-1
1.2 Issue Statement .....	1-2
1.3 Scope .....	1-3
1.4 Assumptions .....	1-4
1.5 Document Organization .....	1-4
2. Needs Assessment .....	2-1
2.1 Background .....	2-1
2.2 Carrier Liaison Committee Activities at ATIS .....	2-2
2.2.1 Issues Task Group on Service Provider Identification .....	2-2
2.2.1.1 Task Group Report .....	2-2
2.2.1.2 Information Needs .....	2-3
2.2.1.3 Other Task Group Report Requirements .....	2-5
2.2.1.4 Identification of Traffic Types .....	2-5
2.2.1.5 Assumptions/Other Considerations .....	2-6
2.2.1.6 Message Processing Committee - OBF Issue 1496 .....	2-6
2.3 Committee T1 - T1S1.3 Network Capabilities Description .....	2-7
2.4 High-Level Industry Requirements .....	2-8
2.5 Case Summary .....	2-11
3. Database Models for Service Provider Identification .....	3-1
3.1 Network (Real-time) Databases .....	3-1
3.1.1 National Toll-Free Database Model .....	3-1
3.1.2 Regional Number Portability Database Model .....	3-2
3.1.3 Individual Company LIDB Model .....	3-2
3.1.4 Individual Company AIN Database Model .....	3-3
3.2 Stand-Alone (Non Real-Time) Database .....	3-3
3.2.1 Flat-File Model .....	3-4
3.3 Data Exchange .....	3-4
3.4 Summary .....	3-5
4. Architectural Alternatives .....	4-1
4.1 Non Real-Time Approach .....	4-1
4.1.1 General Description .....	4-2
4.1.1.1 Advantages of Non Real-Time Approach .....	4-3
4.1.1.2 Disadvantages of Non Real-Time Approach .....	4-4

---

4.1.2	Non Real-Time - Network Systems Impacts .....	4-4
4.1.2.1	Database.....	4-4
4.1.2.2	Common Channel Signaling.....	4-5
4.1.2.3	Switching Systems.....	4-5
4.1.2.4	Operations Support Systems.....	4-7
4.1.3	Non Real-Time - Meeting High-Level Requirements .....	4-9
4.1.4	Detailed Summary for Non Real-Time Approach .....	4-10
4.1.5	Relative Cost of Non Real-Time Approach.....	4-11
4.2	GR-2970-CORE Approach .....	4-12
4.2.1	General Description .....	4-12
4.2.1.1	Advantages of GR-2970-CORE .....	4-13
4.2.1.2	Disadvantages of GR-2970-CORE.....	4-14
4.2.2	GR-2970-CORE - Network Systems Impacts .....	4-14
4.2.2.1	Database.....	4-14
4.2.2.2	Common Channel Signaling.....	4-15
4.2.2.3	Switching System Impacts.....	4-15
4.2.2.4	Operations Systems Impacts.....	4-18
4.2.3	GR-2970-CORE - Meeting High-Level Requirements .....	4-19
4.2.4	Detailed Summary for GR-2970-CORE Approach .....	4-20
4.2.5	Relative Cost of GR-2970-CORE Approach.....	4-22
4.3	Network Database Approaches .....	4-23
4.3.1	General Description .....	4-23
4.3.1.1	Advantages of a Network Database.....	4-24
4.3.1.2	Disadvantages of a Network Database .....	4-24
4.3.2	Network Database With No SPI in ISUP Signaling .....	4-25
4.3.2.1	Overview.....	4-25
4.3.2.2	Network Systems Impacts .....	4-25
4.3.2.3	Common Channel Signaling.....	4-26
4.3.2.4	Switching Systems.....	4-28
4.3.2.5	Operations Systems Impacts.....	4-30
4.3.2.6	Meeting High-Level Requirements .....	4-31
4.3.2.7	Detailed Summary .....	4-32
4.3.2.8	Relative Cost.....	4-33
4.3.3	Network Database With SPI Included in ISUP Signaling .....	4-34
4.3.3.1	Overview.....	4-34
4.3.3.2	Network Systems Impacts .....	4-35
4.3.3.3	Common Channel Signaling.....	4-36
4.3.3.4	Switching Systems.....	4-37
4.3.3.5	Operations Systems Impacts.....	4-38
4.3.3.6	Meeting High-Level Requirements .....	4-38
4.3.3.7	Detailed Summary .....	4-39
4.3.3.8	Relative Cost.....	4-41
4.4	Hybrid Approaches .....	4-42
4.4.1	Database Approach with Signaling of Calling Party SPI .....	4-42

---

---

4.4.1.1	General Description .....	4-42
4.4.1.2	Advantages .....	4-44
4.4.1.3	Disadvantages .....	4-44
4.4.1.4	Network Systems Impacts .....	4-45
4.4.1.5	Common Channel Signaling.....	4-45
4.4.1.6	Switching System .....	4-46
4.4.1.7	Operations Systems Impacts.....	4-47
4.4.1.8	Meeting High-Level Requirements .....	4-48
4.4.1.9	Detailed Summary .....	4-49
4.4.1.10	Relative Cost.....	4-50
4.4.2	Combined GR-2970-CORE/Database Approach.....	4-51
4.4.2.1	General Description .....	4-51
4.4.2.2	Advantages .....	4-53
4.4.2.3	Disadvantages .....	4-53
4.4.2.4	Network Systems Impacts .....	4-54
4.4.2.5	Database.....	4-54
4.4.2.6	Common Channel Signaling.....	4-55
4.4.2.7	Switching Systems.....	4-55
4.4.2.8	Operations Systems Impacts.....	4-57
4.4.2.9	Meeting High-Level Requirements .....	4-57
4.4.2.10	Detailed Summary .....	4-58
4.4.2.11	Relative Cost.....	4-60
4.5	Approaches Using xPIC.....	4-61
4.5.1	The xPIC Provisioning Approach .....	4-61
4.5.1.1	General Description .....	4-61
4.5.1.2	Advantages of the xPIC Provisioning Approach.....	4-62
4.5.1.3	Disadvantages of the xPIC Provisioning Approach .....	4-62
4.5.1.4	Network Systems Impacts .....	4-63
4.5.1.5	Common Channel Signaling.....	4-63
4.5.1.6	Switching System .....	4-63
4.5.1.7	Operations Systems Impacts.....	4-64
4.5.1.8	Meeting High-Level Requirements .....	4-65
4.5.1.9	Detailed Summary .....	4-66
4.5.1.10	Relative Cost.....	4-67
4.5.2	xPIC Provisioning Approach Combined with a Non Real-Time Database.....	4-68
4.5.2.1	General Description .....	4-68
4.5.2.2	Advantages .....	4-69
4.5.2.3	Disadvantages .....	4-69
4.5.2.4	Network Systems Impacts .....	4-69
4.5.2.5	Common Channel Signaling.....	4-70
4.5.2.6	Switching System .....	4-70
4.5.2.7	Operations Systems Impacts.....	4-71
4.5.2.8	Meeting High-Level Requirements .....	4-71

---

4.5.2.9	Detailed Summary .....	4-72
4.5.2.10	Relative Cost.....	4-74
5.	Interactions and Developing Issues.....	5-1
5.1	Industry Workshop on Service Provider Identification .....	5-1
5.1.1	Background .....	5-1
5.1.2	Key Discussion Results.....	5-3
6.	Summary .....	6-1
6.1	Conclusions.....	6-2
References	.....	References-1
Acronyms	.....	Acronyms-1

## List of Figures

Figure 4-1.	Non Real-Time Database - Centralized Download .....	4-3
Figure 4-2.	GR-2970-CORE Approach to Service Provider Identification .....	4-13
Figure 4-3.	Network Database With No SPI in ISUP Signaling .....	4-23
Figure 4-4.	Network Database with SPI Included in ISUP Signaling.....	4-35
Figure 4-5.	Database Approach With Signaling of Calling Party SPI .....	4-43
Figure 4-6.	Combined GR-2970-CORE/Database Approach .....	4-52
Figure 4-7.	xPIC Provisioning Approach .....	4-61
Figure 6-1.	Meeting High-Level Requirements .....	6-2
Figure 6-2.	Relative Costs of SPI Alternatives .....	6-3



---

## List of Tables

Table 4-1.	Non Real-Time - Meeting Requirements .....	4-9
Table 4-2.	Non Real-Time - Relative Cost .....	4-11
Table 4-3.	GR-2970-CORE - Meeting Requirements .....	4-20
Table 4-4.	GR-2970-CORE - Relative Cost .....	4-22
Table 4-5.	Network Database With No SPI in ISUP - Meeting Requirements .....	4-31
Table 4-6.	Network Database With No SPI in ISUP - Relative Cost.....	4-33
Table 4-7.	Network Database With SPI in ISUP - Meeting Requirements .....	4-39
Table 4-8.	Network Database With SPI in ISUP - Relative Cost .....	4-41
Table 4-9.	Database With Limited Signaling - Meeting Requirements.....	4-48
Table 4-10.	Database With Limited Signaling - Relative Cost.....	4-50
Table 4-11.	Combined GR-2970-CORE/Database - Meeting Requirements .....	4-58
Table 4-12.	Combined GR-2970-CORE/Database - Relative Cost.....	4-60
Table 4-13.	xPIC Provisioning - Meeting Requirements.....	4-65
Table 4-14.	xPIC Provisioning - Relative Cost.....	4-67
Table 4-15.	xPIC with a Non Real-Time Database - Meeting Requirements .....	4-71
Table 4-16.	xPIC with a Non Real-Time Database - Relative Cost.....	4-74