

Table of Contents

1 Introduction

1.1 Organization and Purpose	1-1
1.2 Reason for Reissue	1-2

2 Trunking Service Concepts and Objectives

2.1 Basic Service Criteria	2-1
2.2 Terms for Expressing Trunking Performance and Service Criteria	2-1
2.3 Major Elements of Trunking Service Criteria	2-2
2.4 Considerations Underlying Quality of Service Criteria	2-4
2.5 Considerations Underlying Methods Application Criteria	2-6
2.6 IntraLATA and Exchange Access Service Criteria - ABD	2-9

3 Basic Traffic Characteristics and Principles for Trunk Engineering

3.1 Types of Traffic	3-1
3.1.1 Poisson Distributed Traffic	3-2
3.1.2 Peaked Traffic	3-3
3.1.3 Smooth Traffic	3-4
3.2 Statistical Equilibrium	3-5
3.3 Immediate Connection and Independent Sources	3-6
3.4 Holding Time Distribution	3-6
3.5 Number of Sources	3-6
3.6 Blocking and Retrials	3-8
3.7 Seasonal and Hourly Variations	3-8
3.7.1 Seasonal Variations	3-8
3.7.2 Hourly Variations	3-9
3.7.3 Odd Ball Days	3-10
3.8 Within-the-Hour Variation (Peakedness)	3-10
3.8.1 Peaked Traffic Loads	3-11
3.8.2 Equivalent Random Theory	3-17
3.8.3 Effect of Peakedness on Measurements and Estimates of Loads and Trunks	3-21
3.8.4 Determining Peakedness of Overflow Loads	3-26
3.8.5 Determining Peakedness of Offered Loads	3-33
3.8.6 Effect of Systematic Variations in Source Load	3-40
3.8.7 Computing Peakedness Factors to Reflect Only Within-the-hour Variation Effects	3-40
3.8.8 Special Considerations	3-47
3.8.9 Manual Operations for Implementation of Peakedness Engineering	3-53
3.9 Day-to-Day Variation	3-71
3.9.1 Adjusting Trunk Group Loads For Day-to-Day Variations	3-71
3.9.2 Conditions Under Which No Adjustment Is Required	3-73
3.9.3 Comparative Accuracy of Loads Developed From Varying Type Inputs to Erlang B	3-74
3.9.4 Cause of Varying Erlang B Solutions	3-77
3.9.5 Day-to-Day Adjustment Factor Tables	3-82

3.9.6 Effect of Day-to-Day Adjustments	3-84
3.9.7 Procedures for Day-to-Day Variation Adjustments	3-85
4 Classical Queuing Models: Theories, Variations, Limitations and Applications	
4.1 Binomial	4-1
4.2 Poisson	4-2
4.3 Engset	4-3
4.4 Erlang B	4-5
4.5 Erlang C	4-8
4.6 Wilkinson Equivalent Random Theory	4-9
4.7 Neal-Wilkinson	4-11
5 Trunk Group Types	
5.1 General	5-1
5.2 Traffic Characteristics on Various Types of Trunk Groups	5-2
5.2.1 Background	5-2
5.2.2 Only-Route	5-2
5.2.3 Primary High Usage (PHU)	5-3
5.2.4 Intermediate High Usage (IHU)	5-3
5.2.5 Final	5-3
5.3 Theory Most Applicable to Trunk Group Types	5-5
6 Trunk Network Design	
6.1 Network Configurations	6-1
6.1.1 General	6-1
6.1.2 Alternate Routing	6-1
6.2 Types of Configurations	6-2
6.2.1 General	6-2
6.2.2 Nonalternate Route Networks - Nonhierarchical	6-3
6.2.3 Nonalternate Route Networks - Hierarchical	6-3
6.2.4 Single Tandem Network - Hierarchical - With Single Stage Alternate Routing	6-5
6.2.5 Multitandem Networks	6-6
6.2.6 Exchange Access	6-12
6.3 Principles of Load Allocation and Economic CCS	6-15
6.3.1 General	6-15
6.3.2 Economic CCS	6-16
6.3.3 Cost Ratios	6-20
6.4 Traffic Routing	6-21
6.4.1 Routing Considerations	6-21
6.4.2 Routing Rules - Overview	6-22
6.4.3 Routing and Alternate Routing Rules	6-23
6.5 Busy Hour Concepts	6-38
6.5.1 General	6-38
6.5.2 Types of Busy Hours	6-39
6.5.3 Busy Hour Determination	6-40
6.6 Load Selection Concepts	6-41

6.6.1	General	6-41
6.6.2	Types of Loads and Load-Sets	6-42
6.6.3	Objectives of Load Selection	6-43
6.6.4	Sequential Objectives for Load Selection	6-43
6.6.5	Load Selection Problems	6-44
6.6.6	The Significant-Hour Concept	6-45
6.6.7	Summary	6-48
 7 Traffic Load Concepts		
7.1	Traffic Measurements	7-1
7.1.1	Trunk Group Measurements	7-1
7.2	Retrial Effects on Offered Load Calculations	7-4
7.2.1	Interpreting Trunk Data Affected By NC	7-4
7.2.2	Overall Effects of Retrials	7-4
7.2.3	Adjusting Measured Loads for Retrials	7-6
7.2.4	Adjustment Factors	7-8
7.3	Sizing the Network	7-10
7.3.1	General	7-10
7.3.2	Sizing Concepts	7-12
7.3.3	Procedures for Sizing Trunk Groups	7-14
 8 Trunk Group Structural Arrangements		
8.1	Areas of Application	8-1
8.2	One-Way Versus Two-Way Trunk Groups	8-1
 9 Modular Engineering		
9.1	General	9-1
9.2	The Traffic Facility Engineering Objective	9-1
9.3	The Modular Engineering Approach	9-2
9.4	Modular Engineering Studies	9-2
9.5	Summary of Study Results	9-3
9.5.1	One-Way High-Usage Groups	9-3
9.5.2	Two-Way High-Usage Groups	9-3
9.5.3	Rounding Thresholds	9-3
9.5.4	Administrative/Maintenance Cost	9-4
9.5.5	Separate Local/Toll Network	9-4
9.5.6	Increased Switching and Switch-Exhaust Penalties	9-4
9.5.7	Other Carrier Systems	9-4
9.5.8	Grade-of-Service Groups	9-5
9.6	Guidelines for Modular Trunk Group Engineering	9-6
 10 Signaling		
10.1	Background	10-1
10.2	Common Channel Signaling	10-2
10.2.1	Trunk Engineering Implications	10-2
10.2.2	The Intelligent Network	10-2
10.3	CCS Network Topology	10-3
10.3.1	CCS Network Configurations	10-4

10.3.2 Signaling Links	10-7
10.3.2.1 CCS Link Engineering —General	10-7
10.4 The CCS Signaling Process	10-8
10.4.1 Signal Units	10-8
10.4.2 Signaling Messages	10-12
10.4.2.1 Message Structure	10-13
10.4.2.2 Signaling Network Management Messages	10-14
10.4.2.3 Signaling Test and Maintenance Messages	10-17
10.4.2.4 Circuit-Related Messages	10-17
10.4.2.5 Non-Circuit-Related Messages	10-24
10.4.3 CCS Protocol Structure	10-26
10.5 Signaling Link Engineering	10-27
10.5.1 Signaling Link Capacities	10-28
10.5.2 Signaling Load Estimation	10-28
10.5.2.1 Trunk Signaling Loads	10-29
10.5.2.2 Service Signaling Loads	10-29
10.5.3 Linkset Sizing	10-30

11 Common Channel Signaling (CCS) Enabled Services

11.1 800 Data Base Service	11-1
11.1.1 Architecture and Call Handling	11-2
11.2 Alternate Billing Service	11-3
11.2.1 Architecture and Call Handling	11-3
11.3 CLASS Services	11-5
11.3.1 Architecture and Call Handling	11-6

Appendix A: Related Documents

To Contact Telcordia Customer Service or to Order Documents	A-2
---	-----

Appendix B: Glossary

B.1 General	B-1
B.2 Structure of the Glossary	B-1
B.3 Alphabetical Glossary of Terms and Definitions	B-2
B.4 Glossary of Terms Specific to Signaling System No. 7	B-19

List of Figures

Figure 2-1	Twenty Day Record of Percent Blocking	2-5
Figure 2-2	Average Business Day (ABD) Service Criteria and Busy Hour Method for IntraLATA and Exchange Access Trunk Groups	2-9
Figure 3-1	Poisson Distributed Traffic	3-3
Figure 3-2	Peaked Traffic	3-4
Figure 3-3	Smooth Traffic	3-5
Figure 3-4	Effect of Finite Sources on Capacity at B.01	3-7
Figure 3-5	Calling Rate at the Busy Hour for a One-Year Period	3-9
Figure 3-6	Hourly Variation in Residential and Business Calls	3-9
Figure 3-7	Potential Statistical Measures for Identifying Similar Types of Traffic Distributions	3-12
Figure 3-8	Computation of Variance and Peakedness Factor of Offered Load	3-12
Figure 3-9	Plot of Poisson Distribution	3-13
Figure 3-10	Plot of Moderate Peaked Distribution	3-14
Figure 3-11	Plot of More Pronounced Peaked Distribution	3-15
Figure 3-12	Approximate Effect of Five Trunk High-Usage Group on Poisson Distribution	3-16
Figure 3-13	Approximate Distribution of Calls Overflowing from Five Trunks	3-18
Figure 3-14	Load Carrying Capacity of Trunks as a Function of Offered Load, Trunk Number, and Nature of Offered Load	3-19
Figure 3-15	Effect of Peakedness When Estimating Overflow From IHU Trunk Groups	3-22
Figure 3-16	Effect of Peakedness on Trunk Requirements – No Allowance for Day-to-Day Variation	3-22
Figure 3-17	Understatements Resulting From Conversion of Carried CCS Without Recognizing Peakedness	3-23
Figure 3-18	Overstatements Resulting From Conversion of Percent Overflow to Offered CCS Without Recognizing Peakedness	3-24
Figure 3-19	Ratio of Overflow of Peaked Offered Load to Overflow of Equal-Sized Poisson Offered Load	3-25
Figure 3-20	Ratio of Carried Given Poisson Offered Load to Carried Given Equal-Sized Peaked Offered Load	3-26
Figure 3-21	Peakedness of Overflow When a Poisson Load With a Peakedness Factor of 1.0 is Offered to X Trunks	3-27
Figure 3-22	Peakedness of Overflow When a Peaked Load With a Peakedness Factor of 2.0 is Offered to X Trunks	3-28
Figure 3-23	Peakedness of Overflow When a Peaked Load With a Peakedness Factor of 3.0 is Offered to X Trunks	3-29
Figure 3-24	Summation Method for Developing the Weighted Peakedness Factor of the Offered Load to an Alternate Route Group	3-37
Figure 3-25	Summary of Methods for Computing Peakedness Factor of Offered Loads to Alternate Route Groups	3-39
Figure 3-26	Effect of Day-to-Day Variation on Peakedness Factor of Offered and Overflow Load	3-41
Figure 3-27	Effect of 0.2 Change in Peakedness of Offered Load	3-42
Figure 3-28	Effect of Day-to-Day Variations on Estimates of Measured Peakedness Factors	3-44

Figure 3-29	Effect of Maintenance Outage On Measured Peakedness Factor . . .	3-46
Figure 3-30	Effect on Variance of Independent Versus Dependent Traffic Streams	3-49
Figure 3-31	Directional Alternate Routing	3-50
Figure 3-32	Problem Solution Using Peakedness Table I (Peakedness Factor of Offered Load and Number of Trunks as Inputs)	3-55
Figure 3-33	Problem Solution Using Peakedness Table II (Peakedness Factor of Offered Load and Erlang B LTCCS as Inputs)	3-56
Figure 3-34	Problem Solution Using Peakedness Table II (Erlang B LTCCS and Ratio of Actual Overflow to Erlang B Estimated Overflow as Inputs) . . .	3-58
Figure 3-35	Problem Solution Using Peakedness Table III (Peakedness Factor of Offered Load and Number of Trunks as Inputs)	3-59
Figure 3-36	Suggested Adjustments for Day-to-Day Variations	3-72
Figure 3-37	Illustration of Day-to-Day Variations and Load Solutions	3-73
Figure 3-38	Illustration Of Nonlinear Relationship Among Offered, Carried and Overflow Loads Based on Erlang B	3-78
Figure 3-39	Comparison of Erlang B Estimates With Adjusted Total Loads to Illustrate Bias	3-79
Figure 3-40	Illustration of Linear Relationship Between Offered Loads and Percent Overflow Based on Erlang B at Normal Ranges of Occupancy . . .	3-80
Figure 3-41	Adjustment of Loads for Day-to-Day Variations and Effects on Grade of Service	3-85
Figure 4-1	Blocking Effects, Calls Held Versus Calls Cleared	4-4
Figure 4-2	Erlang B Load/Blocking Curves for 5 to 80 Trunks	4-6
Figure 4-3	Erlang B Load/Blocking Curves for 20 to 30 Trunks	4-7
Figure 4-4	Relationship of Load/Blocking Curve to Alternate Routing Trunk Table	4-8
Figure 4-5	Assumptions Underlying Basic Traffic Theories	4-13
Figure 5-1	Offered Loads That 45 Trunks Can Serve at B.01	5-1
Figure 5-2	Assumed Characteristics of Traffic on Various Types of Trunk Groups	5-4
Figure 5-3	Recommended Theory for Trunk Group Types	5-5
Figure 6-1	Traffic Item Routing via IHU Trunk Groups	6-2
Figure 6-2	Nonalternate Route Network - Nonhierarchical	6-3
Figure 6-3	Nonalternate Route Network - Hierarchical	6-4
Figure 6-4	Single Tandem Network with Single Stage Alternate Routing	6-5
Figure 6-5	Originating Sector Configuration - Single Tandem Switch with Single Stage Alternate Routing	6-7
Figure 6-6	Terminating Sector Configuration - Single Tandem Switch with Single Stage Alternate Routing	6-8
Figure 6-7	Central Tandem Configuration - Single Tandem Switch with Multistage Alternate Routing	6-10
Figure 6-8	Combined Sector Tandem Configuration with Multistage Alternate Routing	6-11
Figure 6-9	Principal Sector Tandem Configuration with Multi-Stage Alternate Routing	6-12
Figure 6-10	Basic IC LATA Access Routing Options	6-13
Figure 6-11	Service Prefix Routing	6-14
Figure 6-12	Sectored Routing	6-14
Figure 6-13	Out-of-LATA Routing	6-15

Figure 6-14	Relationships Involved in Alternate Routing Arrangement	6-16
Figure 6-15	Example of Alternate Routes	6-17
Figure 6-16	Distribution of Offered Load in Accordance with Erlang “Lost-Calls-Cleared” Assumption	6-19
Figure 6-17	Example for Two-Ladder Limit Rule	6-24
Figure 6-18	Example for Two-Ladder Direction Rule	6-25
Figure 6-19	Example for Multiple Switching Function Rule	6-26
Figure 6-20	Example for One-Level Limit Rule	6-27
Figure 6-21	Example for Switch Low Rule	6-27
Figure 6-22	Example for Traffic Grouping Rule	6-28
Figure 6-23	Example of Functional Level Switching for the Traffic Grouping Rule	6-29
Figure 6-24	Example for Single Route Rule	6-30
Figure 6-25	Example of Intraladder Trunking for the Single Route Rule	6-30
Figure 6-26	Example for Load Accumulation Sequence Rule	6-31
Figure 6-27	Logic for Determining Candidate Trunk Groups (Illustrative Example)	6-32
Figure 6-28	Example for Two-Way Interdependency Rule	6-36
Figure 6-29	Example for Alternate Route Selection Rule	6-37
Figure 6-30	Example for One-Switch Alternate Route Rule	6-38
Figure 6-31	Two-Level Multistage Sector Tandem Configuration	6-45
Figure 7-1	Plot of Percentage of Ineffective Attempts (NC) Which Abandon Versus Observed Percentage of NC	7-5
Figure 7-2	Basing Primary High-Usage Group	7-16
Figure 7-3	Sizing Primary High-Usage Group	7-18
Figure 7-4	Basing Intermediate High-Usage Group	7-20
Figure 7-5	Sizing Intermediate High-Usage Group	7-22
Figure 7-6	Basing Final Group	7-24
Figure 7-7	Sizing Final Group	7-26
Figure 7-8	Basing Only Route Group	7-28
Figure 7-9	Sizing Only Route Group	7-29
Figure 8-1	Load Profiles	8-2
Figure 10-1	STP Configuration	10-4
Figure 10-2	Paired STPs	10-4
Figure 10-3	Mated STP Pair Interconnection	10-5
Figure 10-4	Two-Level STP Hierarchy	10-5
Figure 10-5	Regional STP Pair with Subtending Secondary-Level STPs	10-6
Figure 10-6	Extended (E) Links to Remote STP Pair	10-7
Figure 10-7	Typical Signaling Link Traffic	10-8
Figure 10-8	Signal Unit Formats	10-9
Figure 10-9	Message Structure	10-13
Figure 10-10	Signaling Network Management Messages	10-15
Figure 10-11	Signaling Network Test and Maintenance Messages	10-17
Figure 10-12	Circuit-Related Messages	10-19
Figure 10-13	Circuit-Related Messages and Parameters	10-22
Figure 10-14	Circuit-Related Message Parameters	10-23
Figure 10-15	Unitdata and Unitdata Service Messages	10-25
Figure 10-16	SS7 Protocol Structure	10-26
Figure 11-1	800 Data Base Service Architecture	11-2
Figure 11-2	Alternate Billing Service Architecture	11-4

Figure 11-3 **Generic CLASS Service Architecture 11-7**

List of Tables

Table 3-1	Peakedness Table I	3-62
Table 3-2	Peakedness Table II	3-66
Table 3-3	Peakedness Table III	3-68
Table 3-4	Peakedness Table IV	3-69
Table 3-5	Day-to-Day Adjustment Factors, Table IA	3-81
Table 3-6	Day-to-Day Adjustment Factors, Table IB	3-81
Table 3-7	Day-to-Day Adjustment Factors, Table II	3-83
Table 3-8	Day-to-Day Adjustment Factors, Table III	3-84
Table 7-1	Measurement Validation Conditions	7-3
Table 7-2	Customer Retrial Adjustment Factors, Table I	7-10
Table 7-3	Customer Retrial Adjustment Factors, Table II	7-12
Table 7-4	Summary of Data Handling Procedures for Basing and Sizing Trunk Groups	7-14
Table 9-1	Guidelines for Modularly Engineering High-Usage Trunk Groups . .	9-6
Table 9-2	Guidelines for Modularly Engineering Grade-of-Service Trunk Groups	9-7
Table 10-1	Linkset Capacities Table I	10-30
Table 10-2	Linkset Capacities Table II	10-31
Table 10-3	Linkset Capacities Table III	10-31
Table 10-4	Linkset Capacities Table IV	10-31