

Generic Operations Requirements for Broadband Interswitching System Interface and Networking

Contents

1.	Introduction	1-1
1.1	Purpose	1-1
1.2	Scope	1-1
1.3	Document Organization	1-2
1.4	Related Bellcore, Standards, and Industry Documents	1-2
1.5	Requirements Definitions and Conventions	1-5
2.	Overview and Background	2-1
2.1.	B-ISSI and IntraLATA ATM Networking	2-1
2.1.1	Broadband Network Interconnection Model	2-1
2.1.2	B-ISSI and its Protocol Architecture	2-2
2.1.3	ATM Networking Functions	2-4
2.2.	Operations Principles for Multiservice ATM Networking	2-4
2.3.	ATM Networking Operations Functions	2-5
2.3.1	Performance Management Aspects	2-7
2.3.2	Fault Management Aspects	2-7
2.3.3	Configuration Management Aspects	2-8
2.3.4	Network Data Collection Aspects	2-8
2.3.5	Security Management Aspects	2-9
2.3.6	Accounting Management Aspects	2-9
2.4.	Information Model Supporting Operations Interfaces	2-9
3.	ATM Common Platform Operations Criteria	3-1
4.	Operations Criteria to Support SMDS	4-1
4.1	Introduction	4-1
4.2	Configuration Management Criteria	4-2
4.2.1	Introduction	4-2
4.2.2	Summary of Configuration Management Functions	4-5

4.2.3	Interswitch SMDS Configurable Data.....	4-5
4.2.3.1	BSS Identification Data.....	4-7
4.2.3.2	IntraLATA Routing Data.....	4-7
4.2.3.3	InterLATA Routing Data.....	4-9
4.2.3.4	Congestion Management Parameters Data.....	4-10
4.2.3.5	SMDS ISSI Link Set Data.....	4-10
4.2.3.6	Group Address Resolution Data.....	4-11
4.2.4	Distribution of Configurable Data.....	4-11
4.3	Performance Management Criteria.....	4-12
4.3.1	Introduction.....	4-12
4.3.2	AAL Type 3/4 Common Part Performance Monitoring.....	4-13
4.3.3	Service-Specific Performance Monitoring.....	4-13
4.3.3.1	Monitoring Invalid Protocol Fields.....	4-14
4.3.3.2	Monitoring SIP/ISSIP Protocol Field Consistency.....	4-15
4.3.3.3	Monitoring ISSIP Routing Errors.....	4-16
4.4	Fault Management Criteria.....	4-16
4.4.1	Traffic Verification Procedures.....	4-17
4.4.2	Internal Diagnostics.....	4-18
4.5	Network Data Collection.....	4-19
4.5.1	Introduction.....	4-19
4.5.2	Summary of Existing NDC Requirements.....	4-19
4.5.2.1	Common Data Collection Overview.....	4-19
4.5.2.2	Data Collecting and Reporting Overview.....	4-20
4.5.3	Scheduled Measurements.....	4-20
4.5.3.1	SMDS ISSI Traffic Measurements.....	4-21
4.5.3.2	Switch Configuration Disagreement Measurements.....	4-22
4.5.3.3	B-ISSI SMDS Congestion Measurements.....	4-23
4.5.4	Special Studies Measurements.....	4-25
4.5.4.1	Traffic Characterization.....	4-25
4.5.4.2	Traffic Measurements Using Protocol Analyzer.....	4-26
5.	Operations Criteria to Support Frame Relay Service.....	5-1
5.1	Introduction.....	5-1
5.2	Architectural Perspective.....	5-1
5.3	Configuration Management Criteria.....	5-2
5.3.1	Introduction.....	5-2
5.3.2	Trunk Group Parameters.....	5-3
5.3.3	Trunk Parameters.....	5-4
5.3.4	PVC Parameters.....	5-5

5.4	Performance Management Criteria.....	5-5
5.4.1	Introduction.....	5-5
5.4.2	Performance Monitoring.....	5-5
5.4.2.1	Protocol Parameters.....	5-6
5.4.2.2	Cross-BSS Performance Monitoring.....	5-8
5.4.2.3	Protocol Performance Monitoring Algorithms and Strategy..	5-8
5.4.2.4	Disagreements.....	5-11
5.4.3	Network Traffic Management.....	5-11
5.4.3.1	NTM Reports.....	5-11
5.5	Fault Management Criteria.....	5-12
5.5.1	Introduction.....	5-12
5.5.2	Alarm Surveillance.....	5-12
5.5.3	Failure Location and Testing.....	5-13
5.6	Network Data Collection Criteria.....	5-13
5.6.1	Introduction.....	5-13
5.6.2	Managing Collection and Reporting of Measurements.....	5-13
5.6.3	Scheduled Measurements.....	5-13
5.6.3.1	BSS Measurements.....	5-13
5.6.3.2	Trunk Group Measurements.....	5-14
5.6.3.3	Trunk Measurements.....	5-15
5.6.4	Special Studies Measurements.....	5-16
6.	Operations Criteria to Support Cell Relay Service.....	6-1
	References.....	References-1
	Acronyms.....	Acronyms-1
	Glossary.....	Glossary-1