

BRIDLE WIRE

Contents

| | |
|--|-----|
| 1. Introduction | 1 |
| 1.1 Scope | 1 |
| 1.2 Organization | 1 |
| 2. General Information | 1 |
| 2.1 Definition and Purpose | 1 |
| 2.2 Analysis Criteria | 1 |
| 2.3 Safety Considerations | 2 |
| 3. General Requirements | 2 |
| 3.1 Analysis Procedures | 2 |
| 3.2 Packaging Requirements | 2 |
| 3.2.1 Package Marking. | 2 |
| 3.3 Quality Assurance - Program Requirements | 2 |
| 4. Design Requirements | 2 |
| 4.1 Conductors | 3 |
| 4.1.1 Material. | 3 |
| 4.1.2 Factory Joints. | 3 |
| 4.2 Insulation | 3 |
| 4.2.1 Raw Material. | 3 |
| 4.2.2 Porosity. | 3 |
| 4.2.3 Adhesion. | 3 |
| 4.2.4 Compression Resistance. | 3 |
| 4.2.5 Elongation. | 3 |
| 4.2.6 Low Temperature Flexibility. | 3 |
| 4.2.7 Impact Test. | 3 |
| 4.2.8 Shrink-back. | 4 |
| 4.2.9 Light Absorption. | 4 |
| 4.2.10 Conductor Marking. | 4 |
| 4.2.11 Patching. | 4 |
| 4.3 Assembly Requirements | 4 |
| 4.4 Electrical Requirements | 4 |
| 4.4.1 Continuity, Shorts and Crosses. | 4 |
| 4.4.2 Conductor Resistance. | 4 |
| 4.4.3 Insulation Imperfections. | 5 |
| 4.4.4 Electrical Tests (Wet). | 5 |
| TABLE I — Raw Material Requirements For PVC Insulation | 6 |
| APPENDIX A — Compression Test | A-1 |
| APPENDIX B — Shrink-Back Test | B-1 |
| APPENDIX C — Insulation Spark Test | C-1 |

PRELIMINARY