

Table of Contents

1 Introduction

1.1 Purpose and Scope	1-1
1.2 Organization	1-1
1.3 Summary of Changes	1-1

2 General Information

2.1 Definition	2-1
2.2 Use	2-1
2.3 Transportation and Packaging	2-1

3 General Requirements

3.1 General Criteria	3-1
3.2 Product Criteria	3-1
3.3 Quality Assurance	3-1
3.4 Label Marking	3-1
3.5 Material Safety Data Sheet (MSDS)	3-2
3.6 Environmental Impact	3-2
3.7 Order of Testing	3-2
3.8 TDI Content	3-2
3.9 Carcinogen Content	3-3

4 Performance Requirements

4.1 Sample Materials	4-1
4.2 Sample Preparation	4-1
4.3 Water Bath Test	4-1
4.4 Pre-Conditioning of Splices	4-2

5 Material Requirements

5.1 Chemical Requirements	5-1
5.1.1 Isocyanate Content of Urethanes	5-1
5.1.2 Vapor Analysis	5-1
5.2 Physical Requirements	5-1
5.2.1 Corrosion of Copper	5-1
5.2.1.1 Outline of Method	5-1
5.2.1.2 Method of Specifying	5-1
5.2.1.3 Apparatus and Materials	5-2
5.2.1.3.1 Material	5-2
5.2.1.3.2 Laboratory Equipment	5-2
5.2.1.3.3 Miscellaneous Material	5-2
5.2.1.4 Procedure	5-2
5.2.1.4.1 Preparation of Test Specimen	5-2
5.2.1.4.2 Visual Inspection Method	5-3
5.2.1.4.3 Electrical Detection Method	5-3
5.2.2 Hydrolytic Stability	5-4
5.2.3 Peak Exotherm	5-4

5.2.4	Water Absorption	5-4
5.2.5	Dry Heat Aging	5-4
5.2.6	Fungi Resistance	5-4
5.2.7	Gel Time	5-4
5.2.8	Volumetric Expansion	5-4
5.2.9	Stress Cracking of Polyethylene	5-5
5.2.10	Viscosity	5-5
5.2.11	Tensile Strength	5-5
5.2.12	Elongation	5-5
5.2.13	Tear Strength	5-5
5.2.14	Work of Re-entry	5-5
5.2.15	Stress Cracking of Polycarbonate	5-6
5.2.16	Water Sensitivity	5-6
5.2.17	Pour Point	5-6
5.2.18	Compatibility	5-6
5.2.19	Shelf Life	5-6
5.2.20	Colors	5-6
5.2.21	Bond to Materials	5-6
5.2.22	Odor	5-7
5.2.23	Phase Stability	5-7
5.2.24	Coated Conductor Pull-out	5-7
5.2.25	Liquid Compatibility	5-7
5.2.26	Filling Compound Compatibility	5-7
5.3	Electrical Requirements	5-7
5.3.1	Insulation Resistance	5-7
5.3.1.1	Outline of Method	5-7
5.3.1.2	Method of Specifying	5-8
5.3.1.3	Applicability	5-8
5.3.1.4	Apparatus	5-8
5.3.1.5	Procedure	5-8

6 Test Methods

6.1	Hydrolytic Stability	6-1
6.2	Exotherm	6-1
6.3	Dry Heat Aging	6-1
6.4	Gel Time	6-1
6.5	Volumetric Expansion	6-1
6.6	Stress Cracking of Polycarbonate	6-1
6.7	Water Sensitivity	6-2
6.8	Tear Strength at 77° F After Dry Heat Aging	6-2
6.9	Compatibility	6-2
6.10	Shelf Life	6-2
6.11	Colors	6-3
6.12	Bond to Materials	6-3
6.13	Odor	6-3
6.14	Phase Stability	6-3
6.15	Coated Conductor Pull Out	6-3
6.16	Liquid Compatibility	6-4
6.17	Filling Compound Compatibility	6-4

Appendix A: References

Requirement-Object Index

List of Figures

Figure 5-1	Printed Circuit Test Pattern for Testing Corrosivity of Casting Resin Compounds	5-9
Figure 5-2	Printed Circuit Board Specimen Supported in 16 oz. Bottle for Humidity Control	5-10
Figure 5-3	Eleven Position Switchable Test Fixture for Monitoring Corrosion Tests	5-11
Figure 5-4	Electrode Assembly	5-12
Figure 5-5	Test Specimen	5-13
Figure 6-1	Coated Conductor Pull Out Test	6-5