

**GENERIC SYSTEM REQUIREMENTS
IN SUPPORT OF SWITCHED MULTI-MEGABIT DATA SERVICE**

CONTENTS

1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 Changes from TA-TSY-000772, Issue 3 and Supplement 1	1-4
1.3 Organization of Document	1-5
1.4 Key Bellcore Documents	1-6
1.5 Conventions	1-6
2. Background and Overview	2-1
2.1 The Need for SMDS in Customer Environments and Applications	2-1
2.1.1 The Impact of Information Processing Trends and Applications	2-1
2.1.2 The Need to Ease Geographical Limitations	2-2
2.2 The Role of SMDS in a Customer Data Communications Environment	2-3
2.3 The Application of MAN Technology in a Network Supporting SMDS	2-7
2.3.1 A MAN Standard as the Basis for SIP	2-7
2.3.2 MAN Technology as a Basis of Switching Systems	2-9
2.4 Evolution to the Support of SMDS by Broadband ISDN	2-10
3. SMDS Features	3-1
3.1 Overview of Switched Multi-megabit Data Service (SMDS)	3-1
3.2 Feature Description	3-2
3.2.1 Individually Addressed SMDS Data Unit Transport	3-2
3.2.2 Local Communications for Multi-CPE Access Arrangements	3-3
3.2.3 Addresses	3-3
3.2.3.1 Individual Address Format	3-3
3.2.3.2 Group Address Format	3-3
3.2.3.3 Correspondence of Individual Addresses to SNIs	3-3
3.2.4 Source Address Validation	3-4
3.2.5 Group Addressed SMDS Data Unit Transport	3-4
3.2.5.1 Group Address Composition	3-4
3.2.5.2 Transfer of Group Addressed SMDS Data Units	3-5
3.2.6 Address Screening	3-5
3.2.6.1 Individual Address Screens	3-5
3.2.6.2 Group Address Screens	3-6
3.2.6.3 Association of Address Screens with Addresses Identifying an SNI	3-6
3.2.6.4 Destination Address Screening	3-7
3.2.6.5 Source Address Screening	3-7
3.2.7 Access Classes	3-8
3.2.8 Multiple Data Units in Transit Concurrently	3-9
4. Subscriber-Network Interface	4-1
4.1 Definition of SNI	4-1
4.2 SMDS Interface Protocol (SIP)	4-3
4.2.1 Level 3 Peer-to-Peer Protocol Specification	4-5
4.2.1.1 Level 3 Protocol Data Unit Format	4-5
4.2.1.2 Level 3 Protocol Procedures	4-10

4.2.2	Level 2 Peer-to-Peer Protocol Specification	4-12
4.2.2.1	Level 2 Protocol Data Unit Format	4-12
4.2.2.2	Level 2 Protocol Procedures	4-14
4.2.3	SIP Level 1 Control Information	4-21
4.3	Access Classes and Enforcement	4-23
4.3.1	Access Class Mechanism	4-23
4.3.2	Access Class Parameters	4-24
4.3.3	Parameter Values and Relation to Access Classes	4-25
5.	Performance and Quality of Service	5-1
5.1	Availability Objectives	5-3
5.1.1	Scheduled Service Time	5-3
5.1.2	Mean Time Between Service Outages	5-3
5.1.3	Mean-Time-To-Restore	5-3
5.2	Accuracy Objectives	5-3
5.2.1	Errored L3_PDU Ratio	5-4
5.2.2	Misdelivered L3_PDU Ratio	5-4
5.2.3	L3_PDU Not Delivered Ratio	5-4
5.2.4	Duplicated L3_PDU Ratio	5-5
5.2.5	Mis-sequenced L3_PDU Ratio	5-5
5.3	L3_PDU Delay Objectives	5-5
5.3.1	Delay for Individually Addressed L3_PDU	5-6
5.3.2	Delay for Group Addressed L3_PDU	5-6
6.	SS Capacity Generic Requirements	6-1
6.1	Number of SNIs to be Supported by an SS	6-1
6.2	Addressing Criteria and Considerations	6-1
7.	Miscellaneous Generic Requirements	7-1
7.1	Power Supply Requirements	7-1
7.2	Physical Requirements	7-1
7.2.1	Shock and Vibration	7-1
7.2.2	Human Factors	7-1
7.2.3	Fire Resistance	7-1
7.3	Environmental Requirements	7-1
7.3.1	Temperature And Humidity	7-1
7.3.1.1	In Operation	7-1
7.3.1.2	In Storage	7-2
7.3.2	Altitude	7-2
7.3.3	Heat Dissipation	7-2
7.3.4	Acoustical Noise	7-2
7.3.5	Airborne Contaminants	7-2
7.3.6	Electrical Protection	7-2
7.3.7	Electromagnetic Emission and Immunity	7-2
7.3.8	Electrostatic Discharge	7-3
7.3.9	Environmental Impact and Conservation	7-3
7.4	Electrical Safety Requirements	7-3
7.5	Quality and Reliability	7-3
7.5.1	Hardware Reliability Predictions	7-3
7.5.2	Device Reliability	7-4
7.5.3	Physical Design	7-4

7.5.4 Software Quality	7-4
7.5.5 Manufacturing Process	7-4
7.6 System Administration	7-4
7.6.1 Documentation	7-4
7.6.2 Transmission Performance Information	7-4
8. List of Acronyms	8-1
9. Referenced Documents	9-1

LIST OF FIGURES

Figure 1.1. Network in Support of SMDS	1-3
Figure 2.1. Example Scenario of the Use of SMDS with DARPA Protocols	2-4
Figure 2.2. Example Scenario of the Use of SMDS with OSI Protocols	2-5
Figure 2.3. Example Scenario of Bridging Between SMDS and a LAN	2-6
Figure 2.4. (a) Single CPE Access and (b) Multi-CPE Access Arrangements	2-8
Figure 4.1. SMDS Access Configurations	4-2
Figure 4.2. SIP Protocol Stack	4-3
Figure 4.3. Encapsulation of User Information by the Layers of SIP	4-4
Figure 4.4. SIP Level 3 Protocol Data Unit Format	4-5
Figure 4.5. Address Field	4-6
Figure 4.6. Header Extension Field Format	4-7
Figure 4.7a. Example Header Extension with One Carrier Value Specified	4-9
Figure 4.7b. Example Header Extension with Two Carrier Values Specified	4-10
Figure 4.8. SIP Level 2 Protocol Data Unit Format	4-12
Figure 4.9. Access Control Field (CPE → SS)	4-12
Figure 4.10. Access Control Field (SS → CPE)	4-13
Figure 4.11. Segmentation of an L3_PDU into L2_PDUs	4-15
Figure 4.12. State Diagram of SS Procedures for Sending an L2_PDU	4-17
Figure 4.13. SS Level 2 Receiver State Machine for MID x	4-20
Figure 4.14. SIP Level 1 Control Information Fields (M2 and M1 octets)	4-22
Figure 5.1. Scope of SNI-to-SNI Objectives	5-2

LIST OF TABLES

Table 3.1. Choices for Access Classes	3-9
Table 4.1. Element Types	4-8

Table 4.2. Relation of Number of Carriers to Carrier Selection Element Length	4-9
Table 4.3. Segment Type Values	4-13
Table 4.4a. MID Page Allocation Field Values	4-23
Table 4.4b. Page Counter Modulus Codes	4-23
Table 4.5. Parameter Values for Access Classes	4-26
Table 7.1. Radiated Emission Requirements	7-3
Table 7.2. Conducted Emission Requirements	7-3

LIST OF APPENDICES

Appendix A — IEEE P802.6 and SIP	(A1 - A4)
--	-----------