Generic Requirements for Low Speed SMDS Access

Contents

1. Introduction 1-1
1.1 Purpose and Scope 1-1
1.2 Document Organization 1-1
1.3 Changes from TA-TSV-001239, Issue 1 1-2
1.4 Key References 1-3
1.5 Requirements Terminology 1-4

2. Background 2-1
2.1. SMDS Overview 2-1
2.2. Motivation for Low Speed SMDS Access 2-2
2.3 Low Speed SMDS Access Overview 2-3

3. SMDS Features 3-1
3.1 Low Speed SMDS Access Feature Support 3-1
3.2 Feature Deviations for Low Speed SMDS Access 3-1
3.2.1 Number of Individual Addresses per DXI/SNI 3-1
3.2.2 Group Address Composition 3-2
3.2.3 Access Classes 3-2
3.2.4 Multiple Concurrent Data Units in Transit 3-2

4. Data Exchange Interface/Subscriber-Network Interface 4-1
4.1 Definition of DXI/SNI 4-1
4.2 DXI/SNI Protocol 4-1
4.2.1 DXI/SNI Level 3 Protocol Specification 4-1
4.2.2 DXI/SNI Level 2 Protocol Specification 4-2
4.2.3 Physical Layer 4-3

5. Architecture for Low Speed SMDS Access 5-1
5.1 Access Server (AS) Architecture 5-1

5.1.1 AS Interface Support 5-1
5.1.2 AS Processing Delay 5-3
5.1.3 SMDS-to-Access Server Interface (SSI) 5-3
5.1.4 Access Server Support of SMDS Features 5-4
5.1.4.1 Individually Addressed SMDS Data Unit Transport 5-5
5.1.4.2 Group Addressed SMDS Data Unit Transport 5-5
5.1.5 Modifications to SMDS SS Requirements 5-6
5.2 Integrated SMDS SS Architecture 5-7

6. Operations Technology Criteria 6-1
6.1 Changes to Section 6 Since TA-TSV-001239, Issue 1 6-2
6.2 Potential Operations Communications Architectures 6-3
6.3 Memory Administration 6-6
6.3.1 Provisioning-Driven Functions 6-7
6.3.2 System Administration Functions 6-7
6.3.3 Memory Administration Data 6-8
6.3.3.1 Access Server Frame Size 6-9
6.3.3.2 DXI/SNI Provisioning 6-9
6.3.3.3 SSI Provisioning 6-10
6.3.3.4 Address Screening 6-11
6.3.3.5 Group Addressing 6-12
6.3.3.6 Carrier Pre-Selection 6-12
6.3.3.7 End-User Blocking 6-13
6.3.3.8 Heart Beat Poll Administration 6-13
6.3.3.9 Administered Data to Support Usage Measurements for Billing 6-13
6.4 Maintenance 6-14
6.4.1 Alarm Monitoring 6-14
6.4.2 Performance Monitoring 6-15
6.4.2.1 Common Performance Monitoring Criteria 6-15
6.4.2.2 Level 3 Protocol Monitoring 6-16

6.4.2.3 Level 2 Protocol Monitoring 6-17
6.4.2.4 Physical Level Performance Monitoring 6-19
6.4.3 Testing 6-20
6.4.3.1 Diagnostics 6-20
6.4.3.2 Heart Beat Poll 6-20
6.4.3.3 Loopbacks 6-21
6.5 Network Traffic Management and Network Data Collection Criteria 6-22
6.5.1 General Criteria for Network Data Collection 6-22
6.5.2 SIP Level 3 NDC Criteria 6-23
6.5.3 NDC Level 2 Scheduled Measurements 6-25
6.5.4 Congestion Management 6-26
6.6 Order of Precedence Criteria 6-28
6.6.1 Order of Precedence for an AS Processing DXI/SNIs at Ingress 6-28
6.6.2 Order of Precedence for an SMDS SS Processing DXI/SNIs at Ingress 6-29
6.6.3 Order of Precedence for DXI/SNIs at Egress 6-31
6.6.4 Order of Precedence for SSIs 6-32
6.7 Operations Interface Criteria 6-32
6.8 SMDS SS Operations Impacts Related to Section 5.1.5 6-34

7. Performance and Quality of Service 7-1
7.1 Availability Objectives 7-1
7.2 Accuracy Objectives 7-1
7.3 L3_PDU Delay Objectives 7-1

8. Miscellaneous Generic Requirements 8-1
8.1 Usage Information to Support Billing 8-1
8.1.1 Access Server Architecture 8-1
8.1.2 Integrated SMDS SS Architecture 8-2
8.1.3 Segment Count 8-2
8.2 Miscellaneous AS Generic Requirements 8-2

References R-1

Acronyms A-1

List of Figures

Figure 2-1. DQDB-based SMDS Access 2-1

Figure 2-2. Relationship of Services 2-2

Figure 2-3. DQDB-based SMDS Access Implementation of the DXI 2-3

Figure 2-4. Low Speed SMDS Access 2-4

Figure 5-1. Access Server Architecture 5-1

Figure 6-1. Potential Operations Architecture for the Access Server Network Topology 6-5

Figure 6-2. Potential Operations Architecture for the Integrated SMDS SS Network Topology 6-6

Figure 6-3. Heart Beat Poll Procedure 6-21

Figure 7-1. Reference Connection for Delay 7-2

List of Tables

Table 6-1. Order-of-Precedence for an AS Processing DXI/SNIs at Ingress 6-29

Table 6-2. Order-of-Precedence for an SMDS SS Processing DXI/SNIs at Ingress 6-30

Table 6-3. Order-of-Precedence for DXI/SNIs at Egress 6-32

Table 7-1. Delay (msec) for Individually Addressed 512, 1600 and 4096 Octet L3_PDUs 7-3

Table 7-2. Delay (msec) for Group Addressed 512, 1600 and 4096 Octet L3_PDUs 7-4