

# Table of Contents

## 1 Scope and Objectives

## 2 Functions and Applications

2.1 Functions . . . . .	2-1
2.2 Applications . . . . .	2-2

## 3 Network Compatibility Requirements

3.1 Introduction . . . . .	3-1
3.1.1 DSX-1 Cross-Connect . . . . .	3-1
3.1.2 DSX-3 Cross-Connect . . . . .	3-1
3.1.3 DS1 Formats . . . . .	3-1
3.1.4 DS3 Format . . . . .	3-2
3.2 Transmission Requirements . . . . .	3-2
3.2.1 Synchronization . . . . .	3-2
3.2.2 Jitter . . . . .	3-5
3.2.3 Framing Requirements . . . . .	3-5
3.2.4 Transmission Path . . . . .	3-6
3.2.4.1 Bit and Signaling Integrity . . . . .	3-6
3.2.4.2 Codes for Unused SYNTRAN Bits . . . . .	3-6
3.2.4.3 Transmission Delays through ADM 3/X . . . . .	3-7
3.2.4.4 Signaling Delay . . . . .	3-7
3.2.4.5 Signaling Distortion . . . . .	3-7
3.3 SYNTRAN Transmission Modes . . . . .	3-7
3.3.1 Byte Synchronous Mode . . . . .	3-7
3.3.1.1 Carrier Failure Alarm Operation . . . . .	3-9
3.3.1.2 ADM 3/X Trunk Conditioning . . . . .	3-10
3.3.2 Bit-Synchronous Mode . . . . .	3-12
3.4 Maintenance Objectives and Requirements . . . . .	3-13
3.4.1 General . . . . .	3-13
3.4.2 DS3 Maintenance . . . . .	3-13
3.4.2.1 DS3 Signal Failure . . . . .	3-13
3.4.2.2 DS3 AIS Processing . . . . .	3-15

## 4 Feature Listing

4.1 Required Features . . . . .	4-1
4.2 Optional Features . . . . .	4-1

## 5 Feature Descriptions

5.1 Required Features . . . . .	5-1
5.1.1 DS1 to DS3 Multiplexing/Demultiplexing . . . . .	5-1
5.1.2 DS0 Cross-Connection . . . . .	5-1
5.1.3 Remote and Local Operations Interfaces . . . . .	5-2
5.1.3.1 Required Operations Interfaces . . . . .	5-5
5.1.3.2 Data Link Interface . . . . .	5-5
5.1.3.3 Provisioning . . . . .	5-6

5.1.4	Local Non-Volatile Backup Memory . . . . .	5-7
5.1.5	ADM 3/X Frame Maintenance . . . . .	5-7
5.1.5.1	Alarms/Status Information . . . . .	5-8
5.1.5.2	Diagnostics/Maintenance . . . . .	5-9
5.1.6	Facility Maintenance . . . . .	5-10
5.1.7	Interface Security . . . . .	5-11
5.2	Optional Features . . . . .	5-11
5.2.1	Optional Operations Features . . . . .	5-11
5.2.1.1	Access and Test . . . . .	5-11
5.2.1.2	System Maintenance/Performance Monitoring . . . . .	5-13
5.2.2	Sub-DS1 Cross-Connect Capability . . . . .	5-14
5.2.2.1	Local Cross-Connect Capability . . . . .	5-14
5.2.2.2	Low Bit-Rate Voice . . . . .	5-15
5.2.2.3	Other Sub-DS1 Signals . . . . .	5-15
5.2.3	DS1 Interface Capabilities . . . . .	5-15
5.2.3.1	Non-Standard 1.544-Mb/s Formats . . . . .	5-15
5.2.3.2	Alternative Interface Configurations . . . . .	5-15
5.2.4	Fiber Interface . . . . .	5-15
5.2.5	Alternative Low-Speed Interfaces . . . . .	5-16
5.2.5.1	DS1C Interface . . . . .	5-16
5.2.5.2	2.048-Mb/s Interface . . . . .	5-16
5.2.5.3	DS2 Interface . . . . .	5-16
5.2.5.4	DS3 Interface . . . . .	5-16
5.2.6	ADM 3/X Ring Applications . . . . .	5-17
5.2.7	Software Generics . . . . .	5-17
5.2.8	Local Secondary Non-Volatile Backup Memory . . . . .	5-17

**6 Quality and Reliability**

6.1	Reliability Objectives . . . . .	6-1
6.2	Reliability Predictions . . . . .	6-1
6.3	Device Reliability . . . . .	6-2
6.4	Physical Design . . . . .	6-2
6.5	Software Quality . . . . .	6-3
6.6	Manufacturing Quality Program . . . . .	6-3
6.7	Customer Verification of Quality and Reliability . . . . .	6-3
6.8	Product Support . . . . .	6-4

**7 Criteria for Loop Applications**

7.1	Physical Environment . . . . .	7-1
7.1.1	ADM 3/X Located in on Customer Premises . . . . .	7-1
7.1.2	ADM 3/X Located in Outside Plant . . . . .	7-1
7.1.3	ADM 3/X Optical Fiber Integration . . . . .	7-2
7.1.4	DS1 Concerns . . . . .	7-2
7.2	Electrical Environment . . . . .	7-2
7.2.1	Electrical Safety . . . . .	7-2
7.2.2	Electrical Protection . . . . .	7-2
7.3	Electromagnetic Environment . . . . .	7-3

**Appendix A: Specification of the 64-kb/s Data Link Protocol**

A.1 Overview . . . . . A-1  
A.2 Protocol . . . . . A-1  
A.3 Applications . . . . . A-2

**Appendix B: HDLC Frame Structure**

**Appendix C: Normal Response Mode**

**Appendix D: References**

**Appendix E: Acronyms**

## List of Figures

Figure 2-1	ADM 3/X Add-Drop Configuration . . . . .	2-1
Figure 2-2	ADM 3/X Terminal Configuration . . . . .	2-2
Figure 3-1	ADM 3/X Timing . . . . .	3-4
Figure 3-2	Input Jitter Accommodation (Tolerance) Requirements . . . . .	3-5
Figure 3-3	ADM 3/X DS3 Maintenance Example . . . . .	3-14
Figure 5-1	NTE Overview . . . . .	5-2
Figure 5-2	OS/NTE Interfaces Strategic View . . . . .	5-3
Figure 5-3	Relationship of Standard Interface Publications . . . . .	5-4
Figure 5-4	Example of the Use of the 64-kb/s Data Link . . . . .	5-6
Figure 5-5	Test Access Digroup . . . . .	5-12

## List of Tables

Table 3-1	Synchronization Sources . . . . .	3-2
Table 3-2	Requirements for Frozen Signaling Bits . . . . .	3-11
Table 3-3	Trunk Conditioning Signals . . . . .	3-11
Table 3-4	Trunk Conditioning Modes . . . . .	3-12
Table 5-1	Provisioning Driven Memory Administration Functions . . . . .	5-7
Table 5-2	Maintenance Functions . . . . .	5-10