

# Contents

<b>Notice Of Disclaimer</b> . . . . .	iii
<b>List of Figures</b> . . . . .	ix
<b>List of Tables</b> . . . . .	xi
<b>Executive Summary</b> . . . . .	xiii
<b>1 Introduction</b>	
1.1 Purpose and Scope . . . . .	1-1
1.2 Organization . . . . .	1-1
1.3 Levels of System Characteristics . . . . .	1-2
1.4 Reasons for Conversion from a Technical Advisory . . . . .	1-3
<b>2 General Requirements</b>	
2.1 General Design Requirements . . . . .	2-1
2.1.1 (R) Fail-Safe Design . . . . .	2-1
2.1.2 (R) Open Architecture and Backward Compatibility . . . . .	2-1
2.2 Engineering, Installation, and Maintenance . . . . .	2-1
2.2.1 (R) Code Compliance . . . . .	2-1
2.2.2 (R) Fire Resistance . . . . .	2-2
2.2.3 (R) Environmental Requirements . . . . .	2-2
2.2.4 (R) Electromagnetic Interference (EMI) . . . . .	2-3
2.2.5 (R) Ground System . . . . .	2-3
2.2.6 (R) Electrostatic Discharge (ESD) . . . . .	2-3
2.2.7 (R) Electrical Isolation . . . . .	2-4
2.2.8 (R) Frame Current . . . . .	2-4
2.2.9 (R) Shipping Temperature and Humidity . . . . .	2-4
2.2.10 (R) Acoustical Noise . . . . .	2-5
2.2.11 (R) Protection and Hazards . . . . .	2-5
2.2.12 (R) Toxic Materials . . . . .	2-5
2.2.13 (O) Marking of Components . . . . .	2-5
2.2.14 (R) Sparing . . . . .	2-6
2.2.15 (R) Nameplate . . . . .	2-6
<b>3 Electrical Requirements</b>	
3.1 (R) AC Input Source . . . . .	3-1
3.2 (R) AC Ground . . . . .	3-2
3.3 (R) Inrush Current . . . . .	3-2
3.4 (O) Power Factor . . . . .	3-2
3.5 (R) AC Input Protection . . . . .	3-3
3.6 (R) Low AC Voltage Protection . . . . .	3-3
3.7 (R) Hold-Up Time . . . . .	3-3

3.8 (R) Phase Failure . . . . .	3-3
3.9 (R) Power Interruption . . . . .	3-3
3.10 (R) Voltage Output . . . . .	3-4
3.11 (R) Output Voltage Adjustment . . . . .	3-4
3.12 (R) Voltage Regulation . . . . .	3-4
3.13 (R) Voltage/Temperature Coefficient . . . . .	3-5
3.14 (R) Warm-Up Time . . . . .	3-5
3.15 (R) Voltage Drift . . . . .	3-5
3.16 (R) Current Limit . . . . .	3-5
3.17 (R) Stability . . . . .	3-6
3.18 (R) Dynamic Response . . . . .	3-6
3.19 (R) Output Protection and Disconnect . . . . .	3-6
3.20 (R) Wideband Output Noise . . . . .	3-6
3.21 (R) Electromagnetic Interference (EMI) . . . . .	3-7
3.22 (O) Efficiency . . . . .	3-7
3.23 (R) Soft Start . . . . .	3-8
3.24 (R) Discharge of Capacitors . . . . .	3-8
3.25 (R) Induced Frame Current . . . . .	3-8

#### **4 Physical Design**

4.1 (R) Enclosure . . . . .	4-1
4.2 (R) Shock and Vibration . . . . .	4-1
4.3 (R) Earthquake . . . . .	4-1
4.4 (O) Paint . . . . .	4-1
4.5 (R) Cooling . . . . .	4-1
4.6 (R) Heating . . . . .	4-2
4.7 (R) Materials . . . . .	4-2
4.8 (O) Handling . . . . .	4-2

#### **5 Rectifier Interfaces and Alarms**

5.1 (R) Rectifier Alarms . . . . .	5-1
5.2 (R) Internal Over-Voltage Shutdown . . . . .	5-1
5.3 (R) Current Limit Adjustment . . . . .	5-2
5.4 (R) Internal Protection . . . . .	5-2
5.5 (O) Test Points . . . . .	5-2
5.6 (R) Rectifier Reliability and Maintainability . . . . .	5-2
5.7 (R) PWB Nesting . . . . .	5-2
5.8 (R) Jacks . . . . .	5-3

#### **6 Components**

6.1 (R) Transformers and Magnetic Coils . . . . .	6-1
6.2 (R) Hook-Up Wire . . . . .	6-1
6.3 (R) Power Conductors . . . . .	6-3
6.4 (R) Electrical and Mechanical Hardware . . . . .	6-3
6.5 (R) Electrical Power Wire Terminations . . . . .	6-4

6.6 (R) Resistors . . . . .	6-4
6.7 (R) Electrolytic Capacitors . . . . .	6-4
6.8 (R) Non-Electrolytic Capacitors . . . . .	6-5
6.9 (R) Semiconductors . . . . .	6-5
6.10 (R) Circuit Breakers . . . . .	6-5
6.11 (R) Fuses . . . . .	6-6
6.12 (R) Relays . . . . .	6-6
6.13 (R) Switches . . . . .	6-6
6.14 (R) Printed Wire Boards . . . . .	6-7
6.15 (R) Requirements for Stand-Alone Power Supplies . . . . .	6-8

## 7 Quality Assurance, Documentation and Training

7.1 (O) Hardware Quality Assurance Plan . . . . .	7-1
7.2 (O) Documentation . . . . .	7-1
7.3 (O) Training Requirements . . . . .	7-2

## 8 Performance Verification and Test Procedures

8.1 General Tests and Inspections for Section 2 . . . . .	8-1
8.1.1 (R) Fire Resistance (Section 2.2.2†) . . . . .	8-1
8.1.2 (R) Operating Environment (Section 2.2.3†) . . . . .	8-1
8.1.3 (R) Electrostatic Discharge (Section 2.2.6†) . . . . .	8-1
8.1.4 (R) Electrical Isolation (Section 2.2.7†) . . . . .	8-2
8.1.5 (R) Shipping Temperature and Humidity (Section 2.2.9†) . . . . .	8-2
8.1.6 (O) Acoustical Noise (Section 2.2.10†) . . . . .	8-2
8.1.7 (R) Safety and Hazards (Section 2.2.11†) . . . . .	8-2
8.1.8 (R) Toxic Materials (Section 2.2.12†) . . . . .	8-2
8.1.9 (R) Marking of Components (Section 2.2.13†) . . . . .	8-3
8.1.10 (R) Nameplate (Section 2.2.15†) . . . . .	8-3
8.2 Electrical Tests for Section 3 . . . . .	8-3
8.2.1 (R) AC Input Source (Section 3.1) . . . . .	8-3
8.2.2 (R) AC Ground (Section 3.2) . . . . .	8-5
8.2.3 (R) Inrush Current (Section 3.3†) . . . . .	8-5
8.2.4 (O) Power Factor (Section 3.4†) . . . . .	8-6
8.2.5 (R) AC Input Protection (Section 3.5†) . . . . .	8-6
8.2.6 (R) Low AC Voltage Protection (Section 3.6†) . . . . .	8-6
8.2.7 (R) Phase Failure (Section 3.8†) . . . . .	8-6
8.2.8 (R) Power Interruption (Section 3.8 and Section 3.9†) . . . . .	8-7
8.2.9 (R) Voltage Output (Section 3.10†) . . . . .	8-7
8.2.10 (R) Output Voltage Adjustment (Section 3.11†) . . . . .	8-7
8.2.11 (R) Voltage Regulation (Section 3.12†) . . . . .	8-7
8.2.12 (R) Voltage/Temperature Coefficient (Section 3.13†) . . . . .	8-8
8.2.13 (R) Warm-Up Time (Section 3.14†) . . . . .	8-8
8.2.14 (R) Voltage Drift (Section 3.15†) . . . . .	8-8
8.2.15 (R) Current Limit (Section 3.16†) . . . . .	8-8
8.2.16 (R) Stability (Section 3.17†) . . . . .	8-9
8.2.17 (R) Dynamic Response (Section 3.18†) . . . . .	8-9

- 8.2.18 (R) Wideband Output Noise (Section 3.20†) . . . . . 8-9
- 8.2.19 (R) Electromagnetic Interference (EMI) (Section 3.21†) . . . . . 8-9
- 8.2.20 (O) Efficiency (Section 3.22†) . . . . . 8-9
- 8.2.21 (R) Soft Start (Section 3.23†) . . . . . 8-9
- 8.2.22 (R) Discharge of Capacitors (Section 3.24†) . . . . . 8-10
- 8.2.23 (R) Induced Frame Current (Section 3.25†) . . . . . 8-10
- 8.3 Physical Design Tests and Inspections for Section 4 . . . . . 8-10
  - 8.3.1 (R) Enclosure (Section 4.1†) . . . . . 8-10
  - 8.3.2 (R) Shock and Vibration (Section 4.2†) . . . . . 8-10
  - 8.3.3 (R) Earthquake (Section 4.3†) . . . . . 8-10
  - 8.3.4 (O) Paint (Section 4.4†) . . . . . 8-10
  - 8.3.5 (R) Cooling and Heating (Section 4.5 and Section 4.6†) . . . . . 8-10
  - 8.3.6 (R) Materials (Section 4.7†) . . . . . 8-11
  - 8.3.7 (O) Handling (Section 4.8†) . . . . . 8-11
- 8.4 Electrical Tests for Section 5 . . . . . 8-11
  - 8.4.1 (R) Internal Over-Voltage Shutdown (Section 5.2) . . . . . 8-11
  - 8.4.2 (R) Current Limit Adjustment (Section 5.3†) . . . . . 8-11
  - 8.4.3 (R) Internal Protection (Section 5.4†) . . . . . 8-11
  - 8.4.4 (O) Test Points (Section 5.5†) . . . . . 8-11
  - 8.4.5 (R) Rectifier Reliability and Maintainability (Section 5.6†) . . . . . 8-11
  - 8.4.6 (R) PWB Nesting (Section 5.7†) . . . . . 8-12
  - 8.4.7 (R) Jacks (Section 5.8†) . . . . . 8-12
- 8.5 Components Tests and Inspections for Section 6 . . . . . 8-12
  - 8.5.1 (R) Transformers and Magnetic Coils (Section 6.1†) . . . . . 8-12
  - 8.5.2 (R) Power Conductors (Section 6.3†) . . . . . 8-12
  - 8.5.3 (R) Electrical and Mechanical Hardware (Section 6.4†) . . . . . 8-13
  - 8.5.4 (R) Electrical Power Wire Terminations (Section 6.5†) . . . . . 8-13
  - 8.5.5 (R) Resistors (Section 6.6†) . . . . . 8-13
  - 8.5.6 (R) Electrolytic Capacitors (Section 6.7†) . . . . . 8-13
  - 8.5.7 (R) Non-Electrolytic Capacitors (Section 6.8†) . . . . . 8-13
  - 8.5.8 (R) Semiconductors (Section 6.9†) . . . . . 8-13
  - 8.5.9 (R) Circuit Breakers (Section 6.10†) . . . . . 8-13
  - 8.5.10 (R) Fuses (Section 6.11†) . . . . . 8-13
  - 8.5.11 (R) Relays (Section 6.12†) . . . . . 8-14
  - 8.5.12 (R) Switches (Section 6.13†) . . . . . 8-14
  - 8.5.13 (R) Printed Wire Boards (Section 6.14†) . . . . . 8-14
- 8.6 (O) Documentation Tests and Inspections (Section 7.2†) . . . . . 8-14

## 9 Glossary

### Appendix A: References

- Note . . . . . A-2
  - To Contact Telcordia Customer Service or to Order Documents . . . . . A-2
  - To Order Documents From Within Telcordia (Employees Only) . . . . . A-2

## List of Figures

Figure 8-1	Test Connections . . . . .	8-4
------------	----------------------------	-----



## List of Tables

Table 2-1	Isolation Test Voltages . . . . .	2-4
Table 3-1	Voltage Limits . . . . .	3-1
Table 3-2	Adjustment Voltage Range . . . . .	3-4
Table 3-3	Noise Levels . . . . .	3-7
Table 3-4	Desired Rectifier Efficiency . . . . .	3-7
Table 5-1	Alarms and Controls . . . . .	5-1
Table 6-1	Maximum Allowable Temperature . . . . .	6-1
Table 6-2	Maximum Permissible Current . . . . .	6-2
Table 6-3	Maximum Operating Voltage and Temperature . . . . .	6-2
Table 6-4	Suggested Torques, Clamping Load, and Electrical Current Rating . . . . .	6-3
Table 6-5	Semiconductor Torque Limits . . . . .	6-5
Table 6-6	Allowable Temperatures For Switches and Contacts . . . . .	6-6
Table 8-1	Test Equipment . . . . .	8-5