

# Table of Contents

## 1 Introduction

|                                                                                    |     |
|------------------------------------------------------------------------------------|-----|
| 1.1 Purpose and Scope . . . . .                                                    | 1-1 |
| 1.2 Items Not Covered in This GR . . . . .                                         | 1-2 |
| 1.3 Requirements Terminology . . . . .                                             | 1-2 |
| 1.4 Requirement Labeling Conventions . . . . .                                     | 1-3 |
| 1.4.1 Numbering of Requirement and Related Objects . . . . .                       | 1-3 |
| 1.4.2 Requirement, Conditional Requirement, and Objective Identification . . . . . | 1-4 |
| 1.5 Organization . . . . .                                                         | 1-4 |
| 1.6 Reasons for GR-1089-CORE . . . . .                                             | 1-5 |
| 1.6.1 Reasons for GR-1089-CORE, Issue 6 . . . . .                                  | 1-5 |
| 1.7 Application of This Document . . . . .                                         | 1-6 |
| 1.8 Guidelines for Equipment Evaluation . . . . .                                  | 1-7 |
| 1.9 Documentation . . . . .                                                        | 1-7 |
| 1.9.1 General . . . . .                                                            | 1-7 |
| 1.9.2 Root Cause Analysis . . . . .                                                | 1-8 |
| 1.10 Number of Samples To Be Tested . . . . .                                      | 1-8 |
| 1.11 Relation to Other Telcordia Documents . . . . .                               | 1-9 |
| 1.12 Navigating the GR-1089 Portable Document Format (PDF) File . . . . .          | 1-9 |

## 2 System-Level Electrostatic Discharge (ESD) and Electrical Fast Transient (EFT)

|                                                                      |     |
|----------------------------------------------------------------------|-----|
| 2.1 System-Level ESD . . . . .                                       | 2-1 |
| 2.1.1 Overview . . . . .                                             | 2-1 |
| 2.1.2 ESD Immunity Criteria . . . . .                                | 2-1 |
| 2.1.2.1 Immunity Criteria — Normal Operation . . . . .               | 2-2 |
| 2.1.2.2 Immunity Criteria — Installation and Maintenance . . . . .   | 2-2 |
| 2.1.2.3 ESD Warning Label Requirements . . . . .                     | 2-2 |
| 2.1.2.4 Equipment-Specific Requirements . . . . .                    | 2-3 |
| 2.1.2.4.1 Additional Equipment Requirements . . . . .                | 2-3 |
| 2.1.2.4.2 Maintenance Information . . . . .                          | 2-3 |
| 2.1.3 Service-Affecting Responses and Manual Interventions . . . . . | 2-3 |
| 2.1.4 ESD Test Methods and Procedures . . . . .                      | 2-4 |
| 2.1.4.1 Test Methods — Normal Operation . . . . .                    | 2-4 |
| 2.1.4.2 Test Methods — Installation and Maintenance . . . . .        | 2-4 |
| 2.1.4.3 Selection of Test Points . . . . .                           | 2-4 |
| 2.1.4.3.1 Test Points — Normal Operation . . . . .                   | 2-5 |
| 2.1.4.3.2 Test Points — Installation and Maintenance . . . . .       | 2-5 |
| 2.1.4.4 EUT Operating Conditions . . . . .                           | 2-5 |
| 2.1.4.5 ESD Test Site . . . . .                                      | 2-6 |
| 2.2 Electrical Fast Transient (EFT) . . . . .                        | 2-7 |
| 2.2.1 EFT Test Methods and Procedures . . . . .                      | 2-7 |

## 3 Electromagnetic Interference (EMI)

|                                        |     |
|----------------------------------------|-----|
| 3.1 General . . . . .                  | 3-1 |
| 3.1.1 Overview . . . . .               | 3-1 |
| 3.1.2 Intent of EMI Criteria . . . . . | 3-1 |

|           |                                                                                   |      |
|-----------|-----------------------------------------------------------------------------------|------|
| 3.1.3     | FCC Part 15 Criteria . . . . .                                                    | 3-2  |
| 3.1.4     | Consolidating Testing . . . . .                                                   | 3-3  |
| 3.1.5     | Documentation . . . . .                                                           | 3-3  |
| 3.2       | Emission Criteria . . . . .                                                       | 3-3  |
| 3.2.1     | Radiated Emission Criteria . . . . .                                              | 3-4  |
| 3.2.1.1   | Electric Fields Radiated Emission Criteria for Unintentional Radiators . . . . .  | 3-4  |
| 3.2.1.2   | Electric Fields Radiated Emission Criteria for Intentional Radiators . . . . .    | 3-7  |
| 3.2.2     | Conducted Emission Criteria for Power Ports . . . . .                             | 3-8  |
| 3.2.2.1   | Conducted Emission Requirements for AC Power Ports — Voltage . . . . .            | 3-8  |
| 3.2.2.2   | Conducted Emission Requirements for AC and DC Power — Current . . . . .           | 3-9  |
| 3.2.3     | Conducted Emission Requirements for Telecommunication Ports — Current . . . . .   | 3-10 |
| 3.3       | Immunity Criteria . . . . .                                                       | 3-11 |
| 3.3.1     | Radiated Immunity Criteria . . . . .                                              | 3-11 |
| 3.3.1.1   | Electric Fields Radiated Immunity Criteria with Doors and Covers Closed . . . . . | 3-12 |
| 3.3.1.2   | Electric Fields Radiated Immunity Criteria with Doors and Covers Open . . . . .   | 3-12 |
| 3.3.2     | Conducted Immunity Criteria for AC and DC Power Ports . . . . .                   | 3-12 |
| 3.3.3     | Conducted Immunity Criteria for Telecommunications Ports . . . . .                | 3-13 |
| 3.3.3.1   | Conducted Immunity Requirements for Signal and Telecommunication Leads . . . . .  | 3-13 |
| 3.3.3.2   | Conducted Immunity Requirements for Voiceband Leads . . . . .                     | 3-13 |
| 3.4       | Measurement Procedures Associated With Emissions . . . . .                        | 3-14 |
| 3.4.1     | Scope . . . . .                                                                   | 3-14 |
| 3.4.2     | Related Standards . . . . .                                                       | 3-14 |
| 3.4.3     | Measuring Instrumentation . . . . .                                               | 3-14 |
| 3.4.3.1   | General . . . . .                                                                 | 3-14 |
| 3.4.3.2   | Measurement Instrumentation . . . . .                                             | 3-15 |
| 3.4.3.3   | Measuring Instrument Calibration . . . . .                                        | 3-15 |
| 3.4.3.4   | Detector Function Selection and Bandwidth . . . . .                               | 3-15 |
| 3.4.3.5   | Antennas . . . . .                                                                | 3-16 |
| 3.4.4     | General Test Conditions . . . . .                                                 | 3-17 |
| 3.4.4.1   | Emission Measurement Uncertainty . . . . .                                        | 3-17 |
| 3.4.4.2   | Testing at an Open-Area Test Site (OATS) . . . . .                                | 3-18 |
| 3.4.4.3   | Testing at User's Installation (On-Premises Testing) . . . . .                    | 3-18 |
| 3.4.4.3.1 | System Premises . . . . .                                                         | 3-18 |
| 3.4.4.3.2 | Number of Systems To Be Tested . . . . .                                          | 3-18 |
| 3.4.4.3.3 | Selection of Systems for Test . . . . .                                           | 3-19 |
| 3.4.4.4   | Testing in a Shielded Enclosure . . . . .                                         | 3-20 |
| 3.4.4.5   | Subsystem Emission Limits Allocation . . . . .                                    | 3-20 |
| 3.4.4.6   | Units of Measurement . . . . .                                                    | 3-20 |
| 3.4.4.7   | Data Reporting Format . . . . .                                                   | 3-21 |
| 3.4.4.8   | Test Conditions for EUT . . . . .                                                 | 3-21 |
| 3.4.4.8.1 | EUT Installation . . . . .                                                        | 3-21 |
| 3.4.4.8.2 | Conditioning of the EUT . . . . .                                                 | 3-22 |
| 3.4.4.8.3 | Interfacing Units and Simulators . . . . .                                        | 3-22 |
| 3.4.4.8.4 | EUT Grounding . . . . .                                                           | 3-23 |

- 3.4.4.8.5 DC Return . . . . . 3–23
- 3.4.4.9 Test Environment . . . . . 3–24
- 3.4.4.10 Arrangements of EUT . . . . . 3–24
- 3.4.4.11 Arrangements of Intentional Radiators . . . . . 3–25
- 3.4.5 Conducted Emissions Measurements . . . . . 3–25
  - 3.4.5.1 Measurement Procedures . . . . . 3–25
    - 3.4.5.1.1 AC Power Ports (Voltage) . . . . . 3–25
    - 3.4.5.1.2 AC Power Ports (Current) . . . . . 3–26
    - 3.4.5.1.3 DC Power Ports (Current) . . . . . 3–26
    - 3.4.5.1.4 Telecommunications Ports . . . . . 3–26
- 3.4.6 Radiated Emission Measurements . . . . . 3–28
  - 3.4.6.1 Determination of Test Radial . . . . . 3–28
  - 3.4.6.2 Radiated Radio Noise Tests . . . . . 3–29
- 3.4.7 Retesting With System Evolution and Growth . . . . . 3–29
  - 3.4.7.1 System Evolution . . . . . 3–29
  - 3.4.7.2 System Growth . . . . . 3–30
- 3.5 Measurement Procedures Associated With Immunity . . . . . 3–30
  - 3.5.1 Scope . . . . . 3–30
  - 3.5.2 Measuring Instrumentation . . . . . 3–30
    - 3.5.2.1 Receivers . . . . . 3–30
    - 3.5.2.2 Current Probes . . . . . 3–31
    - 3.5.2.3 Antennas . . . . . 3–31
    - 3.5.2.4 Signal Sources . . . . . 3–31
  - 3.5.3 Test Conditions for EUT . . . . . 3–31
    - 3.5.3.1 Non-Switching Systems . . . . . 3–32
    - 3.5.3.2 Bit Error Rate (BER) . . . . . 3–32
    - 3.5.3.3 Synchronization . . . . . 3–32
    - 3.5.3.4 Voiceband Noise . . . . . 3–33
  - 3.5.4 Data Reporting Format . . . . . 3–34
  - 3.5.5 Radiated Immunity Measurements . . . . . 3–34
    - 3.5.5.1 Shielded Enclosures . . . . . 3–34
    - 3.5.5.2 Subsystem Testing . . . . . 3–34
    - 3.5.5.3 Measurement Procedures . . . . . 3–34
      - 3.5.5.3.1 EUT and Antenna Positioning . . . . . 3–34
      - 3.5.5.3.2 Calibration of Generated Fields . . . . . 3–35
      - 3.5.5.3.3 EUT Leads . . . . . 3–36
      - 3.5.5.3.4 EUT Grounding . . . . . 3–37
      - 3.5.5.3.5 DC Return . . . . . 3–37
      - 3.5.5.3.6 Test Signal Modulation . . . . . 3–39
      - 3.5.5.3.7 Frequencies and Amplitudes To Be Measured . . . . . 3–39
  - 3.5.6 Conducted Immunity Measurements . . . . . 3–41
    - 3.5.6.1 Test Signal Modulation . . . . . 3–41
    - 3.5.6.2 Frequency Scanning and Test Selection . . . . . 3–41
    - 3.5.6.3 Calibration of Test Signal . . . . . 3–41
    - 3.5.6.4 AC and DC Leads (Common-Mode Injection) . . . . . 3–41
    - 3.5.6.5 Telecommunications Ports —Voiceband, Telecommunications and  
Signal Leads (Common-Mode Injection) . . . . . 3–42

**4 Lightning and Power Fault**

- 4.1 Overview . . . . . 4–1

|             |                                                                                                                   |      |
|-------------|-------------------------------------------------------------------------------------------------------------------|------|
| 4.2         | Electrical Protection on Coaxial and Paired-Conductor Systems . . . . .                                           | 4-4  |
| 4.2.1       | Primary and Secondary Voltage-Limiting Protectors . . . . .                                                       | 4-4  |
| 4.2.2       | Current-Limiting Protectors . . . . .                                                                             | 4-6  |
| 4.2.3       | Fuse Links . . . . .                                                                                              | 4-6  |
| 4.2.4       | Considerations for Equipment That Can Be Located at Cell Sites or Other<br>Locations With Tall Antennas . . . . . | 4-6  |
| 4.3         | Lightning Effects on Paired-Conductor Cables . . . . .                                                            | 4-7  |
| 4.3.1       | Longitudinal Surges . . . . .                                                                                     | 4-7  |
| 4.3.2       | Metallic Surges . . . . .                                                                                         | 4-8  |
| 4.4         | AC Power Fault Effects on Paired-Conductor Cables . . . . .                                                       | 4-8  |
| 4.4.1       | Power Contact to Telecommunications OSP . . . . .                                                                 | 4-8  |
| 4.4.2       | Fault Induction From Electric Power Lines . . . . .                                                               | 4-9  |
| 4.5         | General Testing Information and Guidelines . . . . .                                                              | 4-9  |
| 4.5.1       | Test Equipment . . . . .                                                                                          | 4-9  |
| 4.5.2       | Safety Precautions . . . . .                                                                                      | 4-10 |
| 4.5.3       | Test Samples, Test Modes, and Circuit Analysis . . . . .                                                          | 4-10 |
| 4.5.4       | Termination of Equipment Port Conductors During Tests . . . . .                                                   | 4-11 |
| 4.5.4.1     | Series-Type Equipment . . . . .                                                                                   | 4-13 |
| 4.5.5       | Test Duration and Time Between Tests . . . . .                                                                    | 4-13 |
| 4.5.6       | Lightning Surge and AC Power Fault Test Connections . . . . .                                                     | 4-13 |
| 4.5.6.1     | Generator Connections . . . . .                                                                                   | 4-13 |
| 4.5.6.2     | EUT Grounding . . . . .                                                                                           | 4-16 |
| 4.5.6.3     | DC Return . . . . .                                                                                               | 4-16 |
| 4.5.6.4     | Wiring Simulators for Second-Level Power Fault Tests . . . . .                                                    | 4-16 |
| 4.5.7       | Conformance Criteria . . . . .                                                                                    | 4-17 |
| 4.5.7.1     | First-Level Criteria . . . . .                                                                                    | 4-17 |
| 4.5.7.2     | Second-Level Criteria . . . . .                                                                                   | 4-18 |
| 4.5.8       | Determination of Secondary Protector Values for Undervoltage/<br>Undercurrent Tests . . . . .                     | 4-19 |
| 4.5.8.1     | Lightning — Secondary Protection . . . . .                                                                        | 4-19 |
| 4.5.8.2     | Power Fault — Secondary Protection . . . . .                                                                      | 4-19 |
| 4.5.9       | Equipment Interfacing With Agreed or Non-Field Replaceable Integrated<br>Primary Protectors . . . . .             | 4-20 |
| 4.6         | Testing Requirements . . . . .                                                                                    | 4-22 |
| 4.6.1       | Design Verification Tests for Telecommunications Ports . . . . .                                                  | 4-23 |
| 4.6.1.1     | Short Circuit Test (Telecommunications Type 1, 3, and 5 Ports) . . . . .                                          | 4-23 |
| 4.6.1.2     | Ethernet Interface Considerations (Telecommunications Type 1, 2, 3,<br>3a/5a, 3b/5b, 4, 4a, or 5 Ports) . . . . . | 4-23 |
| 4.6.1.3     | Cell Site Inter-Structure Withstand Criteria (Telecommunications Type<br>3a/5a and 8b Ports) . . . . .            | 4-24 |
| 4.6.1.3.1   | Option A — Isolation Test . . . . .                                                                               | 4-25 |
| 4.6.1.3.2   | Option B — Surge Test . . . . .                                                                                   | 4-27 |
| 4.6.2       | Lightning Requirements and Test Criteria . . . . .                                                                | 4-30 |
| 4.6.2.1     | First-Level Lightning Surge . . . . .                                                                             | 4-30 |
| 4.6.2.1.1   | First-Level Lightning Criteria for Telecommunications Ports (Type<br>1, 3, 3b/5b, and 5 Ports) . . . . .          | 4-30 |
| 4.6.2.1.2   | First-Level Lightning Surge Test Procedure Guidelines for<br>Telecommunications Ports . . . . .                   | 4-31 |
| 4.6.2.1.2.1 | Test Procedure for Surge Test Number 1 of <a href="#">Table 4-2</a> —<br>Multiport OSP Test . . . . .             | 4-31 |

- 4.6.2.1.2.2 Test Procedure for Surge Test Number 2 and Surge Test Number 2.1 of [Table 4-2](#) — OSP Interface Tests . . . . . 4-32
- 4.6.2.1.2.3 Test Procedure for Surge Test Number 3 of [Table 4-2](#) — Gas Tube Interaction Test . . . . . 4-33
- 4.6.2.1.2.4 Test Procedure for Surge Test Number 4 of [Table 4-2](#) — Inductive Kick Test for OSP Interfaces . . . . . 4-34
- 4.6.2.1.2.5 Test Procedure for Surge Test Number 5 of [Table 4-2](#) — Fast Rise Time Test for Remote OSP Interfaces . . . . . 4-34
- 4.6.2.1.2.6 Test Procedure for Surge Test Number 6 of [Table 4-2](#) — Higher Ground Resistance for Remote OSP Interface . . . . . 4-35
- 4.6.2.1.2.7 Test Procedure and Criteria for Surge Test Number 7 of [Table 4-2](#) — High Lightning Exposure Test for Remote OSP Interfaces . . . . . 4-36
- 4.6.2.1.3 Intra-Building or Intra-Site Lightning Criteria (Telecommunications Type 2, 3a/5a, 4, 4a Ports) . . . . . 4-37
- 4.6.2.1.4 Specific Test Procedures and Conditions for Intra-Building and Intra-Site Lightning Test of Type 2, 3a/5a, 4 and 4a Ports . . . . . 4-38
  - 4.6.2.1.4.1 Test Procedure for Surge Test Number 10 of [Table 4-2](#) — Alternative Intra-Building for Up to 2 Pairs Per Port (Metallic) . . . . . 4-40
  - 4.6.2.1.4.2 Test Procedure for Surge Test Number 10.1 of [Table 4-2](#) — Alternative Intra-Building with Secondary Protectors Up to 2 Pairs Per Port (Metallic) . . . . . 4-40
- 4.6.2.1.5 First-Level Lightning Criteria for Antenna Ports (Telecommunications Type 6 Ports) . . . . . 4-44
- 4.6.2.1.6 First-Level Lightning Criteria for AC Power Ports (Telecommunications Type 7 Ports) . . . . . 4-45
- 4.6.2.1.7 DC Power to Antenna Lightning Criteria (Type 8a Ports) . . . . . 4-45
  - 4.6.2.1.7.1 Test Procedure for Surge Test Number 22 of [Table 4-2](#) — Tower Mounted Transceiver Fed With Remote DC Power Test . . . . . 4-46
- 4.6.3 Second-Level Lightning Requirements . . . . . 4-54
  - 4.6.3.1 Second-Level Lightning for Telecommunication Ports (Type 1, 3, and 5 Ports) . . . . . 4-54
  - 4.6.3.2 Second-Level Lightning for AC Power Ports (Type 7 Ports) . . . . . 4-55
- 4.6.4 Power Fault Requirements . . . . . 4-56
  - 4.6.4.1 First-Level Power Fault/Induction Requirements . . . . . 4-56
  - 4.6.4.2 Second-Level Power Fault Requirements . . . . . 4-59
- 4.7 Criteria for Equipment With Integrated Primary Protection . . . . . 4-68
  - 4.7.1 Equipment Classification . . . . . 4-70
  - 4.7.2 Protector Requirements . . . . . 4-72
  - 4.7.3 Lightning Surge and Power Fault Tests for Protected Circuits . . . . . 4-73
  - 4.7.4 Fusing Coordination for Unprotected Circuits . . . . . 4-73
    - 4.7.4.1 Fusing Coordination for Circuits That Contain Components or Circuitry That Act as OSP Fuse Links . . . . . 4-74
      - 4.7.4.1.1 Enclosure Suitable for Fusing . . . . . 4-75
    - 4.7.4.2 Fusing Coordination for Circuits Not Containing Components or Circuitry That Act as OSP Fuse Links . . . . . 4-75
  - 4.7.5 Dielectric Withstand . . . . . 4-77
  - 4.7.6 EIPP Cable Requirements . . . . . 4-77

|                                                                                               |      |
|-----------------------------------------------------------------------------------------------|------|
| 4.7.7 AC Power Fault Immunity — Unprotected Circuits . . . . .                                | 4-78 |
| 4.7.8 Lightning Surge Tests — Unprotected Circuits . . . . .                                  | 4-78 |
| 4.7.8.1 Lightning Surge Tests for Severe Climatic Conditions — Unprotected<br>Units . . . . . | 4-79 |
| <b>5 Steady-State Power Induction</b>                                                         |      |
| 5.1 Overview . . . . .                                                                        | 5-1  |
| 5.2 Longitudinal Induction Criteria . . . . .                                                 | 5-2  |
| 5.2.1 Longitudinal Induction Test Circuit . . . . .                                           | 5-3  |
| 5.2.2 Calibration Procedure . . . . .                                                         | 5-7  |
| 5.2.3 Test Procedures . . . . .                                                               | 5-8  |
| 5.2.3.1 Analog Loop Testing . . . . .                                                         | 5-8  |
| 5.2.3.2 Analog Loop Criteria . . . . .                                                        | 5-9  |
| 5.2.3.3 Digital Loop Testing . . . . .                                                        | 5-14 |
| 5.2.3.4 Line/Span Powering Loop Testing . . . . .                                             | 5-16 |
| <b>6 DC Potential Difference</b>                                                              |      |
| <b>7 Electrical and Optical Safety Criteria</b>                                               |      |
| 7.1 Overview . . . . .                                                                        | 7-1  |
| 7.2 Listing Requirements . . . . .                                                            | 7-2  |
| 7.3 Classification of Voltages . . . . .                                                      | 7-2  |
| 7.3.1 Continuous Voltage and Current Limits . . . . .                                         | 7-3  |
| 7.3.1.1 Class A1 Voltage Limits . . . . .                                                     | 7-4  |
| 7.3.1.2 Class A2 Voltage Limits . . . . .                                                     | 7-8  |
| 7.3.1.3 Class A3 Voltage Limits . . . . .                                                     | 7-11 |
| 7.3.1.4 Class AB Voltage Limits . . . . .                                                     | 7-14 |
| 7.3.1.5 Class B Voltage Limits . . . . .                                                      | 7-14 |
| 7.3.1.6 Class C Voltage Limits . . . . .                                                      | 7-14 |
| 7.4 Continuous Source Requirements . . . . .                                                  | 7-14 |
| 7.4.1 Class A1 Voltage Accessibility Requirements . . . . .                                   | 7-17 |
| 7.4.2 Class A2 Voltage Accessibility Requirements . . . . .                                   | 7-17 |
| 7.4.3 Class A3 Voltage Accessibility Requirements . . . . .                                   | 7-17 |
| 7.4.4 Class AB Voltage Accessibility Requirements . . . . .                                   | 7-18 |
| 7.4.5 Class B Voltage Accessibility Requirements . . . . .                                    | 7-18 |
| 7.4.6 Class C Voltage Accessibility Requirements . . . . .                                    | 7-18 |
| 7.5 Duration-Limited Source Requirements . . . . .                                            | 7-18 |
| 7.5.1 Interrupted/Tripped Sources . . . . .                                                   | 7-18 |
| 7.5.1.1 Ring-Trip Test Procedure . . . . .                                                    | 7-20 |
| 7.5.2 Transient Sources . . . . .                                                             | 7-20 |
| 7.6 Power Limitation Requirement . . . . .                                                    | 7-21 |
| 7.7 Leakage Currents From Exposed Surfaces . . . . .                                          | 7-22 |
| 7.7.1 General Considerations . . . . .                                                        | 7-22 |
| 7.7.2 Leakage Current Requirements . . . . .                                                  | 7-23 |
| 7.7.2.1 Leakage Current Requirements for Large-Area Contact . . . . .                         | 7-23 |
| 7.7.2.2 Leakage Current Requirements for Small-Area Contact . . . . .                         | 7-24 |
| 7.7.2.3 Leakage Current Between Surfaces of Equipment . . . . .                               | 7-24 |
| 7.8 Laser Safety and Labeling Criteria . . . . .                                              | 7-24 |

## 8 Corrosion

|                                                               |     |
|---------------------------------------------------------------|-----|
| 8.1 Polarity of DC Voltages Applied to OSP Cabling . . . . .  | 8-1 |
| 8.2 Magnitude of DC Voltages Applied to OSP Cabling . . . . . | 8-1 |

## 9 Bonding and Grounding

|                                                                                 |      |
|---------------------------------------------------------------------------------|------|
| 9.1 Scope . . . . .                                                             | 9-1  |
| 9.2 General Requirements Principles . . . . .                                   | 9-1  |
| 9.3 Equipment Grounding Systems . . . . .                                       | 9-2  |
| 9.3.1 Common Bonding Network (CBN) . . . . .                                    | 9-3  |
| 9.3.2 Isolated Bonding Network (IBN) . . . . .                                  | 9-3  |
| 9.4 AC Equipment Grounding . . . . .                                            | 9-4  |
| 9.5 Communication Equipment Grounding . . . . .                                 | 9-4  |
| 9.5.1 Network Telecommunication Facilities . . . . .                            | 9-5  |
| 9.5.2 Locations Where the NEC Applies . . . . .                                 | 9-5  |
| 9.5.3 Outside Plant (OSP) . . . . .                                             | 9-6  |
| 9.6 Equipment Unit Bonding and Grounding . . . . .                              | 9-6  |
| 9.7 Provisions for Equipment Unit Assembly Bonding and Grounding . . . . .      | 9-7  |
| 9.7.1 Connectors and Connection Methods for Equipment Unit Assemblies . . . . . | 9-8  |
| 9.7.2 Bonding of Circuit Packs . . . . .                                        | 9-9  |
| 9.8 DC Power System Grounding . . . . .                                         | 9-9  |
| 9.8.1 Centralized Power Sources . . . . .                                       | 9-9  |
| 9.8.2 Embedded Power Sources . . . . .                                          | 9-9  |
| 9.8.3 Bonding of Battery Return (BR) Input Terminals . . . . .                  | 9-12 |
| 9.9 Bonding and Grounding Conductor and Connection Requirements . . . . .       | 9-12 |
| 9.9.1 Bonding and Grounding Conductors . . . . .                                | 9-13 |
| 9.9.2 Connections . . . . .                                                     | 9-13 |
| 9.9.3 Connectors . . . . .                                                      | 9-14 |
| 9.10 Short-Circuit Tests . . . . .                                              | 9-14 |
| 9.10.1 DC Power Sources . . . . .                                               | 9-14 |
| 9.10.2 AC Power Sources . . . . .                                               | 9-16 |
| 9.11 Other Grounding Considerations . . . . .                                   | 9-17 |
| 9.12 Compatibility of Former IBN Equipment With CBN Currents . . . . .          | 9-17 |
| 9.12.1 Test Conditions for EUT . . . . .                                        | 9-18 |
| 9.12.1.1 Conditioning of the EUT . . . . .                                      | 9-18 |
| 9.12.1.2 Interfacing Units and Simulators . . . . .                             | 9-18 |
| 9.12.1.3 DC Power Leads . . . . .                                               | 9-19 |
| 9.12.1.4 Bonding Conductors . . . . .                                           | 9-19 |
| 9.12.1.5 Shelf-Mounted EUT . . . . .                                            | 9-19 |
| 9.12.1.6 Reference Plane . . . . .                                              | 9-19 |
| 9.12.1.7 Test Environment . . . . .                                             | 9-19 |
| 9.12.2 Identification of Test Points . . . . .                                  | 9-20 |
| 9.12.3 DC Fault Test . . . . .                                                  | 9-20 |
| 9.12.4 Frame EFT Test . . . . .                                                 | 9-22 |
| 9.12.4.1 Laboratory Arrangement of the EUT . . . . .                            | 9-22 |
| 9.12.4.2 In-Situ Arrangement of the EUT . . . . .                               | 9-23 |
| 9.12.5 Frame Surge Test . . . . .                                               | 9-24 |
| 9.12.5.1 Laboratory Arrangement of the EUT . . . . .                            | 9-24 |
| 9.12.5.2 In-Situ Arrangement of the EUT . . . . .                               | 9-25 |
| 9.12.6 AC Fault Test . . . . .                                                  | 9-26 |

|                                                                                 |      |
|---------------------------------------------------------------------------------|------|
| 9.13 Grounding Connector for Equipment With Integrated Primary Protection . . . | 9–28 |
| 9.13.1 Grounding Conductors in the EIPP . . . . .                               | 9–29 |

## **10 Criteria for DC Power Port of Telecommunications Load Equipment**

|                                                                         |      |
|-------------------------------------------------------------------------|------|
| 10.1 Input DC Voltage . . . . .                                         | 10–1 |
| 10.2 Minimum Operating Voltage . . . . .                                | 10–1 |
| 10.3 Overvoltage (Steady State) . . . . .                               | 10–1 |
| 10.4 Overvoltage Transient . . . . .                                    | 10–1 |
| 10.5 Protective Device Operation Transient . . . . .                    | 10–2 |
| 10.6 Noise Returned by the Network Equipment (Noise Emission) . . . . . | 10–2 |
| 10.6.1 Wideband Frequency Noise Emission . . . . .                      | 10–3 |
| 10.7 Power Input Noise Immunity . . . . .                               | 10–4 |
| 10.8 Markings and Documentation . . . . .                               | 10–4 |

## **Appendix A: Definition of Double-Exponential Waveform and Waveform Characterization**

|                                                                           |     |
|---------------------------------------------------------------------------|-----|
| A.1 Guidelines for the Characterization of Test Generators . . . . .      | A–4 |
| A.1.1 Three-Terminal Generator Characterization Procedure . . . . .       | A–4 |
| A.1.2 Two-Terminal Generator Characterization Procedure . . . . .         | A–5 |
| A.1.3 Twenty-Five Terminal Generator Characterization Procedure . . . . . | A–5 |

## **Appendix B: Application Guidelines**

|                                                          |     |
|----------------------------------------------------------|-----|
| B.1 Application Guidelines for Equipment Ports . . . . . | B–2 |
|----------------------------------------------------------|-----|

## **Appendix C: References**

|                                                                                  |     |
|----------------------------------------------------------------------------------|-----|
| C.1 Telcordia Reference Notes . . . . .                                          | C–5 |
| C.1.1 Contact Telcordia . . . . .                                                | C–5 |
| C.1.2 Order Documents Online From the Telcordia Information SuperStore . . . . . | C–5 |
| C.1.3 Telcordia Web Site for Generic Requirements Information . . . . .          | C–6 |

## **Appendix D: Definitions**

## **Appendix E: Acronyms**

## **Appendix F: Wireless**

## **Requirement-Object Index (ROI)**



## List of Figures

|             |                                                                                                                                     |      |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------|------|
| Figure 2-1  | Physical Arrangements for EFT Testing . . . . .                                                                                     | 2-8  |
| Figure 2-2  | Physical Arrangements for EFT Testing Using Non-Conductive Support . . . . .                                                        | 2-9  |
| Figure 3-1  | Requirement R3-2 [8] and Objective O3-3 [9] Limits for Class A Electric Field Emissions at 3-Meter and 10-Meter Distances . . . . . | 3-5  |
| Figure 3-2  | Requirement R3-4 [10] Limits for Electric Field Emissions at 3-Meter and 10-Meter Distances . . . . .                               | 3-7  |
| Figure 3-3  | Conducted Emissions Limits on Telecommunication Ports . . . . .                                                                     | 3-11 |
| Figure 3-4  | Test Setup for Conducted Emission Tests on AC and DC Power Ports (Current) . . . . .                                                | 3-27 |
| Figure 3-5  | Test Setup for Conducted Emission Tests on Telecommunication Ports . . . . .                                                        | 3-28 |
| Figure 3-6  | Synchronization Test Configuration . . . . .                                                                                        | 3-33 |
| Figure 3-7  | Cable Arrangement for EUTs With Overhead Cables . . . . .                                                                           | 3-38 |
| Figure 3-8  | Injection Probe Calibration Setup . . . . .                                                                                         | 3-43 |
| Figure 3-9  | Test Setup for Conducted Immunity Tests on AC and DC Power Ports . . . . .                                                          | 3-44 |
| Figure 3-10 | Test Setup for Conducted Immunity Tests for Telecommunications Ports (Voiceband, Signal, and Telecommunications Leads) . . . . .    | 3-45 |
| Figure 4-1  | Surge Test Number 4 Inductive Kick Test Terminations for OSP Interfaces . . . . .                                                   | 4-12 |
| Figure 4-2  | Application of Lightning and AC Power Fault Test Voltages . . . . .                                                                 | 4-15 |
| Figure 4-3  | Option A – Isolation Test for Type 3a/5a Interfaces . . . . .                                                                       | 4-26 |
| Figure 4-4  | Option A – Isolation Test for Type 8b Interfaces . . . . .                                                                          | 4-26 |
| Figure 4-5  | Option B – Surge Option B for 8b Power Port . . . . .                                                                               | 4-29 |
| Figure 4-6  | Test Connections for Gas Tube Interaction Test . . . . .                                                                            | 4-34 |
| Figure 4-7  | Higher Ground Resistance Test for Two-Wire Interface . . . . .                                                                      | 4-35 |
| Figure 4-8  | Higher Ground Resistance Test for Four-Wire Interface . . . . .                                                                     | 4-35 |
| Figure 4-9  | High Lightning Exposure Coordination Test for Remote OSP Interfaces . . . . .                                                       | 4-37 |
| Figure 4-10 | Test Circuit for Multi-Pair Ports — Metallic Test . . . . .                                                                         | 4-39 |
| Figure 4-11 | Test Circuit for Multi-Pair Ports — Longitudinal Test . . . . .                                                                     | 4-40 |
| Figure 4-12 | Test Circuit for Paired-Conductor Ports Providing a Connection Means for the Shielded Cable . . . . .                               | 4-43 |
| Figure 4-13 | Test Circuit for Coaxial Cable Ports Providing a Connection Means for the Shielded Cable . . . . .                                  | 4-43 |
| Figure 4-14 | Test Circuit for Unshielded PoE Ports — Metallic Test (SW Sets Mode A or Mode B Testing) . . . . .                                  | 4-44 |
| Figure 4-15 | DC-Fed Tower Mounted Transceiver and Power Source Test . . . . .                                                                    | 4-46 |
| Figure 4-16 | High-Impedance Inductive Source Test Circuit . . . . .                                                                              | 4-59 |
| Figure 4-17 | Upper Limit of Time-Current Characteristic for Type 1 Port Wiring Simulator . . . . .                                               | 4-65 |
| Figure 4-18 | Second-Level AC Power Fault Test Arrangement Using External Wiring Simulator – Metallic . . . . .                                   | 4-66 |
| Figure 4-19 | Second-Level AC Power Fault Test Arrangement Using External Wiring Simulator – Longitudinal . . . . .                               | 4-66 |

|             |                                                                                                                              |      |
|-------------|------------------------------------------------------------------------------------------------------------------------------|------|
| Figure 4-20 | Second-Level AC Power Fault Pair-to-Pair Test Arrangement for Four-Wire Interfaces Using External Wiring Simulator . . . . . | 4-67 |
| Figure 4-21 | Illustration of Components and Circuits in EIPP . . . . .                                                                    | 4-70 |
| Figure 5-1  | Longitudinal Induction Test Circuit . . . . .                                                                                | 5-4  |
| Figure 5-2  | Line Circuit Functional Test Arrangement . . . . .                                                                           | 5-11 |
| Figure 5-3  | Line Circuit Noise Measurement Test Arrangement for Equipment on Customer End . . . . .                                      | 5-12 |
| Figure 5-4  | Line Circuit Noise Measurement Test Arrangement for Equipment on Central Office End . . . . .                                | 5-13 |
| Figure 5-5  | Holding Coil . . . . .                                                                                                       | 5-14 |
| Figure 7-1  | Class A1 Voltage Limits (Sheet 1 of 2) . . . . .                                                                             | 7-6  |
| Figure 7-2  | Class A2 Voltage Limits (Sheet 1 of 2) . . . . .                                                                             | 7-9  |
| Figure 7-3  | Class A3 Voltage Limits (Sheet 1 of 2) . . . . .                                                                             | 7-12 |
| Figure 7-4  | Test Finger . . . . .                                                                                                        | 7-16 |
| Figure 7-5  | Interrupted/Tripped Criterion Defining the Duration for Which a Current of a Given Magnitude Is Allowed to Persist . . . . . | 7-21 |
| Figure 7-6  | Test Circuit Example for Determining Volt-Ampere Characteristics . . . . .                                                   | 7-22 |
| Figure 9-1  | Illustration of Three Options for Grounding an Output of Embedded DC Power Source . . . . .                                  | 9-11 |
| Figure 9-2  | Configuration of the DC Fault Test . . . . .                                                                                 | 9-21 |
| Figure 9-3  | Configuration of the Proposed EFT Frame Test . . . . .                                                                       | 9-23 |
| Figure 9-4  | An Alternative Configuration for the EFT Test . . . . .                                                                      | 9-24 |
| Figure 9-5  | Laboratory Configuration for the Frame Surge Test . . . . .                                                                  | 9-25 |
| Figure 9-6  | In-Situ Configuration for the Frame Surge Test . . . . .                                                                     | 9-26 |
| Figure 9-7  | Laboratory Configuration of the EUT for the AC Fault Test . . . . .                                                          | 9-27 |
| Figure 9-8  | In-Situ Configuration of the EUT for the AC Fault Test . . . . .                                                             | 9-28 |
| Figure 10-1 | Noise Return Test Circuit . . . . .                                                                                          | 10-3 |
| Figure A-1  | Double Exponential Voltage/Current Waveform of A/B . . . . .                                                                 | A-1  |
| Figure A-2  | Double Exponential Voltage Waveform of A/B for 1.2/50 and 10/700 Surges of Table A-1 . . . . .                               | A-2  |

## List of Tables

|            |                                                                                           |      |
|------------|-------------------------------------------------------------------------------------------|------|
| Table 3-1  | Radiated Emission Requirement and Objective for Electric Fields . . . . .                 | 3-4  |
| Table 3-2  | Radiated Emission Requirement for Electric Fields (Doors and Covers<br>Open) . . . . .    | 3-6  |
| Table 3-3  | Conducted Emission Limits for AC Power Ports for Class A Equipment<br>— Voltage . . . . . | 3-8  |
| Table 3-4  | Conducted Emission Limits for AC Power Ports for Class B Equipment<br>— Voltage . . . . . | 3-9  |
| Table 3-5  | Conducted Emission Requirements for AC and DC Power Ports —<br>Current . . . . .          | 3-9  |
| Table 3-6  | Conducted Emission Requirements for Telecommunication Ports —<br>Current . . . . .        | 3-10 |
| Table 3-7  | Conducted Immunity Requirements for Power Ports . . . . .                                 | 3-13 |
| Table 3-8  | Conducted Immunity Requirements for Voiceband Leads . . . . .                             | 3-14 |
| Table 3-9  | Instrumentation Bandwidths . . . . .                                                      | 3-15 |
| Table 3-10 | 1 to 10 GHz Immunity Scan Rate and Step Size . . . . .                                    | 3-39 |
| Table 3-11 | Frequencies of Key Interest . . . . .                                                     | 3-40 |
| Table 4-1  | Test Connections of Telecommunications Port . . . . .                                     | 4-14 |
| Table 4-2  | First-Level Lightning Surge . . . . .                                                     | 4-47 |
| Table 4-3  | Second-Level Lightning Surge <sup>[3]</sup> . . . . .                                     | 4-56 |
| Table 4-4  | First-Level Power Fault Tests . . . . .                                                   | 4-58 |
| Table 4-5  | Second-Level Power Fault Tests . . . . .                                                  | 4-62 |
| Table 4-6  | Applicability of EIPP Requirements . . . . .                                              | 4-71 |
| Table 4-7  | Fusing Coordination for Unprotected Circuits . . . . .                                    | 4-75 |
| Table 4-8  | AC Power Fault Immunity — Unprotected Circuits . . . . .                                  | 4-78 |
| Table 4-9  | Second-Level Lightning Surges for EEPP and Some EIPP . . . . .                            | 4-79 |
| Table 4-10 | Lightning Surges for Severe Climatic Conditions . . . . .                                 | 4-80 |
| Table 5-1  | Longitudinal Induction Test Circuit Criteria . . . . .                                    | 5-5  |
| Table 5-2  | Suggested Loop Lengths . . . . .                                                          | 5-6  |
| Table 7-1  | Values of Maximum Test Resistance . . . . .                                               | 7-4  |
| Table 7-2  | Accessibility to Continuous Class A Voltages . . . . .                                    | 7-15 |
| Table 9-1  | Test Overcurrent Device Selection . . . . .                                               | 9-21 |
| Table 9-2  | Grounding Conductor Size for Fuse-Less Protector Block in the<br>EUT . . . . .            | 9-29 |
| Table 9-3  | Grounding Conductor Size for Fused Protector Block in the EUT . . . . .                   | 9-29 |
| Table A-1  | Waveform Tolerances . . . . .                                                             | A-3  |
| Table B-1  | Applicable Criteria Set A for Network Equipment . . . . .                                 | B-1  |
| Table B-2  | Applicable Criteria Set B for Network Equipment Ports . . . . .                           | B-2  |
| Table B-3  | Application Chart for Equipment Ports . . . . .                                           | B-5  |

