

Table of Contents

1 Introduction

- 1.1 Purpose and Scope 1-1
- 1.2 Items Not Covered in This GR 1-2
- 1.3 Requirements Terminology 1-3
- 1.4 Requirement Labeling Conventions 1-3
 - 1.4.1 Numbering of Requirement and Related Objects 1-3
 - 1.4.2 Requirement, Conditional Requirement, and Objective Identification 1-4
- 1.5 Organization 1-4
- 1.6 Reasons for GR-1089, Issue 7 1-6
- 1.7 Application of This Document 1-6
- 1.8 Guidelines for Equipment Evaluation 1-7
- 1.9 Documentation 1-8
 - 1.9.1 General 1-8
 - 1.9.2 Root Cause Analysis 1-8
- 1.10 Number of Samples To Be Tested 1-9
- 1.11 Relation to Other Telcordia Documents 1-9
- 1.12 Navigating the GR-1089 Portable Document Format (PDF) File 1-9

2 System-Level Electrostatic Discharge (ESD) and Electrical Fast Transient (EFT)

- 2.1 System-Level ESD 2-1
 - 2.1.1 Overview 2-1
 - 2.1.2 ESD Immunity Criteria 2-1
 - 2.1.2.1 Immunity Criteria – Normal Operation 2-2
 - 2.1.2.2 Immunity Criteria – Installation and Maintenance 2-2
 - 2.1.2.3 ESD Warning Label Requirements 2-3
 - 2.1.2.4 Equipment-Specific Requirements 2-3
 - 2.1.2.4.1 Additional Equipment Requirements 2-3
 - 2.1.2.4.2 Maintenance Information 2-3
 - 2.1.3 Service-Affecting Responses and Manual Interventions 2-3
 - 2.1.4 ESD Test Methods and Procedures 2-4
 - 2.1.4.1 Test Methods – Normal Operation 2-4
 - 2.1.4.2 Test Methods – Installation and Maintenance 2-5
 - 2.1.4.3 Selection of Test Points 2-5
 - 2.1.4.3.1 Test Points – Normal Operation 2-5
 - 2.1.4.3.2 Test Points – Installation and Maintenance 2-6
 - 2.1.4.4 EUT Operating Conditions 2-6
 - 2.1.4.5 ESD Test Site 2-7
- 2.2 Electrical Fast Transient (EFT) 2-7
 - 2.2.1 EFT Test Methods and Procedures 2-8

3 Electromagnetic Interference (EMI)

- 3.1 General 3-1
 - 3.1.1 Overview 3-1
 - 3.1.2 Intent of EMI Criteria 3-1
 - 3.1.3 FCC Part 15 Criteria 3-2

3.1.4	Consolidating Testing	3-3
3.1.5	Documentation	3-3
3.2	Emission Criteria	3-3
3.2.1	Radiated Emission Criteria	3-4
3.2.1.1	Electric Fields Radiated Emission Criteria for Unintentional Radiators	3-4
3.2.1.2	Electric Fields Radiated Emission Criteria for Intentional Radiators	3-7
3.2.2	Conducted Emission Criteria for Power Ports	3-8
3.2.2.1	Conducted Emission Requirements for AC Power Ports – Voltage	3-8
3.2.2.2	Conducted Emission Requirements for AC and DC Power – Current	3-9
3.2.3	Conducted Emission Requirements for Telecommunication Ports – Current	3-10
3.3	Immunity Criteria	3-11
3.3.1	Radiated Immunity Criteria	3-11
3.3.1.1	Electric Fields Radiated Immunity Criteria with Doors and Covers Closed	3-12
3.3.1.2	Electric Fields Radiated Immunity Criteria with Doors and Covers Open	3-12
3.3.2	Conducted Immunity Criteria for AC and DC Power Ports	3-12
3.3.3	Conducted Immunity Criteria for Telecommunications Ports	3-13
3.3.3.1	Conducted Immunity Requirements for Signal and Telecommunication Leads	3-13
3.3.3.2	Conducted Immunity Requirements for Voiceband Leads	3-13
3.4	Measurement Procedures Associated With Emissions	3-14
3.4.1	Scope	3-14
3.4.2	Related Standards	3-14
3.4.3	Measuring Instrumentation	3-14
3.4.3.1	General	3-14
3.4.3.2	Measurement Instrumentation	3-15
3.4.3.3	Measuring Instrument Calibration	3-15
3.4.3.4	Detector Function Selection and Bandwidth	3-15
3.4.3.5	Antennas	3-16
3.4.4	General Test Conditions	3-17
3.4.4.1	Emission Measurement Uncertainty	3-17
3.4.4.2	Testing at an Open-Area Test Site (OATS)	3-18
3.4.4.3	Testing at User’s Installation (On-Premises Testing)	3-18
3.4.4.3.1	System Premises	3-18
3.4.4.3.2	Number of Systems To Be Tested	3-18
3.4.4.3.3	Selection of Systems for Test	3-19
3.4.4.4	Testing in a Shielded Enclosure	3-20
3.4.4.5	Subsystem Emission Limits Allocation	3-20
3.4.4.6	Units of Measurement	3-20
3.4.4.7	Data Reporting Format	3-21
3.4.4.8	Test Conditions for EUT	3-21
3.4.4.8.1	EUT Installation	3-21
3.4.4.8.2	Conditioning of the EUT	3-22
3.4.4.8.3	Interfacing Units and Simulators	3-22
3.4.4.8.4	EUT Grounding	3-23

3.4.4.8.5 DC Return	3-23
3.4.4.9 Test Environment	3-24
3.4.4.10 Arrangements of EUT	3-24
3.4.4.11 Arrangements of Intentional Radiators	3-25
3.4.5 Conducted Emissions Measurements	3-25
3.4.5.1 Measurement Procedures	3-26
3.4.5.1.1 AC Power Ports (Voltage)	3-26
3.4.5.1.2 AC Power Ports (Current)	3-26
3.4.5.1.3 DC Power Ports (Current)	3-26
3.4.5.1.4 Telecommunications Ports	3-27
3.4.6 Radiated Emission Measurements	3-29
3.4.6.1 Determination of Test Radial	3-29
3.4.6.2 Radiated Radio Noise Tests	3-29
3.4.7 Retesting With System Evolution and Growth	3-30
3.4.7.1 System Evolution	3-30
3.4.7.2 System Growth	3-30
3.5 Measurement Procedures Associated With Immunity	3-31
3.5.1 Scope	3-31
3.5.2 Measuring Instrumentation	3-31
3.5.2.1 Receivers	3-31
3.5.2.2 Current Probes	3-31
3.5.2.3 Antennas	3-31
3.5.2.4 Signal Sources	3-32
3.5.3 Test Conditions for EUT	3-32
3.5.3.1 Non-Switching Systems	3-32
3.5.3.2 Bit Error Rate (BER)	3-33
3.5.3.3 Synchronization	3-33
3.5.3.4 Voiceband Noise	3-33
3.5.4 Data Reporting Format	3-34
3.5.5 Radiated Immunity Measurements	3-34
3.5.5.1 Shielded Enclosures	3-34
3.5.5.2 Subsystem Testing	3-35
3.5.5.3 Measurement Procedures	3-35
3.5.5.3.1 EUT and Antenna Positioning	3-35
3.5.5.3.2 Calibration of Generated Fields	3-36
3.5.5.3.3 EUT Leads	3-36
3.5.5.3.4 EUT Grounding	3-37
3.5.5.3.5 DC Return	3-37
3.5.5.3.6 Test Signal Modulation	3-39
3.5.5.3.7 Frequencies and Amplitudes To Be Measured	3-39
3.5.6 Conducted Immunity Measurements	3-41
3.5.6.1 Test Signal Modulation	3-41
3.5.6.2 Frequency Scanning and Test Selection	3-41
3.5.6.3 Calibration of Test Signal	3-41
3.5.6.4 AC and DC Leads (Common-Mode Injection)	3-41
3.5.6.5 Telecommunications Ports —Voiceband, Telecommunications and Signal Leads (Common-Mode Injection)	3-42

4 Lightning and Power Fault

4.1 Overview	4-1
------------------------	-----

4.2	Electrical Protection on Coaxial and Paired-Conductor Systems	4-5
4.2.1	Primary and Secondary Voltage-Limiting Protectors	4-5
4.2.2	Current-Limiting Protectors	4-6
4.2.3	Fuse Links	4-7
4.2.4	Considerations for Equipment That Can Be Located at Cell Sites or Other Locations With Tall Antennas	4-7
4.3	Lightning Effects on Paired-Conductor Cables	4-8
4.3.1	Longitudinal Surges	4-8
4.3.2	Metallic Surges	4-9
4.4	AC Power Fault Effects on Paired-Conductor Cables	4-9
4.4.1	Power Contact to Telecommunications OSP	4-9
4.4.2	Fault Induction From Electric Power Lines	4-9
4.5	General Testing Information and Guidelines	4-10
4.5.1	Test Equipment	4-10
4.5.2	Safety Precautions	4-10
4.5.3	Test Samples, Test Modes, and Circuit Analysis	4-11
4.5.3.1	Test Exemptions and Special Considerations	4-12
4.5.4	Termination of Equipment Port Conductors During Tests	4-14
4.5.4.1	Series-Type Equipment	4-16
4.5.5	Test Duration and Time Between Tests	4-16
4.5.6	Lightning Surge and AC Power Fault Test Connections	4-17
4.5.6.1	Generator Connections	4-17
4.5.6.2	EUT Grounding	4-19
4.5.6.3	DC Return	4-19
4.5.6.4	Wiring Simulators for Second-Level Power Fault Tests	4-19
4.5.7	Conformance Criteria	4-20
4.5.7.1	First-Level Criteria	4-20
4.5.7.2	Second-Level Criteria	4-21
4.5.8	Determination of Secondary Protector Values for Undervoltage/ Undercurrent Tests	4-22
4.5.8.1	Lightning – Secondary Protection	4-22
4.5.8.2	Power Fault – Secondary Protection	4-23
4.5.9	Equipment Interfacing With Agreed or Non-Field Replaceable Integrated Primary Protectors	4-23
4.6	Testing Requirements	4-26
4.6.1	Design Verification Tests for Telecommunications Ports	4-29
4.6.1.1	Short Circuit Test (Telecommunications Type 1, 3, and 5 Ports)	4-29
4.6.1.2	Ethernet Interface Considerations (Telecommunications Type 1, 2, 3, 3a/5a, 3b/5b, 4, 4a, or 5 Ports)	4-29
4.6.1.3	Cell Site Inter-Structure Withstand Criteria (Telecommunications Type 3a/5a and 8b Ports)	4-30
4.6.1.3.1	Isolation Test	4-30
4.6.2	Lightning Requirements and Test Criteria	4-33
4.6.2.1	First-Level Lightning Surge	4-33
4.6.2.1.1	First-Level Lightning Criteria for Telecommunications Ports (Type 1, 3, 3b/5b, and 5 Ports)	4-33
4.6.2.1.2	First-Level Lightning Surge Test Procedure Guidelines for Telecommunications Ports	4-34
4.6.2.1.2.1	Test Procedure for Surge Test Number 1 of Table 4-2 – Multiport OSP Test	4-34

- 4.6.2.1.2.2 Test Procedure for Surge Test Number 2 and Surge Test Number 2.1 of [Table 4-2](#) – OSP Interface Tests 4-35
- 4.6.2.1.2.3 Test Procedure for Surge Test Number 3 of [Table 4-2](#) – Gas Tube Interaction Test 4-36
- 4.6.2.1.2.4 Test Procedure for Surge Test Number 4 of [Table 4-2](#) – Inductive Kick Test for OSP Interfaces 4-37
- 4.6.2.1.2.5 Test Procedure for Surge Test Number 5 of [Table 4-2](#) – Fast Rise Time Test for Remote OSP Interfaces 4-38
- 4.6.2.1.2.6 Test Procedure for Surge Test Number 6 of [Table 4-2](#) – Higher Ground Resistance for Remote OSP Interface 4-38
- 4.6.2.1.2.7 Test Procedure and Criteria for Surge Test Number 7 of [Table 4-2](#) – High Lightning Exposure Test for Remote OSP Interfaces 4-39
- 4.6.2.1.3 Intra-Building or Intra-Site Lightning Criteria (Telecommunications Type 2, 3a/5a, 4, 4a Ports) 4-40
- 4.6.2.1.4 Specific Test Procedures and Conditions for Intra-Building and Intra-Site Lightning Test of Type 2, 3a/5a, 4 and 4a Ports 4-41
 - 4.6.2.1.4.1 Test Procedure for Surge Test Number 10 of [Table 4-2](#) – Alternative Intra-Building for Up to 2 Pairs Per Port (Metallic) 4-43
 - 4.6.2.1.4.2 Test Procedure for Surge Test Number 10.1 of [Table 4-2](#) – Alternative Intra-Building with Secondary Protectors Up to 2 Pairs Per Port (Metallic) 4-43
- 4.6.2.1.5 First-Level Lightning Criteria for Antenna Ports (Telecommunications Type 6 Ports) 4-46
- 4.6.2.1.6 First-Level Lightning Criteria for AC Power Ports (Telecommunications Type 7 Ports) 4-47
- 4.6.2.1.7 DC Mains (Type 8 and 8b Ports) and DC Power to Antenna Lightning Criteria (Type 8a Ports) 4-48
 - 4.6.2.1.7.1 Test Procedure for Surge Test Number 22 of [Table 4-2](#) – Tower Mounted Transceiver Fed With Remote DC Power Test 4-48
- 4.6.3 Second-Level Lightning Requirements 4-58
 - 4.6.3.1 Second-Level Lightning for Telecommunication Ports (Type 1, 3, and 5 Ports) 4-58
 - 4.6.3.2 Second-Level Lightning for AC Power Ports (Type 7 Ports) 4-59
- 4.6.4 Power Fault Requirements 4-60
 - 4.6.4.1 First-Level Power Fault/Induction Requirements 4-60
 - 4.6.4.2 Second-Level Power Fault Requirements 4-63
- 4.7 Criteria for Equipment With Integrated Primary Protection 4-72
 - 4.7.1 Equipment Classification 4-74
 - 4.7.2 Protector Requirements 4-76
 - 4.7.3 Lightning Surge and Power Fault Tests for Protected Circuits 4-77
 - 4.7.4 Fusing Coordination for Unprotected Circuits 4-77
 - 4.7.4.1 Fusing Coordination for Circuits That Contain Components or Circuitry That Act as OSP Fuse Links 4-78
 - 4.7.4.1.1 Enclosure Suitable for Fusing 4-79
 - 4.7.4.2 Fusing Coordination for Circuits Not Containing Components or Circuitry That Act as OSP Fuse Links 4-80

4.7.5 Dielectric Withstand	4-81
4.7.6 EIPP Cable Requirements	4-81
4.7.7 AC Power Faults – Unprotected Circuits	4-82
4.7.8 Lightning Surge Tests – Unprotected Circuits	4-83
4.7.8.1 Lightning Surge Tests for Severe Climatic Conditions – Unprotected Units	4-84
5 Steady-State Power Induction	
5.1 Overview	5-1
5.2 Longitudinal Induction Criteria	5-2
5.2.1 Longitudinal Induction Test Circuit	5-3
5.2.2 Calibration Procedure	5-7
5.2.3 Test Procedures	5-8
5.2.3.1 Analog Loop Testing	5-8
5.2.3.2 Analog Loop Criteria	5-9
5.2.3.3 Digital Loop Testing	5-14
5.2.3.4 Line/Span Powering Loop Testing	5-16
6 DC Potential Difference	
7 Electrical and Optical Safety Criteria	
7.1 Overview	7-1
7.2 Listing Requirements	7-2
7.3 Classification of Voltages	7-2
7.3.1 Continuous Voltage and Current Limits	7-3
7.3.1.1 Class A1 Voltage Limits	7-5
7.3.1.2 Class A2 Voltage Limits	7-8
7.3.1.3 Class A3 Voltage Limits	7-11
7.3.1.4 Class AB Voltage Limits	7-14
7.3.1.5 Class B Voltage Limits	7-14
7.3.1.6 Class C Voltage Limits	7-14
7.4 Continuous Source Requirements	7-14
7.4.1 Class A1 Voltage Accessibility Requirements	7-17
7.4.2 Class A2 Voltage Accessibility Requirements	7-17
7.4.3 Class A3 Voltage Accessibility Requirements	7-17
7.4.4 Class AB Voltage Accessibility Requirements	7-18
7.4.5 Class B Voltage Accessibility Requirements	7-18
7.4.6 Class C Voltage Accessibility Requirements	7-18
7.5 Duration-Limited Source Requirements	7-18
7.5.1 Interrupted/Tripped Sources	7-18
7.5.1.1 Ring-Trip Test Procedure	7-20
7.5.2 Transient Sources	7-20
7.6 Power Limitation Requirement	7-21
7.7 Leakage Currents From Exposed Surfaces	7-22
7.7.1 General Considerations	7-22
7.7.2 Leakage Current Requirements	7-23
7.7.2.1 Leakage Current Requirements for Large-Area Contact	7-23
7.7.2.2 Leakage Current Requirements for Small-Area Contact	7-24
7.7.2.3 Leakage Current Between Surfaces of Equipment	7-24
7.8 Laser Safety and Labeling Criteria	7-24

8 Corrosion

8.1 Polarity of DC Voltages Applied to OSP Cabling 8-1
 8.2 Magnitude of DC Voltages Applied to OSP Cabling 8-1

9 Bonding and Grounding

9.1 Scope 9-1
 9.2 General Requirements Principles 9-1
 9.3 Equipment Grounding Systems 9-2
 9.3.1 Common Bonding Network (CBN) 9-3
 9.3.2 Isolated Bonding Network (IBN) 9-3
 9.4 AC Equipment Grounding 9-4
 9.5 Communication Equipment Grounding 9-5
 9.5.1 Network Telecommunication Facilities 9-5
 9.5.2 Locations Where the NEC Applies 9-6
 9.5.3 Outside Plant (OSP) 9-6
 9.6 Equipment Unit Bonding and Grounding 9-6
 9.7 Provisions for Equipment Unit Assembly Bonding and Grounding 9-7
 9.7.1 Connectors and Connection Methods for Equipment Unit Assemblies 9-8
 9.7.2 Bonding of Circuit Packs 9-9
 9.8 DC Power System Grounding 9-9
 9.8.1 Centralized Power Sources 9-9
 9.8.2 Embedded Power Sources 9-9
 9.8.3 Bonding of Battery Return (BR) Input Terminals 9-12
 9.9 Bonding and Grounding Conductor and Connection Requirements 9-16
 9.9.1 Bonding and Grounding Conductors 9-16
 9.9.2 Connections 9-16
 9.9.3 Connectors 9-17
 9.10 Short-Circuit Tests 9-18
 9.10.1 DC Power Sources 9-18
 9.10.2 AC Power Sources 9-20
 9.11 Other Grounding Considerations 9-21
 9.12 Compatibility of Former IBN Equipment With CBN Currents 9-21
 9.12.1 Test Conditions for EUT 9-21
 9.12.1.1 Conditioning of the EUT 9-21
 9.12.1.2 Interfacing Units and Simulators 9-22
 9.12.1.3 DC Power Leads 9-22
 9.12.1.4 Bonding Conductors 9-22
 9.12.1.5 Shelf-Mounted EUT 9-23
 9.12.1.6 Reference Plane 9-23
 9.12.1.7 Test Environment 9-23
 9.12.2 Identification of Test Points 9-23
 9.12.3 DC Fault Test 9-24
 9.12.4 Frame EFT Test 9-26
 9.12.4.1 Laboratory Arrangement of the EUT 9-26
 9.12.4.2 In-Situ Arrangement of the EUT 9-27
 9.12.5 Frame Surge Test 9-28
 9.12.5.1 Laboratory Arrangement of the EUT 9-28
 9.12.5.2 In-Situ Arrangement of the EUT 9-29
 9.12.6 AC Fault Test 9-30

9.13 Grounding Connector for Equipment With Integrated Primary Protection . . .	9-32
9.13.1 Grounding Conductors in the EIPP	9-33

10 Criteria for DC Power Port of Telecommunications Load Equipment

10.1 Input DC Voltage	10-1
10.2 Minimum Operating Voltage	10-1
10.3 Overvoltage (Steady State)	10-1
10.4 Overvoltage Transient	10-1
10.5 Protective Device Operation Transient	10-2
10.6 Noise Returned by the Network Equipment (Noise Emission)	10-2
10.6.1 Wideband Frequency Noise Emission	10-3
10.7 Power Input Noise Immunity	10-4
10.8 Markings and Documentation	10-4

Appendix A: Definition of Double-Exponential Waveform and Waveform Characterization

A.1 Guidelines for the Characterization of Test Generators	A-4
A.1.1 Three-Terminal Generator Characterization Procedure	A-5
A.1.2 Two-Terminal Generator Characterization Procedure	A-5
A.1.3 Twenty-Five Terminal Generator Characterization Procedure	A-5

Appendix B: Application Guidelines

B.1 Application Guidelines for Equipment Ports	B-2
--	-----

Appendix C: Wireless

Appendix D: Radiated Immunity in the millimeter Wave (mmW) Frequency Ranges - Informative Annex

Appendix E: Section 4 First-Level Lightning Criteria Discussion

E.1 Section 4 Background	E-2
--	-----

Appendix F: References

F.1 Telcordia Documents	F-1
F.2 External Documents	F-2
F.3 To Obtain Additional Reference Material	F-6
F.4 Family of Requirements (FR) and Family of Documents (FD) Sets	F-6
F.5 Reference Notes	F-7
F.5.1 Contact Customer Service	F-7
F.5.2 Order Documents Online from the Information SuperStore	F-7
F.5.3 Websites for Generic Requirements Information	F-8
F.5.4 Licensing Agreements for Telcordia Documents	F-8

Appendix G: Definitions

Appendix H: Acronyms

Requirement-Object Index (ROI)

List of Figures

Figure 2-1	Physical Arrangements for EFT Testing	2-9
Figure 2-2	Physical Arrangements for EFT Testing Using Non-Conductive Support	2-10
Figure 3-1	Requirement R3-2 [8] and Objective O3-3 [9] Limits for Class A Electric Field Emissions at 3-Meter (10-Footer) and 10-Meter (33-Footer) Distances	3-5
Figure 3-2	Requirement R3-4 [10] Limits for Electric Field Emissions at 3-Meter (10-Footer) and 10-Meter (33-Footer) Distances	3-7
Figure 3-3	Conducted Emissions Limits on Telecommunication Ports	3-11
Figure 3-4	Test Setup for Conducted Emission Tests on AC and DC Power Ports (Current)	3-28
Figure 3-5	Test Setup for Conducted Emission Tests on Telecommunication Ports	3-28
Figure 3-6	Synchronization Test Configuration	3-34
Figure 3-7	Cable Arrangement for EUTs With Overhead Cables	3-38
Figure 3-8	Injection Probe Calibration Setup	3-43
Figure 3-9	Test Setup for Conducted Immunity Tests on AC and DC Power Ports	3-44
Figure 3-10	Test Setup for Conducted Immunity Tests for Telecommunications Ports (Voiceband, Signal, and Telecommunications Leads)	3-45
Figure 4-1	Cell-Site Port Examples	4-14
Figure 4-2	Surge Test Number 4 Inductive Kick Test Terminations for OSP Interfaces	4-15
Figure 4-3	Application of Lightning and AC Power Fault Test Voltages	4-18
Figure 4-4	Isolation Test for Type 3a/5a Interfaces	4-31
Figure 4-5	Isolation Test for Type 8b Interfaces	4-32
Figure 4-6	Test Connections for Gas Tube Interaction Test	4-37
Figure 4-7	Higher Ground Resistance Test for Two-Wire Interface	4-38
Figure 4-8	Higher Ground Resistance Test for Four-Wire Interface	4-39
Figure 4-9	High Lightning Exposure Coordination Test for Remote OSP Interfaces	4-40
Figure 4-10	Test Circuit for Multi-Pair Ports – Metallic Test	4-42
Figure 4-11	Test Circuit for Multi-Pair Ports – Longitudinal Test	4-43
Figure 4-12	Test Circuit for Paired-Conductor Ports Providing a Connection Means for the Shielded Cable	4-44
Figure 4-13	Test Circuit for Coaxial Cable Ports Providing a Connection Means for the Shielded Cable	4-45
Figure 4-14	Test Circuit for Unshielded PoE Ports – Metallic Test (SW Sets Mode A or Mode B Testing)	4-46
Figure 4-15	Test Circuit for Antenna Ports (Telecommunications Type 6 Ports)	4-47
Figure 4-16	DC-Fed Tower Mounted Transceiver and Power Source Test	4-49
Figure 4-17	High-Impedance Inductive Source Test Circuit	4-63
Figure 4-18	Upper Limit of Time-Current Characteristic for Type 1 Port Wiring Simulator	4-69
Figure 4-19	Second-Level AC Power Fault Test Arrangement Using External Wiring Simulator – Metallic	4-70

Figure 4-20	Second-Level AC Power Fault Test Arrangement Using External Wiring Simulator – Longitudinal	4-70
Figure 4-21	Second-Level AC Power Fault Pair-to-Pair Test Arrangement for Four-Wire Interfaces Using External Wiring Simulator	4-71
Figure 4-22	Illustration of Components and Circuits in EIPP	4-74
Figure 5-1	Longitudinal Induction Test Circuit	5-4
Figure 5-2	Line Circuit Functional Test Arrangement	5-11
Figure 5-3	Line Circuit Noise Measurement Test Arrangement for Equipment on Customer End	5-12
Figure 5-4	Line Circuit Noise Measurement Test Arrangement for Equipment on Central Office End	5-13
Figure 5-5	Holding Coil	5-14
Figure 7-1	Class A1 Voltage Limits (Sheet 1 of 2)	7-6
Figure 7-2	Class A2 Voltage Limits (Sheet 1 of 2)	7-9
Figure 7-3	Class A3 Voltage Limits (Sheet 1 of 2)	7-12
Figure 7-4	Test Finger	7-16
Figure 7-5	Interrupted/Tripped Criterion Defining the Duration for Which a Current of a Given Magnitude Is Allowed to Persist	7-21
Figure 7-6	Test Circuit Example for Determining Volt-Ampere Characteristics	7-22
Figure 9-1	Illustration of Three Options for Grounding an Output of Embedded DC Power Source	9-11
Figure 9-2	Continuity Test Setup	9-14
Figure 9-3	Hipot Tester Setup	9-15
Figure 9-4	Impulse Generator Setup	9-16
Figure 9-5	Configuration of the DC Fault Test	9-25
Figure 9-6	Configuration of the Proposed EFT Frame Test	9-27
Figure 9-7	An Alternative Configuration for the EFT Test	9-28
Figure 9-8	Laboratory Configuration for the Frame Surge Test	9-29
Figure 9-9	In-Situ Configuration for the Frame Surge Test	9-30
Figure 9-10	Laboratory Configuration of the EUT for the AC Fault Test	9-31
Figure 9-11	In-Situ Configuration of the EUT for the AC Fault Test	9-32
Figure 10-1	Noise Return Test Circuit	10-3
Figure A-1	Double Exponential Voltage/Current Waveform of A/B	A-1
Figure A-2	Double Exponential Voltage Waveform of A/B for 1.2/50 and 10/700 Surges of Table A-1	A-2

List of Tables

Table 1	Participants in the Development of GR-1089-CORE, Issue 7	Preface–xviii
Table 2-1	GR-1089 Section 2 ESD Test Levels	2–3
Table 3-1	Radiated Emission Requirement and Objective for Electric Fields	3–4
Table 3-2	Radiated Emission Requirement for Electric Fields (Doors and Covers Open)	3–6
Table 3-3	Conducted Emission Limits for AC Power Ports for Class A Equipment – Voltage	3–8
Table 3-4	Conducted Emission Limits for AC Power Ports for Class B Equipment – Voltage	3–9
Table 3-5	Conducted Emission Requirements for AC and DC Power Ports – Current	3–9
Table 3-6	Conducted Emission Requirements for Telecommunication Ports – Current	3–10
Table 3-7	Conducted Immunity Requirements for Power Ports	3–13
Table 3-8	Conducted Immunity Requirements for Voiceband Leads	3–14
Table 3-9	Instrumentation Bandwidths	3–15
Table 3-10	1 to 10 GHz Immunity Scan Rate and Step Size	3–39
Table 3-11	Frequencies of Key Interest	3–40
Table 4-1	Test Connections of Telecommunications Port	4–17
Table 4-2	First-Level Lightning Surge	4–50
Table 4-3	Second-Level Lightning Surge	4–60
Table 4-4	First-Level Power Fault Tests	4–62
Table 4-5	Second-Level Power Fault Tests	4–66
Table 4-6	Applicability of EIPP Requirements	4–75
Table 4-7	Fusing Coordination for Unprotected Circuits	4–79
Table 4-8	AC Power Fault – Unprotected Circuits	4–83
Table 4-9	Second-Level Lightning Surges for EEPP and Some EIPP	4–83
Table 4-10	Lightning Surges for Severe Climatic Conditions	4–84
Table 5-1	Longitudinal Induction Test Circuit Criteria	5–5
Table 5-2	Suggested Loop Lengths	5–6
Table 7-1	Values of Maximum Test Resistance	7–4
Table 7-2	Accessibility to Continuous Class A Voltages	7–15
Table 9-1	Test Overcurrent Device Selection	9–25
Table 9-2	Grounding Conductor Size for Fuse-Less Protector Block in the EUT	9–33
Table 9-3	Grounding Conductor Size for Fused Protector Block in the EUT	9–33
Table A-1	Waveform Tolerances	A–3
Table B-1	Applicable Criteria Set A for Network Equipment	B–1
Table B-2	Applicable Criteria Set B for Network Equipment Ports	B–2
Table B-3	Application Chart for Equipment Ports	B–6
Table D-1	FCC Authorized mmW Bands	D–2
Table D-2	Test Levels	D–4

