

Contents

| | |
|---|-----|
| 1. Introduction | 1-1 |
| 1.1 Scope | 1-1 |
| 1.2 Reasons For Reissue | 1-1 |
| 1.3 Organization | 1-1 |
| 1.4 Requirements Terminology | 1-2 |
| 1.5 Requirement Labeling Conventions | 1-3 |
| 1.5.1 Numbering of Requirement and Related Objects | 1-3 |
| 2. General Information | 2-1 |
| 2.1 Description of Product | 2-1 |
| 2.1.1 Standard Riser Cable | 2-1 |
| 2.1.2 Hybrid Riser Cable | 2-1 |
| 2.1.3 Data Grade Riser Cable | 2-2 |
| 2.2 Ordering Options | 2-2 |
| 2.3 Quality Assurance Programs | 2-2 |
| 2.4 Comprehensive Tests | 2-2 |
| 3. General Requirements | 3-1 |
| 3.1 Safety Considerations | 3-1 |
| 3.2 Units and Tolerances | 3-1 |
| 3.3 Shipping and Packing | 3-2 |
| 3.4 Identification Marking | 3-3 |
| 3.5 End Sealing | 3-3 |
| 3.6 Information Accompanying the Reel | 3-3 |
| 3.7 Additional Requirements | 3-3 |
| 3.7.1 Mechanical Reel Protection | 3-3 |
| 3.7.2 Pulling Eyes | 3-3 |
| 4. Mechanical Design Requirements | 4-1 |
| 4.1 Conductors | 4-1 |
| 4.2 Conductor Insulation | 4-1 |
| 4.2.1 Material | 4-1 |
| 4.2.1.1 Standard Riser Cable Units | 4-1 |
| 4.2.1.2 High-Frequency Units | 4-1 |
| 4.2.2 Insulation Test Requirements | 4-2 |
| 4.2.2.1 Insulation Imperfections | 4-2 |
| 4.2.2.2 Insulation Adhesion | 4-2 |
| 4.2.2.3 Elongation | 4-2 |
| 4.2.3 Compression Resistance | 4-2 |
| 4.2.4 Cold Bend for Insulation | 4-2 |
| 4.2.5 Shrinkback | 4-3 |
| 4.2.6 Cut - Through Resistance | 4-3 |
| 4.2.7 Patching | 4-3 |
| 4.2.8 Insulation Colors and Color Coding Requirements | 4-3 |
| 4.2.8.1 Standard Riser Cable Units | 4-3 |
| 4.2.8.2 High-Frequency Units | 4-4 |

| | |
|--|-----|
| 4.2.9 Heat Aging | 4-6 |
| 4.3 Binders | 4-6 |
| 4.4 Core Wrap | 4-6 |
| 4.5 Aluminum Shield | 4-6 |
| 4.6 Outer Jacket | 4-7 |
| 4.6.1 Jacket Material | 4-7 |
| 4.6.2 Jacket Thickness Requirements | 4-7 |
| 4.6.3 Bonded Sheath Adherence | 4-7 |
| 4.7 Fire Resistance Requirements | 4-8 |
| 5. Core Layups for All Riser Cables | 5-1 |
| 5.1 Core Layups for Standard Riser Cable | 5-1 |
| 5.1.1 Cables (100 to 900 Pairs) | 5-1 |
| 5.1.2 Cables (Greater than 900 Pair) | 5-2 |
| 5.1.3 Cables (3600 Pair Alternate Design) | 5-2 |
| 5.2 Core Layups for Hybrid Riser Cable | 5-2 |
| 5.3 Core Layups for Data Grade Riser Pairs | 5-3 |
| 5.4 Defective Pairs for All Riser Cables | 5-3 |
| 5.5 Defective Pair Marking for All Riser Cables | 5-4 |
| 5.6 Spare Pairs for All Riser Cables | 5-4 |
| 6. Mechanical Tests | 6-1 |
| 6.1 Cold Bend | 6-1 |
| 6.2 Impact Test | 6-1 |
| 6.3 Horizontal Scrape Abrasion Test | 6-1 |
| 7. Electrical Requirements for Riser Cables | 7-1 |
| 7.1 Electrical Requirements for Standard Riser Cable | 7-1 |
| 7.1.1 DC Resistance | 7-1 |
| 7.1.2 DC Resistance Unbalance | 7-1 |
| 7.1.3 Mutual Capacitance | 7-1 |
| 7.1.4 Capacitance Unbalance | 7-1 |
| 7.1.5 Attenuation | 7-1 |
| 7.1.6 Crosstalk | 7-2 |
| 7.1.7 Insulation Resistance | 7-2 |
| 7.1.8 DC Voltage Test | 7-2 |
| 7.1.8.1 Conductor-to-Conductor | 7-3 |
| 7.1.8.2 Core-to-Shield | 7-3 |
| 7.1.9 Shield Resistance | 7-3 |
| 7.1.10 Continuity of Metallic Cable Elements | 7-3 |
| 7.2 Electrical Requirements for High-Frequency Units of Hybrid Riser Cable and Data Grade Riser Cable | 7-3 |
| 7.2.1 DC Resistance | 7-4 |
| 7.2.2 DC Resistance Unbalance | 7-4 |
| 7.2.3 Mutual Capacitance | 7-4 |
| 7.2.4 Capacitance Unbalance: Pair-to-Ground | 7-4 |
| 7.2.5 Attenuation | 7-5 |
| 7.2.6 Near End Crosstalk (NEXT) | 7-6 |
| 7.2.7 Characteristic Impedance | 7-6 |

| | |
|--|-----|
| 7.2.8 Structural Return Loss (SRL) | 7-7 |
| 7.2.9 Insulation Resistance | 7-7 |
| 7.2.10 DC Voltage Test | 7-7 |
| 7.2.10.1 Conductor-to-Conductor | 7-7 |
| 7.2.10.2 Core-to-Shield | 7-8 |
| 7.2.11 Shield Resistance | 7-8 |
| 7.2.12 Continuity of Metallic Cable Elements | 7-8 |
| Appendix A: Core Layups | A-1 |
| Appendix B: References | B-1 |
| Appendix C: Glossary | C-1 |

List of Figures

| | | |
|--------------|---|------|
| Figure A-1. | 12, 13 and 25 Pair Primary Units | A-2 |
| Figure A-2. | 50 and 100 Pair Multi Units; 100 Pair Core Layup | A-3 |
| Figure A-3. | 150, 200, 300 Pair Core Layup; 300 Pair Multiunit | A-4 |
| Figure A-4. | 400, 600 and 900 Pair Core Layups | A-5 |
| Figure A-5. | 1200, 1500 and 1800 Pair Core Layups | A-6 |
| Figure A-6. | 2100 and 2400 Pair Core Layups | A-7 |
| Figure A-7. | 2700 Pair Core Layups | A-8 |
| Figure A-8. | 3000 Pair AWG Core Layups | A-9 |
| Figure A-9. | 3600 Pair 26 AWG Core Layups | A-10 |
| Figure A-10. | 3600 Pair Core Layup - 300 Pair Multiunits | A-11 |

List of Tables

| | | |
|------------|---|-----|
| Table 4-1. | Munsell Color Requirements for Insulated Conductors | 4-4 |
| Table 4-2. | Insulation Colors for High-Frequency Units | 4-5 |
| Table 4-3. | Jacket Thickness Requirements | 4-7 |
| Table 5-1. | Binder Color Combinations | 5-2 |
| Table 5-2. | Color Code for Spare Pairs | 5-5 |
| Table 7-1. | Maximum Average Attenuation | 7-2 |
| Table 7-2. | Conductor-to-Conductor DC Test Voltage | 7-3 |
| Table 7-3. | Attenuation Versus Frequency | 7-5 |
| Table 7-4. | Power Sum NEXT Versus Frequency | 7-6 |
| Table 7-5. | Structural Return Loss | 7-7 |