

Table of Contents

Preface	xiii
--------------------------	------

1 Introduction

1.1 Purpose and Scope of Document	1-2
1.2 Organization	1-2
1.3 Harmonization With GR-1221-CORE	1-3
1.4 Reasons for Reissue	1-3
1.4.1 Changes from GR-1209-CORE, Issue 3	1-3
1.4.2 Changes from GR-1209-CORE, Issue 2	1-4
1.5 Requirements Terminology	1-4
1.6 Requirement Labeling Conventions	1-5
1.6.1 Numbering of Requirement and Related Objects	1-5
1.6.2 Requirement, Conditional Requirement, and Objective Identification	1-6

2 General Information

2.1 Scope	2-1
2.2 Passive Optical Components - Couplers and WDMs	2-2
2.2.1 General Product Description	2-2
2.2.2 Coupler and WDM Classes	2-3
2.2.3 Coupler and WDM Technology	2-5
2.2.4 Coupler and WDM Applications	2-7
2.2.4.1 Bidirectional Transmission	2-7
2.2.4.1.1 Steps for Converting to Bidirectional Interoffice Transmission	2-9
2.2.4.2 Hybrid Fiber Coax (HFC) Architecture for Video and Telephony	2-10
2.2.4.3 Fiber in the Loop Systems	2-12
2.3 Passive Optical Components - Filters	2-14
2.3.1 General Product Information	2-14
2.3.2 Filter Classes	2-14
2.3.3 Fiber Optic Filter Technology	2-15
2.3.3.1 Dielectric Interference Coatings	2-15
2.3.3.2 Fiber Optic Bragg Grating	2-15
2.3.3.3 Fiber Fabry-Perot Filters	2-16
2.3.4 Fiber Optic Filter Applications	2-16
2.3.4.1 Fiber Optic Filters in EDFAs	2-16
2.3.4.1.1 Optical Pump Filters for EDFAs	2-17
2.3.4.1.2 EDFA Pump Power Suppression/Recycling	2-17
2.3.4.1.3 ASE Suppression in EDFAs	2-18
2.3.4.1.4 Gain Flattening in EDFAs	2-19
2.3.4.2 Fiber Optic Filters in Multiwavelength Networks	2-19
2.3.4.3 Wavelength Add-Drop Multiplexers (WADMs)	2-21
2.3.4.4 Fiber Optic Filters in Remote Fiber Test Systems	2-23
2.4 Passive Optical Components - Isolators and Circulators	2-23
2.4.1 General Product Description	2-23
2.4.2 Isolator and Circulator Classes	2-25

- 2.4.2.1 Polarization/Analyzer Isolators 2-25
- 2.4.2.2 Walk-off Isolators 2-27
- 2.4.2.3 Optical Circulators 2-28
- 2.4.3 Isolator Technology 2-31
- 2.4.4 Isolator and Circulator Applications 2-32
 - 2.4.4.1 Transmitter Protection 2-32
 - 2.4.4.2 Optical Amplifiers 2-33
 - 2.4.4.3 In-Line Noise Reduction 2-34
 - 2.4.4.4 Circulator Applications 2-35
 - 2.4.4.4.1 Bidirectional Transmission 2-35
 - 2.4.4.4.2 Optical Amplifiers and Systems 2-35
 - 2.4.4.4.3 Dispersion Compensation 2-36
 - 2.4.4.4.4 Optical MUX/DEMUX 2-36
- 2.5 Passive Optical Modules 2-37

3 General and Design Criteria

- 3.1 Documentation 3-1
 - 3.1.1 General Documentation 3-1
 - 3.1.2 Workcenter Information Package 3-2
- 3.2 Marking, Packaging, and Shipping 3-2
 - 3.2.1 Packaged Equipment Shock Criteria 3-3
 - 3.2.1.1 Category A Containers 3-3
 - 3.2.1.2 Category B Containers 3-4
 - 3.2.2 Unpackaged Equipment Shock Criteria 3-4
 - 3.2.3 Transportation Vibration Criteria 3-5
 - 3.2.3.1 Transportation Environment 3-5
- 3.3 Physical Design Criteria 3-6
 - 3.3.1 General Physical Design Criteria 3-6
 - 3.3.2 Optical Fiber 3-6
 - 3.3.3 Optical Connectors 3-7
 - 3.3.4 Materials 3-8
 - 3.3.4.1 Toxicity 3-8
 - 3.3.4.2 Corrosion Resistance 3-8
 - 3.3.4.3 Dissimilar Metals 3-8
 - 3.3.4.4 Fungus Resistance 3-8
 - 3.3.4.5 Flammability 3-8
 - 3.3.5 Safety 3-9
 - 3.3.6 Mounting 3-9
- 3.4 Passive Optical Component Qualification 3-10
- 3.5 Reliability Assurance 3-11
- 3.6 Quality Technology Program 3-12
- 3.7 Application Environments 3-13
 - 3.7.1 Background 3-13
 - 3.7.2 Environmental Classification Definitions 3-14

4 Optical Performance Criteria

4.1	Optical Bandpass	4-4
4.1.1	Optical Bandpass - General	4-4
4.1.2	Optical Bandpass Guidelines	4-5
4.1.3	Optical Bandpass Testing	4-8
4.1.4	DWDM Bandpass Testing	4-9
4.1.5	Center Wavelength Definition	4-9
4.1.6	Central Frequency of DWDM Components Testing	4-10
4.2	Insertion Loss	4-10
4.2.1	Insertion Loss for All Products	4-10
4.2.2	Insertion Loss for Optical Isolators and Circulators	4-12
4.2.3	Insertion Loss for Fiber Optic Filters	4-13
4.2.4	Insertion Loss for Gain Flattening Filters	4-13
4.2.5	Insertion Loss Testing	4-14
4.3	Uniformity	4-14
4.3.1	Uniformity for All Products	4-14
4.3.2	Uniformity for Optical Isolators and Circulators	4-16
4.3.3	Uniformity (Flatness) for Fiber Optic Filters	4-17
4.3.4	Uniformity Testing	4-17
4.4	Isolation	4-17
4.4.1	WDM Wavelength Isolation or Far-End Crosstalk (FEXT)	4-17
4.4.1.1	WDM Wavelength Isolation or FEXT Testing	4-18
4.4.1.2	DWDM Wavelength Isolation or Adjacent Channel Crosstalk Testing	4-18
4.4.2	Isolation for Optical Isolators and Circulators	4-19
4.4.3	Wavelength Isolation (Optical Crosstalk) for Filters	4-19
4.5	Directivity	4-20
4.5.1	Directivity for All Products	4-20
4.5.2	Directivity for Optical Isolators and Circulators	4-21
4.5.3	Directivity for Fiber Optic Filters	4-21
4.5.4	Directivity Testing	4-21
4.6	Return Loss	4-21
4.6.1	Return Loss for All Products	4-21
4.6.2	Return Loss for Optical Isolators and Circulators	4-22
4.6.3	Return Loss for Fiber Optic Filters	4-22
4.7	Polarization-Dependent Loss (PDL)	4-23
4.7.1	PDL for All Products	4-23
4.7.2	PDL for Optical Isolators and Circulators	4-23
4.7.3	PDL for Fiber Optic Filters	4-24
4.7.4	PDL Testing	4-24
4.8	Polarization-Dependent Wavelength (PDW)	4-25
4.8.1	PDW for Fiber Optic Filters	4-25
4.8.2	PDW Testing	4-26
4.9	Polarization Mode Dispersion (PMD)	4-27
4.9.1	PMD for All Products	4-27
4.9.2	PMD for Optical Isolators and Circulators	4-27
4.9.3	PMD for Fiber Optic Filters	4-27
4.9.4	PMD Testing	4-28
4.10	Temperature Effects on DWDM Components	4-28
4.11	Other Fiber Optic Filter-Specific Criteria	4-28

4.11.1 Center Wavelength Misalignment 4-28
 4.11.2 Polarization Sensitivity 4-29

5 Environmental and Mechanical Performance Criteria

5.1 Performance Criteria 5-1
 5.2 Standard Conditions of Test 5-1
 5.3 Operating Environments 5-2
 5.4 Environmental and Mechanical Criteria 5-2
 5.4.1 Transportation and Handling Criteria 5-3
 5.4.1.1 Temperature-Humidity Aging 5-3
 5.4.1.2 Vibration 5-4
 5.4.1.3 Component Impact 5-5
 5.4.1.4 Module Impact 5-5
 5.4.1.5 Temperature Cycling 5-6
 5.4.2 Operational Performance Criteria 5-6
 5.4.2.1 Temperature-Humidity Cycle: Controlled Environment 5-6
 5.4.2.2 Temperature-Humidity Cycle: Uncontrolled Environment 5-7
 5.4.2.3 Water Immersion 5-9
 5.4.2.4 Controlled DWDM Temperature Effects 5-9
 5.4.2.5 Uncontrolled DWDM Temperature Effects 5-9
 5.4.3 Fiber Integrity Criteria 5-10
 5.4.3.1 Fiber Flex 5-10
 5.4.3.2 Fiber Twist 5-10
 5.4.3.3 Fiber Side Pull 5-10
 5.4.3.4 Fiber and Cable Retention (Straight Pull) 5-11
 5.5 Optical Measurement Facilities 5-12

Appendix A: The Transfer Matrix

A.1 Definition of Terms A-1
 A.2 Example A-3

Appendix B: Example Operational Shock and Vibration Proposal

B.1 Definitions B-1
 B.2 Test Conditions B-1
 B.3 Test Fixtures B-2
 B.4 Sample Size B-2
 B.5 Measurement Methodology B-3
 B.6 Acceptance Criteria B-3

Appendix C: References

C.1 Telcordia Documents C-1
C.2 External References C-2
C.3 Telcordia Reference Notes C-5
 C.3.1 Contact Telcordia C-5
 C.3.2 Order Documents Online From the Telcordia Information SuperStore . . C-5
 C.3.3 Telcordia Web Sites for Generic Requirements Information C-6
 C.3.4 Telcordia Licensing Agreements C-6

Appendix D: Acronyms

Appendix E: Glossary

Requirement-Object Index

List of Figures

Figure 2-1	Symbols for Passive Components: (a) Star Coupler, (b) Tree Coupler, Splitter or Combiner, (c) WDM	2-2
Figure 2-2	Example of Common Coupler and WDM Packages	2-3
Figure 2-3	Example of Insertion Loss versus Wavelength for Three Types of 1 x 2 Couplers	2-4
Figure 2-4	Three Splitters as Examples of Fabrication Technologies	2-6
Figure 2-5	Arrayed Waveguide	2-7
Figure 2-6	1 x 1 Protected a) Unidirectional Transmission and b) Bidirectional Transmission Using Couplers or WDMs	2-8
Figure 2-7	N-Channel Bidirectional WDM Transmission	2-9
Figure 2-8	A Sample Frequency Allocation Spectrum for Video and POTS Services	2-10
Figure 2-9	An Example of Hybrid Fiber/Coax (HFC) Architecture With 1 x 4 Splitting	2-11
Figure 2-10	A Point-to-Multipoint FITL System With 1 x 8 Splitting	2-12
Figure 2-11	Point-to-Multipoint ODN Reference Model	2-13
Figure 2-12	Block Diagram of a Fiber Optic Filter	2-14
Figure 2-13	Forming a Grating Structure in an Optical Fiber	2-16
Figure 2-14	1480-nm Pump Filter in an EDFA	2-17
Figure 2-15	Pump Power Suppression Using a Longpass Filter at the Amplifier Output	2-18
Figure 2-16	Fiber Bragg-Grating Filter for Pump Power Reflection	2-18
Figure 2-17	Example of Wideband Uniform Gain Spectrum	2-19
Figure 2-18	Broadcast-and-Select WDM Star Network	2-20
Figure 2-19	(a) Wavelength-Routing WDM Network and (b) Associated Wavelength Assignment Table	2-21
Figure 2-20	WADM Using Optical Circulators	2-22
Figure 2-21	WADM Using Dielectric Thin Film Bandpass Filters	2-22
Figure 2-22	Symbols for (a) an Optical Isolator; (b) a Three-Port Optical Circulator	2-23
Figure 2-23	Schematic Showing Operation of a Magneto-Optical Isolator	2-24
Figure 2-24	An Example of Temperature Dependence of the Backward Loss in Single-Stage and Double-Stage Isolators	2-25
Figure 2-25	Configuration of a Cascaded Optical Isolator	2-26
Figure 2-26	Operating Principle of a Reciprocal Isolator	2-26
Figure 2-27	Operating Principle for a Polarization-Independent Walk-Off Isolator	2-27
Figure 2-28	Schematic for a Polarization-Independent Quasi-Circulator	2-29
Figure 2-29	Positions and Polarization of Beam 2 and Beam 2' on Some Element Surfaces (a) A -A', (b) B -B', (c) C -C', and (d) D -D' in Figure 2-28	2-30
Figure 2-30	Isolation Bandwidths for Isolators Made Using Yttrium Iron Garnet (YIG) and Bismuth Iron Garnet (BIG) at 1550 nm	2-31
Figure 2-31	A Schematic Configuration of the DFB Integrated Laser Module	2-33
Figure 2-32	OFA Gain Module Followed (a) or Preceded (b) by an Isolator	2-34
Figure 2-33	Three Discrete Reflections Between a Transmitter and Receiver	2-34

Figure 2-34 Bidirectional Transmission Using Circulators 2-35

Figure 2-35 Dispersion Compensation Using an Optical Circulator 2-36

Figure 2-36 A Schematic for an Optical Add/Drop Multiplexer Using Optical
Circulators 2-37

Figure 3-1 Category A Container Packaged Equipment Shock Criteria:
Table 4-7 of GR-63 3-4

Figure 3-2 Transportation Vibration Environment: Figure 4-4 in GR-63 3-5

Figure 4-1 Center Wavelength, Offset, and Bandwidth for a Demultiplexer 4-5

Figure 4-2 DWDM Reflection Spectrum 4-8

Figure 4-3 Gain Flattening Filter Spectrum 4-14

Figure 4-4 A Uniformity Measurement Example for a 1 x 2 Coupler 4-16

Figure 4-5 Configuration for Measuring Polarization-Dependent Loss 4-25

Figure 4-6 Polarization-Affected Wavelength Offset 4-26

Figure 5-1 Controlled Temperature Cycling Test Profile 5-7

Figure 5-2 Uncontrolled Temperature Cycling Test Thermal Profile 5-8

Figure 5-3 Example of Transmission Measurement Facility 5-12

Figure B-1 Output Power Variation B-1

List of Tables

Table 3-1	Category B Container Packaged Equipment Shock Criteria: Table 4-8 in GR-63	3-4
Table 3-2	Unpackaged Equipment Shock Criteria: Table 4-9 in GR-63	3-5
Table 4-1	Optical Performance Criteria Summary	4-1
Table 4-2	Nominal Optical Bandpass Ranges	4-4
Table 4-3	Grid Central Frequencies	4-6
Table 4-4	Insertion Loss Criteria for Digital and AM-VSB Transmission	4-11
Table 4-5	Insertion Loss Criteria for 1 x N and 2 x N Couplers	4-12
Table 4-6	Uniformity Criteria and Effective Minimum Loss	4-15
Table 4-7	PDL Requirement for MxN Couplers	4-23
Table 4-8	Polarization Mode Dispersion of Passive Optical Components	4-27
Table 5-1	Environmental and Mechanical Requirements	5-3
Table 5-2	Classification Guidelines for Impact Testing	5-6
Table 5-3	Fiber Ribbon Cable Retention Loads	5-12
Table B-1	Operational Shock and Vibration Test Conditions	B-2
Table B-2	Operational Shock and Vibration Measurement Requirements	B-3
Table B-3	Operational Shock and Vibration Acceptance Criteria	B-3