

Table of Contents

1 Introduction

- 1.1 Scope 1-1
- 1.2 Application 1-1
- 1.3 Document Organization 1-2
- 1.4 Reasons for GR-1217-CORE, Issue 2, December 2008 1-2
- 1.5 Requirements Terminology 1-3
- 1.6 Requirement Labeling Conventions 1-3
 - 1.6.1 Numbering of Requirement and Related Objects 1-3
 - 1.6.2 Requirement, Conditional Requirement, and Objective Identification . . . 1-4

2 General Requirements and Administration

- 2.1 Safety 2-1
- 2.2 Other Requirements 2-1
- 2.3 Nonconformance 2-1
- 2.4 Administration 2-2
- 2.5 Numerical Values 2-2
- 2.6 Workmanship Standards 2-3

3 System Requirements for Connector Products

- 3.1 Environmental Exposure Requirements 3-1
 - 3.1.1 IEEE Std 1156.1 (IEEE Standard Microcomputer Environmental Specifications for Computer Modules) 3-1
 - 3.1.2 IEEE Std 1156.1 Performance Levels 3-1
 - 3.1.2.1 Maximum Exposure Temperature 3-2
 - 3.1.2.2 Other Environmental Requirements 3-2
- 3.2 System Quality Requirements 3-2
 - 3.2.1 Basis for Quality Classification 3-2
 - 3.2.2 System Quality Requirement I for Small Systems 3-3
 - 3.2.3 Service Quality Requirement II for Medium Systems 3-3
 - 3.2.4 Service Quality Requirement III for Large Systems 3-4

4 Connector Classification and Reliability Assurance

- 4.1 Classification by Quality Level 4-2
- 4.2 Methodology to Demonstrate Reliability 4-2
 - 4.2.1 Connector Failure Rates Determined from Field Experience 4-2
 - 4.2.2 Failure Mechanisms Considered in Connector Qualification 4-3
- 4.3 Organization of Qualification Procedures and Reliability Verification 4-4
 - 4.3.1 Standard Testing Procedures 4-4
 - 4.3.2 New Technology Prequalification and Reliability Verification 4-5
- 4.4 The Concept of Performance Testing 4-5
- 4.5 Connector Qualification 4-5
- 4.6 Incoming Inspection Acceptance Tests 4-6
 - 4.6.1 Ship-to-Stock Practices 4-7

5 Design Requirements

- 5.1 Physical and Mechanical Requirements 5-1
 - 5.1.1 General 5-1
 - 5.1.2 Contact Normal Force 5-4
 - 5.1.3 Contact Wipe 5-4
 - 5.1.4 Geometry of Contact Surfaces 5-4
 - 5.1.5 Mate/Unmate Force 5-5
 - 5.1.6 Insertion/Removal Force 5-5
 - 5.1.6.1 Loose Pin 5-5
 - 5.1.6.2 Press Fit 5-5
 - 5.1.7 Plated Through-Hole Requirements for Use With Press Fit Pins 5-6
 - 5.1.8 Contact Strength 5-9
 - 5.1.9 Polarizing Method 5-9
- 5.2 Contact Metallization 5-9
 - 5.2.1 General 5-9
 - 5.2.2 Contact Metallization Thickness 5-10
 - 5.2.3 Porosity 5-11
 - 5.2.4 Surface Roughness 5-11
 - 5.2.5 Durability of Contact Finishes 5-11
- 5.3 Lubrication 5-13
 - 5.3.1 Lubrication of Noble Metallizations 5-14
 - 5.3.2 Lubrication of Non-Noble Metallizations 5-14
- 5.4 Electrical Requirements 5-15
 - 5.4.1 Contact Resistance 5-15
 - 5.4.2 Contact Resistance Stability 5-16
 - 5.4.3 Contact Disturbance 5-16
 - 5.4.4 Low-Nanosecond Events 5-16
 - 5.4.5 Current Rating 5-17
 - 5.4.6 Temperature Rise at Rating 5-17
 - 5.4.7 Insulation Resistance 5-17
 - 5.4.8 Withstanding Voltage 5-18
- 5.5 Temperature/Humidity Stress Immunity 5-18
- 5.6 Miscellaneous Requirements for Special Connector Types 5-18
 - 5.6.1 Semi-Permanent Mechanical Connections 5-18
 - 5.6.2 Component Sockets 5-19
 - 5.6.3 Component Socket Usage 5-20
 - 5.6.4 Zero Insertion Force Connectors 5-20
 - 5.6.5 Coaxial Connectors 5-20
- 5.7 Summary Table for Design Requirements for Separable Connectors 5-21

6 Design Verification and Performance Testing

- 6.1 Physical and Mechanical Requirements 6-1
 - 6.1.1 Visual Examination 6-1
 - 6.1.2 Examination of Dimension, Markings, and Mass 6-1
 - 6.1.3 Contact Normal Force 6-1
 - 6.1.4 Mate/Unmate Force 6-2
 - 6.1.5 Insertion/Removal Force 6-2
 - 6.1.6 Plated-Through Hole Requirements for Use With Press Fit Pins 6-2
 - 6.1.7 Contact Strength 6-2

- 6.1.8 Contact Metallization Thickness 6-3
- 6.1.9 Contact Finish, Surface Roughness, Porosity, and Adhesion 6-3
- 6.1.10 Durability of Noble Metal Contact Finishes 6-4
- 6.1.11 Durability of Non-Noble Metal Contact Finishes 6-5
- 6.2 Electrical Requirements 6-6
 - 6.2.1 Low-Level Contact Resistance (LLCR) 6-6
 - 6.2.2 Contact Resistance (Specified Test Current Method) 6-6
 - 6.2.3 Contact Disturbance 6-6
 - 6.2.4 Low-Nanosecond Events 6-7
 - 6.2.5 Current Rating 6-7
 - 6.2.6 Temperature Rise at Rating 6-7
 - 6.2.7 Insulation Resistance 6-7
 - 6.2.8 Withstanding Voltage 6-8
- 6.3 Environmental Stress Immunity 6-8
 - 6.3.1 General 6-8
 - 6.3.2 Temperature Life 6-9
 - 6.3.3 Thermal Shock 6-9
 - 6.3.4 Moisture Resistance (Humidity With Thermal Cycling) Test 6-10
 - 6.3.5 Vibration and Mechanical Shock Testing 6-11
 - 6.3.5.1 Testing “Connectors Without Mass Loading” 6-11
 - 6.3.5.2 Testing “PWB/Connector Assemblies” 6-12
 - 6.3.5.3 Testing “System Level Assemblies,” Vibration Only 6-12
 - 6.3.6 Four-Gas MFG Testing 6-13
- 6.4 Special Tests for Semi-Permanent Mechanical Connections 6-14
 - 6.4.1 Contact Resistance Stability of Semi-Permanent Connections 6-14
 - 6.4.2 Gas Tight Hermeticity of Non-Noble Metal Contacts 6-14
 - 6.4.3 Flex/Pull Test for Semi-Permanent Cable Connections 6-14
- 6.5 Test Organization and Sequencing 6-15
 - 6.5.1 Samples Required 6-15
 - 6.5.2 Alternative Industry Standard Tests 6-15
 - 6.5.3 Qualification Test Environment 6-17
 - 6.5.4 EIA Qualification Test Sequences 6-17

7 New Technology Prequalification and Reliability Verification

- 7.1 Purpose of Prequalification 7-1
 - 7.1.1 Instances Where Prequalification Is Required 7-1
 - 7.1.1.1 Specific Concerns 7-1
- 7.2 Sample Sizes and Acceptance Criteria 7-2
 - 7.2.1 Sample Sizes and Criteria for Prequalification 7-2
 - 7.2.1.1 Lot-by-Lot Sampling 7-2
 - 7.2.1.2 Control Samples 7-2
- 7.3 Environmental Stress Tests for New Technology Prequalification and Reliability Verification 7-3
 - 7.3.1 Temperature Life Test 7-3
 - 7.3.2 Humidity With Temperature Cycling Test 7-4
 - 7.3.3 Vibration and Mechanical Shock Testing 7-4
 - 7.3.3.1 Testing “Connectors Without Mass Loading” 7-4
 - 7.3.3.2 Testing “PWB/Connector Assemblies” 7-5
 - 7.3.3.3 Testing “System Level Assemblies” 7-5
 - 7.3.4 Mixed Flowing Gas Testing 7-5

8 Requalification

| | |
|---|-----|
| 8.1 Periodic Full Requalification | 8-1 |
| 8.2 Significant Changes Requiring Requalification | 8-1 |
| 8.3 Periodic Partial Requalification | 8-2 |
| 8.3.1 Quality Level II and III | 8-2 |

9 Test Methods

| | |
|---|------|
| 9.1 Environmental Tests | 9-1 |
| 9.1.1 Environmental Preconditioning | 9-1 |
| 9.1.1.1 Dust and Fiber Contamination Test Module | 9-1 |
| 9.1.1.2 Prewear and Postwear Module | 9-3 |
| 9.1.2 Vibration and Mechanical Shock | 9-3 |
| 9.1.2.1 Testing of Connectors Without Mass Loading | 9-3 |
| 9.1.2.1.1 Sample Size for Connectors Without Mass Loading | 9-4 |
| 9.1.2.2 Vibration and Shock Tests for PWB/Connector Assemblies (With Mass Loading) | 9-4 |
| 9.1.2.2.1 Sample Size and Acceptance Criteria for PWB/Connector Assemblies With Mass Loading | 9-5 |
| 9.1.2.3 Vibration and Shock Tests for System Level Assemblies | 9-6 |
| 9.1.2.3.1 Test Sequence for System Level Vibration Test | 9-6 |
| 9.1.2.3.2 Criteria for the System Vibration Test | 9-6 |
| 9.1.3 Four-Gas MFG Testing | 9-6 |
| 9.1.3.1 Test Control and Verification | 9-8 |
| 9.1.3.2 MFG Test Sequence With Parallel Mated and Unmated Exposure | 9-8 |
| 9.1.3.3 MFG Test Sequence With Sequential Mated and Unmated Exposure | 9-9 |
| 9.2 Fretting and Lubrication Tests | 9-10 |
| 9.2.1 Fretting Test — Standard Rider/Flat Method | 9-10 |
| 9.2.2 Connector Hardware Vibration Test for Fretting and Lubrication | 9-10 |
| 9.2.3 Hardware Test for Noble Metal Contacts | 9-13 |
| 9.3 Metal Finishes | 9-14 |
| 9.3.1 Thickness of Noble Metal Contact Finishes | 9-14 |
| 9.3.2 Noble Metal Porosity Testing | 9-14 |
| 9.3.2.1 Alkaline Polysulfide Test for Porosity | 9-14 |
| 9.3.2.2 Electrographic Tests — Gel | 9-15 |
| 9.3.2.3 Corrosive Gas Tests — Nitric Acid Vapor | 9-15 |
| 9.3.3 Finish Adherence | 9-16 |
| 9.4 Flex/Pull Test for Permanent Cable Connections | 9-16 |

Appendix A: References

Appendix B: Glossary and Acronyms

| | |
|------------------------------------|-----|
| B.1 Definitions of Terms | B-1 |
| B.2 Acronyms | B-5 |

Requirement-Object Index

List of Figures

| | | |
|------------|--|------|
| Figure 5-1 | Transverse Section of a Press-Fit Assembly | 5-7 |
| Figure 5-2 | Longitudinal Section of a Press-Fit Assembly | 5-8 |
| Figure 6-1 | Temperature Cycling With Humidity Chamber Profiles | 6-11 |
| Figure 9-1 | Hourly Temperature Cycle for Fretting and Lubrication Test . . . | 9-12 |

List of Tables

| | | |
|-----------|---|------|
| Table 4-1 | Definition of Quality Levels | 4-1 |
| Table 5-1 | Connector Applications and Durability | 5-11 |
| Table 5-2 | Connector Metallization, Lubrication, Durability | 5-12 |
| Table 5-3 | Lubricants for Noble Metallization Contacts | 5-14 |
| Table 5-4 | Examples of Lubricants for Tin/Lead-to-Tin/Lead or Reflowed Tin-to-Reflowed Tin Contacts | 5-15 |
| Table 5-5 | Generic Design Requirements for All Types of Separable Connectors | 5-22 |
| Table 6-1 | Summary of Standard Test Procedures for Design Qualification | 6-16 |
| Table 6-2 | Telcordia Modified Recommended Test Sequences | 6-18 |
| Table 7-1 | Sample Sizes and Test Criteria | 7-2 |
| Table 9-1 | Dust Composition Number 1 (Benign) | 9-2 |
| Table 9-2 | Gas Compositions for Industrial MFG Gas Testing | 9-7 |