

Contents

Preface.....	Preface-1
1. Introduction.....	1-1
1.1 Purpose of Document.....	1-1
1.2 Scope of Document	1-1
1.3 Organization of Document.....	1-2
1.4 Requirements Terminology	1-2
1.5 Requirement Labeling Conventions	1-3
1.5.1 Numbering of Requirement and Related Objects.....	1-3
1.5.2 Requirement, Conditional Requirement, and Objective Object Identification	1-4
1.6 Reason for Reissue	1-4
2. Background	2-1
2.1 MRVT Introduction.....	2-1
2.1.1 MRVT Brief Procedure Description	2-2
2.2 SRVT Introduction.....	2-3
2.2.1 SRVT Brief Procedure Description.....	2-5
2.3 Backward Compatibility	2-6
2.4 Differences in MRVT and SRVT Procedure Between the OMAP Protocol and this Document.....	2-7
3. MRVT Requirements.....	3-1
3.1 Requirements Common to All CCS Nodes	3-1
3.1.1 Node Capabilities.....	3-1
3.1.2 Simultaneous MRVT Initiation.....	3-1
3.1.3 DMRVT Parameter.....	3-2
3.1.4 Maximum Number of Crossed STPs	3-2
3.1.5 Data Collected by the Node.....	3-2
3.1.6 Backward Compatibility Support	3-3
3.1.7 Command Support at OS Interfaces.....	3-4
3.2 Requirements Specific to STPs	3-4
3.2.1 STP Capabilities.....	3-4
3.2.2 NMRVT Parameter.....	3-5
3.2.3 Enabling and Disabling Internetwork Testing	3-5
3.2.4 Command Support at OS Interfaces.....	3-5
3.2.5 MRVT Messages Sent by an STP's Mate	3-6
3.2.6 Performance Requirements.....	3-6
3.3 Requirements Specific to End-Nodes.....	3-7
3.3.1 End-Node Capabilities	3-8
3.3.2 Command Support at OS Interfaces.....	3-8
3.3.3 End-Nodes with Multiple Point Codes.....	3-8
3.3.4 Performance Requirements.....	3-9

4.	SRVT Requirements.....	4-1
4.1	Requirements Common to All CCS Nodes	4-1
4.1.1	Node Capabilities.....	4-1
4.1.2	Simultaneous SRVT Initiation	4-2
4.1.3	DSRVT Parameter.....	4-2
4.1.4	Maximum Number of Crossed TSPs	4-2
4.1.5	Specifying Network Identifiers for Internetwork Tests.....	4-3
4.1.6	Data Collected by the Node.....	4-3
4.1.7	Backward Compatibility Support	4-4
4.2	Requirements Specific to STPs	4-5
4.2.1	STP Capabilities.....	4-5
4.2.2	NSRVT Parameter.....	4-5
4.2.3	Enabling and Disabling Internetwork Testing	4-5
4.2.4	Command Support at OS Interfaces.....	4-6
4.2.5	Performance Requirements.....	4-6
4.3	Requirements Specific to End-Nodes.....	4-8
4.3.1	End-Node Capabilities	4-8
4.3.2	End-Nodes With Multiple Point Codes	4-8
4.3.3	Performance Requirements.....	4-8
5.	MRVT Procedure Description	5-1
5.1	Terminology.....	5-1
5.2	The MTP Routing Verification Test (MRVT) Message	5-3
5.3	The MTP Routing Verification Acknowledgment (MRVA) Message	5-3
5.4	The MTP Routing Verification Result (MRVR) Message	5-4
5.5	Overview of the Intranetwork MRVT Procedure.....	5-5
5.6	Intranetwork MRVT Procedure.....	5-9
5.6.1	At the Node Initiating the Test.....	5-9
5.6.1.1	Initial Actions.....	5-10
5.6.1.2	Subsequent Actions.....	5-10
5.6.2	At an Intermediate Node.....	5-11
5.6.2.1	Initial Actions.....	5-11
5.6.2.2	Subsequent Actions.....	5-11
5.6.3	At a Test Destination Receiving an MRVT Message.....	5-11
5.7	Internetwork MRVT Procedure.....	5-12
5.7.1	At an Outgoing Gateway in an Initiating or Intermediate Network	5-12
5.7.2	At an Incoming Gateway in an Intermediate or Terminating Network	5-12
5.7.3	At Other Nodes in an Intermediate or Terminating Network ..	5-15
5.7.4	Screening	5-15
5.7.5	Reception of a Message for an Unknown Destination.....	5-15
5.8	Timer T1	5-15
6.	SRVT Procedure Description	6-1

6.1	Terminology.....	6-1
6.2	Overview of the Differences Between the SRVT and MRVT.....	6-5
6.3	The SCCP Routing Verification Test (SRVT) Message.....	6-5
6.4	The SCCP Routing Verification Acknowledgment (SRVA) Message	6-6
6.5	The SCCP Routing Verification Result (SRVR) Message.....	6-8
6.6	Overview of the Intranetwork SRVT Procedure.....	6-8
6.7	Intranetwork SRVT Procedure.....	6-14
6.7.1	At the Node Initiating the Test.....	6-14
6.7.1.1	Initial Actions.....	6-15
6.7.1.2	Subsequent Actions.....	6-17
6.7.2	At an ITSP Receiving a No-Compare Form SRVT Message	6-17
6.7.2.1	Initial Actions.....	6-17
6.7.2.2	Subsequent Actions.....	6-18
6.7.3	Differences Between Final and Intermediate TSP	6-19
6.7.4	At a TSP Receiving a Compare Form SRVT Message	6-19
6.7.5	At a Test Destination.....	6-19
6.8	Internetwork SRVT Procedure.....	6-20
6.8.1	At an Outgoing Gateway in an Initiating or Intermediate Network.....	6-20
6.8.2	At an Incoming Gateway in an Intermediate or Terminating Network	6-20
6.8.3	At Other SPs in an Intermediate or Terminating Network.....	6-22
6.8.4	Screening	6-23
6.9	Differences Between Internetwork SRVT and SRVTISNI	6-23
6.9.1	The SRVTISNI Message.....	6-24
6.9.2	The SRVAISNI Message	6-24
6.9.3	The SRVRISNI Message	6-24
6.9.4	At the Node Initiating the Test.....	6-25
6.9.5	Actions at a Gateway in an Intermediate or Terminating Network.....	6-25
6.9.6	At the Test Destination	6-26
6.10	Timers T2 and T2C.....	6-26
Appendix A: SRVT Requirements in Support of Local Number Portability		A-1
A.1	Overview of LNP	A-1
A.2	Definition of Terms.....	A-2
A.3	SRVT Architecture Considerations.....	A-2
A.3.1	Number Portability GTT Function	A-2
A.3.2	Number Portability Database Function	A-6
A.4	SRVT Requirements and Procedures for LNP Support.....	A-6
A.4.1	SRVT Node Requirements to Provide LNP Support.....	A-6
A.4.1.1	Implementation of NP GTT Function at the SCCP layer.....	A-7
A.4.1.2	Implementation of NP GTT Function at the Application Layer.....	A-7

	A.4.1.2.1	Requirements Specific to STPs	A-7
	A.4.1.2.2	Requirements Specific to NP GTT Nodes.....	A-8
A.4.2		SRVT Procedures to Provide LNP Support	A-9
	A.4.2.1	Procedures Specific to Networks with an SCCP Layer NP GTT Node Implementation	A-9
	A.4.2.2	Procedures Specific to Networks with an Application Layer NP GTT Node Implementation	A-10
	A.4.2.3	Procedures Common to All Implementations	A-11
		A.4.2.3.1 False Loop Detection	A-11
		A.4.2.3.2 Compare Message Enhancement.....	A-13
A.5		Summary	A-13
Appendix B: RVT Support for the XUDT Message Type			15
B.1		RVT Support for Segmentation	15
B.2		RVT Support for Intermediate Network Selection (INS).....	16
B.3		RVT Support for UDT/XUDT Message Change.....	17
B.4		Summary	18
Acronyms			Acronyms-1
References.....			References-1

List of Figures

Figure 2-1.	Sample Network Where an MRVT is Conducted.....	2-2
Figure 2-2.	Sample Network Where MRVAs and MRVR Traces are Returned...	2-3
Figure 2-3.	Sample Network Where an SRVT is Conducted.....	2-5
Figure 5-1.	Sample Network Where an MRVT is Conducted.....	5-6
Figure 6-1.	Sample Network Where an SRVT is Conducted.....	6-9
Figure A-1.	Pre-LNP Network Architecture	A-3
Figure A-2.	SCCP Layer NP GTT Functionality Network Architecture.....	A-3
Figure A-3.	Application Layer NP GTT Functionality Network Architecture ...	A-5

List of Tables

Table 5-1.	Suggested Values for Time Intervals M_i and DMRVT in the OMAP Protocol Specifications ^{[1][2]}	5-17
------------	---	------