
ISDN Call Deflection for Primary Rate Interfaces Generic Requirements

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Purpose and Scope	1-1
1.2 Definition of Terms	1-4
1.3 Terminal Assumptions	1-5
1.4 Structure of this Document	1-9
1.5 Summary of Major Changes	1-9
1.6 Requirements Terminology	1-11
1.7 Requirement Labeling Conventions	1-12
1.7.1 Numbering of Requirement and Related Objects	1-12
1.7.2 Requirement, Conditional Requirement, and Objective Object Identification	1-12
2. Feature Overview	2-1
2.1 High-Level Feature Description	2-1
2.1.1 Call Deflection	2-1
2.1.2 Call Deflection After Answer (CDAA)	2-3
2.1.3 Call Return	2-4
2.2 User Perspective	2-4
2.2.1 Calling User	2-5
2.2.2 Deflecting User (I-CD Subscriber)	2-6
2.2.2.1 Call Deflection Before Answer	2-8
2.2.2.2 Call Deflection After Answer	2-8
2.2.3 Deflected-to User	2-9
3. Feature Requirements	3-1
3.1 Feature Operations	3-1
3.1.1 Main Feature Operations	3-1
3.1.1.1 General	3-1
3.1.1.2 Call Associated Information Retention for Redirection	3-2
3.1.1.3 Call Deflection Before Answer	3-3
3.1.1.4 Call Deflection Before Answer with Call Return	3-8
3.1.1.5 Call Deflection After Answer	3-9
3.1.1.6 CDAA with Call Return	3-12
3.1.1.7 Preliminary Invoke Screening	3-13
3.1.1.8 Redirection	3-18
3.1.1.9 Treatment to Deflected-to User	3-27

3.1.1.10	Treatment to Calling User-Call Deflection Before Answer	3-27
3.1.1.11	Treatment to Calling User - CDAA.....	3-35
3.1.2	Other Feature Operations	3-39
3.1.2.1	Deflection Counters	3-39
3.1.2.2	Redirecting Number Presentation.....	3-40
3.1.2.3	Routing Information	3-41
3.1.2.4	Other Switch Actions when Deflected Call is Answered / Cleared	3-42
3.1.3	Release Treatment	3-43
3.1.3.1	Release Treatment for the Deflecting User.....	3-43
3.1.3.2	Release Treatment for the Deflected-to User	3-44
3.1.3.3	Release Treatment for the Calling User.....	3-45
3.1.4	Interworking Feature Operations	3-45
3.1.5	Error Treatment And Abnormal Events	3-45
3.1.5.1	Deflection Request as First Response to SETUP	3-46
3.1.5.2	Preliminary Invoke Screening	3-46
3.1.5.3	Call Deflection Invocation in Normal Call Control Messages 3-48	
3.1.5.4	Subsequent Request for the Same Call	3-49
3.1.5.5	Deflecting User Answering during Redirection	3-49
3.1.5.6	Timer Expiry.....	3-49
3.1.5.7	Call Failure	3-50
3.1.5.8	Call Clearing Initiated by Deflecting User	3-50
3.1.5.9	Call Clearing Initiated by Calling User	3-51
3.2	Internal Call-Processing Controls	3-52
3.2.1	Class Of Service / Configuration	3-52
3.2.2	Screening.....	3-52
3.2.3	Routing.....	3-52
3.2.4	Charge Treatment Determination.....	3-53
3.2.5	Overload.....	3-53
3.3	Signaling / Message Structure.....	3-54
3.3.1	Customer Signaling / User-network Interface.....	3-54
3.3.1.1	Message Structure.....	3-54
3.3.1.2	Information Elements	3-58
3.3.1.3	Component Coding for Call Deflection.....	3-59
3.3.1.4	Component Coding for Notification of Clearing of a Deflected Call	3-63
3.3.2	SS7 Interface Signaling.....	3-64
3.3.3	Interworking with Other Signaling Systems	3-64
3.4	Administration / Operations	3-65
3.4.1	Memory Administration (Service Changes/Subscription Parameters) 3-66	
3.4.1.1	Subscription Parameters per Interface	3-66

3.4.1.2	Switch Parameters.....	3-68
3.4.2	Network Maintenance	3-69
3.4.2.1	Surveillance	3-69
3.4.2.2	Testing	3-71
3.4.3	Network Data Collection (NDC)	3-72
3.4.4	Network Traffic Management (NTM)	3-73
3.4.5	AMA Recording and Comptroller	3-73
3.5	Interactions	3-74
3.5.1	Call-by-Call Service Selection.....	3-74
3.5.1.1	OUTWATS Selection	3-74
3.5.1.2	Foreign Exchange Selection	3-75
3.5.1.3	Tie Trunk Selection	3-76
3.5.1.4	INWATS	3-78
3.5.1.5	Hotel/Motel and Selective Class Of Call Screening (SCOCS) 3-79	
3.5.1.6	Call-By-Call Access to Interexchange Carrier (IXC) Services	3-80
3.5.2	ISDN Call Forwarding	3-81
3.5.2.1	Sequential Diverting Limit	3-81
3.5.2.2	Call Forwarding Variable/Interface Busy.....	3-81
3.5.2.3	Call Forwarding Don't Answer	3-82
3.5.3	ISDN Calling Number Identification Services	3-83
3.5.4	ISDN Calling Name Identification Services	3-84
3.5.5	Electronic Key Telephone Service (EKTS)	3-84
3.5.6	User-user Signaling.....	3-84
3.5.7	Interactions with Other PRI Services.....	3-84
3.5.7.1	Two B-Channel Transfer (TBCT)	3-84
3.6	Timing and Tolerances.....	3-85
4.	Signaling System 7 Requirements	4-1
4.1	SS7 Support for Feature Operations.....	4-1
4.1.1	Main Feature Operations.....	4-1
4.1.1.1	General.....	4-1
4.1.1.2	Call Associated Information Retention for Redirection	4-6
4.1.1.3	Call Deflection Before Answer.....	4-6
4.1.1.4	Call Deflection Before Answer with Call Return.....	4-15
4.1.1.5	CDAA	4-26
4.1.1.6	CDAA with Call Return	4-32
4.1.1.7	Preliminary Invoke Screening	4-39
4.1.1.8	Redirection.....	4-39
4.1.1.9	Treatment to Deflected-to User	4-55
4.1.1.10	Treatment to Calling User - Call Deflection Before Answer .. 4-57	
4.1.1.11	Treatment to Calling User - After Answer	4-73
4.1.2	Other Feature Operations	4-76

4.1.2.1	Redirecting Number Presentation.....	4-76
4.1.2.2	Routing Information	4-77
4.1.2.3	Other Switch Actions when Deflected Call is Answered / Cleared	4-78
4.1.3	Release Treatment.....	4-78
4.1.3.1	Release Treatment for the Deflecting User.....	4-78
4.1.3.2	Release Treatment for the Deflected-to User	4-79
4.1.3.3	Release Treatment for the Calling User.....	4-79
4.1.4	Interworking Feature Operations	4-79
4.1.5	Error Treatment And Abnormal Events.....	4-80
4.1.5.1	Preliminary Invoke Screening	4-80
4.1.5.2	Call Deflection Invocation in Normal Call Control Messages 4-80	
4.1.5.3	Subsequent Request for the Same Call	4-80
4.1.5.4	Deflecting User Answering During Redirection	4-80
4.1.5.5	Timer Expiry.....	4-80
4.1.5.6	Call Failure	4-81
4.1.5.7	Call Clearing Initiated by Deflecting User	4-81
4.1.5.8	Call Clearing Initiated by Calling User	4-81
4.1.5.9	Notification of Clearing to Deflecting User	4-81
4.2	Internal Call-Processing Controls	4-81
4.2.1	Class Of Service / Configuration	4-81
4.2.2	Code Interpretation.....	4-82
4.2.3	Screening.....	4-82
4.2.4	Routing.....	4-82
4.2.5	Charge Treatment Determination.....	4-82
4.2.6	Overload.....	4-82
4.3	Signaling / Message Structure.....	4-82
4.3.1	Customer Signaling / User-Network Interface.....	4-82
4.3.2	SS7 Interface Signaling.....	4-82
4.3.2.1	SS7 ISDNUP Messages	4-83
4.3.2.2	SS7 ISDNUP Parameters.....	4-84
4.3.3	Interworking with Other Signaling Systems	4-90
4.4	Administration / Operations	4-92
4.4.1	Memory Administration (Service Changes/Subscription Parameters) 4-92	
4.4.2	Network Maintenance	4-92
4.4.3	Network Data Collection (NDC)	4-93
4.4.4	Network Traffic Management (NTM)	4-93
4.4.5	AMA Recording and Comptroller	4-93
4.5	Interactions	4-93
4.5.1	Call-By-Call Service Selection	4-93
4.5.2	ISDN Call Forwarding	4-93
4.5.3	ISDN Calling Number Identification Services	4-93

4.5.4	Electronic Key Telephone Service (EKTS)	4-93
4.5.5	User-User Signaling	4-94
4.6	Timing and Tolerances.....	4-94
5.	Line Diagrams.....	5-1
Appendix A:	Data Dictionary for ISDN Call Deflection	A-1
A.1	Scope and Definition	A-1
A.2	Allowed Data Values	A-2
A.3	Data Dictionary	A-3
Appendix B:	Addressing-Data-Elements	B-1
References	References-1
Glossary	Glossary-1

List of Figures

Figure 1-1.	Example of Call Deflection	1-2
Figure 1-2.	Example of Interoffice Call Deflection	1-3
Figure 3-1.	Flow of Information Used in Redirection.....	3-22
Figure 4-1.	Example in Which Deflecting Users (1), (2), and (3) Reside on Same Switch	4-48
Figure 4-2.	Example in Which Deflecting User (3) and Previous Deflecting Users Reside on Different Switches	4-52
LD 5-1.	Service Invocation Allowed at Various States of the Call	5-1
LD 5-2.	Rejection of Deflection Request.....	5-2
LD 5-3.	Successful Call Deflection.....	5-3
LD 5-4.	Failed Call Deflection.....	5-4
LD 5-5.	Options Available after Failed Call Deflection	5-5
LD 5-6.	CDAA after Failed Deflection Request.....	5-6
LD 5-7.	Call Deflection with Call Return	5-7
LD 5-8.	Unsuccessful Call Deflection with Call Return.....	5-8
LD 5-9.	Successful CDAA.....	5-9
LD 5-10.	Failed CDAA.....	5-10
LD 5-11.	Options after Failed CDAA.....	5-11
LD 5-12.	Successful CDAA with Call Return	5-12
LD 5-13.	Failed CDAA with Call Return	5-13
LD 5-14.	Notification of Diversion.....	5-14
LD 5-15.	Notification of Delay	5-15
LD 5-16.	Additional ALERTing Messages Suppressed	5-16
LD 5-17.	Notification of Diversion and Suppression of Messages.....	5-17
LD 5-18.	Notification of Clearing.....	5-18
LD 5-19.	Deflecting User Answers during Deflection.....	5-19
LD 5-20.	Early Clearing By Deflecting User.....	5-20
LD 5-21.	Deflecting User Answers during Deflection with Call Return	5-21
LD 5-22.	Early Clearing by Deflecting User with Call Return.....	5-22
LD 5-23.	Call Deflection Before Answer (After ALERTing), with no Call Return.....	5-23
LD 5-24.	Call Deflection Before Answer (T-delay expires), with no Call Return	5-24
LD 5-25.	Call Deflection Before Answer (After ALERTing), with Call Return...	5-25
LD 5-26.	Call Deflection After Answer, with no Call Return	5-26
LD 5-27.	Call Deflection After Answer, with Call Return	5-27
LD 5-28.	Call Deflection Before Answer (After ALERTING), with Call Return - Un- successful	5-28
LD 5-29.	Call Deflection After Answer, with Call Return - Unsuccessful.....	5-29
LD 5-30.	Call Deflection Before Answer with Call Return, Deflecting User Answers Call, Update Backward Call Indicator	5-30

List of Tables

Table 3-1.	Recognition of Condition 1: Unsuccessful Deflection	3-4
Table 3-2.	Recognition of Condition 2: Successful Deflection: Answer by the Deflected-to User.....	3-5
Table 3-3.	Recognition of Condition 3: Alerting or Interworking at the Switch Serving the Deflected-to User	3-5
Table 3-4.	Mapping from Information Provided in Original SETUP and in Deflection Request into Information Used to Set Up Call to Deflected-to User.....	3-23
Table 3-5.	Formatted Display Text to Provide Notification of Diversion to Calling User.....	3-34
Table 3-6.	Coding of Call Deflection Display Information	3-35
Table 3-7.	FACILITY Message Content - I-CD Subscriber Requests Deflection ..	3-54
Table 3-8.	DISConnect Message Content - Switch Sends Acknowledgment to Deflecting User to Indicate Successful Deflection Attempt.....	3-55
Table 3-9.	FACILITY Message Content - Switch Sends Error Indication to Deflecting User to Indicate Unsuccessful Deflection Attempt	3-55
Table 3-10.	DISConnect Message Content - Deflecting User Initiates Call Clearing After Sending a Deflection Request.....	3-56
Table 3-11.	NOTIFY Message Content - Switch Sends an Indication to I-CD Subscriber that the Previously Identified Deflected Call has been Cleared	3-56
Table 3-12.	NOTIFY Message Content - Switch Notifies ISDN Calling User Served on a BRI that the Call has been Diverted	3-57
Table 3-13.	SETUP Message Content - Switch Offers the Deflected Call to the Deflected-to User.....	3-57
Table 4-1.	Interoffice Requirements to Support I-CD Service Operations.....	4-2
Table 4-2.	Summary of the Appropriate Referenced Procedures to Follow for Unsuccessful Deflections.....	4-3
Table 4-3.	Recognition of Alerting or Interworking at the Deflecting User's Switch.....	4-5
Table 4-4.	SS7 ISDNUP Message Structure.....	4-83