

Contents

1. Introduction	1-1
1.1 Purpose	1-1
1.2 Requirements Terminology	1-2
1.2.1 Numbering of Requirement and Related Objects	1-2
1.3 Definitions	1-3
1.3.1 Switch Response Time	1-3
1.3.2 Switch Processing Time	1-3
1.3.3 Link Output Delay	1-3
1.3.4 Normal Load	1-4
1.3.5 CCS Switching Office (CCSSO)	1-5
1.3.6 Service Switching Point (SSP)	1-5
1.3.7 Wink	1-5
1.3.8 0ZZ Sequence	1-5
1.3.9 Automatic Number Identification (ANI) Sequence	1-6
1.3.10 Address Sequence	1-6
1.4 Organization	1-6
2. Switch Call Segments	2-1
2.1 ISDNUP Message Call Segments	2-1
2.2 Alerting Call Segments	2-2
2.3 ISDN Access Message Call Segments	2-2
2.4 TCAP Message Call Segments	2-2
2.5 Announcement/Tone Call Segments	2-3
2.6 Connection Call Segments	2-3
2.7 MF Call Segments	2-3
2.8 SS7-MF Interworking Call Segments	2-4
3. Switch Processing Time Requirements	3-1
4. Link Output Delay	4-1
5. Switch Response Time	5-1
Appendix A: Examples of Switch Processing	A-1
References	References-1
Acronyms	Glossary-1

List of Tables

Table 3-1.	Switch Processing Time Requirements	3-1
Table 3-2.	Switch Processing Time Conditional Requirements	3-2
Table 4-1.	Link Output Delay	4-1
Table 5-1.	Switch Response Time Assuming Typical Traffic Mix and Message Lengths	5-2