

Contents

Generic Requirements Notice Of Disclaimer	iii
List of Figures	viii
List of Tables	ix
Preface	xi
The Telcordia Technologies GR Process	xi
About GR-1399-CORE	xi
To Submit Comments	xii
1 Introduction	
1.1 Purpose and Scope	1-1
1.2 Organization	1-1
1.3 Introduction to Revision 1	1-2
1.3.1 Purpose and Reason for Revision	1-2
1.4 Requirements Terminology	1-2
1.5 Requirement Labeling Conventions	1-3
1.5.1 Numbering of Requirement and Related Objects	1-3
1.5.2 Requirement, Conditional Requirement, and Objective Identification	1-4
2 General Information	
2.1 Description of Product	2-1
2.2 Ordering Options	2-2
2.2.1 User Considerations	2-2
2.3 Requirements Terminology	2-2
2.4 Reference Documents	2-3
2.5 Safety Considerations	2-3
2.6 Units and Tolerances	2-3
2.7 Quality Assurance Programs	2-4
2.8 Product Classification - Revision 1	2-5
2.8.1 Product Designation with Attenuation Group	2-5
2.8.2 Commonly Used Coaxial Distribution Cable	2-6
3 General Requirements	
3.1 Packaging Requirements	3-1
3.2 End Sealing	3-1
3.3 Marking	3-1
3.3.1 Package and Reel Marking	3-1
3.3.2 Jacket Marking	3-1
3.3.3 Length Marking	3-1
3.3.4 Jacket Marking Durability	3-2
3.3.5 Compatibility with Hardware	3-2

4 Mechanical Design and Test Requirements

4.1	Product Designation	4-1
4.2	Copper-Clad Aluminum Center Conductor	4-2
4.2.1	Material	4-2
4.2.2	Joints	4-2
4.2.3	Center Conductor Dimensions	4-2
4.3	Dielectric	4-2
4.3.1	Foam Dielectric	4-3
4.3.1.1	Foam Dielectric Material	4-3
4.3.1.2	Shrinkback	4-4
4.3.1.3	Thermal Oxidative Stability – OIT Test of Foam Dielectric	4-4
4.3.1.3.1	OIT Test Method – Initial	4-4
4.3.1.3.2	OIT Test Method – After Aging	4-5
4.3.1.3.3	OIT Requirements	4-5
4.3.1.4	Shear Adhesion of Foam Dielectric to Center Conductor	4-5
4.3.1.5	Tensile Adhesion of Foam Dielectric to Center Conductor	4-6
4.3.1.6	Patching	4-6
4.3.2	Disc and Air Dielectric	4-7
4.3.2.1	Disc and Air Dielectric Material	4-7
4.3.2.2	Tensile Adhesion of Disc to Center Conductor	4-7
4.3.2.3	Shear Adhesion of Disc to Center Conductor	4-8
4.3.2.4	Thermal Oxidative Stability – OIT of Disc and Air Dielectric	4-8
4.3.2.5	Patching	4-8
4.4	Outer Conductor (Shield)	4-9
4.4.1	Outer Conductor Dimensions	4-9
4.5	Dielectric-to-Outer Conductor Bonding	4-10
4.6	Flooding Compound Under Jacket	4-10
4.6.1	Compound Flow	4-10
4.6.2	Corrosion Resistance	4-11
4.7	Cable Jacket	4-11
4.7.1	Thermal Oxidative Stability – OIT Test	4-12
4.7.2	Ultraviolet Light Stability	4-12
4.7.3	Jacket Diameters	4-13
4.7.4	Jacket Thickness	4-14
4.7.5	Jacket Eccentricity	4-15
4.7.6	Integral Messenger (IM)	4-16
4.7.6.1	Joints	4-16
4.7.6.2	Messenger Wire Separation	4-16
4.8	Gopher Protected (GP) Armor	4-16
4.8.1	Armor Construction	4-16
4.8.2	Material	4-17
4.8.3	Gopher Resistance Test	4-17
4.9	Outer Jacket	4-18

5 Completed Cable Physical Tests

5.1	Cable Bend Test	5-1
-----	---------------------------	-----

5.2 Cable Impact Test	5-1
5.3 PE Jacket Longitudinal Shrinkage	5-1
5.4 Adhesion of Dielectric to Outer Conductor	5-1
5.5 Adhesion of Outer Conductor to Jacket	5-2
5.6 Abrasion Resistance	5-2
5.7 Expansion Loop Test	5-2
5.8 Water Penetration Test (Buried Cable Only)	5-3
5.9 Flammability	5-3
5.10 National Electrical Code Listing	5-3

6 Completed Cable Electrical Requirements

6.1 Continuity and Shorts	6-1
6.2 Conductor Resistance	6-1
6.3 Impedance	6-2
6.4 Structural Return Loss (SRL)	6-2
6.5 Attenuation	6-2
6.6 Dielectric Strength Between Conductors	6-4
6.7 Jacket Leakage Test	6-4
6.8 Insulation Resistance	6-4

Appendix A: Durability of Printing and Marking Test

Specimen Preparation	A-1
Apparatus	A-1
Exposure	A-1
Procedure	A-1

Appendix B: Products Not Commonly Used by Telcordia Client Companies

Appendix C: References

Note	C-3
To Contact Telcordia Customer Service or to Order Documents	C-3
To Order Documents From Within Telcordia (Employees Only)	C-3

Requirement-Object Index

List of Figures

Figure 4-1	Construction of Foam Dielectric Coaxial Distribution Cable	4-3
Figure 4-2	Cross-Section of Disc and Air Dielectric Coaxial Cable	4-7

List of Tables

Table 2-1	Cable Products and their Attenuation Groups	2-5
Table 2-2	Commonly Used Coaxial Distribution Cables	2-6
Table 4-1	Product Designation of Coaxial Distribution Cable	4-1
Table 4-2	Properties of Polyethylene	4-4
Table 4-3	Foam Dielectric Adhesion to Center Conductor	4-6
Table 4-4	Disc Dielectric Adhesion to Center Conductor	4-8
Table 4-5	Mechanical Properties of Aluminum Outer Conductor	4-9
Table 4-6	Dimensions of Center and Outer Conductors	4-9
Table 4-7	Distribution Cable Jacket Material Requirements	4-11
Table 4-8	Nominal Diameters over Jacket, in. (mm)	4-13
Table 4-9	Minimum Spot/Minimum Average Thickness, in. (mm)	4-14
Table 6-1	DC Resistance at 20°C (68°F), Ohms/kft (Ohms/km), Max	6-1
Table 6-2	Attenuation at 20°C (68°F), dB/100 ft. (dB/100 m), Maximum	6-3
Table B-1	Product Designation of Coaxial Distribution Cable Not Commonly Used by the Telcordia Client Companies	B-1