

---

# PCS Access Services Interface Specification in Support of PCS Routing Service, PCS Home Database Service, and PCS IS-41 Message Transport Service

## Contents

Preface .....	Preface-1
1. Introduction.....	1-1
1.1 Purpose.....	1-1
1.2 Organization.....	1-1
1.3 Relationship to Bellcore and Industry Documents.....	1-2
2. Overview of PCS Access Services.....	2-1
2.1 Numbering Options.....	2-2
2.2 High-level Service Descriptions .....	2-3
2.2.1 PCS Routing Service.....	2-5
2.2.2 PCS Home Database Service .....	2-5
2.2.3 PCS IS-41 Message Transport Service .....	2-7
3. PCS Routing Service.....	3-1
3.1 PCS Routing Service Description .....	3-1
3.2 Architecture Overview .....	3-3
3.2.1 Types of Interconnection .....	3-3
3.2.2 BCC Network Elements.....	3-4
3.2.3 PSP Network Elements .....	3-5
3.3 Service Activation for PCS Providers.....	3-5
3.3.1 Service Activation.....	3-5
3.3.1.1 Service Negotiation .....	3-6
3.3.1.2 Service Management .....	3-7
3.3.1.2.1Service Management User Functions .....	3-7
3.4 Messages in Support of PCS Routing Service .....	3-7
3.4.1 Message Format and Encoding.....	3-7
3.4.2 Message Routing Procedures .....	3-7
3.4.3 Message Flows.....	3-8
3.4.3.1 Message Flows in Support of Call Delivery.....	3-8
3.4.3.1.1LocationRequest .....	3-8
3.4.3.1.2RedirectionRequest.....	3-11
3.4.4 Call Set-up.....	3-14
3.5 Testing Capabilities to Support PCS Routing Service.....	3-17
3.5.1 Application-Level Testing .....	3-17
3.5.2 SCCP, MTP and Physical Link Testing.....	3-18
3.6 Accounting Management .....	3-19

---

---

3.7	PCS Routing Service Performance .....	3-19
4.	PCS Home Database Service .....	4-1
4.1	PCS Home Database Service Description.....	4-1
4.1.1	Registration .....	4-3
4.1.1.1	Wireless Registration.....	4-4
4.1.1.2	Wireline Registration.....	4-4
4.1.2	Support of Call Delivery .....	4-4
4.1.3	Authentication .....	4-4
4.1.4	Service Validation.....	4-5
4.1.5	Vertical Services .....	4-5
4.1.5.1	Support of IS-41 Vertical Features .....	4-6
4.1.5.2	Call Screening.....	4-6
4.1.5.3	Time Of Day (TOD) Routing .....	4-6
4.1.6	Profile Manipulation .....	4-6
4.2	Architecture Overview .....	4-7
4.2.1	Types of Interconnection .....	4-8
4.2.2	BCC Network Elements.....	4-8
4.2.3	PSP Network Elements .....	4-9
4.3	Service Activation and Service Assurance for PCS Providers .....	4-9
4.3.1	Service Activation.....	4-9
4.3.1.1	Service Negotiation .....	4-10
4.3.1.2	Service Management .....	4-12
4.3.1.2.1	Subscriber Administration .....	4-13
4.3.1.2.2	Subscription Administration.....	4-13
4.3.1.2.3	Service Administration .....	4-15
4.3.1.2.4	Network Administration .....	4-15
4.3.2	Service Assurance .....	4-16
4.3.2.1	Service Management .....	4-16
4.4	Service Activation and Service Assurance for PCS End Users .....	4-16
4.4.1	Service Activation.....	4-16
4.4.1.1	Service Negotiation .....	4-17
4.4.1.2	Service Management .....	4-17
4.4.1.2.1	Subscription Administration.....	4-17
4.4.2	Service Assurance .....	4-19
4.4.2.1	Service Management .....	4-19
4.5	Messages in Support of PCS Home Database Service.....	4-19
4.5.1	Message Format and Encoding .....	4-19
4.5.2	Message Routing Procedures .....	4-19
4.5.3	Message Flows.....	4-19
4.5.3.1	Message Flows in Support of Call Delivery.....	4-21
4.5.3.1.1	RoutingRequest.....	4-21
4.5.3.2	Message Flows in Support of Registration.....	4-24
4.5.3.2.1	Wireless Registration.....	4-24
4.5.3.2.2	Wireless Cancellation of Previous Registration .....	4-27

---

---

4.5.3.2.3	UnreliableRoamerDataDirective .....	4-29
4.5.3.3	Message Flows in Support of Authentication.....	4-31
4.5.3.3.1	Subscriber Credit Verification.....	4-31
4.5.3.4	Message Flows in Support of Service Validation.....	4-33
4.5.3.4.1	HLR Update of Roamer VLR Profile.....	4-33
4.5.3.4.2	Subscriber Credit Verification.....	4-36
4.5.3.5	Message Flows for Vertical Service Support .....	4-37
4.5.3.5.1	TransferToNumberRequest .....	4-37
4.5.3.5.2	RemoteFeatureControlRequest.....	4-39
4.5.3.5.3	CSSInactive .....	4-41
4.6	Testing Capabilities to Support PCS Home Database Service .....	4-43
4.6.1	Application-Level Testing .....	4-43
4.6.2	SCCP, MTP and Physical Link Testing.....	4-45
4.7	Accounting Management .....	4-46
4.8	PCS Home Database Service Performance.....	4-46
5.	PCS IS-41 Message Transport Service .....	5-1
5.1	PCS IS-41 Message Transport Service Description.....	5-1
5.2	Architecture Overview .....	5-1
5.2.1	Types of Interconnection .....	5-1
5.3	Service Activation for PCS Providers.....	5-2
5.3.1	Service Activation.....	5-2
5.3.1.1	Service Negotiation .....	5-2
5.3.1.2	Service Management .....	5-3
5.3.1.2.1	Service Management User Functions .....	5-4
5.4	Messages In Support of PCS IS-41 Message Transport Service .....	5-4
5.4.1	Message Format and Encoding .....	5-4
5.4.2	Message Routing Procedures .....	5-4
5.4.3	Message Flows.....	5-4
5.5	Accounting Management .....	5-5
5.6	PCS IS-41 Message Transport Service Performance.....	5-5
Appendix A:	Network Interconnection Architecture .....	A-1
A.1	Signaling Overview.....	A-1
A.2	CCS Network Interconnection Architectures.....	A-1
A.3	Interface Protocol .....	A-2
A.4	Network Management.....	A-4
A.4.1	Screening at the STP.....	A-4
A.4.2	Screening at the SCP.....	A-5
Appendix B:	Message Formatting and Encoding.....	B-1
B.1	TCAP Formats .....	B-1
B.1.1	TCAP INVOKE .....	B-2
B.1.2	TCAP RETURN RESULT .....	B-3
B.1.3	TCAP RETURN ERROR .....	B-4
B.1.4	TCAP REJECT .....	B-10

---

---

B.2	IS-41 Maintenance Parameter .....	B-13
B.3	IS-41 Messages and Parameters .....	B-13
Appendix C:	TCAP Message Routing Procedures .....	C-1
C.1	Message Routing Procedures .....	C-1
C.1.1	Message Transfer Part (MTP) .....	C-1
C.1.2	SCCP/Global Title Translation (GTT) .....	C-3
C.1.3	SCCP Intermediate Signaling Network Identification .....	C-5
C.2	TCAP Message Routing .....	C-7
C.2.1	Routing Possibilities .....	C-8
C.2.1.1	Registration .....	C-8
C.2.1.1.1	Originating PSP Selects the ICN .....	C-9
C.2.1.1.2	Terminating PSP Selects the ICN .....	C-10
C.2.1.2	Subscriber Qualification During Call Origination .....	C-12
C.2.1.3	Call Delivery .....	C-13
References	.....	References-1
Acronym List	.....	Glossary-1

---

## List of Figures

Figure 2-1.	PCS Access Services Concept .....	2-1
Figure 2-2.	PCS Access Services Overview .....	2-4
Figure 3-1.	Routing from a Terminating BCC Network .....	3-2
Figure 3-2.	Routing from an Originating BCC Network .....	3-3
Figure 3-3.	PCS Routing Service Architecture .....	3-4
Figure 3-4.	LocationRequest .....	3-9
Figure 3-5.	RedirectionRequest.....	3-12
Figure 4-1.	PCS Home Database Service at Home MSC.....	4-2
Figure 4-2.	PCS Home Database Service w/Terminating PCS Routing Service .....	4-2
Figure 4-3.	PCS Home Database Service w/Organizing PCS Routing Service .....	4-3
Figure 4-4.	PCS Home Database Service Architecture.....	4-8
Figure 4-5.	RoutingRequest .....	4-21
Figure 4-6.	Registration Notification .....	4-24
Figure 4-7.	RegistrationCancellation .....	4-28
Figure 4-8.	UnreliableRoamerDataDirective .....	4-29
Figure 4-9.	Subscriber Credit Verification.....	4-31
Figure 4-10.	HLR Update of Roamer VLR Profile .....	4-34
Figure 4-11.	TransferToNumberRequest .....	4-37
Figure 4-12.	RemoteFeatureControlRequest.....	4-39
Figure 4-13.	CSSInactive .....	4-41
Figure 5-1.	PCS IS-41 Message Transport Service.....	5-2
Figure A-1.	- D-Link Interconnection Architecture .....	A-2
Figure A-2.	- A-Link Interconnection Architecture .....	A-2
Figure A-3.	- SS7 Protocol.....	A-3
Figure C-1.	Reference Architecture .....	C-8
Figure C-2.	Originating PSP (PSP1) selects the ICN .....	C-9
Figure C-3.	Terminating PSP (PSP3) selects the ICN .....	C-11
Figure C-4.	QualificationRequest message .....	C-12
Figure C-5.	Call Delivery.....	C-13



---

## List of Tables

Table 3-1.	Expanded LOCREQ message.....	3-10
Table 3-2.	Expanded locreq message.....	3-11
Table 3-3.	REDIRREQ message.....	3-13
Table 3-4.	Return Error message in response to REDIRREQ .....	3-14
Table 3-5.	Initial Address Message Parameter Values .....	3-16
Table 4-1.	MTP & SCCP Parameter Values - Query from PSP/VLR to HLR .....	4-20
Table 4-2.	MTP & SCCP Parameter Values - Reply from HLR to PSP/VLR .....	4-21
Table 4-3.	ROUTREQ message.....	4-22
Table 4-4.	routreq message .....	4-23
Table 4-5.	REQNOT message .....	4-25
Table 4-6.	regnot message .....	4-26
Table 4-7.	Populating RegistrationNotification Return Result Parameters .....	4-27
Table 4-8.	REGCANC message.....	4-28
Table 4-9.	regcanc message .....	4-29
Table 4-10.	UnreliableRoamerDataDirective message.....	4-30
Table 4-11.	UnreliableRoamerDataDirective message.....	4-30
Table 4-12.	QUALREQ message.....	4-32
Table 4-13.	qualreq message.....	4-33
Table 4-14.	QUALDIR message.....	4-35
Table 4-15.	qualdir message .....	4-36
Table 4-16.	TRANUMREQ message .....	4-38
Table 4-17.	tr anumreq message .....	4-39
Table 4-18.	RemoteFeatureControlRequest message .....	4-40
Table 4-19.	remotefeaturecontrolrequest message.....	4-41
Table 4-20.	CSSINACT message .....	4-42
Table 4-21.	cssinact message .....	4-43
Table B-1.	Private Specifier .....	B-1
Table B-2.	TCAP INVOKE.....	B-2
Table B-3.	TCAP RETURN RESULT .....	B-3
Table B-4.	TCAP RETURN ERROR.....	B-4
Table B-5.	TCAP REJECT .....	B-10
Table C-1.	MTP Routing Summary Table .....	C-3
Table C-2.	Global Title Routing Summary Table .....	C-5
Table C-3.	ISNI Routing Summary Table.....	C-7