

Table of Contents

1 Introduction

1.1	Reasons for GR-1502-CORE Reissues	1-1
1.1.1	Reasons for GR-1502-CORE, Issue 9	1-1
1.1.2	Reasons for GR-1502-CORE, Issue 8	1-2
1.1.3	Reasons for GR-1502-CORE, Issue 7	1-2
1.1.4	Reasons for GR-1502-CORE, Issue 6	1-3
1.1.5	Reasons for GR-1502-CORE, Issue 5	1-4
1.1.6	Reasons for GR-1502-CORE, Issue 4	1-5
1.1.7	Reasons for GR-1502-CORE, Issue 3	1-5
1.1.8	Reasons for GR-1502-CORE, Issue 2	1-6
1.2	Purpose	1-6
1.3	General	1-6
1.4	DESP Responsibilities	1-7
1.5	Site Survey	1-8
1.5.1	General	1-8
1.6	Document Organization	1-13
1.6.1	Revisions	1-16
1.7	Requirements Terminology	1-16
1.8	Requirement Labeling Conventions	1-17
1.8.1	Numbering of Requirement and Related Objects	1-17
1.8.2	Requirement, Conditional Requirement, and Objective Identification	1-17
1.9	Navigating the GR-1502 Portable Document Format (PDF) File	1-17

2 Equipment Layout

2.1	General	2-1
2.2	Equipment Layout Requirements	2-2
2.2.1	COMMON LANGUAGE® Equipment Identification Code (CLEI™) Labels	2-2
2.3	Floor Plan	2-3
2.4	Floor Plan Data (FPD)	2-5
2.5	Equipment Frames	2-7
2.5.1	Floor Anchors	2-9
2.6	Securing Equipment Using Threaded Rod Into Anchors in the Concrete Floor	2-10
2.7	Cross-Connect Systems	2-13
2.8	DC Power Equipment	2-14
2.9	Building Integrated Timing Supply (BITS)	2-15

3 Cross-Connect Systems

3.1	General	3-1
3.2	Zoning and Spread	3-1
3.3	Conventional Distributing Frame (DF)	3-1
3.4	Manual Digital Cross-Connect (DSX) Line-Ups	3-2
3.5	Electronic Digital Cross-Connect (DCS) Systems	3-2
3.6	Modular (Cosmic) Distributing Frames	3-2
3.7	Fiber Distribution Frames (FDFs)	3-3

- 3.8 Subscriber Digital Distributing Frames (SDDFs) 3-3
- 3.9 Terminal Strips/Connecting Block 3-3
- 3.10 Protector Blocks 3-3
- 3.11 Termination for Digital Loop Carrier (DLC) Pairs 3-3
- 3.12 Electrical Protection 3-4
- 3.13 Frame Conversion 3-4
- 3.14 Splicing 3-4

4 Power Facilities - Battery/Rectifiers (AC/DC)

- 4.1 General 4-1
- 4.2 Rectifiers 4-1
- 4.3 Charging (Rectifiers) Equipment 4-4
- 4.4 Batteries 4-5
 - 4.4.1 Flooded Lead Antimony and Lead Calcium Cells 4-6
- 4.5 Engineering Guidelines 4-8
- 4.6 Alarms 4-9

5 Power Facilities - Converters (DC/DC)

- 5.1 General 5-1
- 5.2 Alarm Features 5-1

6 Power Facilities - Inverters (DC/AC)

- 6.1 General 6-1
- 6.2 Inverter Selection 6-1
- 6.3 Load Classification 6-1
- 6.4 Alarm Features 6-2

7 Power Facilities - Uninterruptable Power Supplies (UPS)

- 7.1 General 7-1
- 7.2 Large UPS 7-1
- 7.3 Definition of Terms 7-1
- 7.4 Apparatus Considerations 7-2

8 Power Facilities - Standby AC Power

- 8.1 General 8-1
- 8.2 Engine 8-1
- 8.3 Alarms 8-5
- 8.4 Automatic Transfer Switch 8-6
- 8.5 Main Line Circuit Breaker 8-7
- 8.6 Bonding and Grounding 8-7
- 8.7 Engine Room Environment 8-8
- 8.8 Acoustics 8-8
- 8.9 Enclosures 8-8

9 Power Facilities - Power Systems Monitor/Controller (PSMC)

- 9.1 General 9-1
- 9.2 Standard Monitor and Control Points 9-1
- 9.3 Alarms 9-5

9.4 Statistical Channels	9-5
9.5 Energy Management/Sequencing	9-6
10 Power Facilities - DC Power Distribution	
10.1 General	10-1
10.2 Telecommunications Equipment Loads	10-1
10.3 Power Plant Distribution Characteristics	10-1
10.4 Cabling Sizing and Bus Bars	10-2
10.5 Connectors	10-4
10.6 Circuit Protector Sizing	10-4
10.7 Distribution Sources	10-5
11 Power Facilities - Ring, Tone, and Cadence Plants	
11.1 General	11-1
11.2 Ringing Systems	11-1
11.3 Ringing Plant - Ringing Tone Distribution	11-2
11.4 Ringing Plant Alarms	11-2
12 Central Office Grounding	
12.1 General	12-1
12.2 Central Office Ground (CO GRD) Systems	12-2
12.2.1 Ground Bars Under Raised Floors	12-8
12.2.2 Incidental Grounds	12-8
12.3 Isolated Ground Planes (Isolated Bonding Network [IBN])	12-9
12.4 Power Plants	12-9
12.5 Equipment Isolation	12-11
12.6 AC Equipment Grounding (ACEG)	12-12
12.7 Ring Ground System	12-12
12.7.1 Exterior Ring Ground	12-12
12.7.2 Interior Ring Ground	12-13
12.8 Radio Room and Antenna Tower Environment	12-13
12.9 Cable Entrance Facility Bonding and Grounding	12-14
12.10 Computer Room Ground Environment	12-14
12.10.1 Operations Support Systems (OSS)	12-14
12.11 Grounding Engineering Requirements	12-15
13 Cable Rack	
13.1 General	13-1
13.2 Description and Sizes	13-1
13.3 Location	13-3
13.4 Engineering Requirements	13-4
13.5 Support of Cable Rack	13-10
13.6 Bracing	13-14
14 Auxiliary Framing	
14.1 General	14-1
14.2 Hanger Rods	14-4
14.3 Ceiling Fastening Arrangements	14-5

- 14.4 Types of Auxiliary Framing 14-6
- 14.5 Auxiliary Framing Arrangement 14-8
- 14.6 Stanchions 14-10
- 14.7 Community Dial Offices (CDOs) and Non-Traditional Equipment
Locations 14-11
- 14.8 Bracing 14-11
- 14.9 Equipment Frames 14-12

15 Auxiliary Framing - High-Type

16 Rolling Ladders

- 16.1 General 16-1
- 16.2 Rolling Ladders - Track Type 16-1
 - 16.2.1 Location of Ladders 16-3
 - 16.2.2 Slant of Ladders 16-3
- 16.3 Rolling Ladder Track 16-4
- 16.4 Height of Ladder 16-7

17 Bracing

- 17.1 General 17-1
- 17.2 Auxiliary Frame Bracing for Seismic Zones 0, 1, and 2 17-3
- 17.3 Auxiliary Frame Bracing for Seismic Zones 3 and 4 17-4
- 17.4 Cable Rack Bracing for All Seismic Zones 17-4
- 17.5 Fastening at the Tops of Frames 17-5
 - 17.5.1 Distributing Frames and Protector Frames 17-5
 - 17.5.2 Power Equipment 17-5
- 17.6 Bracing for Community Dial Office (CDO) and Non-Traditional Equipment
Locations 17-6

18 Cable Distribution Systems (CDSs)

- 18.1 General 18-1
- 18.2 Applications 18-1
- 18.3 CDSs for Fiber Optic Cable and Associated Equipment 18-1
- 18.4 Fire and Electrical Requirements for Optical Fiber Cables 18-4
- 18.5 Telecommunications Carrier Responsibilities 18-4

19 Frame and Aisle Lighting

- 19.1 General 19-1
- 19.2 Description 19-1
- 19.3 Engineering Requirements 19-2

20 Appliance Outlets and Miscellaneous Raceway

- 20.1 General 20-1
- 20.2 Outlets 20-1
- 20.3 Armored Cable 20-2

21 DC Powered Task Lighting

- 21.1 General 21-1

21.2	Lighting Placement	21-1
21.3	Record Requirements	21-2
22 Operations Support Systems (OSS)		
22.1	General	22-1
22.2	Location and Layout	22-1
22.3	Environmental Controls	22-2
22.4	Power Requirements	22-3
22.4.1	Existing Conditions	22-3
22.5	Communications Protocol	22-4
22.6	Alarms	22-5
23 Alarms		
23.1	General	23-1
23.2	Remote Telemetry Design Criteria	23-4
23.3	Detail Engineering Requirements	23-7
23.4	Power Equipment	23-8
23.5	Building/Environmental	23-9
23.6	Central Office Switching Systems	23-9
23.7	Performance Monitoring (PM)	23-10
23.8	Transmission/Facility Equipment	23-10
24 Wire and Cable Requirements		
24.1	General	24-1
24.2	General Considerations	24-1
24.2.1	Cable Diversification	24-2
24.3	Uses of Wire and Cable	24-2
24.3.1	Timing Cable and Associated Equipment	24-4
24.3.2	Shielded Cable	24-5
24.3.3	Coax Cable	24-5
24.3.4	Fiber Optic Cable	24-6
25 General Interface Requirements		
25.1	General	25-1
25.2	Equipment Interconnect Requirements	25-1
25.3	Human Interaction Requirements	25-1
25.4	Interconnect Drawings	25-2
25.5	Point of Contact - Engineering	25-2
25.6	Point of Contact - Assignments	25-2
26 Central Office Equipment (COE) Building Environment Requirements		
26.1	General	26-1
26.2	Vertical Space Planning	26-1
26.3	Thermal	26-3
26.4	Fire Resistance	26-5
26.4.1	General	26-5
26.4.2	Labels	26-6
26.5	Firestopping	26-6

- 26.5.1 General 26–6
- 26.6 Earthquake and Office Vibration 26–10
- 26.7 Airborne Contaminants 26–11
- 26.8 Acoustic Noise 26–11
- 26.9 Illumination 26–12
- 26.10 Electromagnetic Compatibility 26–14
- 26.11 Electrostatic Discharge 26–16

27 Central Office Equipment (COE) Records - Introduction

- 27.1 General 27–1
- 27.2 Drawing/Documentation Definitions 27–1

28 Office Record Index, Serial Numbers, and Central Office Listing (COL)

- 28.1 General 28–1
- 28.2 Office Record Index (ORI) 28–1
- 28.3 Serial Numbers 28–2
- 28.4 Central Office Listing (COL) 28–2

29 Numbering System

- 29.1 General 29–1
- 29.2 Prefix 29–1
- 29.3 Base Number 29–1
- 29.4 Sub-Code 29–2
- 29.5 Dash Number 29–2
- 29.6 Alpha Suffix 29–3
- 29.7 Expanded Dash Numbers 29–3

30 Central Office Base Records

- 30.1 General 30–1
- 30.2 Records 30–2
 - 30.2.1 Grounding Schematic 30–6
 - 30.2.2 Framework Record 30–7
 - 30.2.3 Optical Plan Record 30–7
- 30.3 Distributing Frame (DF) Records 30–7
- 30.4 Power Equipment Records 30–9
 - 30.4.1 Power Board Front and Rear Equipment Records 30–10
 - 30.4.2 Power Wiring Lists and Block Schematics 30–11
 - 30.4.3 AC Wiring Lists and Front Equipment Record 30–11
 - 30.4.4 Power Raceway and Cable Running List 30–11
 - 30.4.5 Fuse Bay Equipment Records 30–11
 - 30.4.6 Ring Tone and Cadence Records 30–13
 - 30.4.7 Miscellaneous Power Records 30–13
- 30.5 Front Equipment Records 30–13
 - 30.5.1 Miscellaneous 30–15
- 30.6 Wiring Lists 30–15
- 30.7 Alarm Records 30–16
- 30.8 Assignment Records 30–16
- 30.9 Application Schematics 30–16
- 30.10 Miscellaneous Cable Records 30–17

30.11	Miscellaneous Switchboard Records	30-17
30.12	Cross-Connect Records/Charts	30-17
30.13	Numbering Plans for COE	30-17
31	Supplier Standard Drawings/Documents	
31.1	General	31-1
31.2	Supplier/Manufacturer Drawing/Document Types	31-1
31.3	Engineering Requirements	31-2
32	Interconnect Drawings	
32.1	General	32-1
32.2	Purpose	32-1
32.3	Interconnect Drawing Availability	32-2
33	Central Office Base Record Marking and Creation	
33.1	General	33-1
33.2	Marking Records	33-1
33.3	Updating Existing Records	33-3
33.4	Updating Family of Records	33-3
33.5	Updating Distributing Frame (DF) Records	33-5
33.6	Updating Power Equipment Records	33-6
33.7	Updating Wiring List and Equipment Records	33-7
33.8	Updating Front Equipment Records and Associated Wiring List Records	33-8
33.9	Updating Miscellaneous Records	33-9
33.10	Updating Framework Record	33-9
33.11	Creating Records	33-9
33.12	Renumbering Records	33-10
33.13	Voiding Records	33-10
33.14	Retention (R) Records	33-11
33.15	Non-Active (N) Records	33-11
33.16	Hot Slide Procedures	33-11
34	Procedures and Flows	
34.1	General	34-1
34.2	Obtaining Records	34-1
34.3	Distribution of Central Office Base Records	34-1
34.4	How to Obtain Documentation Other Than Central Office Base Records	34-2
34.5	Additional References	34-2
35	Items Common to All Records	
35.1	Title Box Requirements	35-1
35.2	Issue Notes	35-2
35.3	Notes	35-3
36	Document Types/Dash Numbers	
37	Detail Engineering Service Provider (DESP) Output	
37.1	General	37-1

37.2 Specification Cover Sheet 37–2

37.3 Specification Section A 37–3

37.4 Specification Section B 37–13

37.5 Specification Section C 37–17

37.6 Appendixes to Specifications 37–17

37.7 Specification Completion and Distribution 37–19

38 Equipment Removal and Cable Mining

38.1 Introduction 38–1

38.2 General 38–1

38.3 Safety 38–2

38.4 Hazardous Material/Waste 38–2

38.5 Scrap Material Segregation and Disposition 38–3

 38.5.1 General 38–3

 38.5.2 Disposition 38–4

38.6 Office Drawings and Records 38–4

38.7 Prevention of Service Interruption or Degradation 38–4

38.8 Equipment Protection 38–4

38.9 Scrap Material Bins and Containers 38–5

38.10 Grounding 38–5

38.11 Equipment Removed for Reuse 38–6

 38.11.1 General 38–6

 38.11.2 Workmanship Requirements 38–6

38.12 DC Power Circuit and Fuse Removal 38–6

 38.12.1 General 38–6

 38.12.2 Safety Precautions and Equipment Protection 38–7

 38.12.3 Workmanship Requirements 38–7

38.13 AC Circuit and Raceway Removal 38–8

 38.13.1 General 38–8

 38.13.2 Safety Precautions and Equipment Protection 38–8

 38.13.3 Workmanship Requirements 38–8

38.14 Cable Removal and Mining 38–9

 38.14.1 General 38–9

 38.14.2 Cable Cutting Procedures and Precautions 38–9

 38.14.3 Workmanship Requirements 38–9

38.15 Units and Equipment Frame Removal 38–9

38.16 Appliance Outlets, Lights, Switches, and Risers 38–9

38.17 Rolling Ladders 38–10

38.18 Overhead Ironwork and Bracing 38–10

 38.18.1 General 38–10

 38.18.2 Safety Precautions and Equipment Protection 38–10

38.19 Battery Removal 38–10

 38.19.1 Safety Precautions and Equipment Protection 38–10

 38.19.2 Workmanship Requirements 38–11

39 Equipment Retired in Place (RIP)

39.1 Introduction 39–1

39.2 General 39–1

39.3 Equipment Retired 39–1

39.4 Power Distribution Bay 39–1

39.5 Office Alarms and Records 39-2
39.6 Circuit Packs 39-2

Appendix A: References

A.1 Telcordia Reference Notes A-3
 A.1.1 Contact Telcordia A-3
 A.1.2 Order Documents Online From the Telcordia Information SuperStore A-3
 A.1.3 To Order Documents From Within Telcordia (Employees Only) A-3
 A.1.4 Telcordia Web Sites for Generic Requirements Information A-4

Appendix B: List of Acronyms and Definition of Terms

Requirement-Object Index (ROI)

List of Figures

Figure 2-1 Equipment Frame - Overall Dimensions 2-16

Figure 2-2 Framework Upright - Equipment Mounting Hole Pattern 2-17

Figure 2-3 Cable Rack (top) Mounting Hole Pattern 2-18

Figure 2-4 Adapter Plate and Spacer 2-19

Figure 2-5 Special System Cable Racks for 21- and 15-Inch Deep Frames . . . 2-20

Figure 2-6 Seismic Zone Map 2-21

Figure 2-7 Floor Supported Rectifier Cabinets - Floor and Top Fastenings . . 2-22

Figure 2-8 Cable Holes/Slots, Auxiliary Framing, Columns, Ceiling Inserts and
Line-Ups 2-23

Figure 2-9 Ladder Track, Cross Aisles, Fluorescent Lighting Fixtures 2-24

Figure 2-10 Columns, Ceiling Bracing, Cable Holes, Main Aisles 2-25

Figure 2-11 Floor Fastening at Cable Hole for Frame 2-26

Figure 2-12 Floor Fastening at Cable Hole for Frame With Sheet Metal Base
(Deleted) 2-27

Figure 2-13 Typical Anchor Patterns 2-28

Figure 4-1 Typical Power Distribution System 4-10

Figure 4-2 Rectifier Plant 4-11

Figure 10-1 Two-Way Loop Voltage Drop 10-7

Figure 12-1 Central Office Ground System Integrated Ground Plane 12-17

Figure 12-2 Grounding for Integrated and Isolated Ground Planes (IBN) Powered
From Common Power Plant 12-18

Figure 12-3 Maximum Multi-Floor Stored Program Control System (SPCS) Ground
Plane Spread When a Single SPCS Dedicated Power Plant Supplies
Power to One or More SPCS Offices 12-19

Figure 12-4 Microwave Ring Ground System and Principal Ground Bonds . . . 12-20

Figure 12-5 Grounding Conductor Bonded to Ferromagnetic Raceway 12-21

Figure 12-6 Typical Conductor Marking Tags 12-21

Figure 12-7 Vertical Equalizer 12-22

Figure 12-8 Typical Equipment Connected to CO GRD System 12-23

Figure 12-9 Central Office Ground Bar - Horizontal Orientation 12-24

Figure 12-10 Central Office Ground Bar - Vertical Orientation 12-25

Figure 12-11 Cable Support From Cable Rack 12-26

Figure 12-12 Cable Support From Auxiliary Framing 12-27

Figure 12-13 Typical Horizontal Equalizer Configuration 12-28

Figure 13-1 Straight Sections Ladder-Type Cable Rack 13-15

Figure 13-2 Mounting Snap-On Cable Horns on Ladder-Type Cable Rack 13-16

Figure 13-3 Straight Clamp for Stringers of Same Width (Deleted) 13-16

Figure 13-3A Splice for Stringers of Same Width 13-17

Figure 13-4 Straight Sections Modified Ladder-Type Cable Rack Unsecured
Cabling 13-19

Figure 13-5 Examples of Cable Horns 13-20

Figure 13-6 Corner Clamps: Stringers With Same Widths 13-21

Figure 13-7 Corner Clamps: Stringers With Different Widths 13-22

Figure 13-8 Corner Clamp for Stringers of Different Widths - Left (Deleted) . . 13-22

Figure 13-9 Junction Corner Clamp for Stringers of Same Width - Left
(Deleted) 13-22

Figure 13-10	Junction Corner Clamp for Stringers of Same Width - Right (Deleted)	13-22
Figure 13-11	45-Degree Outside Turn	13-23
Figure 13-12	45-Degree Inside Turn	13-24
Figure 13-13	90-Degree Edge Clamp for Inside Turn (Deleted)	13-24
Figure 13-14	90-Degree Edge Clamp for Outside Turn (Deleted)	13-24
Figure 13-15	90-Degree Inside Turn	13-25
Figure 13-16	90-Degree Outside Turn	13-26
Figure 13-17	Securing End of Vertical Rack	13-27
Figure 13-18	Terminating Vertical Cable Rack at Cable Hole Channel-Type Sheathing	13-28
Figure 13-19	Terminating Vertical Cable Rack at Cable Hole Angle-Type Sheathing	13-29
Figure 13-20	Typical Support of Cable Rack in Cable Shaft	13-30
Figure 13-21	Mounting Rubber Bumpers on Exposed Ends of Cable Rack Stringers	13-31
Figure 13-22	90-Degree Turn in Same Plane	13-32
Figure 13-23	Closing Ends of Ladder-Type Cable Rack at Junctions and Offsets	13-33
Figure 13-24	T-Intersection	13-34
Figure 13-25	Small Offset Less Than Width of Rack and in Same Plane	13-35
Figure 13-26	Small Horizontal Offset Less Than Width of Rack With 2-Inch Vertical Offset Between Rack (Deleted)	13-35
Figure 13-27	Offset Same as Width of Rack and in Same Plane, Ladder-Type Rack	13-36
Figure 13-28	In-Line Junction - Large Offset, Less Than the Width of Rack	13-37
Figure 13-29	Joining Ladder-Type Racks of Different Widths in Same Plane - Smaller Rack Approximately in Center	13-38
Figure 13-30	In-Line Junction - Racks of Different Width	13-39
Figure 13-31	Right Angle Junction - Three Racks of Different Widths	13-40
Figure 13-32	90-Degree Outside Turn for a Radius of More Than 6 Inches	13-41
Figure 13-33	Corner Bracket at Turn or Intersection (Deleted)	13-41
Figure 13-34	90-Degree Inside Turn for a Radius of More Than 6 Inches	13-42
Figure 13-35	90-Degree Inside Turn for a Radius of 6 Inches or Less (Deleted)	13-42
Figure 13-36	90-Degree Outside Turn for a Radius of 6 Inches or Less (Deleted)	13-42
Figure 13-37	Right Angle Junction - Small Vertical Offset (Views A, B, C)	13-43
Figure 13-38	Large Vertical Offset in Horizontal Racks - Greater Than 9 Inches	13-45
Figure 13-39	Cross-Aisle Cable Rack Run Non-Continuously Over Aisles at Higher Level Than Over-Frame Rack Intersection	13-46
Figure 13-40	Cable Rack Turn for Power or Fiber Cable Runs	13-47
Figure 13-41	Cross-Aisle Cable Rack Run Continuously Over Aisles at Higher Level Than Over-Frame Rack (Deleted)	13-47
Figure 13-42	Power Cable Support Bracket for Power Cables Without Main-Aisle or End-Aisle Cable Rack (Deleted)	13-47
Figure 13-43	Cable Support From Cable Rack	13-48
Figure 13-44	Power Cable Support Bracket Attached to Auxiliary Framing With Retaining Spring (Deleted)	13-48
Figure 13-45	Cable Rack Support - Directly to Auxiliary Framing	13-49

Figure 13-46	Main or Cross-Aisle Cable Rack Supported by Additional Auxiliary Framing Below Regular Framing - Using Threaded Rods	13-50
Figure 13-47	Main or Cross-Aisle Cable Rack Supported by Additional Auxiliary Framing Above Regular Framing	13-51
Figure 13-48	Cable Rack Support Below Auxiliary Framing With Hanger Rods	13-52
Figure 13-49	Hanger Rod Extended With Spliced Coupling (Deleted)	13-52
Figure 13-50	Supporting 5-Inch Cable Rack From Threaded Rod	13-53
Figure 13-51	Hanger Rod Offset to Clear Cable-Rack Clamp, Cable-Rack Strap, or Other Obstruction (Deleted)	13-54
Figure 13-52	Supporting 5-Inch Cable Rack From Embedded Insert in Ceiling (Deleted)	13-54
Figure 13-53	Supporting 1-Foot, and 1-Foot 3-Inch Cable Rack From Embedded or Exposed Ceiling Channel (Deleted)	13-54
Figure 13-54	Supporting Cable Rack From Embedded Insert in Ceiling (Deleted)	13-54
Figure 13-55	Bracing Hanger Rod-Supported Cable Rack With Rod-Type Bracing (Deleted)	13-54
Figure 13-56	Bracing Hanger Rod-Supported Cable Rack With Angle-Type Bracing (Deleted)	13-54
Figure 13-57	Pipe Supported Cable Rack Over Low-Type Auxiliary Framing (Deleted)	13-54
Figure 13-58	Cable Rack Support - Horizontal 5- or 12-Inch Rack to Wall (5-inch Rack Shown)	13-55
Figure 13-59	Insulating Junction for Cable Rack (Deleted)	13-55
Figure 13-60	Cable Support Bracket from Cable Rack Stringer or Auxiliary Framing (Deleted)	13-55
Figure 13-61	Additional Cable Support - Cable Sag Prevention	13-56
Figure 13-62A	Right Angle Junction - Additional Cable Support, Cable Racks in Same Plane	13-57
Figure 13-63	Vertical Cable Clamp - Power Cable Run	13-58
Figure 13-64	Vertical Cable Runs in Exposed Locations	13-59
Figure 13-65	Vertical Cable Runs in Cable Shafts or Enclosures	13-60
Figure 13-66	Example of a 90-Degree Spiral with 90-Degree Turn	13-61
Figure 13-67	Example of a Spiral Cable Rack	13-62
Figure 13-68	Example of a 90-Degree Double Outside Turn	13-63
Figure 13-69	Example of a 90-Degree Double Inside Turn	13-64
Figure 13-70	Right Angle Junction - Large Vertical Offset End-to-Side Junction of Connecting Racks - Greater Than 9 Inches	13-65
Figure 13-71	Right Angle Junction - Vertical to Horizontal Rack - Large Cable Radius (Bottom); Right Angle Junction - Abrupt Cable Radius (Top)	13-66
Figure 13-72	Cable Rack Support - Horizontal Cable Racks to Floor	13-67
Figure 13-73	Cable Rack C-Clip and G-Clip	13-68
Figure 13-74	Cable Rack Support to Wall or Column	13-68
Figure 13-75	Right Angle Junction - Line-Up and Cross-Aisle Cable Rack, Cross-Aisle Rack Raised 2 Inches to Clear Apparatus	13-69
Figure 13-76	Right Angle Junction - Vertical to Horizontal Rack - Small Cable Radius (Top); Right Angle Junction Between Horizontal Racks (Bottom)	13-70
Figure 13-77	Terminating Vertical Cable Rack at Auxiliary Framing	13-71

Figure 13-78	Cable Racks Supported Directly to Auxiliary Framing With J-Bolts or Spanners	13-72
Figure 13-79	45-Degree Right Angle Junction	13-73
Figure 13-80	45- or 90-Degree Intermediate Junction (45-Degree Shown)	13-74
Figure 14-1	Typical Arrangement of Auxiliary Framing for Ladder Type Cable Rack Over Line-Up of Frames	14-13
Figure 14-2	Typical Arrangement of Auxiliary Framing	14-14
Figure 14-3	Typical Arrangement of Auxiliary Framing Transport Area - Building Columns and Ceiling Inserts Prearranged to Facilitate Precabbling	14-15
Figure 14-4	Auxiliary Framing Fastened to Underside of Cable Rack (Deleted)	14-15
Figure 14-5	Auxiliary Framing Attached to 1-Inch Junction Pipe Extended Beyond the End of Cable Duct-Type Frame	14-16
Figure 14-6	Auxiliary Framing Attached Directly to Cable Duct-Type Frames or to Junction Pipe at Location of Future Frame	14-17
Figure 14-7	Support for Frame Pipe Extending Beyond End of Cable Duct-Type Frame	14-18
Figure 14-8	Auxiliary Framing Attached to Cable Duct-Type Frame or to Junction Pipe at Location of a Future Frame	14-19
Figure 14-9	Auxiliary Framing Fastened to Cable Duct-Type Frame or to Junction Pipe at Location of Future Frame	14-20
Figure 14-10	Auxiliary Framing Fastened to Top Angles	14-21
Figure 14-11	Auxiliary Framing Fastened to Single Top-Angle Frames	14-22
Figure 14-12	V-Bolt Frame Support Assembly	14-23
Figure 14-13	Auxiliary Framing Fastened to Single Top-Angle Frames - Framing Support Offset to Clear Frame Upright	14-24
Figure 14-14	V-Bolt Frame Support Offset to Clear Frame Upright	14-25
Figure 14-15	Auxiliary Framing Fastened to Single Top-Angle Frames - 11-Foot 9-1/2-Inch Framing (Deleted)	14-25
Figure 14-16	Arrangement for Extending Channel Framing to Eliminate Necessity of Cutting Back Existing Framing	14-26
Figure 14-17	Support Low- to High-Level Framing (Deleted)	14-27
Figure 14-18	Auxiliary Framing Junction - Single Level	14-27
Figure 14-19	Single-Level Auxiliary Framing Junction of Primary and Secondary Channels	14-28
Figure 14-20	Splicing Auxiliary Framing - Channels to Channels Using 3-Hole Splice Plates for Seismic Zones 0, 1, and 2	14-29
Figure 14-21	Splicing Auxiliary Framing - Common Applications Using 3-Hole Splice Plates (Deleted)	14-29
Figure 14-22	Arrangement for Extending Channel Framing with Channel Framing - Eliminating Necessity of Cutting Back Existing Frames	14-30
Figure 14-23	Finishing Clips on Auxiliary Framing	14-31
Figure 14-24A	Pipe Stanchion Support of Auxiliary Framing	14-32
Figure 14-24B	Stanchion Support of Auxiliary Framing (Seismic Zones 3 and 4)	14-33
Figure 14-25	Double-Level Auxiliary Framing - Fastening Channel Over Channel	14-34
Figure 14-26	Auxiliary Framing Over Battery Control Boards (Deleted)	14-34
Figure 14-27	Auxiliary Framing Attached Directly to Top Angles of Battery Distribution Fuse Boards - 11-Foot 6-Inch Framing (Deleted)	14-34

Figure 14-28 Auxiliary Framing Attached to Top Angles of Battery Distribution Fuse Boards 14-35

Figure 14-29 Auxiliary Framing Attached to Top Angles of Battery Distribution Fuse Boards - 11-Foot 9-1/2-Inch Framing (Deleted) 14-36

Figure 14-30 Auxiliary Framing Over Battery Control Boards Equipped With Rear Doors (Deleted) 14-36

Figure 14-31 Auxiliary Framing Support of Bus Bars at Battery Stands 14-37

Figure 14-32A Bracing Auxiliary Framing to Columns for Seismic Zones 0, 1, and 2 14-38

Figure 14-32B Bracing Auxiliary Framing to Columns for Seismic Zones 0, 1, and 2 (Cont.) 14-38

Figure 14-33 Bracing of Auxiliary Framing With Single-Rod Braces (Moved to Section 17) 14-39

Figure 14-34 Bracing of Auxiliary Framing With Double-Rod Braces (Moved to Section 17) 14-39

Figure 14-35 Bracing of Auxiliary Framing With Double-Angle Braces (Over 1-Foot 6-Inches, But Less Than 4-Foot 10-Inches) (Moved to Section 17) 14-39

Figure 14-36 Fastening Auxiliary Framing Brace to Embedded Ceiling Channel (Moved to Section 17) 14-39

Figure 14-37 Double-Level Auxiliary Framing - Isolating Two Levels of Channels 14-40

Figure 14-38 Auxiliary Framing Support for Short Bus Bars Above Battery Stands 14-41

Figure 14-39 Supporting Frame With Threaded Rod From Framing (Deleted) 14-41

Figure 14-40 Bracing Frames From Auxiliary Framing (Moved to Section 17) 14-41

Figure 14-41 Splicing of Auxiliary Framing Channels in Seismic Zones 3 and 4 14-42

Figure 14-42 Splicing of Auxiliary Framing Channels 1-Inch Difference in Framing Levels (Deleted) 14-42

Figure 14-43 Splicing of Auxiliary Framing Channels 1 to 1-1/2 Inches Difference in Framing Levels 14-43

Figure 14-44 Splicing of Auxiliary Framing Channels 2-Inch Difference in Framing Levels 14-44

Figure 14-45 Hanger Rod Attachments at Ceiling 14-45

Figure 14-46A Auxiliary Framing Brace at Building Wall 14-46

Figure 14-46B Auxiliary Framing Brace at Ceiling 14-47

Figure 14-47 Hanger Rods Passing Through False Ceiling 14-48

Figure 14-48 Hanger Rod Splice 14-48

Figure 14-49 Hanger Bolts Used Where Ceiling Inserts Are Not Provided 14-49

Figure 14-50 Auxiliary Framing Stiffening Clips and Through Bolts 14-50

Figure 14-51 Auxiliary Framing Friction Splices Staggered Across Building Bay 14-51

Figure 14-52 Auxiliary Framing Positive Splices Non-Staggered Across Building Bay 14-52

Figure 14-53 Hanger Rod Attached to Beam Clamp or Ceiling Inserts 14-53

Figure 14-54 Auxiliary Framing Attached to Hanger Rods (Deleted) 14-53

Figure 14-55 Hangar Rods or Bolts Attached at Ends of Auxiliary Framing When Auxiliary Framing Will Not Be Extended 14-54

Figure 14-56	Support of Auxiliary Framing From Ceiling or Other Channels . . .	14-55
Figure 14-57A	Miscellaneous Cable Support Bracket Attached to Auxiliary Framing With Retaining Spring	14-56
Figure 14-57B	Cable Support From Auxiliary Framing	14-57
Figure 14-57C	Cable Support From Auxiliary Framing	14-58
Figure 14-58	Typical Layout of Beam Clamps of Inserts and Primary Channels .	14-59
Figure 14-59	Double-Level Auxiliary Framing - Channels Attached to Channels (Deleted)	14-59
Figure 14-60	Double Framing Under Beams or Girders - Primary Channels at Right Angles to Beams or Girders (Deleted)	14-60
Figure 14-61	Double Framing Under Beams or Girders - Primary Channels Parallel to Beams or Girders (Deleted)	14-60
Figure 14-62	Typical Auxiliary Framing Brace Arrangement (Moved to Section 17)	14-60
Figure 14-63	Typical Auxiliary Framing Layout	14-61
Figure 16-1	Straight-Type Rolling Ladder Assembly Without Brake	16-9
Figure 16-2	Straight-Type Rolling Ladder Assembly With Brake	16-10
Figure 16-3	Platform-Type Rolling Ladder Assembly	16-11
Figure 16-4	Location and Clearance for Ladders and Distributing Frames . . .	16-12
Figure 16-5	Location and Clearance for Ladders at Relay Racks, Fuse Bays . .	16-13
Figure 16-6	Spacings of Ladders Near Walls, Columns, or Between Equipment Frames	16-14
Figure 16-7	Number of Sections of Track Required for Various Lengths of Track	16-15
Figure 16-8	Splicing Sleeves for Ladder Track	16-16
Figure 16-9	Track Support Brackets	16-17
Figure 16-10	Track Supported Parallel to/or at Right Angles to Auxiliary Framing, Parallel Shown	16-18
Figure 16-11	Track Supported Directly From and at Right Angles to Auxiliary Framing	16-19
Figure 16-12	Track Supported From and at Right Angles to Auxiliary Framing - Sloping Track - 2-Inch Difference in Auxiliary Framing Level	16-20
Figure 16-13	Track Supported From Auxiliary Framing With Extension Rod . .	16-21
Figure 16-14	Track Supported Directly From Ceiling	16-22
Figure 16-15	Track Supported From Lattice Work	16-23
Figure 16-16	Track Supported Parallel to Wood Joists	16-24
Figure 16-17	Track Supported at Right Angles to Wood Joists	16-25
Figure 16-18	Track Supported Directly From Timbers	16-26
Figure 16-19	Track Supported from Timbers With Extension Rod	16-27
Figure 16-20	Ladder Track End Brace Where Auxiliary Framing Beyond End of Track Cannot Be Used	16-28
Figure 16-21	Ladder Track Side Braces and Preferred Location for End Braces	16-29
Figure 16-22	Ladder Stop at Support Bracket	16-30
Figure 16-23	Location of End Supports and Ladder Stops in Track	16-31
Figure 16-24	Ladder Tracks Supported From Wall	16-32
Figure 16-25	Ladder Track Plug	16-33
Figure 16-26	End Cap	16-33
Figure 17-1	Auxiliary Framing Brace for Use in High Ceiling Areas	17-8
Figure 17-2	Auxiliary Framing Brace for Use in High Ceiling Areas	17-9

Figure 17-3	Fastening Auxiliary Framing Brace to Embedded Ceiling Channel	17-10
Figure 17-4	Arrangements of Auxiliary Framing Braces	17-11
Figure 17-5	Typical Auxiliary Framing Arrangement	17-12
Figure 17-6	Supplementary Framing and Braces at Unequipped Rows of Frames (Deleted)	17-13
Figure 17-7	Angle Bracing From Auxiliary Framing (Deleted)	17-13
Figure 17-8	Splicing of Auxiliary Framing Channels 2-Inch Difference in Framing Levels (Deleted)	17-13
Figure 17-9	Auxiliary Framing Splices - 1 Inch Difference in Framing Levels (Deleted)	17-13
Figure 17-10	Splicing of Auxiliary Framing Channels 1-1/2 Inches Difference in Framing Levels (Deleted)	17-13
Figure 17-11	Auxiliary Framing Splices - Same Level (Deleted)	17-13
Figure 17-12	Support of Ladder-Type Cross-Aisle Cable Racks Not Attached Directly to Auxiliary Framing (Deleted)	17-13
Figure 17-13	Sidewise Bracing of Ladder-Type Cross-Aisle Cable Rack With Threaded Rod Braces	17-14
Figure 17-14	Sidewise Bracing of Ladder-Type Cross-Aisle Cable Rack With Angle Braces When Cable Is Not Attached Directly to Auxiliary Framing in Seismic Zones 3 and 4	17-15
Figure 17-15	Cable Rack End Brace - Cable Rack Not Attached Directly to Auxiliary Framing (Threaded Rod Brace) Used in Seismic Zones 0, 1, and 2	17-16
Figure 17-16	Braces at Right Angles to Embedded Channel (Deleted)	17-17
Figure 17-17	Bracing in Line With Embedded Channel (Deleted)	17-17
Figure 17-18	Cable Rack End Brace - Cable Rack Not Attached Directly to Auxiliary Framing (With Angle Bracket) Used in Seismic Zones 3 and 4	17-17
Figure 17-19	Typical Auxiliary Framing Brace Arrangement	17-18
Figure 17-20	Typical Warren Truss Type Brace Arrangement for Floor-Supported Equipment Environments	17-19
Figure 17-21	Cable Rack Support - Cable Rack 2 Inches Above Auxiliary Framing (Deleted)	17-20
Figure 17-22	Bracing Cable Racks to Distributing Frame Verticals	17-20
Figure 17-23	Perpendicular Bracing Using Spacer Between Brace Feet (Deleted)	17-21
Figure 17-24	Angle Braces in Two Directions	17-21
Figure 17-25	Equipment Bracing in CDO Type Offices - Bracing Equipment to Walls and Between Cable Racks	17-22
Figure 17-26	Typical Arrangement of Ladder-Type Cable Racks and Braces for a Community Dial Office	17-23
Figure 17-27A	Equipment Bracing in CDO Type Offices - Bracing Distributing Frame to Wall and Between Equipment Line-Up	17-24
Figure 17-27B	Auxiliary Framing Brace at Ceiling	17-25
Figure 17-27C	Auxiliary Framing Brace at Building Wall	17-26
Figure 17-28	Wall Braces for Community Dial Office Frame - Cable Racks	17-27
Figure 17-29	Ceiling Braces for Community Dial Office Distributing Frame and Cable Racks	17-28
Figure 17-30	Fastening Ladder-Type Cross-Aisle Cable Rack to Over-Frame Cable Rack	17-29

Figure 17-31	Seismic Zone Map	17-30
Figure 17-32	Typical Floor-Supported Rectifier Cabinets - Floor and Top Fastenings (Delete)	17-30
Figure 17-33	Fastening a Network Frame to High-Type Auxiliary Framing Where “A” Is Over 1 Foot 6 Inches	17-31
Figure 17-34	Cable Rack End Brace - Cable Rack Not Attached Directly to Auxiliary Framing (Threaded Rod Brace)	17-32
Figure 17-35	Cable Rack End Brace - Cable Rack Not Attached Directly to Auxiliary Framing (with Angle Bracket)	17-33
Figure 17-36	Bracing Battery Stand Parallel to Wall	17-34
Figure 17-37	Arrangement of Ceiling Braces for Metal Battery Stands Arranged in Parallel Line	17-35
Figure 17-38	Supplementary Supports for Bus Bar Runs	17-36
Figure 17-39	Bracing Hanger Rod-Supported Cable Rack With Rod-Type Bracing (Deleted)	17-36
Figure 17-40	Bracing Hanger Rod-Supported Cable Rack With Angle-Type Bracing (Deleted)	17-36
Figure 17-41	Bracing of Auxiliary Framing With Single-Rod Braces	17-37
Figure 17-42	Bracing of Auxiliary Framing With Double-Rod Braces	17-38
Figure 17-43	Bracing of Auxiliary Framing With Double-Angle Braces (Over 1 Foot 8-Inches, But Less Than 5 Feet)	17-39
Figure 17-44	Bracing Frames From Auxiliary Framing	17-40
Figure 17-45	Method of Installing Auxiliary Framing Braces at Same Location	17-41
Figure 17-46	Method of Installing New Brace to Existing Hanger Rod	17-42
Figure 17-47	Auxiliary Framing Stiffening Clips and Through Bolts	17-43
Figure 17-48	Typical Auxiliary Framing Arrangement Low Seismic Risk Areas	17-44
Figure 17-49	Typical Auxiliary Framing Arrangement High Seismic Risk Areas	17-45
Figure 17-50	Typical Application of Cable Rack Bracing	17-46
Figure 18-1	Provision for Slack Storage	18-5
Figure 19-1	Example of a 565 Type Drawing	19-3
Figure 23-1	Telemetry Block Diagram	23-11
Figure 26-1	Radiated Emission Objective for Any Measuring Distance	26-15
Figure 26-2	Office Radiated Emission Objective	26-16
Figure 26-3	Seismic Zone Map	26-18
Figure 26-4	Earthquake Floor Response Criteria	26-19
Figure 26-5	Intumescent Drop-In Cover Support	26-20
Figure 26-6	Example of a Firestopping Certification Label	26-21
Figure 34-1	Engineering Services Records Group Drawing Reproduction Requisition	34-3
Figure 35-1	Title Box (Views 1, 2, and 3)	35-4
Figure 35-2	Issue and Drawing Notes (Views 1 and 2)	35-5
Figure 37-1	Sample Specification	37-20
Figure 37-2	Sample Specification	37-21
Figure 37-3	Sample Specification	37-22
Figure 37-4	Sample Specification	37-23
Figure 37-5	Sample Specification	37-24
Figure 37-6	Sample Specification	37-25
Figure 37-7	Sample Specification	37-26
Figure 37-8	Sample Specification	37-27

Figure 37-9 Sample Specification 37–28
Figure 37-10 Sample Specification 37–29
Figure 37-11 Sample Specification 37–30
Figure 37-12 Sample Specification 37–31
Figure 37-13 Sample Specification 37–32
Figure 37-14 Sample Specification 37–33
Figure 37-15 Sample Specification 37–34
Figure 37-16 Sample Specification 37–35
Figure 37-17 Sample Specification 37–36
Figure 37-18 Sample Specification 37–37
Figure 37-19 Sample Specification 37–38
Figure 37-20 Sample Specification 37–39

List of Tables

Table 2-1	Aisle Spacing	2-1
Table 2-2	Floor Plan Symbols	2-5
Table 4-1	Battery Stand Arrangements	4-7
Table 10-1	CMA-Cable Size Conversion	10-3
Table 13-1	Permissible Pile-Up of Cable	13-6
Table 14-1	Safe Loads	14-3
Table 16-1	Ladder Heights	16-8
Table 17-1	Brace Attachments	17-1
Table 17-2	Brace Usage	17-8
Table 17-3	Brace Attachments	17-18
Table 21-1	PDSC Assignments	21-2
Table 23-1	Alarm Classification and Color	23-4
Table 24-1	Minimum Cable Bending Radii	24-2
Table 26-1	Room and Ambient Temperatures	26-3
Table 26-2	Sound Level Limits	26-12
Table 26-3	Minimum Maintained Illumination Levels	26-13
Table 27-1	GR Sections That Describe COE Records and Procedures	27-1
Table 35-1	Suggested Titles	35-2
Table 36-1	Document Types	36-1
Table 36-2	Dash Numbers/Document Type	36-4
Table 38-1	Potentially Hazardous Materials	38-3
Table B-1	Acronyms	B-1
Table B-2	Glossary Definitions	B-7