

Contents

Preface	Preface-1
1. Introduction	1-1
1.1 Definition	1-1
1.2 Background	1-1
1.2.1 High-Level Description of SS7 Routing Capabilities	1-1
1.2.2 Brief Description of Feature/GRP Communications	1-8
1.3 High-Level Feature Description	1-11
1.4 Automatic Callback (AC) Versus Automatic Recall (AR) -- A Comparison	1-11
1.5 Terminology	1-12
1.6 Requirements Notation	1-14
1.7 Figure Notation	1-14
2. User Perspective	2-1
3. Feature Requirements	3-1
3.1 Feature Operations	3-1
3.1.1 Descriptions of TCAP Messages, Timers, and Announcements	3-1
3.1.2 Feature Processing	3-6
3.1.3 Release Treatment	3-73
3.1.4 Interrupt	3-73
3.1.5 Error Treatment and Abnormal Events	3-73
3.2 Internal Call Processing Controls	3-76
3.2.1 Connections	3-76
3.2.2 Class of Service	3-76
3.2.3 Code Interpretation	3-77
3.2.4 Screening	3-78
3.2.5 Overload	3-78
3.3 Signaling	3-79
3.3.1 Customer Loop	3-79
3.3.2 Customer Signaling	3-79
3.3.3 Intersystem DC Signaling	3-79
3.3.4 Intersystem AC Signaling	3-80
3.4 Routing	3-96
3.5 Administration	3-96
3.5.1 Data Items and Usage	3-96
3.5.2 Service Changes	3-100
3.5.3 Installation	3-100
3.5.4 Traffic Measurements	3-101
3.5.5 Maintenance Measurements	3-101
3.5.6 Automatic Message Accounting	3-101
3.5.7 Input/Output Messages	3-107
3.6 Maintenance	3-108

- 3.7 Performance 3-108
- 3.8 Feature Interactions 3-108
- 3.9 Limitations and Restrictions 3-129
- 3.10 Timing and Tolerances 3-130
- Appendix A: Outgoing Memory Slot Requirements A-1
 - A.1. Introduction A-1
 - A.2 Contents of Outgoing Memory Slot A-1
 - A.3 Update Requirements A-3
 - A.4. Feature Interactions A-6
 - A.4.1 Automatic Recall (AR)/Automatic Callback (AC) A-6
 - A.4.2 Call Forwarding A-7
 - A.4.3 Customized Code Restriction A-7
 - A.4.4 Per-Call Presentation Features A-7
 - A.4.5 Private Branch Exchange A-9
 - A.4.6 Speed Calling A-9
- Appendix B: TCAP Message Formats for Automatic Callback B-1
 - B.1 Introduction B-1
 - B.2 TCAP Message Formats B-2
 - B.2.1 TCAP Information for Initial Query Message B-2
 - B.2.2 TCAP Information for Terminating Scanning Request
Query Message B-8
 - B.2.3 TCAP Information for Originating Scanning-Busy/Idle
Query Message B-12
 - B.3 TCAP Information for Response Messages B-16
 - B.3.1 TCAP Information for the Initial Response Message B-16
 - B.3.2 TCAP Information for the Terminating Scanning Request
Conversation Message B-20
 - B.3.3 TCAP Information for the Terminating Scanning-Idle
Response Message B-22
 - B.3.4 TCAP Information for the Originating Scanning -
Busy/Idle Response Message B-24
 - B.3.5 TCAP Information for Cancel Terminating Scanning
Response Message B-26
 - B.3.6 TCAP Information for Dequeue Call Unidirectional
Message B-30
 - B.3.7 TCAP Information for Messages Containing B-34
 - B.3.8 TCAP Information for Messages Containing Reject
Components B-37
 - B.3.9 TCAP Information for Messages That Report Errors in
Return Results B-39
- Appendix C: Parameter Formats for Automatic Callback C-1
 - C.1 Busy/Idle Status C-1
 - C.2 Duration C-1
 - C.3 Call Forwarding Status C-2
 - C.4 Terminating Restrictions C-3

C.5	DN to Line Service Type Mapping	C-3
C.6	Error Codes	C-5
References		References-1
Glossary		Glossary-1

List of Figures

Figure 1-1.	Example Configuration of Multiple Networks	1-6
Figure 1-2.	Feature/GRP Communication	1-9
Figure 3-1.	AC Overall Picture	3-6
Figure 3-2.	AC Activation Attempt Processing	3-8
Figure 3-3.	Initial AC Processing from the Originating SPCS Perspective	3-24
Figure 3-3.	Initial AC Processing from the Originating SPCS Perspective (Cont.)	3-25
Figure 3-3.	Initial AC Processing from the Originating SPCS Perspective (Cont.)	3-26
Figure 3-4.	Initial AC Processing from Terminating SPCS Perspective . .	3-27
Figure 3-4.	Initial AC Processing from Terminating SPCS Perspective (Cont.)	3-28
Figure 3-5.	Immediate Processing from the Originating SPCS Perspective	3-30
Figure 3-6.	Delayed Processing from the Originating SPCS Perspective .	3-35
Figure 3-7.	Terminating SPCS Responses to the Terminating Scanning Request Query	3-36
Figure 3-8.	Originating Scanning (Originating SPCS View)	3-43
Figure 3-9.	Originating Scanning (Terminating SPCS View)	3-44
Figure 3-9.	Originating Scanning (Terminating SPCS View) (Cont.) . . .	3-45
Figure 3-10.	Terminating Scanning Procedures (Terminating SPCS)	3-49
Figure 3-11.	Determining When AC Request Gets Called Party Idle Notification	3-50
Figure 3-12.	Terminating Scanning (Originating SPCS)	3-51
Figure 3-13.	Queue Serving Procedures	3-53
Figure 3-14.	Call Setup Processing	3-56
Figure 3-15.	Answered Special Ringing	3-59
Figure 3-16.	Unanswered Special Ringing	3-61
Figure 3-17.	Resumed Scanning	3-63
Figure 3-18.	Dequeue Procedures (Originating SPCS View)	3-68
Figure 3-19.	Dequeue Procedures (Terminating SPCS View)	3-69

List of Tables

Table 3-1.	Processing DN-to-Line Service Type Mapping Parameter Requirements	3-23
Table 3-2.	Preservation of Anonymity -- AC Customer's DN	3-123
Table 3-3.	Preservation of Anonymity -- AC Customer's Name	3-124
Table B-1.	TCAP Information for Initial Query Message	B-2
Table B-2.	TCAP Information for Terminating Scanning Request Query Message	B-8
Table B-3.	TCAP Information for Originating Scanning-Busy/Idle Query Message	B-12
Table B-4.	TCAP Information for the Normal Initial Response Message .	B-16
Table B-5.	TCAP Information for the Terminating Scanning Request Conversation	B-20
Table B-6.	TCAP Information for Response Indicating "Called Party Free"	B-22
Table B-7.	TCAP Information for the Normal Originating Scanning - Busy/Idle Response	B-24
Table B-8.	TCAP Information for Message to Cancel Operation	B-26
Table B-9.	TCAP Information for the Dequeue Call Unidirectional Message	B-30
Table B-9.	TCAP Information for the Dequeue Call Unidirectional Message (Continued)	B-31
Table B-10.	TCAP Information for Messages Containing Return Error Components	B-34
Table B-11.	TCAP Information for Messages Containing Reject Components	B-37
Table B-12.	TCAP Information for "Report Error" Messages	B-39